



Complete Integrated LED Lighting Solutions

Acolyte

www.acolyteled.com

Tel: +1 210 360 1444(USA)

Fax: + 85 755 85290710(China) Page 1 of 15 Pages

Report No.:

Test Time: 2018/10/12 15:11

## Luminaire Property

Luminaire Manufacturer:

Luminaire Category: RIBBONLYTE

Luminous Length (mm): 500

Luminous Height (mm): 1

Current: 0.212 A

Power Factor: 1.000

Luminaire Description: RBS220243.0R

Luminous Width (mm): 8

Voltage: 24.0 V

Power: 5.08 W

## Photometric Results

CIE Class: Direct

Measurement Flux: 200.7 lm

Downward Ratio: 99%

Horizontal Diffuse Angle(50%): H124.4

Vertical Diffuse Angle(50%): V122.8

Luminaire Efficacy Rating (LER): 40

Max. Intensity: 61.8 cd

Total Rated Lamp Lumens: 200.7 lm


Efficiency: 100%

Upward Ratio: 1%


Central Intensity: 61.77 cd

Pos of Max. Intensity: H180 V1

Picture Of Luminaire



Luminous Intensity Distribution Curve



Average Diffuse Angle(50%): 123.6° Unit: cd

— C0-C180 — C90-C270

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0: 1.0



Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:

## Luminous Intensity Distribution Curve



C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:

## Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-360.0: 30.0  
Test Lab:  
Test Type: TYPE C  
Temperature: 25  
Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0  
Test Device: GPM-1800B  
Distance: 9.028 m  
Humidity: 60%  
Inspector:




## Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	101	101	101	99
1	108	103	98	94	105	100	96	93	96	93	90	92	89	87	88	86	84	82
2	98	89	82	76	95	87	80	75	83	78	73	80	75	71	77	73	69	67
3	89	78	69	62	86	76	68	62	73	66	60	70	64	59	67	62	58	56
4	81	68	59	52	78	67	58	52	64	57	51	62	55	50	60	54	49	47
5	74	61	51	45	72	60	51	44	57	50	44	55	48	43	53	47	43	40
6	68	55	45	39	66	54	45	38	52	44	38	50	43	38	48	42	37	35
7	63	49	40	34	61	48	40	34	47	39	33	45	38	33	44	38	33	31
8	59	45	36	30	57	44	36	30	43	35	30	41	35	30	40	34	29	27
9	55	41	33	27	53	40	32	27	39	32	27	38	31	27	37	31	26	24
10	51	38	30	24	50	37	30	24	36	29	24	35	29	24	34	28	24	22

Spacing Criteria (0-180): 1.33

Spacing Criteria (90-270): 1.31

Spacing Criteria (Diagonal): 1.45



C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0: 1.0

Test Device: GPM-1800B


Distance: 9.028 m

Humidity: 60%

Inspector:



## Isocandela (rectangle)



I<sub>max</sub> (100%): 62 cd

( 10%):	6 cd	( 20%):	12 cd
( 25%):	15 cd	( 30%):	19 cd
( 40%):	25 cd	( 50%):	31 cd
( 60%):	37 cd	( 70%):	43 cd
( 80%):	49 cd	( 90%):	56 cd

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1800B


Distance: 9.028 m

Humidity: 60%

Inspector:



## IsoLux Plot



Mounting Height: 5.0m Max Lux(100%): 2.5 lx

( 10%): 0.2 lx	( 20%): 0.5 lx
( 25%): 0.6 lx	( 30%): 0.7 lx
( 40%): 1.0 lx	( 50%): 1.2 lx
( 60%): 1.5 lx	( 70%): 1.7 lx
( 80%): 2.0 lx	( 90%): 2.2 lx

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:



acolyte®

Acolyte

www.acolyteled.com

Tel: +1 210 360 1444(USA)



Complete Integrated LED Lighting Solutions

Fax: + 85 755 85290710(China) Page 7 of 15 Pages

## Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300

a b c d e f g h



L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	14362	14109	13791	13321	12749	11785	10229	7801	4122
C90	16107	16223	16077	15631	15126	14336	12512	9452	4010
C180	14783	14518	14213	13843	13426	12721	11540	9427	6307
C270	16026	16188	16381	16433	16340	15593	13960	11104	5581

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1800B


Distance: 9.028 m

Humidity: 60%

Inspector:




## Illuminance at a Distance





## Vertical IsoLux Plot



Lowest(m): 2.0m	Highest(m): 5.0m	Max Lux: 15.4 lx
( 10%): 1.5 lx	( 20%): 3.1 lx	
( 25%): 3.9 lx	( 30%): 4.6 lx	
( 40%): 6.2 lx	( 50%): 7.7 lx	
( 60%): 9.3 lx	( 70%): 10.8 lx	
( 80%): 12.4 lx	( 90%): 13.9 lx	

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:



A C O L Y T E

Acolyte

www.acolyteled.com

Tel: +1 210 360 1444(USA)

Complete Integrated LED Lighting Solutions

Fax: + 85 755 85290710(China) Page 10 of 15 Pages

## Area Flux Table

Unit: lm

Vertical plane		-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90	Flux(T)	Flux(E)
Horizontal plane	-90	0.0	0.0	0.0	0.1	0.1	0.1	0.1	0.1	1.0	1.3	1.6	1.7	1.8	1.8	1.7	1.6	1.5	1.4	1.3	21.4	21.3
	-80	0.0	0.0	0.1	0.2	0.3	0.3	0.4	0.4	1.0	1.3	1.6	1.8	1.9	1.8	1.7	1.6	1.5	1.4	1.3	21.5	21.4
	-70	0.0	0.1	0.1	0.3	0.4	0.6	0.7	0.8	1.1	1.3	1.6	1.8	1.9	1.8	1.7	1.6	1.5	1.4	1.3	20.5	20.4
	-60	0.0	0.1	0.2	0.4	0.6	0.8	1.0	1.1	1.3	1.5	1.6	1.7	1.8	1.7	1.6	1.5	1.4	1.3	1.1	20.3	20.2
	-50	0.0	0.1	0.2	0.4	0.6	0.8	1.0	1.1	1.3	1.5	1.6	1.7	1.8	1.7	1.6	1.5	1.4	1.3	1.1	18.0	17.9
	-40	0.0	0.1	0.3	0.5	0.7	0.9	1.1	1.3	1.5	1.6	1.7	1.8	1.9	1.8	1.7	1.6	1.5	1.4	1.3	14.8	14.7
	-30	0.0	0.1	0.3	0.5	0.8	1.1	1.3	1.5	1.6	1.7	1.8	1.9	1.8	1.7	1.6	1.5	1.4	1.3	1.1	11.1	11.0
	-20	0.0	0.1	0.3	0.6	0.9	1.2	1.4	1.6	1.8	1.9	1.8	1.7	1.6	1.5	1.4	1.3	1.2	1.1	0.9	7.3	7.1
	-10	0.0	0.1	0.4	0.7	1.0	1.3	1.6	1.8	1.9	1.8	1.7	1.6	1.5	1.4	1.3	1.2	1.1	0.9	0.6	3.9	3.7
	0	0.0	0.1	0.4	0.7	1.0	1.3	1.6	1.8	1.9	1.8	1.7	1.6	1.5	1.4	1.3	1.2	1.1	0.9	0.6	1.3	1.2
	10	0.0	0.1	0.4	0.7	1.0	1.3	1.6	1.8	1.9	1.8	1.7	1.6	1.5	1.4	1.3	1.2	1.1	0.9	0.6	0.1	0.0
	20	0.0	0.1	0.4	0.6	0.9	1.2	1.4	1.6	1.8	1.9	1.8	1.7	1.6	1.5	1.4	1.3	1.2	1.1	0.9	0.1	0.0
	30	0.0	0.1	0.3	0.6	0.9	1.2	1.4	1.6	1.8	1.9	1.8	1.7	1.6	1.5	1.4	1.3	1.2	1.1	0.9	0.1	0.0
	40	0.0	0.1	0.3	0.5	0.8	1.1	1.3	1.5	1.6	1.7	1.8	1.9	1.8	1.7	1.6	1.5	1.4	1.3	1.1	0.1	0.0
	50	0.0	0.1	0.3	0.5	0.7	0.9	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	1.8	1.7	1.6	1.5	1.1	0.1	0.0
	60	0.0	0.1	0.2	0.4	0.6	0.8	0.9	1.1	1.1	1.1	1.1	1.0	0.9	0.7	0.6	0.5	0.4	0.3	0.2	0.1	0.0
	70	0.0	0.1	0.1	0.3	0.4	0.6	0.7	0.8	0.8	0.8	0.8	0.7	0.6	0.5	0.4	0.3	0.2	0.1	0.0	0.0	0.0
	80	0.0	0.0	0.1	0.2	0.2	0.3	0.4	0.4	0.4	0.4	0.4	0.4	0.3	0.3	0.3	0.2	0.1	0.1	0.0	0.0	0.0
	90	0.2	1.6	4.2	7.6	11.5	15.3	18.4	20.5	21.5	21.4	21.3	20.2	17.9	14.7	11.0	7.1	3.7	1.2	0.0	199	197
	Flux(E)	0.1	1.5	4.1	7.5	11.4	15.2	18.3	20.4	21.4	21.3	20.2	17.9	14.7	11.0	7.1	3.7	1.2	0.0			
	Flux(T)	0.2	1.6	4.2	7.6	11.5	15.3	18.4	20.5	21.5	21.4	20.3	18.0	14.8	11.1	7.3	3.9	1.3	0.1			
	Flux(E)	0.1	1.5	4.1	7.5	11.4	15.2	18.3	20.4	21.4	21.3	20.2	17.9	14.7	11.0	7.1	3.7	1.2	0.0			
	Flux(T)	0.2	1.6	4.2	7.6	11.5	15.3	18.4	20.5	21.5	21.4	20.3	18.0	14.8	11.1	7.3	3.9	1.3	0.1			

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:



ACOLYTE®

Complete Integrated LED Lighting Solutions


Acolyte

www.acolyteled.com

Tel: +1 210 360 1444(USA)

Fax: + 85 755 85290710(China) Page 11 of 15 Pages

## The Average Illuminance Effective Figure



C Plane (°):0.0-360.0: 30.0  
Test Lab:  
Test Type: TYPE C  
Temperature: 25  
Operator: Aaron

Gamma Plane (°):0.0-180.0: 1.0  
Test Device: GPM-1800B  
Distance: 9.028 m  
Humidity: 60%  
Inspector:



## UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	27.3	29.0	27.7	29.3	29.6	26.9	28.6	27.3	28.9	29.2
3H	29.3	30.9	29.7	31.2	31.6	28.6	30.1	29.0	30.5	30.8
4H	30.1	31.5	30.5	31.9	32.3	29.2	30.6	29.6	31.0	31.4
6H	30.7	32.0	31.1	32.4	32.8	29.5	30.8	29.9	31.2	31.6
8H	30.8	32.1	31.3	32.5	32.9	29.5	30.8	30.0	31.2	31.6
12H	30.9	32.2	31.4	32.5	33.0	29.5	30.8	30.0	31.2	31.6
X=4H Y=2H	27.9	29.3	28.3	29.7	30.1	27.6	29.0	28.0	29.4	29.8
3H	30.2	31.4	30.6	31.8	32.2	29.6	30.8	30.0	31.2	31.6
4H	31.1	32.2	31.5	32.6	33.0	30.3	31.4	30.7	31.8	32.2
6H	31.7	32.7	32.2	33.2	33.6	30.7	31.7	31.2	32.1	32.6
8H	31.9	32.8	32.4	33.3	33.8	30.8	31.7	31.2	32.1	32.6
12H	32.1	32.9	32.6	33.4	33.9	30.8	31.6	31.3	32.1	32.6
X=8H Y=4H	31.3	32.2	31.8	32.7	33.2	30.7	31.6	31.1	32.0	32.5
6H	32.1	32.9	32.6	33.4	33.9	31.2	32.0	31.7	32.5	33.0
8H	32.4	33.1	32.9	33.6	34.1	31.4	32.0	31.9	32.5	33.0
12H	32.6	33.2	33.1	33.7	34.2	31.4	32.0	31.9	32.5	33.1
X=12H Y=4H	31.4	32.2	31.9	32.7	33.2	30.7	31.5	31.2	32.0	32.5
6H	32.2	32.8	32.7	33.3	33.9	31.3	32.0	31.8	32.5	33.0
8H	32.5	33.1	33.0	33.6	34.1	31.5	32.1	32.0	32.6	33.2

Calculate in accordance with CIE 190:2010

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:



## Utilisation Factor Table(Floor cavity)

Utilisation Factors UF(F)			SHR NOM = 1.50								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.57	0.66	0.73	0.79	0.86	0.91	0.95	0.99	1.03
	0.30		0.49	0.58	0.66	0.71	0.80	0.85	0.90	0.95	0.99
	0.20		0.44	0.52	0.60	0.66	0.74	0.81	0.85	0.91	0.96
0.50	0.50	0.20	0.55	0.63	0.71	0.76	0.83	0.88	0.91	0.95	0.98
	0.30		0.48	0.56	0.64	0.70	0.77	0.83	0.87	0.92	0.95
	0.20		0.43	0.51	0.59	0.65	0.73	0.79	0.83	0.89	0.92
0.30	0.50	0.20	0.54	0.61	0.68	0.73	0.80	0.84	0.87	0.92	0.94
	0.30		0.48	0.55	0.63	0.68	0.75	0.80	0.84	0.89	0.92
	0.20		0.43	0.51	0.58	0.64	0.71	0.77	0.81	0.86	0.89
0.00	0.00	0.00	0.41	0.48	0.55	0.60	0.68	0.73	0.76	0.81	0.85
<p>Rating:5W Photometrically tested without ceiling board.</p> <p>Multiply UF values by service correction factors</p> <p>Calculate in accordance with CIBSE Technical Memorandum NO.5 1980</p>											



## Utilisation Factor Table(Wall)

Utilisation Factors UF(W)			SHR NOM = 1.50									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.99	0.84	0.72	0.62	0.50	0.42	0.36	0.28	0.23	
	0.30		0.82	0.72	0.62	0.55	0.45	0.38	0.33	0.26	0.22	
	0.20		0.71	0.63	0.55	0.50	0.41	0.35	0.31	0.25	0.21	
0.50	0.50	0.20	0.95	0.81	0.69	0.60	0.48	0.43	0.34	0.26	0.22	
	0.30		0.81	0.70	0.61	0.54	0.44	0.37	0.32	0.25	0.21	
	0.20		0.70	0.62	0.54	0.49	0.40	0.34	0.30	0.24	0.20	
0.30	0.50	0.20	0.92	0.78	0.66	0.57	0.46	0.38	0.33	0.25	0.21	
	0.30		0.79	0.69	0.59	0.52	0.42	0.36	0.31	0.24	0.20	
	0.20		0.69	0.61	0.53	0.48	0.39	0.33	0.29	0.23	0.19	
0.00	0.00	0.00	0.59	0.52	0.44	0.39	0.32	0.27	0.23	0.18	0.15	
<p>Rating:5W Photometrically tested without ceiling board.</p> <p>Multiply UF values by service correction factors</p> <p>Calculate in accordance with CIBSE Technical Memorandum NO.5 1980</p>												



## Utilisation Factor Table(Ceiling cavity)

Utilisation Factors UF(C)			SHR NOM = 1.50									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.17	0.18	0.19	0.20	0.21	0.21	0.22	0.22	0.23	
	0.30		0.10	0.12	0.13	0.14	0.16	0.17	0.18	0.19	0.20	
	0.20		0.05	0.07	0.08	0.10	0.12	0.13	0.14	0.16	0.17	
0.50	0.50	0.20	0.16	0.18	0.19	0.19	0.20	0.20	0.21	0.21	0.22	
	0.30		0.10	0.12	0.13	0.14	0.15	0.16	0.17	0.18	0.19	
	0.20		0.05	0.07	0.08	0.09	0.11	0.13	0.14	0.16	0.17	
0.30	0.50	0.20	0.16	0.17	0.18	0.18	0.19	0.20	0.20	0.20	0.21	
	0.30		0.10	0.11	0.12	0.13	0.15	0.16	0.17	0.18	0.18	
	0.20		0.05	0.07	0.08	0.09	0.11	0.13	0.14	0.15	0.16	
0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	
<p>Rating:5W Photometrically tested without ceiling board.</p> <p>Multiply UF values by service correction factors</p> <p>Calculate in accordance with CIBSE Technical Memorandum NO.5 1980</p>												