

Report No.:

Test Time: 2023/9/13 16:06

Luminaire Property

Luminaire Manufacturer: ACOLYTE

Luminaire Category: CHANNEL

Luminaire Description: CHAR3C90SWS2203.030

Luminous Length (mm): 500

Luminous Width (mm): 30.5

Luminous Height (mm): 10.7

Voltage: 24.0 V

Current: 0.203 A

Power: 4.89 W

Power Factor: 1.000

Photometric Results

CIE Class: Direct

Measurement Flux: 439.6 lm

Downward Ratio: 99%

Horizontal Diffuse Angle(10%,50%): H151.3,H109.2

Vertical Diffuse Angle(10%,50%): V125.1,V100

Luminaire Efficacy Rating (LER): 90

Max. Intensity: 186.03 cd

Total Rated Lamp Lumens: 439.6 lm

Efficiency: 100%

Upward Ratio: 1%


Central Intensity: 185.93 cd

Pos of Max. Intensity: H0 V1

Picture Of Luminaire



Luminous Intensity Distribution Curve



C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Nick

Gamma Plane (°):0.0-180.0: 1.0


Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:


Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	101	101	101	99
1	110	106	102	99	107	104	100	97	99	97	94	95	93	91	92	90	88	86
2	101	94	88	83	99	92	87	82	88	84	80	85	81	78	82	79	76	74
3	93	84	76	70	91	82	75	70	79	73	68	76	71	67	74	69	66	64
4	86	75	67	61	83	73	66	60	71	64	59	68	63	58	66	61	57	55
5	79	67	59	53	77	66	58	52	64	57	52	62	56	51	60	55	50	48
6	73	61	52	46	71	60	52	46	58	51	46	56	50	45	54	49	45	43
7	68	55	47	41	66	54	46	41	53	46	41	51	45	40	50	44	40	38
8	63	50	42	37	62	50	42	37	48	41	36	47	41	36	46	40	36	34
9	59	46	38	33	58	46	38	33	44	38	33	43	37	33	42	37	32	31
10	55	43	35	30	54	42	35	30	41	34	30	40	34	30	39	34	29	28

Spacing Criteria (0-180): 1.25

Spacing Criteria (90-270): 1.30


Spacing Criteria (Diagonal): 1.34



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°):0.0-180.0: 1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Isocandela (rectangle)




I_{max} (100%): 186 cd

(10%):	19 cd	(20%):	37 cd
(25%):	47 cd	(30%):	56 cd
(40%):	74 cd	(50%):	93 cd
(60%):	112 cd	(70%):	130 cd
(80%):	149 cd	(90%):	167 cd

C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

IsoLux Plot



Mounting Height: 5.0m Max Lux(100%): 7.4 lx

(10%): 0.7 lx	(20%): 1.5 lx
(25%): 1.9 lx	(30%): 2.2 lx
(40%): 3.0 lx	(50%): 3.7 lx
(60%): 4.5 lx	(70%): 5.2 lx
(80%): 6.0 lx	(90%): 6.7 lx

C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick



Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:



Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300

a b c d e f g h




L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	8625	7986	7290	6469	5397	4133	2718	1435	538
C90	11574	8834	4538	2766	2403	2329	1975	1717	1759
C180	8158	7497	6661	5702	4532	3173	1817	774	171
C270	12818	9490	4664	2943	2362	2137	1985	2081	2823

C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Illuminance at a Distance




C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:



Vertical IsoLux Plot



Lowest(m): 2.0m	Highest(m): 5.0m	Max Lux: 46.5 lx
(10%): 4.6 lx	(20%): 9.3 lx	
(25%): 11.6 lx	(30%): 13.9 lx	
(40%): 18.6 lx	(50%): 23.2 lx	
(60%): 27.9 lx	(70%): 32.5 lx	
(80%): 37.2 lx	(90%): 41.8 lx	


C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:



The Average Illuminance Effective Figure



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°):0.0-180.0: 1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	23.2	24.6	23.5	25.0	25.3	16.3	17.8	16.7	18.1	18.4
3H	24.3	25.6	24.7	26.0	26.3	16.8	18.2	17.2	18.5	18.9
4H	24.6	25.8	25.0	26.2	26.6	17.0	18.3	17.5	18.7	19.1
6H	24.7	25.9	25.2	26.3	26.7	17.1	18.3	17.6	18.7	19.1
8H	24.8	25.8	25.2	26.3	26.7	17.2	18.3	17.6	18.7	19.1
12H	24.8	25.8	25.2	26.2	26.7	17.2	18.2	17.6	18.6	19.1
X=4H Y=2H	23.1	24.4	23.6	24.8	25.2	17.3	18.5	17.7	18.9	19.3
3H	24.3	25.3	24.7	25.8	26.2	17.8	18.9	18.3	19.3	19.7
4H	24.7	25.6	25.1	26.0	26.5	18.1	19.0	18.5	19.4	19.9
6H	24.9	25.7	25.3	26.1	26.6	18.2	19.0	18.7	19.5	19.9
8H	24.9	25.6	25.4	26.1	26.6	18.2	19.0	18.7	19.4	19.9
12H	24.9	25.6	25.4	26.1	26.6	18.3	18.9	18.8	19.4	19.9
X=8H Y=4H	24.6	25.3	25.1	25.8	26.3	18.2	19.0	18.7	19.5	19.9
6H	24.8	25.4	25.3	25.9	26.4	18.4	19.0	18.9	19.5	20.0
8H	24.8	25.4	25.3	25.9	26.4	18.5	19.0	19.0	19.5	20.1
12H	24.8	25.3	25.4	25.8	26.4	18.5	19.0	19.0	19.5	20.1
X=12H Y=4H	24.5	25.2	25.0	25.7	26.2	18.2	18.9	18.7	19.4	19.9
6H	24.7	25.3	25.3	25.8	26.3	18.4	19.0	19.0	19.5	20.0
8H	24.8	25.3	25.3	25.8	26.4	18.5	19.0	19.0	19.5	20.1

Calculate in accordance with CIE 190:2010

 C Plane (°):0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Nick

 Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Utilisation Factor Table(Floor cavity)

Utilisation Factors UF(F)			SHR NOM = 1.25								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.62	0.72	0.80	0.85	0.91	0.96	0.99	1.03	1.05
	0.30		0.54	0.65	0.73	0.79	0.86	0.91	0.95	0.99	1.02
	0.20		0.49	0.60	0.68	0.74	0.82	0.87	0.91	0.96	1.00
0.50	0.50	0.20	0.60	0.70	0.77	0.82	0.88	0.92	0.95	0.99	1.01
	0.30		0.53	0.64	0.71	0.77	0.84	0.88	0.92	0.96	0.99
	0.20		0.49	0.60	0.67	0.72	0.80	0.85	0.89	0.93	0.96
0.30	0.50	0.20	0.58	0.68	0.75	0.79	0.85	0.89	0.92	0.95	0.97
	0.30		0.53	0.63	0.70	0.75	0.81	0.86	0.89	0.93	0.95
	0.20		0.48	0.59	0.66	0.71	0.78	0.83	0.86	0.91	0.93
0.00	0.00	0.00	0.46	0.56	0.63	0.68	0.75	0.79	0.82	0.86	0.88
Rating:5W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980											

Utilisation Factor Table(Wall)

Utilisation Factors UF(W)			SHR NOM = 1.25								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.92	0.74	0.62	0.53	0.42	0.34	0.29	0.22	0.18
	0.30		0.76	0.63	0.54	0.47	0.38	0.31	0.27	0.21	0.17
	0.20		0.66	0.55	0.48	0.42	0.34	0.29	0.25	0.20	0.16
0.50	0.50	0.20	0.88	0.70	0.59	0.50	0.40	0.36	0.27	0.21	0.17
	0.30		0.75	0.61	0.52	0.45	0.36	0.30	0.26	0.20	0.16
	0.20		0.65	0.54	0.47	0.41	0.33	0.28	0.24	0.19	0.16
0.30	0.50	0.20	0.85	0.67	0.56	0.48	0.37	0.31	0.26	0.20	0.16
	0.30		0.73	0.59	0.50	0.44	0.35	0.29	0.24	0.19	0.16
	0.20		0.64	0.53	0.45	0.40	0.32	0.27	0.23	0.18	0.15
0.00	0.00	0.00	0.53	0.43	0.36	0.31	0.24	0.20	0.17	0.13	0.11
Rating:5W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980											

Utilisation Factor Table(Ceiling cavity)

Utilisation Factors UF(C)			SHR NOM = 1.25								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.17	0.18	0.19	0.19	0.20	0.21	0.21	0.22	0.22
	0.30		0.10	0.12	0.13	0.14	0.16	0.17	0.18	0.19	0.20
	0.20		0.06	0.08	0.09	0.11	0.13	0.14	0.15	0.17	0.18
0.50	0.50	0.20	0.16	0.17	0.18	0.19	0.20	0.20	0.21	0.21	0.21
	0.30		0.10	0.12	0.13	0.14	0.16	0.17	0.18	0.19	0.20
	0.20		0.06	0.08	0.09	0.10	0.12	0.14	0.15	0.17	0.18
0.30	0.50	0.20	0.16	0.17	0.17	0.18	0.19	0.19	0.20	0.20	0.21
	0.30		0.10	0.11	0.13	0.14	0.15	0.16	0.17	0.18	0.19
	0.20		0.06	0.07	0.09	0.10	0.12	0.14	0.15	0.16	0.17
0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
Rating:5W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980											

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	179.1	0.2	0.2	0.04	0.04
1.0-2.0	178.9	0.5	0.7	0.12	0.16
2.0-3.0	178.7	0.9	1.5	0.19	0.35
3.0-4.0	178.3	1.2	2.7	0.27	0.62
4.0-5.0	177.9	1.5	4.3	0.35	0.97
5.0-6.0	177.3	1.9	6.1	0.42	1.39
6.0-7.0	176.5	2.2	8.3	0.50	1.89
7.0-8.0	175.6	2.5	10.8	0.57	2.46
8.0-9.0	174.9	2.8	13.7	0.65	3.11
9.0-10.0	174.4	3.2	16.8	0.72	3.83
10.0-11.0	173.8	3.5	20.3	0.79	4.62
11.0-12.0	173.1	3.8	24.1	0.86	5.48
12.0-13.0	172.2	4.1	28.2	0.93	6.41
13.0-14.0	171.3	4.4	32.6	1.00	7.41
14.0-15.0	170.4	4.7	37.2	1.06	8.47
15.0-16.0	169.6	5.0	42.2	1.13	9.60
16.0-17.0	168.7	5.3	47.5	1.20	10.80
17.0-18.0	167.8	5.5	53.0	1.26	12.06
18.0-19.0	166.4	5.8	58.8	1.32	13.37
19.0-20.0	165.0	6.0	64.8	1.37	14.75
20.0-21.0	163.8	6.3	71.1	1.43	16.18
21.0-22.0	162.7	6.5	77.6	1.49	17.67
22.0-23.0	161.4	6.8	84.4	1.54	19.21
23.0-24.0	160.1	7.0	91.4	1.59	20.80
24.0-25.0	158.7	7.2	98.6	1.64	22.44
25.0-26.0	157.5	7.4	106.1	1.69	24.13
26.0-27.0	156.2	7.6	113.7	1.74	25.87
27.0-28.0	154.9	7.8	121.6	1.78	27.66
28.0-29.0	153.5	8.0	129.6	1.83	29.48
29.0-30.0	151.9	8.2	137.8	1.87	31.35
30.0-31.0	150.3	8.4	146.2	1.90	33.25
31.0-32.0	148.7	8.5	154.7	1.94	35.19
32.0-33.0	147.1	8.7	163.4	1.97	37.16
33.0-34.0	145.3	8.8	172.1	2.00	39.16
34.0-35.0	143.5	8.9	181.1	2.03	41.19
35.0-36.0	141.7	9.0	190.1	2.05	43.24

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	139.8	9.1	199.2	2.07	45.32
37.0-38.0	137.7	9.2	208.4	2.09	47.41
38.0-39.0	135.7	9.3	217.7	2.11	49.52
39.0-40.0	133.5	9.3	227.0	2.12	51.64
40.0-41.0	131.5	9.4	236.3	2.13	53.77
41.0-42.0	129.5	9.4	245.7	2.14	55.91
42.0-43.0	127.5	9.4	255.2	2.15	58.06
43.0-44.0	125.5	9.5	264.7	2.16	60.21
44.0-45.0	123.4	9.5	274.1	2.16	62.37
45.0-46.0	120.8	9.5	283.6	2.15	64.52
46.0-47.0	118.0	9.4	293.0	2.14	66.65
47.0-48.0	114.8	9.3	302.3	2.11	68.77
48.0-49.0	110.9	9.1	311.4	2.07	70.84
49.0-50.0	106.1	8.9	320.2	2.01	72.85
50.0-51.0	100.7	8.5	328.7	1.94	74.79
51.0-52.0	94.7	8.1	336.9	1.85	76.64
52.0-53.0	88.5	7.7	344.6	1.75	78.39
53.0-54.0	82.3	7.3	351.8	1.65	80.04
54.0-55.0	76.3	6.8	358.6	1.55	81.59
55.0-56.0	70.5	6.4	365.0	1.45	83.04
56.0-57.0	65.1	6.0	371.0	1.35	84.40
57.0-58.0	60.4	5.6	376.6	1.27	85.67
58.0-59.0	56.1	5.2	381.8	1.19	86.86
59.0-60.0	52.2	4.9	386.7	1.12	87.98
60.0-61.0	48.5	4.6	391.4	1.05	89.04
61.0-62.0	45.1	4.3	395.7	0.99	90.03
62.0-63.0	41.6	4.0	399.8	0.92	90.95
63.0-64.0	38.2	3.7	403.5	0.85	91.80
64.0-65.0	34.8	3.4	407.0	0.78	92.58
65.0-66.0	31.5	3.1	410.1	0.71	93.30
66.0-67.0	28.3	2.8	412.9	0.65	93.95
67.0-68.0	25.5	2.6	415.5	0.59	94.53
68.0-69.0	22.8	2.3	417.9	0.53	95.06
69.0-70.0	20.4	2.1	420.0	0.48	95.54
70.0-71.0	18.2	1.9	421.8	0.43	95.97
71.0-72.0	16.3	1.7	423.5	0.38	96.35

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 2)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
72.0-73.0	14.5	1.5	425.0	0.34	96.70
73.0-74.0	12.9	1.4	426.4	0.31	97.01
74.0-75.0	11.5	1.2	427.6	0.28	97.28
75.0-76.0	10.1	1.1	428.7	0.24	97.53
76.0-77.0	8.9	1.0	429.6	0.22	97.74
77.0-78.0	7.8	0.8	430.5	0.19	97.94
78.0-79.0	6.9	0.7	431.2	0.17	98.10
79.0-80.0	6.0	0.6	431.9	0.15	98.25
80.0-81.0	5.2	0.6	432.4	0.13	98.38
81.0-82.0	4.5	0.5	432.9	0.11	98.49
82.0-83.0	3.8	0.4	433.3	0.09	98.58
83.0-84.0	3.2	0.4	433.7	0.08	98.66
84.0-85.0	2.7	0.3	434.0	0.07	98.73
85.0-86.0	2.3	0.2	434.2	0.06	98.79
86.0-87.0	1.9	0.2	434.4	0.05	98.83
87.0-88.0	1.6	0.2	434.6	0.04	98.87
88.0-89.0	1.3	0.1	434.7	0.03	98.90
89.0-90.0	1.0	0.1	434.8	0.03	98.93
90.0-91.0	0.8	0.1	434.9	0.02	98.95
91.0-92.0	0.7	0.1	435.0	0.02	98.97
92.0-93.0	0.6	0.1	435.1	0.01	98.98
93.0-94.0	0.5	0.1	435.1	0.01	98.99
94.0-95.0	0.4	0.0	435.2	0.01	99.00
95.0-96.0	0.4	0.0	435.2	0.01	99.01
96.0-97.0	0.3	0.0	435.2	0.01	99.02
97.0-98.0	0.3	0.0	435.3	0.01	99.03
98.0-99.0	0.3	0.0	435.3	0.01	99.03
99.0-100.0	0.3	0.0	435.3	0.01	99.04
100.0-101.0	0.3	0.0	435.4	0.01	99.05
101.0-102.0	0.3	0.0	435.4	0.01	99.05
102.0-103.0	0.3	0.0	435.4	0.01	99.06
103.0-104.0	0.3	0.0	435.5	0.01	99.07
104.0-105.0	0.3	0.0	435.5	0.01	99.08
105.0-106.0	0.3	0.0	435.5	0.01	99.09
106.0-107.0	0.4	0.0	435.6	0.01	99.09
107.0-108.0	0.4	0.0	435.6	0.01	99.10

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 3)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
108.0-109.0	0.4	0.0	435.7	0.01	99.11
109.0-110.0	0.4	0.0	435.7	0.01	99.12
110.0-111.0	0.4	0.0	435.7	0.01	99.13
111.0-112.0	0.4	0.0	435.8	0.01	99.14
112.0-113.0	0.5	0.0	435.8	0.01	99.15
113.0-114.0	0.5	0.1	435.9	0.01	99.17
114.0-115.0	0.5	0.1	435.9	0.01	99.18
115.0-116.0	0.6	0.1	436.0	0.01	99.19
116.0-117.0	0.6	0.1	436.0	0.01	99.20
117.0-118.0	0.6	0.1	436.1	0.01	99.22
118.0-119.0	0.6	0.1	436.2	0.01	99.23
119.0-120.0	0.6	0.1	436.2	0.01	99.24
120.0-121.0	0.7	0.1	436.3	0.01	99.26
121.0-122.0	0.7	0.1	436.4	0.01	99.27
122.0-123.0	0.7	0.1	436.4	0.01	99.29
123.0-124.0	0.7	0.1	436.5	0.01	99.30
124.0-125.0	0.7	0.1	436.6	0.02	99.32
125.0-126.0	0.8	0.1	436.6	0.02	99.33
126.0-127.0	0.8	0.1	436.7	0.02	99.35
127.0-128.0	0.8	0.1	436.8	0.02	99.36
128.0-129.0	0.8	0.1	436.8	0.02	99.38
129.0-130.0	0.9	0.1	436.9	0.02	99.40
130.0-131.0	0.9	0.1	437.0	0.02	99.41
131.0-132.0	0.9	0.1	437.1	0.02	99.43
132.0-133.0	0.9	0.1	437.1	0.02	99.45
133.0-134.0	0.9	0.1	437.2	0.02	99.46
134.0-135.0	1.0	0.1	437.3	0.02	99.48
135.0-136.0	1.0	0.1	437.4	0.02	99.50
136.0-137.0	1.0	0.1	437.4	0.02	99.52
137.0-138.0	1.0	0.1	437.5	0.02	99.53
138.0-139.0	1.0	0.1	437.6	0.02	99.55
139.0-140.0	1.1	0.1	437.7	0.02	99.57
140.0-141.0	1.1	0.1	437.7	0.02	99.58
141.0-142.0	1.1	0.1	437.8	0.02	99.60
142.0-143.0	1.1	0.1	437.9	0.02	99.62
143.0-144.0	1.1	0.1	438.0	0.02	99.64

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 4)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
144.0-145.0	1.1	0.1	438.0	0.02	99.65
145.0-146.0	1.2	0.1	438.1	0.02	99.67
146.0-147.0	1.2	0.1	438.2	0.02	99.68
147.0-148.0	1.2	0.1	438.2	0.02	99.70
148.0-149.0	1.2	0.1	438.3	0.02	99.72
149.0-150.0	1.2	0.1	438.4	0.02	99.73
150.0-151.0	1.3	0.1	438.5	0.02	99.75
151.0-152.0	1.3	0.1	438.5	0.02	99.76
152.0-153.0	1.3	0.1	438.6	0.02	99.78
153.0-154.0	1.3	0.1	438.6	0.01	99.79
154.0-155.0	1.3	0.1	438.7	0.01	99.81
155.0-156.0	1.4	0.1	438.8	0.01	99.82
156.0-157.0	1.4	0.1	438.8	0.01	99.84
157.0-158.0	1.4	0.1	438.9	0.01	99.85
158.0-159.0	1.4	0.1	438.9	0.01	99.86
159.0-160.0	1.4	0.1	439.0	0.01	99.87
160.0-161.0	1.4	0.1	439.1	0.01	99.88
161.0-162.0	1.4	0.0	439.1	0.01	99.90
162.0-163.0	1.4	0.0	439.1	0.01	99.91
163.0-164.0	1.4	0.0	439.2	0.01	99.92
164.0-165.0	1.4	0.0	439.2	0.01	99.93
165.0-166.0	1.5	0.0	439.3	0.01	99.94
166.0-167.0	1.5	0.0	439.3	0.01	99.94
167.0-168.0	1.5	0.0	439.3	0.01	99.95
168.0-169.0	1.5	0.0	439.4	0.01	99.96
169.0-170.0	1.5	0.0	439.4	0.01	99.97
170.0-171.0	1.5	0.0	439.4	0.01	99.97
171.0-172.0	1.5	0.0	439.5	0.01	99.98
172.0-173.0	1.5	0.0	439.5	0.00	99.98
173.0-174.0	1.5	0.0	439.5	0.00	99.99
174.0-175.0	1.5	0.0	439.5	0.00	99.99
175.0-176.0	1.5	0.0	439.5	0.00	99.99
176.0-177.0	1.5	0.0	439.5	0.00	100.00
177.0-178.0	1.6	0.0	439.6	0.00	100.00
178.0-179.0	1.6	0.0	439.6	0.00	100.00
179.0-180.0	1.6	0.0	439.6	0.00	100.00

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector: