GEN LED acolyte® Architectural Lighting Solutions

Date | Project

Notes

## AC3 CHANNEL FIXTURE

Our AC3 Channel Fixture features a 115-degree narrow beam angle that is ideal for a controlled spread of light. AC3 Channel Fixture is designed for corner and angled applications and includes a choice of clear, frosted or milky lens. Custom design a fixture with our AC3 Channel Fixture and RibbonLyte products.

- Available for field assembly or factory assembly
- Beam Angle 115°
- Wattage Range from 0.75 W/ft (2.46 W/m) to 8.8 W/ft (28.9 W/m)
- Static White delivered lumen range from 44.1 lm/ft (144.6 lm/m) up to 729.4 lm/ft (2392.5 lm/m)
- Assembled in USA





## HOUSING FINISHES



**Silver** Standard | **Black*** | **White*** | **Custom RAL***

*Additional fee applies

## AVAILABLE LENS FINISHES



**Clear Lens**
92% Light Transmission

**Frosted Lens**
85% Light Transmission

**Milky Lens**
70% Light Transmission


## AVAILABLE COLORS & COLOR TEMPERATURES



1800K | 2000K | 2200K | 2400K | 2700K | 3000K | 3500K | 4000K | 6000K | VW | WD | Red | Amber | Green | Blue | RGBW | RGBA | RGBWW | RGB

## DIMENSIONS

### AC3 Channel with Mounting Clip





**Width:** 0.74 in. (18.8 mm)
**Height:** 0.74 in. (18.8 mm)
**Internal Width:** 0.48 in. (12.2 mm)


### Mounting Clip (Included Accessory)

Material: stainless steel

**Side View**





**Top View**




**Width:** 0.55 in. (14 mm)
**Length:** 0.79 in. (20 mm)
**Height:** 0.79 in. (20 mm)

Note: Each section of channel includes 3 mounting clips.

### Assembled View with End Cap




**Width:** 0.79 in. (20 mm)
**Height:** 0.79 in. (20 mm)

**Note: Exterior channel applications** should be securely attached to the mounting surface with appropriate screws and/or liquid nails. Acolyte strongly recommends field assembly for exterior applications. Use mounting clips for interior applications only.


## SPECIFICATIONS

| | |
|---|---|
| **Beam Angle** | 115° |
| **Lens Type** | Clear Lens, Frosted Lens, Milky Lens |
| **Length** | Channel is sold by the foot and cut to your exact desired length. Required amount of mounting clips included. |
| **Operating Voltage** | 24V |
| **Dimming** | MLV / 0-10 Volt / ELV / DALI / DMX / CASAMBI |
| **Operating Temperature** | -40° F to 158° F (-40° C to 70° C) |
| **Colors** | 1800K, 2000K, 2200K, 2400K, 2700K, 3000K, 3500K, 4000K, 6000K, Red, Amber, Green, Blue, Pixel RGB, RGBW, RGBWW, RGBA, VW, Warm Dim (1800K, 2000K, 2200K, Pixel RGB only available in IP20) |
| **CRI** | 90+ CRI (for Static White LEDs only) |
| **Lamp Life** | L70 at 50,000 Hours |
| **MacAdam Ellipses (SDCM)** | 2-Step Binning (for Static White LEDs only) |
| **Certifications** | UL Listed UL 2108 Issued: 2004/02/27 Ed: 1 Rev: 2014/02/24 Low Voltage Lighting Systems CSA C22.2#9.0 Issued: 1996/06/01 Ed: 1 (R2011) General Requirements for Luminaries; with Gen. Inst. 1: 1997, Gen Inst. 2: 1998. ROHS compliant |

## ACCESSORIES

**End Cap**

Material: ABS




End Cap without hole



End Cap with hole



Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

GEN LED acolyte® Architectural Lighting Solutions

## ORDERING GUIDE

## STEP 1 Complete Channel Part Number

| CHANNEL | LENS | HOUSING COLOR |
|---|---|---|
| CHAC3 | | |
| **CHAC3** - AC3 Channel | **C** - Clear Lens* | **SV** - Silver (default) |
| | **F** - Frosted Lens | **BK** - Black** |
| | **M** - Milky Lens | **WH** - White** |
| | * Clear lens is the default option if not specified. | ** Additional fee applies<br>Consult factory for custom colors |


## STEP 2 Complete RibbonLyte Part Number

| CATEGORY | CRI | RIBBON TYPE & IP RATING | | |
|---|---|---|---|---|
| RB | | | | |
| **RB** - RibbonLyte | **0** - Static Color, Color Changing | **SWS220** - Static White Series 2 IP20 | **RGBWW20** - RGBWW 5-in-1 IP20 | **VWS220** - VW Series 2 IP20 |
| | **90** - 90+ CRI Static White | **SWS265** - Static White Series 2 IP65 | **RGBWS220** - RGBW Series 2 IP20 | **VWS265** - VW Series 2 IP65 |
| | | **SWS268** - Static White Series 2 IP68 | **RGBWS265** - RGBW Series 2 IP65 | **VWS268** - VW Series 2 IP68 |
| | | **SWS269** - Static White Series 2 IP69 | **RGBWS265** - RGBW Series 2 IP65 | **VWS269** - VW Series 2 IP69 |
| **NOTE:** To ensure waterproofing standards are met, IP65, IP68 and IP69 RibbonLyte can NOT be cut in the field. | | **SCS220** - Static Color Series 2 IP20 | **WD20** - Warm Dim IP20 | **RGBADD** - Pixel RGB IP20 |
| | | **SCS265** - Static Color Series 2 IP65 | **WD65** - Warm Dim IP65 | |
| | | **SCS268** - Static Color Series 2 IP68 | **XACTA20** - Xacta RibbonLyte IP20 | |
| | | **SCS269** - Static Color Series 2 IP69 | **LINEA20** - Linea RibbonLyte IP20 | |

| WATTAGE | COLOR | |
|---|---|---|
| | | |
| **0.75** - 0.75 W/ft (2.46 W/m - Static White, Static Color) | **18** - 1800K | **RGB27** - Red, Green, Blue + 2700K |
| **1.0** - 1.0 W/ft (3.3 W/m - Variable White) | **20** - 2000K | **RGB30** - Red, Green, Blue + 3000K |
| **1.5** - 1.5 W/ft (4.9 W/m - Static White, Static Color, Variable White) | **22** - 2200K | **RGB40** - Red, Green, Blue + 4000K |
| **2.2** - 2.2 W/ft (7.2 W/m - Static White, Static Color) | **24** - 2400K | **RGB2465** - Red, Green, Blue + 2400K + 6500K |
| **2.4** - 2.4 W/ft (8 W/m - Static White Linea) | **27** - 2700K | **RGBA** - Red, Green, Blue + Amber |
| **3.0** - 3.0 W/ft (9.8 W/m - Static White, Static Color, Variable White) | **30** - 3000K | **RGBS** - Pixel RGB (SPI) |
| **4.3** - 4.3 W/ft (14 W/m - Static White Linea) | **35** - 3500K | **VW** - Variable White (2000K-6500K) |
| **4.4** - 4.4 W/ft (14.4 W/m - Static White, Static Color, RGBW, RGBWW, RGBA) | **40** - 4000K | **VW1833** - Variable White 1800K-3300K (IP20 only) |
| **4.5** - 4.5 W/ft (14.8 W/m - Static White, Variable White) | **60** - 6000K | **2920** - Warm Dim 2900K-2000K (IP20) |
| **5.2** - 5.2 W/ft (17.1 W/m - Warm Dim) | **R** - Red | **1830** - Warm Dim 3000K-1800K (IP20) |
| **5.0** - 5.0 W/ft (16.4 W/m - Static White, Static Color) | **A** - Amber | **2721** - Warm Dim 2700K-2100K (IP65/IP68/IP69) |
| **5.5** - 5.5 W/ft (18.0 W/m - RGBW, RGBA) | **G** - Green | **Z** - Undecided (For quotes only. Must be chosen before final order.) |
| **6.0** - 6.0 W/ft (19.7 W/m - Static White, Static Color, Variable White) | **B** - Blue | |
| **6.1** - 6.1 W/ft (20 W/m - Variable White Linea, Pixel RGB) | | |
| **8.8** - 8.8 W/ft (28.86 W/m - RGBW, RGBWW, RGBA) | | |

| CONNECTION OPTIONS (See diagrams on the right) | | Custom Length (ft.) |
|---|---|---|
| | | |
| **1** - End Feed Bare Wire Connection | **4** - Soldered Daisy Chain | |
| **2** - Back Feed Bare Wire Connection | **5** - Daisy Chain With IP67 Couplers | |
| **3** - End Feed with IP67 Male Coupler | | |

**1.** (Default) **2.** **3.** **4.**



**Wire Length for 1, 2, 3:**
Standard 12 in. / Custom up to 20 feet

**Wire Length for 4:**
Standard 12 in. / Custom up to 20 feet

**5.** **6.**



**Wire Length for 5:**
Standard 3 in. / Custom up to 3 feet

**Wire Length for 6:**
Standard 3 in. / Custom up to 18 in.


## STEP 3 Complete Assembly Option & Length

| ASSEMBLY OPTION | LENGTH (Standard factory assembled length up to 6 ft 6.7 in. / 2 m) |
|---|---|
| | |
| **FI** - Field Assembly | |
| **FA** - Factory Assembly*** | |

*** Factory assembled runs exceeding 6 ft 6.7 in. (2 m) will be split into multiple daisy chained fixtures.

**DO NOT BUTT END CAPS AGAINST EACH OTHER WHEN CREATING LONGER FIXTURES**

Acolyte STRONGLY SUGGESTS field assembly (without using interior end caps) for direct-view fixtures of more than 6 ft 6.7 in. (2 m) in length. Field assembly without interior end caps will eliminate gaps or dead spots that can be caused by butting interior end caps against each other.




FIELD ASSEMBLY EXAMPLE

FACTORY ASSEMBLY EXAMPLE

## RIBBONLYTE SPECIFICATIONS & COMPATIBILITY

| Available Wattages | Incremental Length | LED Pitch | Color Temp. | Delivered Lumens with Clear Lens | | Delivered Lumens with Frosted Lens | | Delivered Lumens with Milky Lens | | Max Length | Compatible with Channel | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | lm/ft | lm/m | lm/ft | lm/m | lm/ft | lm/m | | IP20 | IP65 | IP68 | IP69 |
| 0.75 Static White Series 2 | 1.97 in. (50 mm) | 48 LEDs/ft (160 LEDs/m) | 1800K | 58 | 190.3 | 53.6 | 175.8 | 44.1 | 144.6 | IP20: 49 ft (15 m) IP65/ IP68/ IP69: 32.8 ft (10 m) | ✓ | ✓ | ✓ | ✓ |
| | | | 2000K | 68.3 | 224 | 63.1 | 207 | 52 | 170.6 | | | | | |
| | | | 2200K | 75.2 | 246.7 | 69.5 | 228 | 57.2 | 187.6 | | | | | |
| | | | 2400K | 78 | 255.8 | 72 | 236.2 | 59.3 | 194.5 | | | | | |
| | | | 2700K | 84.9 | 278.5 | 78.4 | 257.2 | 64.6 | 211.9 | | | | | |
| | | | 3000K | 84.9 | 278.5 | 78.4 | 257.2 | 64.6 | 211.9 | | | | | |
| | | | 3500K | 89.7 | 294.2 | 82.9 | 272 | 68.3 | 224 | | | | | |
| | | | 4000K | 92.5 | 303.4 | 85.4 | 280.1 | 70.4 | 230.9 | | | | | |
| | | | 6000K | 90.4 | 296.5 | 83.5 | 273.9 | 68.8 | 225.7 | | | | | |
| 1.5 Static White Series 2 | 1.97 in. (50 mm) | 48 LEDs/ft (160 LEDs/m) | 1800K | 115.9 | 380.2 | 107.1 | 351.3 | 88.2 | 289.3 | IP20: 49 ft (15 m) IP65/ IP68/ IP69: 32.8 ft (10 m) | ✓ | ✓ | ✓ | ✓ |
| | | | 2000K | 135.2 | 443.5 | 125 | 410 | 102.9 | 337.5 | | | | | |
| | | | 2200K | 150.4 | 493.3 | 139 | 455.9 | 114.5 | 375.6 | | | | | |
| | | | 2400K | 155.9 | 511.4 | 144.1 | 472.6 | 118.7 | 389.3 | | | | | |
| | | | 2700K | 169.7 | 556.6 | 156.8 | 514.3 | 129.2 | 423.8 | | | | | |
| | | | 3000K | 169.7 | 556.6 | 156.8 | 514.3 | 129.2 | 423.8 | | | | | |
| | | | 3500K | 178 | 583.8 | 164.5 | 539.6 | 135.5 | 444.4 | | | | | |
| | | | 4000K | 184.9 | 606.5 | 170.9 | 560.6 | 140.7 | 461.5 | | | | | |
| | | | 6000K | 180.8 | 593 | 167 | 547.8 | 137.6 | 451.3 | | | | | |
| 2.2 Static White Series 2 | 1.97 in. (50 mm) | 48 LEDs/ft (160 LEDs/m) | 1800K | 168 | 51 | 155.2 | 509.1 | 127.8 | 419.2 | IP20: 42 ft (12.8 m) IP65/ IP68/ IP69: 32.8 ft (10 m) | ✓ | ✓ | ✓ | ✓ |
| | | | 2000K | 194.3 | 637.3 | 179.5 | 588.8 | 147.8 | 484.8 | | | | | |
| | | | 2200K | 214.5 | 703.6 | 198.2 | 650.1 | 163.2 | 535.3 | | | | | |
| | | | 2400K | 224.7 | 737 | 207.6 | 680.9 | 170.9 | 560.6 | | | | | |
| | | | 2700K | 242.9 | 796.7 | 224.4 | 736 | 184.8 | 606.1 | | | | | |
| | | | 3000K | 246.9 | 809.8 | 228.1 | 748.2 | 187.9 | 616.3 | | | | | |
| | | | 3500K | 257 | 843 | 237.5 | 779 | 195.6 | 641.6 | | | | | |
| | | | 4000K | 269.2 | 883 | 248.7 | 779 | 204.8 | 671.7 | | | | | |
| | | | 6000K | 259.1 | 849.8 | 239.4 | 785.2 | 197.1 | 646.5 | | | | | |
| 3.0 Static White Series 2 | 1.97 in. (50 mm) | 48 LEDs/ft (160 LEDs/m) | 1800K | 231.8 | 760.4 | 214.2 | 702.6 | 176.4 | 578.6 | IP20: 36 ft (11 m) IP65/ IP68/ IP69: 32.8 ft (10 m) | ✓ | ✓ | ✓ | ✓ |
| | | | 2000K | 270.5 | 887.2 | 249.9 | 819.7 | 205.8 | 675 | | | | | |
| | | | 2200K | 298.1 | 977.7 | 275.4 | 903.3 | 226.8 | 743.9 | | | | | |
| | | | 2400K | 303.1 | 994.1 | 280.1 | 918.6 | 230.6 | 756.5 | | | | | |
| | | | 2700K | 339.6 | 1114 | 313.5 | 1028.1 | 258.1 | 846.7 | | | | | |
| | | | 3000K | 359.1 | 1177.9 | 331.4 | 1087.1 | 273 | 895.3 | | | | | |
| | | | 3500K | 367.5 | 1205.3 | 339.2 | 1112.4 | 279.3 | 916.1 | | | | | |
| | | | 4000K | 367.5 | 1205.3 | 339.2 | 1112.4 | 279.3 | 916.1 | | | | | |
| | | | 6000K | 350.8 | 1150.5 | 323.7 | 1061.8 | 266.6 | 874.5 | | | | | |
| 4.4 Static White Series 2 | 1.97 in. (50 mm) | 48 LEDs/ft (160 LEDs/m) | 1800K | 327.9 | 1075.5 | 302.9 | 993.6 | 249.5 | 818.3 | 28 ft 4 in. (8.64 m) | ✓ | ✓ | ✓ | ✓ |
| | | | 2000K | 384.6 | 1261.4 | 355.3 | 1165.4 | 292.6 | 959.7 | | | | | |
| | | | 2200K | 425 | 1394.1 | 392.7 | 1288.1 | 323.4 | 1060.8 | | | | | |
| | | | 2400K | 441.2 | 1447 | 407.7 | 1337.1 | 335.7 | 1101.2 | | | | | |
| | | | 2700K | 494.4 | 1621.6 | 456.3 | 1496.6 | 375.8 | 1232.5 | | | | | |
| | | | 3000K | 522.8 | 1714.7 | 482.5 | 1582.5 | 397.3 | 1303.2 | | | | | |
| | | | 3500K | 534.9 | 1754.5 | 493.7 | 1619.3 | 406.6 | 1333.5 | | | | | |
| | | | 4000K | 534.9 | 1754.5 | 493.7 | 1619.3 | 406.6 | 1333.5 | | | | | |
| | | | 6000K | 510.6 | 1674.8 | 471.2 | 1545.7 | 388.1 | 1272.9 | | | | | |
| 5.0 Static White Series 2 | 1.4 in. (35.7 mm) | 68 LEDs/ft (224 LEDs/m) | 1800K | 381.8 | 1252.3 | 352.8 | 1157 | 290.5 | 952.8 | IP20: 33 ft 4 in. (10.1 m) IP65/ IP68/ IP69: 32.8 ft (10 m) | ✓ | ✓ | | |
| | | | 2000K | 450.8 | 1478.6 | 416.5 | 1366.1 | 343 | 1125 | | | | | |
| | | | 2200K | 492.2 | 1614.4 | 454.8 | 1491.6 | 374.5 | 1228.4 | | | | | |
| | | | 2400K | 505.1 | 1656.8 | 466.8 | 1531 | 384.4 | 1260.8 | | | | | |
| | | | 2700K | 566.1 | 1856.7 | 522.4 | 1713.6 | 430.2 | 1411.2 | | | | | |
| | | | 3000K | 598.5 | 1963.2 | 552.4 | 1811.9 | 454.9 | 1492.1 | | | | | |
| | | | 3500K | 612.5 | 2008.9 | 565.3 | 1854 | 465.5 | 1526.8 | | | | | |
| | | | 4000K | 612.5 | 2008.9 | 565.3 | 1854 | 465.5 | 1526.8 | | | | | |
| | | | 6000K | 584.6 | 1917.6 | 539.6 | 1769.7 | 444.3 | 1457.4 | | | | | |
| 6.0 Static White Series 2 | 1.4 in. (35.7 mm) | 68 LEDs/ft (224 LEDs/m) | 1800K | 452.6 | 1484.7 | 418.2 | 1371.7 | 344.4 | 1129.6 | 28 ft (8.5 m) | ✓ | ✓ | | |
| | | | 2000K | 524.4 | 1720 | 484.5 | 1589.2 | 399.0 | 1308.7 | | | | | |
| | | | 2200K | 585.1 | 1919.2 | 540.6 | 1773.2 | 445.2 | 1460.3 | | | | | |
| | | | 2400K | 601.6 | 1973.2 | 555.9 | 1823.4 | 457.8 | 1501.6 | | | | | |
| | | | 2700K | 674.2 | 2211.3 | 622.2 | 2040.8 | 512.4 | 1680.7 | | | | | |
| | | | 3000K | 712.9 | 2338.2 | 657.9 | 2157.9 | 541.8 | 1777.1 | | | | | |
| | | | 3500K | 729.4 | 2392.5 | 673.2 | 2208.1 | 554.4 | 1818.4 | | | | | |
| | | | 4000K | 729.4 | 2392.5 | 673.2 | 2208.1 | 554.4 | 1818.4 | | | | | |
| | | | 6000K | 696.3 | 2283.8 | 642.6 | 2107.7 | 529.2 | 1735.8 | | | | | |

## RIBBONLYTE SPECIFICATIONS & COMPATIBILITY

| Available Wattages | Incremental Length | LED Pitch | Color Temp. | Delivered Lumens with Clear Lens | | Delivered Lumens with Frosted Lens | | Delivered Lumens with Milky Lens | | Max Length | Compatible with Channel | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | lm/ft | lm/m | lm/ft | lm/m | lm/ft | lm/m | | IP20 | IP65 | IP68 | IP69 |
| 0.75 Static Color Series 2 | 1.97 in. (50 mm) | 48 LEDs/ft (160 LEDs/m) | Red | 28 | 93 | 26 | 86 | 22 | 70.6 | IP20: 49 ft (15 m) IP65/ IP68: 32.8 ft (10 m) | ✓ | ✓ | ✓ | ✓ |
| | | | Green | 121 | 396 | 112 | 366 | 92 | 301.4 | | | | | |
| | | | Blue | 13 | 43 | 12 | 40 | 10 | 32.7 | | | | | |
| | | | Amber | 23 | 77 | 22 | 71 | 18 | 58.6 | | | | | |
| 1.5 Static Color Series 2 | 1.97 in. (50 mm) | 48 LEDs/ft (160 LEDs/m) | Red | 58 | 190 | 54 | 176 | 44 | 144.7 | IP20: 49 ft (15 m) IP65/ IP68: 32.8 ft (10 m) | ✓ | ✓ | ✓ | ✓ |
| | | | Green | 221 | 724 | 204 | 669 | 168 | 551.1 | | | | | |
| | | | Blue | 25 | 81 | 23 | 75 | 19 | 62 | | | | | |
| | | | Amber | 47 | 154 | 43 | 142 | 36 | 117.1 | | | | | |
| 2.2 Static Color Series 2 | 1.97 in. (50 mm) | 48 LEDs/ft (160 LEDs/m) | Red | 85 | 279 | 79 | 258 | 65 | 212.2 | IP20: 42 ft (12.8 m) IP65/ IP68: 32.8 ft (10 m) | ✓ | ✓ | ✓ | ✓ |
| | | | Green | 293 | 963 | 271 | 889 | 223 | 732.4 | | | | | |
| | | | Blue | 36 | 119 | 34 | 110 | 28 | 90.9 | | | | | |
| | | | Amber | 67 | 219 | 62 | 202 | 51 | 166.7 | | | | | |
| 3.0 Static Color Series 2 | 1.97 in. (50 mm) | 48 LEDs/ft (160 LEDs/m) | Red | 110.4 | 362.1 | 102 | 334.6 | 84 | 275.5 | 32.8 ft (10 m) | ✓ | ✓ | ✓ | ✓ |
| | | | Green | 350.9 | 1151 | 323.9 | 1062.2 | 266.7 | 874.8 | | | | | |
| | | | Blue | 69.1 | 226.6 | 63.8 | 209.1 | 52.5 | 172.2 | | | | | |
| | | | Amber | 80.1 | 262.8 | 74 | 242.4 | 60.9 | 199.8 | | | | | |
| 4.4 Static Color Series 2 | 1.97 in. (50 mm) | 48 LEDs/ft (160 LEDs/m) | Red | 153.8 | 504.5 | 142.1 | 466.2 | 117 | 383.9 | 29 ft (8.8 m) | ✓ | ✓ | ✓ | ✓ |
| | | | Green | 474.1 | 1555.1 | 437.6 | 1435.3 | 360.4 | 1182 | | | | | |
| | | | Blue | 97.3 | 319 | 89.8 | 294.4 | 73.9 | 242.5 | | | | | |
| | | | Amber | 101.3 | 332.2 | 93.5 | 306.7 | 77 | 252.6 | | | | | |
| 5.0 Static Color Series 2 | 1.4 in. (35.7 mm) | 68 LEDs/ft (224 LEDs/m) | Red | 170.2 | 558.2 | 157.3 | 515.8 | 129.5 | 424.8 | 30 ft (9.14 m) | ✓ | ✓ | | |
| | | | Green | 534.2 | 1752.1 | 493 | 1617 | 406 | 1331.7 | | | | | |
| | | | Blue | 110.5 | 362.5 | 102 | 334.6 | 84 | 275.5 | | | | | |
| | | | Amber | 119.7 | 392.7 | 110.5 | 362.4 | 91 | 298.5 | | | | | |
| 6.0 Static Color Series 2 | 1.4 in. (35.7 mm) | 68 LEDs/ft (224 LEDs/m) | Red | 204.2 | 669.8 | 188.7 | 618.9 | 155.4 | 509.7 | 28 ft (8.5 m) | ✓ | ✓ | | |
| | | | Green | 624.4 | 2048.2 | 576.3 | 1890.3 | 474.6 | 1556.7 | | | | | |
| | | | Blue | 127.1 | 416.9 | 117.3 | 384.8 | 96.6 | 316.9 | | | | | |
| | | | Amber | 132.6 | 435 | 122.4 | 401.6 | 100.8 | 330.7 | | | | | |
| 2.4 Static White Linea | 1.97 in. (50 mm) | 146 LEDs/ft (480 LEDs/m) | 2700K | 148.1 | 485.8 | 136.9 | 448.8 | 112.7 | 369.6 | 21.3 ft (6.5 m) | ✓ | n/a | n/a | n/a |
| | | | 3000K | 156.4 | 514.3 | 144.5 | 475.2 | 119 | 391.3 | | | | | |
| | | | 3500K | 183.1 | 601.7 | 169.2 | 555.9 | 139.3 | 457.8 | | | | | |
| | | | 4000K | 183.1 | 601.7 | 169.2 | 555.9 | 139.3 | 457.8 | | | | | |
| 3.0 Static White Linea | 1.97 in. (50 mm) | 146 LEDs/ft (480 LEDs/m) | 2700K | 182.2 | 598 | 168.3 | 552.5 | 138.6 | 455 | 21.3 ft (6.5 m) | ✓ | n/a | n/a | n/a |
| | | | 3000K | 201.5 | 661.5 | 186.2 | 611.2 | 153.3 | 503.3 | | | | | |
| | | | 3500K | 215.3 | 706.6 | 198.9 | 652.8 | 163.8 | 537.6 | | | | | |
| | | | 4000K | 229.1 | 751.6 | 211.7 | 694.5 | 174.3 | 571.9 | | | | | |
| 4.3 Static White Linea | 1.97 in. (50 mm) | 146 LEDs/ft (480 LEDs/m) | 2700K | 297.2 | 973.4 | 274.6 | 899.3 | 226.1 | 740.6 | 24.6 ft (7.5 m) | ✓ | n/a | n/a | n/a |
| | | | 3000K | 308.2 | 1012 | 284.8 | 935 | 234.5 | 770 | | | | | |
| | | | 3500K | 340.4 | 1116.9 | 314.5 | 1031.9 | 259 | 849.8 | | | | | |
| | | | 4000K | 340.4 | 1116.9 | 314.5 | 1031.9 | 259 | 849.8 | | | | | |
| 6.1 Variable White Linea | 1.09 in. (27.78 mm) | 175 LEDs/ft (576 LEDs/m) | 2700K + 6500K | 533.6 | 1750.8 | 493 | 1617.6 | 406 | 1332.1 | 16.4 ft (5 m) | ✓ | n/a | n/a | n/a |

## RIBBONLYTE SPECIFICATIONS & COMPATIBILITY

| Available Wattages | Incremental Length | LED Pitch | Color Temp. | Delivered Lumens with Clear Lens | | Delivered Lumens with Frosted Lens | | Delivered Lumens with Milky Lens | | Max Length | Compatible with Channel | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | lm/ft | lm/m | lm/ft | lm/m | lm/ft | lm/m | | IP20 | IP65 | IP68 | IP69 |
| 1.0 Variable White Series 2 | 1.97 in. (50 mm) | 42 LEDs/ft (140 LEDs/m) | 2000K + 6500K | 78.2 | 257 | 72.3 | 237 | 60 | 200 | 32.8 ft (10 m) | ✓ | ✓ | ✓ | ✓ |
| 3.0 Variable White Series 2 | 1.97 in. (50 mm) | 42 LEDs/ft (140 LEDs/m) | 2000K + 6500K | 220.8 | 725 | 205 | 670 | 168 | 551.2 | 32.8 ft (10 m) | ✓ | ✓ | ✓ | ✓ |
| 6.0 Variable White Series 2 | 1.97 in. (50 mm) | 42 LEDs/ft (140 LEDs/m) | 2000K + 6500K | 415 | 1362 | 382.5 | 1255 | 315 | 1033.5 | 19 ft 8 in. (6 m) | ✓ | ✓ | ✓ | ✓ |
| 4.4 RGBW Series 2 | 1.97 in. (50 mm) | 36 LEDs/ft (120 LEDs/m) | RGBW (all on) | 178.2 | 584.5 | 168.3 | 552.2 | 148.5 | 487.2 | 19 ft 8 in. (6 m) | ✓ | n/a | n/a | |
| 5.5 RGBW Series 2 | 1.97 in. (50 mm) | 36 LEDs/ft (120 LEDs/m) | RGBW (all on) | 292 | 957.9 | 275.8 | 904.9 | 243.3 | 798.5 | IP65: 16 ft 4 in. (5 m) IP68: 19 ft 7.9 in. (6 m) | N/A | ✓ | | |
| 8.8 RGBW Series 2 | 1.97 in. (50 mm) | 36 LEDs/ft (120 LEDs/m) | RGBW (all on) | 483.1 | 1584.6 | 456.3 | 1497.1 | 402.6 | 1320.9 | 16 ft 4 in. (5 m) | ✓ | n/a | n/a | n/a |
| 4.4 5-in-1 RGBWW | 2.46 in. (62.5 mm) | 29 LED/ft (96 LED/m) | RGBWW (all on) | 233.6 | 766.3 | 220.7 | 724 | 194.7 | 638.8 | 16 ft 4 in. (5 m) | ✓ | n/a | n/a | |
| 8.8 5-in-1 RGBWW | 2.46 in. (62.5 mm) | 29 LED/ft (96 LED/m) | RGBWW (all on) | 396 | 1298.9 | 374 | 1227.1 | 330 | 1082.7 | 11 ft 6 in. (3.5 m) | ✓ | n/a | n/a | n/a |
| 6.1 Pixel RGB | 3.94 in. (100 mm) | 18 LEDs/ft (60 LEDs/m) | RGB (all on) | 114.5 | 375.4 | 105.8 | 346.8 | 87.2 | 285.6 | 24 ft 7.2 in. (7.5 m) | ✓ | n/a | n/a | n/a |
| 5.2 Warm Dim | 3.94 in. (100 mm) | 36 LEDs/ft (120 LEDs/m) | WARM DIM | 263.1 | 863 | 244.8 | 803.3 | 201.6 | 661.5 | 16 ft 4 in. (5 m) | ✓ | ✓ | | |

## DIODE VISIBILITY CHART (Data below applies to installations with Milky lens only)



**No Visible Diode = N**

Note: Linea RibbonLyte has no visible diode



**With Visible Diode = Y**

| Static White & Static Color RibbonLyte | | | Color Changing RibbonLyte | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| 0.75/1.5/2.2 | 3.0/4.4 | 5.0/6.0 | 4.4 RGBW Series 2 | 5.5 RGBW Series 2 | 8.8 RGBW Series 2 | 4.4 5-in-1 RGBWW | 8.8 5-in-1 RGBWW | 6.1 Pixel RGB | 5.2 Warm Dim | Variable White 1.0/3.0/6.0 |
| IP20 IP65 IP68 IP69 | IP20 IP65 IP68 IP69 | IP20 IP65 | IP20 | IP65 | IP20 | IP20 | IP20 | IP20 | IP20 IP65 | IP20 IP65 IP68 IP69 |
| N | N | N | Y | Y | Y | Y | Y | Y | Y | Y |

## AVAILABLE DRIVERS / CONTROLLERS AND DIMMING OPTIONS / WIRE GAUGE CHART

### 0-10V/ELV/MLV 3-IN-1



**60W, 96W, 288W 0-10V/ELV/MLV 3-in-1 Dimmable Drivers**

Part No.:
- DRVW2460TRI010 (60 W)
- DRVW2496TRI010 (96 W)
- DRVW24288TRI010 (288 W)

24 VDC
120-277 VAC
IP65, dry/damp/wet locations
UL Listed

### ELV



**60W Dimmable Driver**

Part No.:
- DRVW2460ELV

24 VDC
100-130 VAC
Fits in single-gang switch boxes
IP20, dry locations
UL Recognized

### 0-10V VW/WD



**0-10V Dimmable 96W VW/WD Driver**

Part No.:
- DRVW2496VWWD

24 VDC
100-277 VAC
UL wet-rated, dry/damp/wet locations
UL Listed

### COMPACT



**60W, 96W Non-Dimming Compact Drivers**

Part No.:
- DRV2460C (60 W)
- DRV2496C (96 W)

24 VDC
120-277 VAC
IP20, dry locations
UL Class P

### ATHENA WIRELESS COMPATIBLE



**94W Athena Wireless Compatible Drivers**

Part No.:
- DRVW2494ATH1CH (1 channel)
- DRVW2494ATH2CH (2 channel)

24 VDC
100-277 VAC
Dry locations
UL Listed

### CASAMBI COMPATIBLE DRIVERS



**100W & 200W Casambi Compatible 4 Channel Drivers**

Part No.:
- DRVW24100CAS4CH (100 W)
- DRVW24200CAS4CH (200 W)

24 VDC
100-277 VAC
IP66, dry/damp/wet locations
UL Listed, CE, RoHS, Bluetooth, CASAMBI

### DIMMABLE DALI-2 DRIVERS



**96W DIMMABLE DALI-2 DT6 D4I & DALI-2 DT8 D4I DRIVERS**

Part No.:
- DRVW2496DALI1CH (1 channel)
- DRVW2496DALI2CH (2 channel)

24-26 VDC
120-277 VAC
IP67, dry/damp/wet locations
UL Listed

### DIMMABLE DALI-2 DRIVERS



**75W, 150W, 240W DALI-2 Dimmable Drivers**

Part No.:
- DRVW2475DALI1CH (75 W, 1 channel)
- DRVW24150DALI1CH (150 W, 1 channel)
- DRVW24240DALI1CH (240 W, 1 channel)
- DRV24150DALI2CH (150 W, 2 channels)
- DRV24150DALI4CH (150 W, 4 channels)

24 VDC
120-277 VAC
IP67, damp/wet locations (1-channel drivers only)
IP20, dry location (2-channel & 4-channel drivers only)
CE, RoHS, SELV

### DMX CONTROLLERS, VARIABLE WHITE DIMMER, WARM DIM DIMMER - FOR COLOR CHANGING FIXTURES



**GLASS TOUCH WALL CONTROLLERS**
Part No.:
- AWCRGBWWBK
- AWCVWBK



**1 ZONE WALL CONTROLLER**
Part No.: DMXCTRLG



**5 ZONE WALL CONTROLLER**
Part No.: DMXCTRL



**10 ZONE WALL CONTROLLER**
Part No.: DMXCTRLD



**6 UNIVERSE DMX CONTROLLER**
Part No.: DMXCTRLDR6U



**VARIABLE WHITE DIMMER**
Part No.:
- RFDIMVWWH (White)
- RFDIMVWBK (Black)



**WARM DIM DIMMER**
Part No.:
- RFDIMWDWH (White)
- RFDIMWDBK (Black)



**4 CHANNEL WATERPROOF DMX INTERFACE**
Part No.: DMXINFWLCD4



**5 CHANNEL DMX DECODER**
Part No.: DMXINF5




**DMX OPTO SPLITTER**
Part No.: DMXOS8

### DRIVER AND RIBBONLYTE AT FULL LOAD


| Wattages | 30 | | 60 | | 96 | | 150 | | 200 | | 240 | | 300 | | 320 | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Wire Gauge | Feet | Meters | Feet | Meters | Feet | Meters | Feet | Meters | Feet | Meters | Feet | Meters | Feet | Meters | Feet | Meters |
| 24 AWG / 0.25 mm² | 14 | 4.27 | 9 | 2.74 | 5.5 | 1.68 | 3.75 | 1.14 | 2.75 | 0.84 | 2.25 | 0.69 | 1.75 | 0.53 | 1.75 | 0.53 |
| 22 AWG / 0.34 mm² | 22 | 6.71 | 14 | 4.27 | 9 | 2.74 | 5.75 | 1.75 | 4.5 | 1.37 | 3.5 | 1.07 | 2.75 | 0.84 | 2.75 | 0.84 |
| 20 AWG / 0.5 mm² | 35 | 10.67 | 23 | 7.01 | 14 | 4.27 | 9 | 2.74 | 7 | 2.13 | 5.75 | 1.75 | 4.5 | 1.37 | 4.25 | 1.30 |
| 18 AWG / 0.75 mm² | 56 | 17.07 | 37 | 11.28 | 23 | 7.01 | 15 | 4.57 | 11 | 3.35 | 9 | 2.74 | 7.5 | 2.29 | 7 | 2.13 |
| 16 AWG / 1.5 mm² | 90 | 27.44 | 60 | 18.29 | 37 | 11.28 | 24 | 7.32 | 18 | 5.49 | 15 | 4.57 | 12 | 3.66 | 11 | 3.35 |
| 14 AWG / 2.5 mm² | 142 | 43.29 | 95 | 28.96 | 59 | 17.99 | 38 | 11.59 | 28 | 8.54 | 23 | 7.01 | 19 | 5.79 | 17 | 5.18 |
| 12 AWG / 4 mm² | 226 | 68.90 | 151 | 46.04 | 94 | 28.66 | 60 | 18.29 | 45 | 13.72 | 37 | 11.28 | 30 | 9.15 | 28 | 8.54 |
| 10 AWG / 6 mm² | 360 | 109.76 | 240 | 73.17 | 150 | 45.73 | 96 | 29.27 | 72 | 21.95 | 60 | 18.29 | 48 | 14.63 | 45 | 13.72 |
| 8 AWG / 10 mm² | 574 | 175.00 | 381 | 116.16 | 239 | 72.87 | 153 | 46.65 | 115 | 35.06 | 95 | 28.96 | 76 | 23.17 | 71 | 21.65 |

## WIRING DIAGRAMS - STATIC WHITE / STATIC COLOR / RGBW / RGBA / RGBWW


### 0-10 V





### MLV / ELV





### DMX WIRING WITH STATIC WHITE & STATIC COLOR RIBBONLYTE





### DALI-2 WIRING WITH STATIC WHITE & STATIC COLOR RIBBONLYTE




### STATIC WHITE & STATIC COLOR RIBBONLYTE WIRING WITH ATHENA WIRELESS COMPATIBLE DRIVER




### DMX WITH RGBWW 5-IN-1 RIBBONLYTE




### WIRE COLORS


**STATIC WHITE + STATIC COLOR**
Red Wire (+) Positive
Black Wire (-) Negative

**RGBW + RGBA**
Black Wire (+) Positive
Green Wire (-) goes to Green Channel
Red Wire (-) goes to Red Channel
Blue Wire (-) goes to Blue Channel
White Wire (-) goes to White Channel


**RGBWW**
Black (+) Positive
Green Wire (-) goes to Green Channel
Red Wire (-) goes to Red Channel
Blue Wire (-) goes to Blue Channel
White Wire (-) goes to White Channel 1
Brown Wire (-) goes to White Channel 2

# WIRING DIAGRAMS - VARIABLE WHITE


## 2-CHANNEL VARIABLE WHITE DIMMING





## DMX WIRING WITH VARIABLE WHITE RIBBONLYTE




## DALI-2 WIRING WITH VARIABLE WHITE RIBBONLYTE




## VARIABLE WHITE RIBBONLYTE WIRING WITH ATHENA WIRELESS COMPATIBLE DRIVER




## WIRE COLORS

**VARIABLE WHITE**
Black Wire (+) Positive
Red Wire (-) goes to Warm White Channel
Green Wire (-) goes to Cool White Channel

REV.04NOV2026


### GLOBAL HQ
320 Murray Hill Pkwy
East Rutherford, NJ 07073
U.S.
T: (+1) 212 629 6830
E: Sales-US@GENLEDBrands.com

### EUROPEAN HQ
Hogeweyselaan 119
1382 JK Weesp
Netherlands
T: (+31) 346 235 000
E: SalesEurope@GENLEDBrands.com

### MEINA HQ
PO Box 371378, #823, Building 4EA
Dubai Airport Free Zone
Dubai, UAE
T: (+971) 4 701 7901
E: SalesMEINA@genledbrands.com

### ASIA-PACIFIC HQ
Room 402, Building D
Shenshi Tongchuang Science and Technology Park
No. 16 Hongyin Road
Xingqiang Community, Xinhu Street
Guangming District, Shenzhen, China 518107
T: (+86) 755 8529 0710
E: Sales-Pacific@GENLEDBrands.com