

Report No.: 20230811

Test Time: 2023/8/14 11:42

Luminaire Property

Luminaire Manufacturer: ACOLYTE

Luminaire Category: CHANNEL

Luminaire Description: CHAS23BKRB90SWS2206.030

Lamp Description: BLACK LENS

Luminous Width (mm): 21

Voltage: 24.1 V

Power: 9.21 W

Luminous Length (mm): 500

Luminous Height (mm): 18.2

Current: 0.382 A

Power Factor: 1.000

Photometric Results

CIE Class: Direct

Measurement Flux: 172.8 lm

Downward Ratio: 99%

Horizontal Diffuse Angle(10%,50%): H143.5,H82.7

Vertical Diffuse Angle(10%,50%): V135.3,V70.5

Luminaire Efficacy Rating (LER): 19

Max. Intensity: 96.81 cd

Total Rated Lamp Lumens: 172.8 lm


Efficiency: 100%

Upward Ratio: 1%


Central Intensity: 96.57 cd

Pos of Max. Intensity: H150 V2

Picture Of Luminaire



Luminous Intensity Distribution Curve



C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Nick

Gamma Plane (°):0.0-180.0: 1.0

Test Device: GPM-1800B


Distance: 9.028 m

Humidity: 60%

Inspector:




Luminous Intensity Distribution Curve



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:


Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	101	101	101	99
1	110	106	103	99	108	104	101	98	100	97	94	96	93	91	92	90	89	86
2	102	95	89	84	99	93	87	83	89	85	81	86	82	79	83	80	77	75
3	94	85	78	72	91	83	76	71	80	74	70	77	72	69	75	71	67	65
4	87	76	68	62	85	75	68	62	72	66	61	70	65	60	68	63	59	57
5	81	69	61	55	79	68	60	55	66	59	54	64	58	53	62	57	53	51
6	75	63	55	49	73	62	54	49	60	53	48	58	52	48	57	52	47	46
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41
8	66	53	45	40	64	52	45	40	51	44	40	50	44	39	49	43	39	37
9	62	49	42	36	60	49	41	36	47	41	36	46	40	36	45	40	36	34
10	58	46	38	33	57	45	38	33	44	38	33	43	37	33	42	37	33	31

Spacing Criteria (0-180): 1.07

Spacing Criteria (90-270): 0.96

Spacing Criteria (Diagonal): 1.09



C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Nick

Gamma Plane (°):0.0-180.0: 1.0


Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:

Isocandela (rectangle)




I_{max} (100%): 97 cd

(10%):	10 cd	(20%):	19 cd
(25%):	24 cd	(30%):	29 cd
(40%):	39 cd	(50%):	48 cd
(60%):	58 cd	(70%):	68 cd
(80%):	77 cd	(90%):	87 cd

C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

IsoLux Plot



Mounting Height: 5.0m Max Lux(100%): 3.9 lx

(10%): 0.4 lx	(20%): 0.8 lx
(25%): 1.0 lx	(30%): 1.2 lx
(40%): 1.5 lx	(50%): 1.9 lx
(60%): 2.3 lx	(70%): 2.7 lx
(80%): 3.1 lx	(90%): 3.5 lx

C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick



Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:



Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300

a b c d e f g h




L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	3263	2720	2236	1806	1409	1057	740	446	201
C90	4563	3997	3487	3010	2588	2169	1756	1341	779
C180	2849	2337	1881	1478	1115	786	498	248	53
C270	4027	3519	3070	2664	2287	1954	1587	1241	849

C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick


Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:



Illuminance at a Distance



Vertical IsoLux Plot



Lowest(m): 2.0m	Highest(m): 5.0m	Max Lux: 24.2 lx
(10%): 2.4 lx	(20%): 4.8 lx	
(25%): 6.0 lx	(30%): 7.2 lx	
(40%): 9.7 lx	(50%): 12.1 lx	
(60%): 14.5 lx	(70%): 16.9 lx	
(80%): 19.3 lx	(90%): 21.7 lx	

C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Area Flux Table

Unit: lm


Vertical plane		-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90	Flux(T)	Flux(E)
Horizontal plane	-90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	-80	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.5	0.0
	-70	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.8	1.2
	-60	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	3.7
	-50	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	7.6	7.1
	-40	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	11.8	11.3
	-30	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	16.2	15.7
	-20	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	19.9	19.4
	-10	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	22.0	21.5
	0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	22.1	21.6
	10	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	20.2	19.7
	20	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	16.6	16.1
	30	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	12.4	11.9
	40	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	8.2	7.7
	50	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.7	4.2
	60	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.2	1.7
	70	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.7	0.2
	80	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.0
	90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	171	163
	Flux(E)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0		

C Plane (°): 0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:



The Average Illuminance Effective Figure



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°):0.0-180.0: 1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	21.6	23.0	22.0	23.4	23.7	18.7	20.2	19.1	20.5	20.8
3H	23.0	24.3	23.4	24.6	25.0	19.6	20.9	20.0	21.2	21.6
4H	23.5	24.7	23.9	25.1	25.5	19.8	21.0	20.2	21.4	21.8
6H	23.8	24.9	24.3	25.3	25.7	19.9	21.0	20.3	21.4	21.8
8H	23.9	25.0	24.4	25.4	25.8	19.9	21.0	20.3	21.4	21.8
12H	24.0	25.0	24.4	25.4	25.8	19.9	20.9	20.3	21.3	21.7
X=4H Y=2H	21.7	22.9	22.1	23.3	23.7	19.3	20.5	19.7	20.9	21.3
3H	23.2	24.2	23.7	24.7	25.1	20.3	21.3	20.7	21.7	22.2
4H	23.8	24.7	24.3	25.1	25.6	20.6	21.5	21.0	21.9	22.4
6H	24.2	25.0	24.7	25.4	25.9	20.7	21.5	21.2	22.0	22.5
8H	24.3	25.0	24.8	25.5	26.0	20.7	21.5	21.2	21.9	22.4
12H	24.4	25.0	24.9	25.5	26.0	20.7	21.4	21.2	21.9	22.4
X=8H Y=4H	23.8	24.5	24.3	25.0	25.5	20.8	21.5	21.3	22.0	22.5
6H	24.2	24.8	24.7	25.3	25.8	21.0	21.6	21.5	22.1	22.6
8H	24.4	24.9	24.9	25.4	25.9	21.0	21.5	21.5	22.1	22.6
12H	24.5	24.9	25.0	25.4	26.0	21.0	21.5	21.5	22.0	22.6
X=12H Y=4H	23.8	24.4	24.3	24.9	25.4	20.8	21.4	21.3	21.9	22.4
6H	24.2	24.7	24.7	25.2	25.8	21.0	21.5	21.5	22.0	22.6
8H	24.3	24.8	24.9	25.3	25.9	21.0	21.5	21.6	22.0	22.6

Calculate in accordance with CIE 190:2010

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Utilisation Factor Table(Floor cavity)

Utilisation Factors UF(F)			SHR NOM = 1.00								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.64	0.73	0.80	0.85	0.92	0.96	0.99	1.03	1.05
	0.30		0.57	0.67	0.74	0.79	0.86	0.91	0.95	0.99	1.02
	0.20		0.51	0.61	0.69	0.74	0.82	0.87	0.91	0.96	1.00
0.50	0.50	0.20	0.62	0.71	0.78	0.82	0.88	0.92	0.95	0.99	1.01
	0.30		0.56	0.65	0.72	0.77	0.84	0.88	0.92	0.96	0.99
	0.20		0.51	0.61	0.68	0.73	0.80	0.85	0.89	0.93	0.96
0.30	0.50	0.20	0.60	0.69	0.75	0.80	0.85	0.89	0.92	0.95	0.97
	0.30		0.55	0.64	0.71	0.75	0.82	0.86	0.89	0.93	0.95
	0.20		0.51	0.60	0.67	0.72	0.78	0.83	0.86	0.91	0.93
0.00	0.00	0.00	0.48	0.58	0.64	0.69	0.75	0.79	0.82	0.86	0.89
Rating:9W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980											

Utilisation Factor Table(Wall)

Utilisation Factors UF(W)			SHR NOM = 1.00								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.89	0.73	0.61	0.53	0.42	0.35	0.29	0.23	0.18
	0.30		0.74	0.62	0.53	0.47	0.38	0.32	0.27	0.21	0.18
	0.20		0.64	0.54	0.47	0.42	0.35	0.29	0.25	0.20	0.17
0.50	0.50	0.20	0.86	0.69	0.58	0.51	0.40	0.36	0.28	0.21	0.17
	0.30		0.72	0.60	0.52	0.45	0.36	0.30	0.26	0.20	0.17
	0.20		0.63	0.53	0.46	0.41	0.33	0.28	0.24	0.19	0.16
0.30	0.50	0.20	0.83	0.66	0.56	0.48	0.38	0.31	0.26	0.20	0.16
	0.30		0.71	0.58	0.50	0.44	0.35	0.29	0.25	0.19	0.16
	0.20		0.62	0.52	0.45	0.40	0.32	0.27	0.23	0.18	0.15
0.00	0.00	0.00	0.51	0.42	0.35	0.31	0.24	0.20	0.17	0.13	0.11
Rating:9W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980											

Utilisation Factor Table(Ceiling cavity)

Utilisation Factors UF(C)			SHR NOM = 1.00									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.16	0.18	0.19	0.19	0.20	0.21	0.21	0.22	0.22	
	0.30		0.10	0.12	0.13	0.14	0.16	0.17	0.18	0.19	0.20	
	0.20		0.06	0.08	0.09	0.10	0.13	0.14	0.15	0.17	0.18	
0.50	0.50	0.20	0.16	0.17	0.18	0.19	0.19	0.20	0.20	0.21	0.21	
	0.30		0.10	0.12	0.13	0.14	0.16	0.17	0.18	0.19	0.19	
	0.20		0.06	0.08	0.09	0.10	0.12	0.14	0.15	0.17	0.18	
0.30	0.50	0.20	0.15	0.16	0.17	0.18	0.19	0.19	0.20	0.20	0.21	
	0.30		0.10	0.11	0.13	0.14	0.15	0.16	0.17	0.18	0.19	
	0.20		0.06	0.07	0.09	0.10	0.12	0.13	0.15	0.16	0.17	
0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	
Rating:9W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	96.5	0.1	0.1	0.05	0.05
1.0-2.0	96.5	0.3	0.4	0.16	0.21
2.0-3.0	96.3	0.5	0.8	0.27	0.48
3.0-4.0	96.0	0.6	1.5	0.37	0.85
4.0-5.0	95.6	0.8	2.3	0.48	1.33
5.0-6.0	95.1	1.0	3.3	0.58	1.91
6.0-7.0	94.6	1.2	4.5	0.68	2.59
7.0-8.0	93.9	1.3	5.8	0.78	3.36
8.0-9.0	93.2	1.5	7.3	0.87	4.24
9.0-10.0	92.3	1.7	9.0	0.97	5.21
10.0-11.0	91.4	1.8	10.8	1.06	6.26
11.0-12.0	90.4	2.0	12.8	1.14	7.41
12.0-13.0	89.3	2.1	14.9	1.23	8.63
13.0-14.0	88.2	2.3	17.2	1.31	9.94
14.0-15.0	87.0	2.4	19.6	1.38	11.32
15.0-16.0	85.7	2.5	22.1	1.45	12.78
16.0-17.0	84.4	2.6	24.7	1.52	14.30
17.0-18.0	82.9	2.7	27.4	1.58	15.88
18.0-19.0	81.5	2.8	30.3	1.64	17.52
19.0-20.0	80.0	2.9	33.2	1.69	19.21
20.0-21.0	78.4	3.0	36.2	1.74	20.96
21.0-22.0	76.8	3.1	39.3	1.79	22.75
22.0-23.0	75.2	3.2	42.5	1.83	24.57
23.0-24.0	73.5	3.2	45.7	1.86	26.43
24.0-25.0	71.9	3.3	48.9	1.89	28.32
25.0-26.0	70.2	3.3	52.3	1.92	30.24
26.0-27.0	68.4	3.3	55.6	1.94	32.18
27.0-28.0	66.7	3.4	59.0	1.95	34.13
28.0-29.0	64.9	3.4	62.4	1.97	36.10
29.0-30.0	63.2	3.4	65.8	1.98	38.08
30.0-31.0	61.5	3.4	69.2	1.98	40.06
31.0-32.0	59.7	3.4	72.6	1.98	42.04
32.0-33.0	58.0	3.4	76.1	1.98	44.01
33.0-34.0	56.2	3.4	79.5	1.97	45.98
34.0-35.0	54.4	3.4	82.8	1.96	47.94
35.0-36.0	52.7	3.4	86.2	1.94	49.88

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	51.0	3.3	89.5	1.93	51.81
37.0-38.0	49.3	3.3	92.8	1.91	53.71
38.0-39.0	47.6	3.3	96.1	1.88	55.60
39.0-40.0	46.0	3.2	99.3	1.86	57.45
40.0-41.0	44.4	3.2	102.4	1.83	59.28
41.0-42.0	42.8	3.1	105.5	1.80	61.08
42.0-43.0	41.2	3.1	108.6	1.77	62.85
43.0-44.0	39.7	3.0	111.6	1.73	64.58
44.0-45.0	38.1	2.9	114.5	1.70	66.28
45.0-46.0	36.6	2.9	117.4	1.66	67.93
46.0-47.0	35.1	2.8	120.2	1.62	69.55
47.0-48.0	33.7	2.7	122.9	1.58	71.13
48.0-49.0	32.3	2.7	125.6	1.54	72.67
49.0-50.0	31.0	2.6	128.1	1.49	74.16
50.0-51.0	29.6	2.5	130.6	1.45	75.61
51.0-52.0	28.3	2.4	133.1	1.41	77.02
52.0-53.0	27.0	2.4	135.4	1.36	78.38
53.0-54.0	25.8	2.3	137.7	1.32	79.69
54.0-55.0	24.6	2.2	139.9	1.27	80.96
55.0-56.0	23.4	2.1	142.0	1.22	82.18
56.0-57.0	22.2	2.0	144.0	1.18	83.36
57.0-58.0	21.1	2.0	146.0	1.13	84.49
58.0-59.0	20.0	1.9	147.9	1.08	85.57
59.0-60.0	19.0	1.8	149.7	1.04	86.61
60.0-61.0	17.9	1.7	151.4	0.99	87.60
61.0-62.0	16.9	1.6	153.0	0.94	88.54
62.0-63.0	15.9	1.6	154.5	0.90	89.44
63.0-64.0	15.0	1.5	156.0	0.85	90.29
64.0-65.0	14.1	1.4	157.4	0.81	91.10
65.0-66.0	13.2	1.3	158.7	0.76	91.86
66.0-67.0	12.3	1.2	160.0	0.72	92.58
67.0-68.0	11.5	1.2	161.1	0.67	93.25
68.0-69.0	10.7	1.1	162.2	0.63	93.88
69.0-70.0	9.9	1.0	163.2	0.59	94.47
70.0-71.0	9.1	0.9	164.2	0.55	95.02
71.0-72.0	8.4	0.9	165.1	0.51	95.52

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 2)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
72.0-73.0	7.7	0.8	165.9	0.47	95.99
73.0-74.0	7.0	0.7	166.6	0.43	96.41
74.0-75.0	6.4	0.7	167.3	0.39	96.80
75.0-76.0	5.7	0.6	167.9	0.35	97.16
76.0-77.0	5.1	0.5	168.4	0.32	97.47
77.0-78.0	4.6	0.5	168.9	0.28	97.76
78.0-79.0	4.0	0.4	169.3	0.25	98.01
79.0-80.0	3.5	0.4	169.7	0.22	98.23
80.0-81.0	3.0	0.3	170.1	0.19	98.41
81.0-82.0	2.5	0.3	170.3	0.16	98.57
82.0-83.0	2.1	0.2	170.6	0.13	98.71
83.0-84.0	1.7	0.2	170.7	0.11	98.81
84.0-85.0	1.3	0.1	170.9	0.08	98.90
85.0-86.0	1.0	0.1	171.0	0.06	98.96
86.0-87.0	0.7	0.1	171.1	0.04	99.00
87.0-88.0	0.4	0.0	171.1	0.03	99.03
88.0-89.0	0.2	0.0	171.1	0.01	99.04
89.0-90.0	0.1	0.0	171.1	0.01	99.05
90.0-91.0	0.1	0.0	171.1	0.00	99.05
91.0-92.0	0.0	0.0	171.2	0.00	99.05
92.0-93.0	0.0	0.0	171.2	0.00	99.05
93.0-94.0	0.1	0.0	171.2	0.00	99.06
94.0-95.0	0.1	0.0	171.2	0.00	99.06
95.0-96.0	0.1	0.0	171.2	0.00	99.06
96.0-97.0	0.1	0.0	171.2	0.00	99.07
97.0-98.0	0.1	0.0	171.2	0.00	99.07
98.0-99.0	0.1	0.0	171.2	0.00	99.08
99.0-100.0	0.1	0.0	171.2	0.00	99.08
100.0-101.0	0.1	0.0	171.2	0.01	99.09
101.0-102.0	0.1	0.0	171.2	0.01	99.09
102.0-103.0	0.1	0.0	171.2	0.01	99.10
103.0-104.0	0.1	0.0	171.2	0.01	99.10
104.0-105.0	0.1	0.0	171.3	0.01	99.11
105.0-106.0	0.1	0.0	171.3	0.01	99.11
106.0-107.0	0.1	0.0	171.3	0.01	99.12
107.0-108.0	0.1	0.0	171.3	0.01	99.13

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 3)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
108.0-109.0	0.1	0.0	171.3	0.01	99.14
109.0-110.0	0.1	0.0	171.3	0.01	99.15
110.0-111.0	0.1	0.0	171.3	0.01	99.15
111.0-112.0	0.2	0.0	171.3	0.01	99.16
112.0-113.0	0.2	0.0	171.4	0.01	99.17
113.0-114.0	0.2	0.0	171.4	0.01	99.18
114.0-115.0	0.2	0.0	171.4	0.01	99.19
115.0-116.0	0.2	0.0	171.4	0.01	99.20
116.0-117.0	0.2	0.0	171.4	0.01	99.22
117.0-118.0	0.2	0.0	171.5	0.01	99.23
118.0-119.0	0.2	0.0	171.5	0.01	99.24
119.0-120.0	0.2	0.0	171.5	0.01	99.25
120.0-121.0	0.2	0.0	171.5	0.01	99.26
121.0-122.0	0.2	0.0	171.5	0.01	99.28
122.0-123.0	0.2	0.0	171.6	0.01	99.29
123.0-124.0	0.3	0.0	171.6	0.01	99.30
124.0-125.0	0.3	0.0	171.6	0.01	99.32
125.0-126.0	0.3	0.0	171.6	0.01	99.33
126.0-127.0	0.3	0.0	171.7	0.01	99.35
127.0-128.0	0.3	0.0	171.7	0.01	99.36
128.0-129.0	0.3	0.0	171.7	0.01	99.37
129.0-130.0	0.3	0.0	171.7	0.01	99.39
130.0-131.0	0.3	0.0	171.8	0.02	99.40
131.0-132.0	0.3	0.0	171.8	0.02	99.42
132.0-133.0	0.3	0.0	171.8	0.02	99.44
133.0-134.0	0.3	0.0	171.8	0.02	99.45
134.0-135.0	0.4	0.0	171.9	0.02	99.47
135.0-136.0	0.4	0.0	171.9	0.02	99.48
136.0-137.0	0.4	0.0	171.9	0.02	99.50
137.0-138.0	0.4	0.0	172.0	0.02	99.52
138.0-139.0	0.4	0.0	172.0	0.02	99.53
139.0-140.0	0.4	0.0	172.0	0.02	99.55
140.0-141.0	0.4	0.0	172.0	0.02	99.57
141.0-142.0	0.4	0.0	172.1	0.02	99.58
142.0-143.0	0.4	0.0	172.1	0.02	99.60
143.0-144.0	0.5	0.0	172.1	0.02	99.62

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 4)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
144.0-145.0	0.5	0.0	172.2	0.02	99.63
145.0-146.0	0.5	0.0	172.2	0.02	99.65
146.0-147.0	0.5	0.0	172.2	0.02	99.67
147.0-148.0	0.5	0.0	172.2	0.02	99.68
148.0-149.0	0.5	0.0	172.3	0.02	99.70
149.0-150.0	0.5	0.0	172.3	0.02	99.72
150.0-151.0	0.5	0.0	172.3	0.02	99.73
151.0-152.0	0.5	0.0	172.4	0.02	99.75
152.0-153.0	0.5	0.0	172.4	0.02	99.76
153.0-154.0	0.5	0.0	172.4	0.02	99.78
154.0-155.0	0.5	0.0	172.4	0.01	99.79
155.0-156.0	0.6	0.0	172.5	0.01	99.81
156.0-157.0	0.6	0.0	172.5	0.01	99.82
157.0-158.0	0.6	0.0	172.5	0.01	99.84
158.0-159.0	0.6	0.0	172.5	0.01	99.85
159.0-160.0	0.6	0.0	172.6	0.01	99.86
160.0-161.0	0.6	0.0	172.6	0.01	99.88
161.0-162.0	0.6	0.0	172.6	0.01	99.89
162.0-163.0	0.6	0.0	172.6	0.01	99.90
163.0-164.0	0.6	0.0	172.6	0.01	99.91
164.0-165.0	0.6	0.0	172.7	0.01	99.92
165.0-166.0	0.6	0.0	172.7	0.01	99.93
166.0-167.0	0.6	0.0	172.7	0.01	99.94
167.0-168.0	0.6	0.0	172.7	0.01	99.95
168.0-169.0	0.6	0.0	172.7	0.01	99.96
169.0-170.0	0.6	0.0	172.7	0.01	99.96
170.0-171.0	0.6	0.0	172.7	0.01	99.97
171.0-172.0	0.7	0.0	172.8	0.01	99.98
172.0-173.0	0.7	0.0	172.8	0.01	99.98
173.0-174.0	0.7	0.0	172.8	0.00	99.99
174.0-175.0	0.7	0.0	172.8	0.00	99.99
175.0-176.0	0.7	0.0	172.8	0.00	99.99
176.0-177.0	0.7	0.0	172.8	0.00	100.00
177.0-178.0	0.7	0.0	172.8	0.00	100.00
178.0-179.0	0.7	0.0	172.8	0.00	100.00
179.0-180.0	0.7	0.0	172.8	0.00	100.00

C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector: