

## Floodlight Summary:

Report based on lamp delivering 1000 lumens.


Maximum Intensity		4694.8 cd per klm.
(Luminaire orientation as tested.)		0.0 degrees vertical
		0.0 degrees horizontal
Beam Spread	At 10% of Imax	29.3V x 62.4H
	At 50% of Imax	12.8V x 39.2H
	At 90% of Imax	5.6V x 19.0H
Beam Flux	Total	1000.1 lumens per klm.
	To 10% of Imax	784.2 lumens per klm.
	To 50% of Imax	447.4 lumens per klm.
	To 90% of Imax	109.3 lumens per klm.
	Upward LOR	2.3 %
	Downward LOR	97.7 %
Luminaire Efficiency(Light Output Ratio)		100.0 %

H( $\theta$ ) Range:-90 - 90DEG  
H( $\theta$ ) Interval: 0.5DEG  
Test Speed: LOW  
Temperature:25.3DEG  
Operators:  
Test Date:2024-05-16

V( $\beta$ ) Range:-180 - 180DEG  
V( $\beta$ ) Interval: 0.5DEG  
Test System:GO-2000B\_V1 SYSTEM V2.0.351  
Humidity:65.0%  
Test Distance:8.630m [K=1.0000]  
Remarks:

## LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: Mini Linear DC	TYPE:3000K	WEIGHT:
SPEC.: 10 x 40 Beam Angle	DIM.: 605MM	SERIAL No.:IES002393
MFR.:	SUR.:	Shielding Angle:



DATA OF LAMP		Eff:104.42lm/W	
MODEL		Imax(cd)	8944
NOMINAL POWER(W)	18.24	AVAILABILITY(%)	78.3
RATED VOLTAGE(V)	24	Avai. FLUX(lm)	1492
NOMINAL FLUX(lm)	1905	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	1905
TEST VOLTAGE(V)	24	q @50%(H,V)	39,13DEG

VERTICAL( DEG )	AREA FLUX DIAGRAM																UNIT:lm		F t	F a
	0.18	0.22	0.26	0.29	0.32	0.34	0.37	0.38	0.39	0.39	0.39	0.37	0.35	0.33	0.31	0.27	0.23	0.19	5.56	0.00
45	0.21	0.27	0.33	0.39	0.42	0.44	0.48	0.51	0.51	0.51	0.51	0.48	0.45	0.45	0.43	0.37	0.30	0.23	7.28	0.00
40	0.26	0.34	0.45	0.56	0.63	0.63	0.68	0.73	0.73	0.73	0.74	0.69	0.65	0.70	0.64	0.52	0.40	0.29	10.4	0.00
35	0.32	0.45	0.64	0.86	1.04	1.07	1.11	1.23	1.18	1.20	1.27	1.14	1.16	1.19	1.02	0.78	0.54	0.36	16.6	0.00
30	0.41	0.61	0.94	1.36	1.79	2.12	2.27	2.51	2.46	2.49	2.61	2.42	2.40	2.11	1.65	1.16	0.74	0.45	30.5	0.00
25	0.50	0.81	1.36	2.15	3.08	4.15	4.85	5.12	5.32	5.38	5.30	5.28	4.76	3.67	2.67	1.74	0.99	0.55	57.7	5.60
20	0.60	1.04	1.96	3.59	5.54	7.66	10.4	11.2	11.3	11.4	11.6	11.5	8.81	6.78	4.78	2.66	1.33	0.67	113	88.9
15	0.70	1.29	2.72	5.89	10.9	16.3	23.0	29.4	29.6	29.3	30.2	25.1	18.8	13.6	8.09	3.92	1.70	0.79	251	237
10	0.78	1.50	3.49	8.51	17.6	29.6	42.6	54.7	60.7	60.4	55.8	45.6	33.8	21.9	11.8	5.23	2.05	0.88	457	445
5	0.75	1.45	3.42	8.40	17.4	29.4	42.3	53.6	59.7	59.2	53.5	43.9	33.1	21.6	11.6	5.12	1.99	0.85	447	435
0	0.63	1.16	2.51	5.58	10.5	15.9	22.3	27.6	28.4	27.4	26.4	21.7	17.1	12.7	7.55	3.61	1.53	0.69	233	218
-5	0.50	0.85	1.64	3.11	4.86	6.88	9.47	9.63	9.88	9.68	9.25	9.20	6.97	5.50	4.00	2.19	1.06	0.53	95.2	62.3
-10	0.37	0.58	0.98	1.58	2.38	3.29	3.74	3.78	4.01	3.97	3.68	3.69	3.38	2.55	1.81	1.18	0.67	0.37	42.0	0.00
-15	0.26	0.36	0.56	0.88	1.21	1.42	1.38	1.55	1.54	1.52	1.50	1.32	1.46	1.32	0.97	0.63	0.40	0.25	18.5	0.00
-20	0.17	0.22	0.34	0.48	0.60	0.58	0.53	0.61	0.58	0.57	0.58	0.51	0.59	0.64	0.52	0.37	0.24	0.17	8.28	0.00
-25	0.11	0.15	0.21	0.27	0.30	0.27	0.29	0.31	0.30	0.30	0.30	0.28	0.27	0.32	0.29	0.22	0.16	0.11	4.44	0.00
-30	0.08	0.11	0.14	0.16	0.17	0.17	0.19	0.20	0.19	0.19	0.19	0.18	0.17	0.17	0.17	0.14	0.11	0.08	2.82	0.00
-35	0.07	0.08	0.10	0.11	0.12	0.12	0.13	0.14	0.14	0.14	0.14	0.13	0.12	0.11	0.11	0.10	0.08	0.07	2.00	0.00
-40	0.07	0.08	0.10	0.11	0.12	0.12	0.13	0.14	0.14	0.14	0.14	0.13	0.12	0.11	0.11	0.10	0.08	0.07	2.00	0.00
-45	0.07	0.08	0.10	0.11	0.12	0.12	0.13	0.14	0.14	0.14	0.14	0.13	0.12	0.11	0.11	0.10	0.08	0.07	2.00	0.00
-45 -40 -35 -30 -25 -20 -15 -10 HORIZONTAL( DEG ) 10 15 20 25 30 35 40 45																				
F t	6.91	11.5	22.0	44.2	78.8	120	166	203	217	215	204	174	134	95.5	58.4	30.2	14.5	7.53	1803	---
F a	0.00	0.00	0.00	20.9	59.2	102	149	185	199	197	187	157	116	76.7	38.2	4.91	0.00	0.00	---	1492


one-half-peak spread: U:6.0,D:6.9 , L:19.3,R:20.4 Beam Type: Type 4 x 3 (H x V)

H(B) Range:-90 - 90DEG  
H(B) Interval: 0.5DEG  
Test Speed: LOW  
Temperature:25.3DEG  
Operators:  
Test Date:2024-05-16

V(B) Range:-180 - 180DEG  
V(B) Interval: 0.5DEG  
Test System: GO-2000B\_V1 SYSTEM V2.0.351  
Humidity:65.0%  
Test Distance:8.630m [K=1.0000]  
Remarks:

## ISOCANDELA DIAGRAM

NAME: Mini Linear DC	TYPE:3000K	WEIGHT:
SPEC.: 10 x 40 Beam Angle	DIM.: 605MM	SERIAL No.:IES002393
MFR.:	SUR.:	Shielding Angle:




H( $\theta$ ) Range:-90 - 90DEG  
H( $\theta$ ) Interval: 0.5DEG  
Test Speed: LOW  
Temperature:25.3DEG  
Operators:  
Test Date:2024-05-16

V(B) Range:-180 - 180DEG  
V(B) Interval: 0.5DEG  
Test System: GO-2000B\_V1 SYSTEM V2.0.351  
Humidity:65.0%  
Test Distance:8.630m [K=1.0000]  
Remarks:

## ISOLUX DIAGRAM


NAME: Mini Linear DC	TYPE:3000K	WEIGHT:
SPEC.: 10 x 40 Beam Angle	DIM.: 605MM	SERIAL No.:IES002393
MFR.:	SUR.:	Shielding Angle:



H( $\theta$ ) Range:-90 - 90DEG  
H( $\theta$ ) Interval: 0.5DEG  
Test Speed: LOW  
Temperature:25.3DEG  
Operators:  
Test Date:2024-05-16

V(B) Range:-180 - 180DEG  
V(B) Interval: 0.5DEG  
Test System:GO-2000B\_V1 SYSTEM V2.0.351  
Humidity:65.0%  
Test Distance:8.630m [K=1.0000]  
Remarks:

Planar Illuminance Curve




H( $\beta$ ) Range:-90 - 90DEG  
H( $\beta$ ) Interval: 0.5DEG  
Test Speed: LOW  
Temperature:25.3DEG  
Operators:  
Test Date:2024-05-16

V(B) Range:-180 - 180DEG  
V(B) Interval: 0.5DEG  
Test System: GO-2000B\_V1 SYSTEM V2.0.351  
Humidity:65.0%  
Test Distance:8.630m [K=1.0000]  
Remarks:

## AAI CURVES

NAME: Mini Linear DC	TYPE:3000K	WEIGHT:
SPEC. 10 x 40 Beam Angle	DIM.: 605MM	SERIAL No.:IES002393
MFR.:	SUR.:	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H( $\theta$ ) Range:-90 - 90DEG  
H( $\theta$ ) Interval: 0.5DEG  
Test Speed: LOW  
Temperature:25.3DEG  
Operators:  
Test Date:2024-05-16

V(B) Range:-180 - 180DEG  
V(B) Interval: 0.5DEG  
Test System:GO-2000B\_V1 SYSTEM V2.0.351  
Humidity:65.0%  
Test Distance:8.630m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: Mini Linear DC	TYPE:3000K	WEIGHT:
SPEC.: 10 x 40 Beam Angle	DIM.: 605MM	SERIAL No.:IES002393
MFR.:	SUR.:	Shielding Angle:

Table--1

UNIT: cd

H(°) \ V(°)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	6.84	6.21	5.76	5.64	5.88	6.60	7.78	9.27	10.9	12.5	13.7	14.6	15.0	15.0	14.5	13.6	13.0	12.5	12.5
-170	6.84	6.13	5.63	5.43	5.53	5.97	6.71	7.63	8.61	9.55	10.3	11.0	11.4	11.8	12.0	12.3	13.1	14.1	15.0
-160	6.84	6.07	5.52	5.24	5.17	5.30	5.59	5.94	6.25	6.51	6.73	6.94	7.36	8.58	10.00	11.3	12.5	13.2	13.5
-150	6.84	6.03	5.44	5.06	4.85	4.75	4.65	4.52	4.27	3.88	3.56	4.17	5.01	5.97	6.93	7.84	8.59	9.08	9.25
-140	6.84	6.00	5.39	4.94	4.63	4.35	4.03	3.61	3.02	2.67	2.59	2.65	2.86	3.19	3.57	4.04	4.41	4.62	4.64
-130	6.84	6.00	5.37	4.86	4.47	4.12	3.73	3.24	2.88	2.65	2.41	2.15	1.92	1.70	1.65	1.68	1.70	1.68	1.61
-120	6.84	6.02	5.38	4.84	4.39	4.00	3.62	3.30	3.22	3.09	2.91	2.70	2.46	2.20	1.99	1.79	1.62	1.48	1.36
-110	6.84	6.06	5.40	4.85	4.37	3.92	3.52	3.44	3.48	3.49	3.48	3.46	3.41	3.36	3.32	3.29	3.27	3.27	3.29
-100	6.84	6.14	5.49	4.90	4.34	3.84	3.37	3.41	3.48	3.54	3.59	3.64	3.70	3.72	3.72	3.73	3.73	3.73	3.74
-90	6.84	6.25	5.65	5.06	4.47	3.87	3.28	3.29	3.30	3.31	3.32	3.33	3.34	3.34	3.33	3.33	3.32	3.31	3.31
-80	6.84	6.37	5.84	5.26	4.79	4.14	3.22	3.10	3.02	2.95	2.88	2.81	2.72	2.63	2.54	2.45	2.36	2.27	2.18
-70	6.84	6.51	6.42	6.30	5.57	4.77	3.77	3.43	3.50	3.55	3.58	3.58	3.55	3.62	3.74	3.84	3.90	3.92	3.91
-60	6.84	6.66	7.36	7.02	6.73	6.24	5.46	4.60	4.98	5.35	5.69	5.98	6.16	6.33	6.63	6.84	6.92	6.91	6.79
-50	6.84	7.13	7.91	8.19	8.61	8.90	8.65	7.51	7.33	8.26	9.13	9.90	10.5	10.7	11.2	11.6	11.9	11.8	11.6
-40	6.84	7.84	8.60	9.72	11.3	12.7	13.6	13.5	12.1	12.4	14.6	16.7	18.8	20.0	19.1	20.6	21.3	21.3	20.5
-30	6.84	8.33	9.41	11.5	14.3	17.4	20.1	22.3	23.6	24.0	24.9	34.4	46.7	57.2	57.6	46.5	52.2	53.3	47.9
-20	6.84	8.64	10.2	13.4	17.9	22.9	28.0	33.7	40.2	48.8	63.5	91.8	138	204	271	310	294	335	307
-10	6.84	8.89	11.0	15.1	21.2	28.1	36.5	46.8	60.7	82.4	124	224	440	825	1216	1597	2180	1938	1964
0	6.84	9.09	11.5	16.5	23.8	32.6	44.0	58.5	79.4	113	181	368	899	2073	3887	5993	7710	8620	8876
10	6.84	9.05	11.4	15.9	22.5	30.2	39.7	51.7	68.3	94.8	144	257	492	896	1303	1679	2316	2152	2060
20	6.84	8.95	11.0	14.9	20.3	26.7	33.8	42.3	53.3	68.9	94.8	141	212	291	370	433	445	484	442
30	6.84	8.77	10.5	13.5	17.6	22.4	27.6	33.1	39.2	46.3	56.6	72.7	91.4	109	114	106	118	120	112
40	6.84	8.40	9.94	12.1	15.0	18.4	21.7	24.9	27.9	31.8	36.9	42.4	47.3	50.6	50.8	54.7	57.0	57.7	56.6
50	6.84	7.78	9.42	10.8	12.6	14.7	16.7	18.4	20.4	22.8	25.3	27.6	29.8	31.2	33.0	34.5	35.4	35.8	35.6
60	6.84	7.36	8.96	9.71	10.7	11.8	12.9	13.8	15.0	16.1	17.2	18.2	19.1	20.0	20.9	21.7	22.2	22.4	22.3
70	6.84	7.24	8.03	8.91	9.33	9.81	10.3	10.7	11.2	11.6	12.0	12.2	12.4	12.7	13.0	13.2	13.3	13.3	13.2
80	6.84	7.09	7.37	7.67	8.15	8.51	8.66	8.78	8.88	8.96	9.01	9.05	9.07	9.12	9.15	9.17	9.17	9.14	9.10
90	6.84	6.94	7.04	7.15	7.25	7.35	7.46	7.43	7.41	7.39	7.37	7.34	7.32	7.23	7.14	7.05	6.96	6.87	6.78
100	6.84	6.79	6.72	6.65	6.57	6.50	6.40	6.23	6.06	5.91	5.76	5.63	5.49	5.40	5.32	5.27	5.23	5.20	5.17
110	6.84	6.65	6.47	6.29	6.07	5.87	5.67	5.47	5.31	5.18	5.08	4.99	4.91	4.88	4.86	4.83	4.80	4.77	4.74
120	6.84	6.54	6.27	5.97	5.71	5.49	5.36	5.29	5.24	5.25	5.25	5.22	5.16	5.10	5.11	5.11	5.06	4.98	4.85
130	6.84	6.43	6.08	5.75	5.52	5.42	5.43	5.60	5.85	6.12	6.40	6.72	7.07	7.46	7.92	8.34	8.72	8.96	8.97
140	6.84	6.36	5.94	5.62	5.50	5.54	5.83	6.36	7.07	7.84	8.66	9.62	10.7	11.8	12.9	13.9	14.7	15.3	15.6
150	6.84	6.29	5.84	5.58	5.55	5.83	6.43	7.33	8.46	9.76	11.2	12.6	14.0	15.2	16.2	16.8	17.2	17.4	17.4
160	6.84	6.25	5.79	5.58	5.67	6.15	7.04	8.26	9.71	11.3	12.9	14.5	15.9	16.8	17.4	17.9	18.3	18.5	18.6
170	6.84	6.22	5.76	5.61	5.80	6.44	7.52	8.95	10.6	12.2	13.7	15.0	15.9	16.6	17.0	17.0	16.9	17.3	18.3
180	6.84	6.21	5.76	5.64	5.88	6.60	7.78	9.27	10.9	12.5	13.7	14.6	15.0	15.0	14.5	13.6	13.0	12.5	12.5

H(h) Range:-90 - 90DEG  
 H(h) Interval: 0.5DEG  
 Test Speed: LOW  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2024-05-16

V(B) Range:-180 - 180DEG  
 V(B) Interval: 0.5DEG  
 Test System: GO-2000B\_V1 SYSTEM V2.0.351  
 Humidity:65.0%  
 Test Distance:8.630m [K=1.0000]  
 Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: Mini Linear DC	TYPE:3000K	WEIGHT:
SPEC.: 10 x 40 Beam Angle	DIM.: 605MM	SERIAL No.:IES002393
MFR.:	SUR.:	Shielding Angle:

Table--2

UNIT: cd

H(°) V(°)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	11.2	10.4	9.91	9.34	8.47	7.39	6.26	5.22	4.32	3.61	3.18	3.07	3.12	3.25	3.30	3.19	2.93	2.54	
-170	14.7	13.5	12.5	11.1	9.48	7.97	6.45	5.16	4.16	3.47	3.09	3.02	3.10	3.25	3.31	3.20	2.93	2.54	
-160	13.1	12.4	11.3	10.0	8.66	7.21	5.74	4.55	3.71	3.19	2.96	2.97	3.11	3.26	3.31	3.20	2.92	2.54	
-150	9.13	8.69	7.98	7.03	6.02	5.04	4.20	3.61	3.15	2.92	2.89	2.98	3.15	3.30	3.31	3.19	2.90	2.54	
-140	4.67	4.50	4.18	3.75	3.34	2.99	2.77	2.69	2.73	2.81	2.91	3.08	3.24	3.33	3.30	3.14	2.87	2.54	
-130	1.72	1.78	1.81	1.82	1.87	2.06	2.25	2.47	2.68	2.90	3.08	3.23	3.33	3.34	3.26	3.09	2.82	2.54	
-120	1.50	1.65	1.84	2.04	2.25	2.49	2.73	2.94	3.12	3.25	3.32	3.37	3.36	3.31	3.19	3.00	2.77	2.54	
-110	3.29	3.30	3.33	3.38	3.43	3.50	3.52	3.54	3.53	3.49	3.44	3.39	3.32	3.20	3.06	2.89	2.72	2.54	
-100	3.73	3.72	3.71	3.70	3.69	3.67	3.60	3.53	3.45	3.37	3.28	3.19	3.08	2.98	2.87	2.76	2.65	2.54	
-90	3.24	3.17	3.11	3.04	2.97	2.91	2.88	2.86	2.83	2.81	2.78	2.76	2.72	2.69	2.65	2.61	2.58	2.54	
-80	2.17	2.16	2.15	2.15	2.14	2.13	2.19	2.25	2.31	2.37	2.43	2.48	2.52	2.53	2.55	2.55	2.53	2.54	
-70	3.81	3.68	3.51	3.31	3.08	2.93	2.95	2.93	2.86	2.77	2.69	2.68	2.70	2.67	2.59	2.54	2.52	2.54	
-60	6.78	6.67	6.46	6.15	5.74	5.54	5.38	5.09	4.74	4.34	3.93	3.84	3.64	3.31	2.89	2.62	2.53	2.54	
-50	11.7	11.6	11.2	10.6	10.1	9.90	9.38	8.61	7.73	6.78	6.31	6.14	5.43	4.46	3.55	2.83	2.54	2.54	
-40	21.1	20.8	19.9	18.3	19.8	18.8	16.7	14.3	12.1	10.9	10.5	9.46	8.02	6.12	4.43	3.11	2.56	2.54	
-30	52.2	50.5	44.5	59.5	61.0	50.2	36.7	26.1	22.0	19.1	16.4	13.8	11.1	8.17	5.43	3.49	2.60	2.54	
-20	329	283	310	287	228	153	106	67.8	44.4	31.7	24.1	18.8	14.3	10.3	6.46	3.89	2.64	2.54	
-10	1846	2079	1559	1345	1041	621	298	146	78.6	48.0	32.8	23.9	17.5	12.1	7.36	4.22	2.67	2.54	
0	8703	8007	6593	4650	2748	1339	546	228	111	62.7	40.3	28.1	19.9	13.5	7.96	4.40	2.69	2.54	
10	2159	2484	1901	1561	1167	698	346	175	94.9	57.5	38.5	27.4	19.7	13.5	8.16	4.64	2.83	2.54	
20	497	467	483	434	352	261	177	110	70.1	47.3	34.0	25.2	18.5	12.9	7.98	4.70	2.96	2.54	
30	122	119	108	124	125	109	86.7	66.3	49.0	37.0	28.6	22.0	16.5	11.6	7.54	4.62	3.05	2.54	
40	57.9	57.4	55.4	51.8	54.2	51.6	46.2	39.9	34.0	28.5	23.1	18.4	14.1	10.1	6.93	4.50	3.13	2.54	
50	35.9	35.5	34.6	33.0	31.4	30.4	28.4	26.2	23.6	21.0	18.1	14.8	11.6	8.72	6.29	4.38	3.20	2.54	
60	22.4	22.2	21.6	20.9	20.0	19.2	18.4	17.5	16.3	15.0	13.7	11.7	9.51	7.49	5.67	4.26	3.24	2.54	
70	13.3	13.2	13.1	12.9	12.5	12.1	11.9	11.6	11.2	10.8	10.3	9.48	7.95	6.54	5.26	4.18	3.26	2.54	
80	9.04	8.96	8.86	8.74	8.60	8.46	8.47	8.45	8.41	8.33	8.24	8.05	6.98	5.96	4.99	4.09	3.27	2.54	
90	6.78	6.78	6.78	6.78	6.77	6.77	6.81	6.85	6.89	6.93	6.97	7.01	6.27	5.52	4.78	4.03	3.29	2.54	
100	5.18	5.19	5.21	5.24	5.28	5.33	5.44	5.56	5.69	5.84	6.00	6.12	5.68	5.18	4.62	4.00	3.31	2.54	
110	4.77	4.80	4.84	4.86	4.88	4.90	4.96	5.04	5.12	5.22	5.36	5.41	5.16	4.85	4.45	3.94	3.31	2.54	
120	4.99	5.09	5.16	5.18	5.17	5.20	5.23	5.22	5.19	5.16	5.19	5.00	4.78	4.55	4.27	3.86	3.29	2.54	
130	8.98	8.77	8.41	8.00	7.54	7.10	6.70	6.34	6.03	5.74	5.32	4.83	4.55	4.32	4.10	3.78	3.26	2.54	
140	15.3	14.8	14.0	12.9	11.8	10.7	9.53	8.52	7.68	6.65	5.53	4.79	4.36	4.14	3.94	3.67	3.22	2.54	
150	17.4	17.2	16.8	16.1	15.1	13.8	12.3	10.9	8.78	6.92	5.56	4.67	4.18	3.95	3.79	3.57	3.16	2.54	
160	18.6	18.5	18.0	17.5	16.8	15.6	13.0	10.5	8.29	6.50	5.17	4.35	3.92	3.74	3.64	3.45	3.10	2.54	
170	18.3	17.9	17.9	16.7	14.6	12.4	10.4	8.42	6.72	5.33	4.34	3.79	3.55	3.50	3.47	3.32	3.02	2.54	
180	11.2	10.4	9.91	9.34	8.47	7.39	6.26	5.22	4.32	3.61	3.18	3.07	3.12	3.25	3.30	3.19	2.93	2.54	

H<sub>(h)</sub> Range:-90 - 90DEG  
H<sub>(h)</sub> Interval: 0.5DEG  
Test Speed: LOW  
Temperature:25.3DEG  
Operators:  
Test Date:2024-05-16

V(B) Range:-180 - 180DEG  
V(B) Interval: 0.5DEG  
Test System:GO-2000B\_V1 SYSTEM V2.0.351  
Humidity:65.0%  
Test Distance:8.630m [K=1.0000]  
Remarks: