

Report No.:

Test Time: 2018/8/30 14:26

Luminaire Property

Luminaire Manufacturer:

Luminaire Category: RIBBONLYTE

Luminaire Description: RBS2246.027PH 1FT(320mm)

Luminous Length (mm): 320

Luminous Width (mm): 10

Luminous Height (mm): 1

Voltage: 24.0 V

Current: 0.260 A

Power: 6.24 W

Power Factor: 1.000

Photometric Results

CIE Class: Direct

Measurement Flux: 760.2 lm

Downward Ratio: 99%

Horizontal Diffuse Angle(50%): H116.6

Vertical Diffuse Angle(50%): V116.5

Luminaire Efficacy Rating (LER): 122

Max. Intensity: 254.64 cd

Total Rated Lamp Lumens: 760.2 lm


Efficiency: 100%

Upward Ratio: 1%


Central Intensity: 253.7 cd

Pos of Max. Intensity: H150 V0

Picture Of Luminaire



Luminous Intensity Distribution Curve



Average Diffuse Angle(50%): 116.5° Unit: cd

— C0-C180 — C90-C270

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:


Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	99
1	108	104	99	95	106	101	97	94	97	94	91	93	90	88	89	87	85	83
2	98	90	83	77	96	88	82	76	84	79	74	81	77	73	78	74	71	69
3	90	79	71	64	87	77	70	63	74	68	62	71	66	61	69	64	60	58
4	82	70	61	54	80	68	60	54	66	58	53	63	57	52	61	56	51	49
5	75	62	53	46	73	61	52	46	59	51	45	57	50	45	55	49	44	42
6	69	56	47	40	67	55	46	40	53	45	40	51	44	39	50	44	39	37
7	64	51	42	35	62	50	41	35	48	41	35	47	40	35	45	39	34	32
8	60	46	37	32	58	45	37	31	44	37	31	43	36	31	41	35	31	29
9	56	42	34	28	54	42	34	28	40	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	35	29	25	23

Spacing Criteria (0-180): 1.28

Spacing Criteria (90-270): 1.28

Spacing Criteria (Diagonal): 1.40



C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:

Isocandela (rectangle)



Imax (100%): 255 cd

(10%): 25 cd	(20%): 51 cd
(25%): 64 cd	(30%): 76 cd
(40%): 102 cd	(50%): 127 cd
(60%): 153 cd	(70%): 178 cd
(80%): 204 cd	(90%): 229 cd

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:

IsoLux Plot



C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1800B

Distance: 9.028 m



Humidity: 60%

Inspector:

Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300

a b c d e f g h



L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	70775	68882	66577	63341	59109	53205	45071	33601	18187
C90	77685	76902	75747	73863	71285	67146	60295	41714	11805
C180	71040	69321	67173	64279	60217	54610	46830	35909	21199
C270	78147	77517	76485	75044	72732	69030	63732	54976	21498

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:

Illuminance at a Distance



C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:

Vertical IsoLux Plot



Lowest(m): 2.0m	Highest(m): 5.0m	Max Lux: 63.4 lx
(10%): 6.3 lx	(20%): 12.7 lx	
(25%): 15.9 lx	(30%): 19.0 lx	
(40%): 25.4 lx	(50%): 31.7 lx	
(60%): 38.1 lx	(70%): 44.4 lx	
(80%): 50.7 lx	(90%): 57.1 lx	

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1800B

Distance: 9.028 m


Humidity: 60%

Inspector:

Unit: lm

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

The Average Illuminance Effective Figure



C Plane (°):0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	28.0	29.6	28.4	30.0	30.3	27.7	29.4	28.1	29.7	30.0
3H	29.8	31.3	30.2	31.7	32.0	29.4	30.9	29.8	31.2	31.6
4H	30.5	31.9	30.9	32.2	32.6	30.0	31.4	30.4	31.8	32.1
6H	30.9	32.2	31.4	32.6	33.0	30.3	31.6	30.7	32.0	32.4
8H	31.1	32.3	31.5	32.7	33.1	30.3	31.6	30.8	32.0	32.4
12H	31.1	32.3	31.6	32.7	33.2	30.3	31.5	30.8	31.9	32.3
X=4H Y=2H	28.6	30.0	29.0	30.3	30.7	28.4	29.8	28.8	30.1	30.5
3H	30.6	31.8	31.0	32.2	32.6	30.3	31.5	30.7	31.9	32.3
4H	31.4	32.5	31.8	32.9	33.3	31.0	32.0	31.4	32.4	32.9
6H	32.0	32.9	32.4	33.3	33.8	31.4	32.3	31.8	32.7	33.2
8H	32.1	33.0	32.6	33.4	33.9	31.4	32.3	31.9	32.7	33.2
12H	32.2	33.0	32.7	33.5	34.0	31.4	32.2	31.9	32.7	33.2
X=8H Y=4H	31.6	32.5	32.1	33.0	33.4	31.3	32.1	31.7	32.6	33.1
6H	32.3	33.0	32.8	33.5	34.0	31.7	32.5	32.3	33.0	33.5
8H	32.5	33.1	33.0	33.7	34.2	31.9	32.5	32.4	33.0	33.5
12H	32.6	33.2	33.2	33.7	34.3	31.9	32.5	32.4	33.0	33.5
X=12H Y=4H	31.7	32.4	32.1	32.9	33.4	31.3	32.1	31.8	32.6	33.0
6H	32.3	33.0	32.8	33.4	34.0	31.8	32.5	32.3	32.9	33.5
8H	32.6	33.1	33.1	33.6	34.2	31.9	32.5	32.5	33.0	33.6

Calculate in accordance with CIE 190:2010

C Plane (°):0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Aaron

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Utilisation Factor Table(Floor cavity)

Utilisation Factors UF(F)			SHR NOM = 1.25								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.55	0.66	0.73	0.79	0.86	0.92	0.95	1.00	1.03
	0.30		0.47	0.58	0.66	0.72	0.80	0.86	0.90	0.96	0.99
	0.20		0.42	0.52	0.60	0.66	0.75	0.81	0.86	0.92	0.96
0.50	0.50	0.20	0.54	0.64	0.71	0.76	0.83	0.88	0.91	0.96	0.99
	0.30		0.47	0.57	0.64	0.70	0.78	0.83	0.87	0.92	0.96
	0.20		0.41	0.52	0.59	0.65	0.73	0.79	0.83	0.89	0.93
0.30	0.50	0.20	0.52	0.62	0.69	0.73	0.80	0.85	0.88	0.92	0.95
	0.30		0.46	0.56	0.63	0.68	0.76	0.81	0.84	0.89	0.92
	0.20		0.41	0.51	0.58	0.64	0.72	0.77	0.81	0.87	0.90
0.00	0.00	0.00	0.39	0.48	0.55	0.61	0.68	0.73	0.77	0.82	0.85
Rating:6W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980											

Utilisation Factor Table(Wall)

Utilisation Factors UF(W)			SHR NOM = 1.25									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	1.01	0.84	0.71	0.62	0.50	0.41	0.35	0.27	0.22	
	0.30		0.85	0.72	0.62	0.55	0.45	0.38	0.33	0.26	0.21	
	0.20		0.73	0.63	0.55	0.49	0.41	0.35	0.30	0.24	0.20	
0.50	0.50	0.20	0.98	0.81	0.68	0.60	0.47	0.43	0.34	0.26	0.21	
	0.30		0.83	0.70	0.60	0.53	0.43	0.36	0.31	0.24	0.20	
	0.20		0.72	0.62	0.54	0.48	0.40	0.34	0.29	0.23	0.19	
0.30	0.50	0.20	0.95	0.77	0.66	0.57	0.45	0.37	0.32	0.25	0.20	
	0.30		0.81	0.68	0.59	0.52	0.42	0.35	0.30	0.24	0.19	
	0.20		0.71	0.61	0.53	0.47	0.39	0.33	0.28	0.22	0.19	
0.00	0.00	0.00	0.61	0.51	0.44	0.39	0.31	0.26	0.23	0.18	0.14	
Rating:6W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Utilisation Factor Table(Ceiling cavity)

Utilisation Factors UF(C)			SHR NOM = 1.25									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.17	0.18	0.19	0.20	0.21	0.21	0.22	0.22	0.22	
	0.30		0.10	0.12	0.13	0.14	0.16	0.17	0.18	0.19	0.20	
	0.20		0.05	0.07	0.08	0.09	0.12	0.13	0.14	0.16	0.17	
0.50	0.50	0.20	0.16	0.18	0.18	0.19	0.20	0.20	0.21	0.21	0.21	
	0.30		0.10	0.11	0.13	0.14	0.15	0.16	0.17	0.18	0.19	
	0.20		0.05	0.07	0.08	0.09	0.11	0.13	0.14	0.16	0.17	
0.30	0.50	0.20	0.16	0.17	0.18	0.18	0.19	0.20	0.20	0.20	0.21	
	0.30		0.10	0.11	0.12	0.13	0.15	0.16	0.17	0.18	0.18	
	0.20		0.05	0.07	0.08	0.09	0.11	0.13	0.14	0.15	0.16	
0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	
Rating:6W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												