

NEON SILHOUETTE & NEON CONTOUR



NEON
SILHOUETTE

NEON
SILHOUETTE
PLUS

NEON CONTOUR

NEON
CONTOUR
PLUS

NEON SILHOUETTE & NEON CONTOUR

Meet the new NeonLyte[®] from GENLED Acolyte[®]! It's like neon, but better! Our engineering team has produced four new bendable, waterproof light strips that utilize modern LED technology but keep the classic look of neon. The Neon Silhouette and Silhouette Plus feature a flat, bendable channel that produces a narrow, pinpoint beam of light. The Neon Contour and Contour Plus feature a pliable rounded lens that provides a bright light profile. Available in static white, static colors, variable white and color changing RGB, RGBA, RGBW. Silhouette and the Contour are both suitable for use in fine architectural details, façade lighting or lettering.

IP68

RoHS



AVAILABLE COLORS & COLOR TEMPERATURES (*5000K, RGBW, RGBA are not available for Neon Silhouette)



FEATURES

- **Silhouette:**
Static White, Static Color, Variable White, RGB - 3.0 W/ft (9.8 W/m)
- **Contour:**
Static White, Static Colors, Variable White - 3.0 W/ft (9.8 W/m)
RGBW, RGBA - 4.4 W/ft (14.43 W/m)
- **Silhouette Plus & Contour Plus:**
Static White, Static Colors, Variable White - 5.0 W/ft (16.4 W/m)
RGBW, RGBA - 4.4 W/ft (14.43 W/m)
- IP68 rated
- Assembled in USA
- **Silhouette:** 56.52 lm/ft (185.4 lm/m) at 3500K
- **Contour:** 89.88 lm/ft (294.8 lm/m) at 3500K
- **Silhouette Plus:** 104.2 lm/ft (341.8 lm/m) at 3500K
- **Contour Plus:** 139.51 lm/ft (457.6 lm/m) at 3500K
- Dimmable with ELV, MLV, 0-10 Volt, DMX, Lutron A-Series drivers
- 90+ CRI for all color temperatures
- Flexible silicone LED tube creates vivid light and bold statements
- Waterproof and UV resistant
- Unique rounded design helps create signature styles

DIMENSIONS

Silhouette	Silhouette Plus	Contour	Contour Plus
TUBE 0.47" (11.9 mm) 0.24" (6 mm) END CAP 0.55" (14 mm) 0.31" (8 mm) Tube Height: 0.47 in. (11.9 mm) Tube Width: 0.24 in. (6 mm) End Cap Height: 0.55 in. (14 mm) End Cap Width: 0.31 in. (8 mm)	TUBE 0.79 in. (20 mm) 0.47 in. (12 mm) END CAP 0.87 in. (22 mm) 0.56 in. (14.22 mm) Tube Height: 0.79 in. (20 mm) Tube Width: 0.47 in. (12 mm) End Cap Height: 0.87 in. (22 mm) End Cap Width: 0.56 in. (14.22 mm)	TUBE 0.63" (16 mm) 0.32" (8.13 mm) END CAP 0.79" (20 mm) 0.44" (11.18 mm) Tube Height: 0.63 in. (16 mm) Tube Width: 0.32 in. (8.13 mm) End Cap Height: 0.79 in. (20 mm) End Cap Width: 0.44 in. (11.18 mm)	TUBE 0.88 in. (22.35 mm) 0.39 in. (10 mm) END CAP 0.98 in. (24.89 mm) 0.47 in. (11.94 mm) Tube Height: 0.88 in. (22.35 mm) Tube Width: 0.39 in. (10 mm) End Cap Height: 0.98 in. (24.89 mm) End Cap Width: 0.47 in. (11.94 mm)

REV. 04MAR2021