



TUNABLE FROM 2000K TO 6500K | AVAILABLE IN 1 W/FT, 3 W/FT, 6 W/FT

VARIABLE WHITE SERIES 2 RIBBONLYTE

COMMERCIAL | ENTERTAINMENT | HEALTHCARE | HOSPITALITY | MUSEUMS | PUBLIC SPACES | RESIDENTIAL | RETAIL

Our Variable White Series 2 RibbonLyte allows you to adjust for brightness and warmth like never before. Now with 140 LEDs per meter, our improved RibbonLyte provides better color mixing, reduced diode visibility and a wider range of color temperatures for tuning your lighting design. Available in three wattages and with a 2 in. (50 mm) cut length, you can use Variable White Series 2 RibbonLyte with a DMX controller or a 2-channel dimmer to create bright, clear, colder light or the warmest, softest tones.

FEATURES

- Single-row, dual-chip layout means 140 LEDs per meter (42 LEDs per foot!)
- Available in three (3) wattages (1W/ft, 3W/ft, 6W/ft)
- 2 in. (50 mm) cut length adds amazing flexibility to your design
- Color temperature range of 2000K-6500K, 90+ CRI
- Use a DMX controller or 2-channel dimmer to adjust brightness and temperature
- 120° beam angle



RoHS IP20 IP65 IP68

1.0 W/ft

- 90 lm/ft (295 lm/m)
- 77-95 lm/W (Warm - Cool LED)

3.0 W/ft

- 240 lm/ft (790 lm/m)
- 72-90 lm/W (Warm - Cool LED)

6.0 W/ft

- 440 lm/ft (1440 lm/m)
- 62-82 lm/W (Warm - Cool LED)

24V DIMENSIONS	Top View	Side View	Dimensions
IP20	<p>CUTTABLE EVERY: 1.97 in. (50 mm)</p>		<p>Width 0.31 in. (8mm) Max Length* 32 ft 9.7 in. (10 m) Height 0.09 in. (2.3 mm)</p>
IP65	<p>CUTTABLE EVERY: 1.97 in (50mm)</p>		<p>Width 0.31 in (8mm) Max Length* 32 ft 9.7 in (10 m) Height 0.125 in (3.2 mm)</p>
IP68	<p>CUTTABLE EVERY: 1.97 in (50mm)</p>		<p>Width 0.44 in (11.2 mm) Max Length* 32 ft 9.7 in (10 m) Height 0.18 in (4.5 mm)</p>