

WARM DIM RIBBONLYTE

| Tight LED spacing minimizes | | | | | | |
|---|---|------------|----------------------------------|------------------|-------------|--|
| 1 million and the second se | 100% | 75% | 50% | 25% | 1% | |
| or even eliminates hot spots (depending on channel/lens used) | 2900K | 2700K | 2450K | 2225K | 2000K | |
| | | <u></u> | – Warm white a | t full brightnes | s that gets | |
| 5.2 W/ft at full brightness | even warmer as it dims, just like an incandescent lamp! | | | | | |
| 310 lm/ft - just less than | | | | | | |
| 4.4 Static White RibbonLyte | | | | | | |
| FIFE | All the qualities of incandescent light with | | | | | |
| Works with standard 0-10V dimmer or dimming system | | the energy | efficiency of LEI | Os | | |
| Cuttable every 3.94 In (100mm) | | | - Dual chip LEDs | allow dimmin | a from | |
| 24 VDC Voltage | | | 2900K at full brightness down to | | | |
| | | | 2000K with ex | - | | |
| Ideal for coves where warm ambient lighting is desired | | | as you dim | | C | |
| | | | | | | |
| 🕒 CE RoHS IP20 IP65 IP68 | | | | | | |
| LISTED | | | | | REV.200C | |