



**ACOLYTE**  
Architectural Lighting Solutions

# SERIES 2 RIBBONLYTE

**STATIC WHITE** 1800K | 2000K | 2200K | 2400K | 2700K | 3000K | 3500K | 4000K | 6000K

**STATIC COLOR** Red | Amber | Green | Blue | Violet

LED selection for Acolyte's Static White Series 2 RibbonLyte features 1-step MacAdam ellipse binning for 9 brilliant standard dimmable CCTs. LEDs for Static Color Series 2 RibbonLyte are even more precise, binned within 2.5 nanometers. Series 2 RibbonLyte features stellar efficacy and even lumen output with a tight LED pitch for superior blending. We offer short cut lengths for amazing design flexibility, and our slim Micro RibbonLyte is just 0.2 in. (5 mm) wide. When needed, Acolyte manufactures precise custom CCTs and colors to spec. And our Series 2 RibbonLyte products have all earned an "excellent" TM66 rating for circularity.



## 0.75 | 1.5 | 2.2 W/ft

- 0.75 Static White at 3500K: 130 lm/W
- 1.5 Static White at 3500K: 138 lm/W
- 2.2 Static White at 3500K: 135 lm/W
- LED Pitch: 49 LEDs/ft (160 LEDs/m)



## 3.0 | 4.4 W/ft

- 3.0 Static White at 3500K: 137 lm/W
- 4.4 Static White at 3500K: 133 lm/W
- LED Pitch: 49 LEDs/ft (160 LEDs/m)



## 5.0 | 6.0 W/ft

- 5.0 Static White at 3500K: 135 lm/W
- 6.0 Static White at 3500K: 132 lm/W
- LED Pitch: 68 LEDs/ft (224 LEDs/m)



## 1.0 W/ft Micro

- 0.2 in. width (5 mm)
- Fits in 0.3 in. wide channel (7.6 mm)
- 1.0 Static White at 3500K: 109 lm/W
- LED Pitch: 43 LEDs/ft (140 LEDs/m)



## 3.0 | 4.5 W/ft Micro

- 0.2 in. width (5 mm)
- Fits in 0.3 in. wide channel (7.6 mm)
- 3.0 Static White Micro at 3500K: 107 lm/W
- 4.5 Static White Micro at 3500K: 103 lm/W
- LED Pitch: 43 LEDs/ft (140 LEDs/m)

**Declare.**

**TM66  
ASSESSED**



**IP  
20**

**IP  
65**

**IP  
68**

**CRI  
90+**

\* IP65 & IP68 are not available in 1800K, 2000K & 2200K.

\*\* CRI applies to Static White RibbonLyte only.

\*\*\* Applies to Static White Series 2 RibbonLyte from 2200K to 4000K.

REV.03JUN2025