

ARMOR SERIES | RGBW MINI EXTERIOR LINEAR FIXTURES

A high-powered wash fixture with 3 optic options, the RGBW MINI will allow you to custom mix specific colors for special events or company, with the ability to switch to a color that will compliment your buildings or installations natural coloring. With 5 different lengths to choose from, you will be able to find the fixtures to suit your installation. Armor Series RGBW MINI fixtures come with 3 year warranty.



GEL-FLUSH™ TECHNOLOGY

The RGBW MINI is now manufactured with Acolyte's Gel Flush™ Technology. This proprietary innovation prevents breaches from any weather-related elements. Acolyte's exterior products are guaranteed to never leak, condensate, or be breached by any environmental elements. This results in a clear and unobstructed beam of light from the our fixtures. No more water beads changing and or refracting the specified beam angles.



Applications:

Commercial Museums
 Entertainment Public Spaces



ORDERING GUIDE

Category	Voltage	Wattage	Color	FWHM Beam Angle	Mounting Option
MINI	24		RGBW65		
MINI - Armor RGBW Mini	24 - 24V DC	14 - 14 W (12.3" / 313 mm) 24 - 24 W (19.7" / 500 mm) 30 - 30 W (23.8" / 605 mm) 48 - 48 W (39.4" / 1000 mm) 60 - 60 W (47.2" / 1190 mm)	RGBW65 - RGBW + 6500K	15 - 15° 25 - 25° 35 - 35°	TSL - Large Tilttable Stand

INCLUDED ACCESSORIES:

- 1.) Large Tilttable Stand
TSL

OPTIONAL ACCESSORIES:

- 1.) **Armor Series Mounting Arms:**
Small: ARMORMNT0609
Large: ARMORMNT1422
- 2.) **Glare Shield:**
MINISHLD313 (313 mm)
MINISHLD500 (500 mm)
MINISHLD605 (605 mm)
MINISHLD1000 (1000 mm)
MINISHLD1190 (1190 mm)
- 3.) **2 Pin Female Cable to Bare Wire:**
MINICBLFB300 (300 mm)
MINICBLFB500 (500 mm)
MINICBLFB1000 (1000 mm)
MINICBLFB2000 (2000 mm)
- 4.) **2 Pin Male to 2 Pin Female Jumper Cable:**
MINIJUMPMF1000 (1000 mm)
MINIJUMPMF2000 (2000 mm)
- 5.) **3 Pin Female to Bare Wire DMX Cable:**
MINIDMXFB500 (500 mm)
- 6.) **3 Pin Male to 2 Pin Female DMX Jumper Cable:**
MINIDMXMF1000 (1000 mm)
MINIDMXMF2000 (2000 mm)

AVAILABLE COLORS



RGBW+6500K

SPECIFICATIONS / DIMENSIONS / LUMEN DATA

Operating Voltage	24V DC				
Length	12.3" / 313 mm	19.7" / 500 mm	23.8" / 605 mm	39.4" / 1000 mm	47.2" / 1190 mm
Power Consumption	14 W	24 W	30 W	48 W	60 W
LEDs per Fixture	8 LEDs	12 LEDs	15 LEDs	24 LEDs	30 LEDs
Amperage	0.58 A	1 A	1.25 A	2 A	2.5 A
Color / Temperature	RGBW+6500K				
LED Beam Angle	15°, 25°, 35°				
Max Daisy Chained Power	8 fixtures	5 fixtures	4 fixtures	2 fixtures	2 fixtures
Max Daisy Chained DMX	32 fixtures				
Control System	DMX				
LED Binning (SDCM)	3-Step MacAdam ellipse (White Channel Only)				
Ambient Temperature	-40° F to 122° F (-40° C to 50° C)				
Housing / Lens Materials	Housing: Extruded Aluminium / Lens: Clear UV Protected PMMA Cover: Tempered Glass End Caps: Extruded Aluminium / Brackets: Extruded Aluminium Housing, bracket, end cap material - 6063 high density aluminum alloy				
Connector	2 pin power connector / 3 pin DMX signal connector				
Cable Length	11.81" / 300 mm				
Protection Rating	IP66				
Mounting Options	Large Tilttable Stand (180° adjustable), Mounting Arms (available in 2 different sizes)				
Impact Rating	IK08				
Lamp Life	50,000 hours				
Certifications	CE, ETL / Luminaires - UL 1598, 3rd Ed., issued September 17, 2008, Rev. October 17, 2012 / Luminaires - CSA C22.2 No.250.0-08, 3rd Ed., issued September 17, 2008, Rev. October 17, 2012 (R2013)				
Fixture Color Finish	Anodized Silver				

LIGHT OUTPUT FOR 12.3" / 313 MM

LED Beam Angles	15°					25°					35°				
	Red	Green	Blue	White	All	Red	Green	Blue	White	All	Red	Green	Blue	White	All
Color / Temperature	Red	Green	Blue	White	All	Red	Green	Blue	White	All	Red	Green	Blue	White	All
Lumen Output / Foot	155.3	230.9	39.0	277.0	734.7	144.2	248.0	37.2	271.8	735.3	153.8	227.6	39.3	247.6	621.8
Total Lumens	159.1	236.7	40.0	284.0	753.1	147.8	254.2	38.1	278.6	753.7	157.6	233.2	40.2	253.8	637.4

LIGHT OUTPUT FOR 19.7" / 500 MM

LED Beam Angles	15°					25°					35°				
	Red	Green	Blue	White	All	Red	Green	Blue	White	All	Red	Green	Blue	White	All
Color / Temperature	Red	Green	Blue	White	All	Red	Green	Blue	White	All	Red	Green	Blue	White	All
Lumen Output / Foot	155.3	230.9	39.0	277.0	734.7	144.2	248.0	37.2	271.8	735.3	153.8	227.6	39.3	247.6	621.8
Total Lumens	254.9	379.1	64.0	454.8	1206.2	236.7	407.1	61.0	446.2	1207.2	157.6	373.6	77.9	253.8	1020.8

LIGHT OUTPUT FOR 23.8" / 605 MM

LED Beam Angles	15°					25°					35°				
	Red	Green	Blue	White	All	Red	Green	Blue	White	All	Red	Green	Blue	White	All
Color / Temperature	Red	Green	Blue	White	All	Red	Green	Blue	White	All	Red	Green	Blue	White	All
Lumen Output / Foot	155.3	230.9	39.0	277.0	734.7	144.2	248.0	37.2	271.8	735.3	153.8	227.6	39.3	247.6	621.8
Total Lumens	307.9	458.0	77.4	549.5	1457.2	285.9	491.8	73.7	539.1	1458.4	305.0	451.3	77.9	491.1	1233.3

LIGHT OUTPUT FOR 39.4" / 1000 MM

LED Beam Angles	15°					25°					35°				
	Red	Green	Blue	White	All	Red	Green	Blue	White	All	Red	Green	Blue	White	All
Color / Temperature	Red	Green	Blue	White	All	Red	Green	Blue	White	All	Red	Green	Blue	White	All
Lumen Output / Foot	155.3	230.9	39.0	277.0	734.7	144.2	248.0	37.2	271.8	735.3	153.8	227.6	39.3	247.6	621.8
Total Lumens	509.8	758.1	128.1	909.6	2412.3	473.3	814.2	122.1	892.4	2414.3	505.0	747.1	128.9	813.0	2041.7

LIGHT OUTPUT FOR 47.2" / 1190 MM


LED Beam Angles	15°					25°					35°				
	Red	Green	Blue	White	All	Red	Green	Blue	White	All	Red	Green	Blue	White	All
Color / Temperature	Red	Green	Blue	White	All	Red	Green	Blue	White	All	Red	Green	Blue	White	All
Lumen Output / Foot	155.3	230.9	39.0	277.0	734.7	144.2	248.0	37.2	271.8	735.3	153.8	227.6	39.3	247.6	621.8
Total Lumens	610.7	908.2	153.4	1089.7	2889.9	567.0	975.4	146.3	1069.1	2892.3	604.9	895.0	154.4	973.9	2445.8

Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.


DIMENSIONS / MOUNTING HARDWARE

DIMENSION DRAWINGS


12.3 in. / 313 mm:




End view for all sizes:




19.7 in. / 500 mm:




23.8 in. / 605 mm:



39.4 in. / 1000 mm:






47.2 in. / 1190 mm:



MOUNTING HARDWARE

Large Tilttable Stand
For adjustable mounting angles
up to 180°




MOUNTING HARDWARE / ACCESSORIES

MOUNTING HARDWARE


Mounting Arms

Small Mounting Arm Part Number: ARMORMNT0609
Large Mounting Arm Part Number: ARMORMNT1422



Armor Series Mounting Arm

Adjustable mounts (in 3 sizes) help set desired angle and distance from lighting surface



ACCESSORIES




Glare Shield

Part Number: MINISHLD


To reduce glare or redirect light

- MINISHLD313 (313 mm)
- MINISHLD500 (500 mm)
- MINISHLD605 (605 mm)
- MINISHLD1000 (1000 mm)
- MINISHLD1190 (1190 mm)



Adds 2.0" / 50.8 mm to the height of the fixture

FRONT VIEW



SIDE VIEW



2 Pin Female Cable To Bare Wire

Part Number: MINICBLFB

To bare wire for incoming power

- MINICBLFB300 (300mm)
- MINICBLFB500 (500mm)
- MINICBLFB1000 (1000mm)
- MINICBLFB2000 (2000mm)



2 Pin Male To Female Jumper Cable

Part Number: MINIJUMPMF

To connect 2 pin male connector to 2 pin female connector

- MINIJUMPMF1000 (1000mm)
- MINIJUMPMF2000 (2000mm)



3 Pin Female To Bare Wire DMX Input Cable

Part Number: MINIDMXFB

To bare wire for DMX controller

- MINIDMXFB500 (500mm)



3 Pin Male To 3 Pin Female DMX Jumper Cable

Part Number: MINIDMXMF

To connect 3 pin male connector to 3 pin female connector for DMX data

- MINIDMXMF1000 (1000mm)
- MINIDMXMF2000 (2000mm)

CONNECTION / CONNECTORS

DMX:

