

## ARMOR SERIES | NANO EXTERIOR LINEAR FIXTURES

The Nano Linear fixture is the perfect solution for projects that require high output and tight beam control in minimal space. With three premium optic lens options and three standard lengths, the sleek anodized Nano Linear features six brilliant dimmable CCTs (2700K-6000K) that can be tailored for any application. Use Nano Linear to highlight architectural details or navigate small ledges and locations where space is at a premium. Armor Series Nano Linear fixtures come with a three-year warranty.



## GEL-FLUSH™ TECHNOLOGY

The Armor Series Nano Linear fixture is manufactured with GelFlush™ Technology. This proprietary innovation uses a special Dow Corning sealant to protect your lighting from the elements. With Acolyte's Armor Series, there's no leaking and no condensation -- just clear, unobstructed beams of light!



## ORDERING GUIDE

Category	CRI	Wattage	Color Temperature		FWHM Beam Angle	Mounting Option
<b>NANO</b>						
<b>NANO - Armor Nano</b>	<b>80 - 80+ CRI</b>	<b>0.2 - 182 mm / 7.2 in. (3 W)</b>	<b>27 - 2700K</b>	<b>40 - 4000K</b>	<b>25X35° - 25x35°</b>	<b>SI - Snap-In</b>
	<b>90 - 90+ CRI</b>	<b>0.5 - 500 mm / 19.7 in. (9 W)</b>	<b>30 - 3000K</b>	<b>50 - 5000K</b>	<b>30 - 30x30°</b>	<b>TS - Tilttable Stand</b>
		<b>1.0 - 1000 mm / 39.4 in. (18 W)</b>	<b>35 - 3500K</b>	<b>60 - 6000K</b>	<b>55 - 55x55°</b>	

## OPTIONAL ACCESSORIES:

### 1.) Armor Series Mounting Arms:

Small: ARMORMNT0609  
Large: ARMORMNT1422

### 2.) Symmetric Louver:

NANOLOUV182 (182 mm)  
NANOLOUV500 (500 mm)  
NANOLOUV1000 (1000 mm)

### 3.) 2 Pin Male to Female Jumper Cable:

NANOJUMPMF1000 (1000 mm)  
NANOJUMPMF2000 (2000 mm)

### 4.) 2 Pin Female Cable to Bare Wire:

NANOCBLFB300 (300 mm)  
NANOCBLFB500 (500 mm)  
NANOCBLFB1000 (1000 mm)  
NANOCBLFB2000 (2000 mm)

## DRIVERS:

### 96 W Non-dimming Driver



Driver Part No.: DRVW2496

### 0-10V Dimmable Waterproof Drivers



96W Part No.: DRVW249610P  
288W Part No.: DRVW2428810P

### ELV/MLV Dimmable Drivers




60W Part No.: DRVW2460ELVMLV  
96W Part No.: DRVW2496ELVMLV  
150W Part No.: DRVW24150ELVMLV  
300W Part No.: DRVW24300ELVMLV

### DALI Dimmable Drivers




96W Part No.: DRVW2496DALI1CH  
100W Part No.: DRV24100DALI1CH

## AVAILABLE COLOR TEMPERATURES



## AVAILABLE BEAM ANGLES



## SPECIFICATIONS

Operating Voltage	24 VDC								
Length	7.2 in. / 182 mm			19.7 in. / 500 mm			39.4 in. / 1000 mm		
Power Consumption	3 W			9 W			18 W		
LEDs per Fixture	6 LEDs			15 LEDs			30 LEDs		
Amperage	0.125 A			0.375 A			0.75 A		
Max. Run Length	Up to 14 fixtures			Up to 6 fixtures			Up to 4 fixtures		
Color Temperature	2700K, 3000K, 3500k, 4000K, 5000K, 6000K								
LED Beam Angle	30x30°	55x55°	25x35°	30x30°	55x55°	25x35°	30x30°	55x55°	25x35°
Lumen Output / Foot	355	359	352	355	359	352	355	359	352
Total Lumens	212	214	210	582.3	588.7	577.1	1164.6	1177.4	1154.2
Max. Run Length	Up to 14 fixtures			Up to 6 fixtures			Up to 4 fixtures		
Weight	0.77 lb / 0.35kg			1.65 lb / 0.75kg			3.3 lb / 1.5kg		
CRI	80+ or 90+								
LED Binning (SDCM)	3-step (80 CRI) or 2-step (90 CRI)								
Dimming Options	0-10 V, ELV/MLV, DALI								
Binning Tolerance	+/-100K								
Ambient Temperature	-40 — 122 °F (-40 — 50 °C)								
Housing / Lens	Housing: Extruded Aluminium / Lens: Clear UV Protected PMMA Cover: Tempered Glass End Caps: Extruded Aluminium / Brackets: Extruded Aluminium Housing, bracket, end cap material – 6063 high density aluminum alloy								
Connector	2 pin power connector								
Cable Length	11.81 in. / 300 mm								
Protection Rating	IP66								
Impact Rating	IK08								
Mounting Options	Snap-In Clip, Tilttable Stand (140° adjustable), Mounting Arms (available in 2 different sizes)								
Lifetime (L70 reported)	50,000 hours								
Certifications	CE, ETL / Luminaires – UL 1598, 3rd Ed., issued September 17, 2008, Rev. October 17, 2012 / Luminaires – CSA C22.2 No.250.0-08, 3rd Ed., issued September 17, 2008, Rev. October 17, 2012 (R2013)								
Fixture Color Finish	Anodized silver								


\* ALL LUMEN DATA IS FROM 2700K 80 CRI FIXTURES

## DIMENSIONS


7.2 in. / 182 mm:



19.7 in. / 500 mm:



39.4 in. / 1000 mm:




Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

## MOUNTING HARDWARE / ACCESSORIES

### MOUNTING HARDWARE


#### Snap-in Clip

For narrow installations where mounting clips need to be installed first




#### Tilttable Stand

For adjustable mounting angles




#### Mounting Arms

Small Mounting Arm Part Number: ARMORMNT0609  
Large Mounting Arm Part Number: ARMORMNT1422



#### Armor Series Mounting Arm

Adjustable mounts (in 2 sizes) help set desired angle and distance from lighting surface




### ACCESSORIES

#### Louver

Part Number: NANOLOUV

For glare reduction  
Note: This will affect beam angle

NANOLOUV182 (182 mm)  
NANOLOUV500 (500 mm)  
NANOLOUV1000 (1000 mm)



Side View

Not recommended for exterior applications

#### 2 Pin Female Cable To Bare Wire

Part Number: NANOCBLFB

To bare wire for incoming power

NANOCBLFB300 (300 mm)  
NANOCBLFB500 (500 mm)  
NANOCBLFB1000 (1000 mm)  
NANOCBLFB2000 (2000 mm)



#### 2 Pin Male To Female Jumper Cable

Part Number: NANOJUMPMF

To connect 2 pin male connector to 2 pin female connector

NANOJUMPMF1000 (1000 mm)  
NANOJUMPMF2000 (2000 mm)




### INCLUDED IN BOX




Fixture with 19.7 in. / 500mm input/output cables  
+ 2 pin connectors

CONNECTION


NON-DIMMING FOR CASE 1:




CASE 2.



0-10V DIMMING:




ELV/MLV DIMMING:




## CONNECTION

### DALI DIMMING:



### CONNECTORS:



REV.09.JUL.2025

#### GLOBAL HQ

320 Murray Hill Pkwy  
East Rutherford, NJ 07073  
U.S.  
T: (+1) 212 629 6830  
E: Sales-US@GENLEDBrands.com

#### EUROPEAN HQ

Hogeweysestraat 119  
1382 JK Weesp  
Netherlands  
T: (+31) 346 235 000  
E: SalesEurope@GENLEDBrands.com

#### MEINA HQ

PO Box 371378, #823, Building 4EA  
Dubai Airport Free Zone  
Dubai, UAE  
T: (+971) 4 701 7901  
E: SalesMEINA@genledbrands.com

#### ASIA-PACIFIC HQ

Room 402, Building D  
Shenxi Tongchuang Science and Technology Park  
No. 16 Hongyin Road  
Xingqiang Community, Xinhua Street  
Guangming District, Shenzhen, China 518107  
T: (+86) 755 8529 0710  
E: Sales-Pacific@GENLEDBrands.com