

ATOM LINEAR FIXTURE

The Atom Linear Fixture is designed with a compact form and precision beam angle control for indoor wall grazer applications in minimal space. It has two beam angle options, including one with a built-in honeycomb louver. Available in three lengths and six Static White CCTs (2700K-6000K), Atom fixtures are easy to install and connect.

- Three lengths:
6 W, 9 LEDs per 11.8 in. (300 mm) fixture
12 W, 18 LEDs per 23.6 in. (600 mm) fixture
24 W, 36 LEDs per 47.2 in. (1200 mm) fixture
- 2700K, 3000K, 3500K, 4000K, 5000K, 6000K
- Beam Angles: 25x25°, 25x35°
(25x35° uses honeycomb louver)
- Install with 180° tiltable stands
- 80+ CRI
- Dim with 0-10 V, DALI, Triac
- IP40 for indoor use



IP40

ORDERING GUIDE

Category	Length	Glare Shield	Color Temperature	FWHM Beam Angle	Mounting Options
ATOM					
ATOM - Atom Linear	12 - 11.8 in. / 300 mm (6 W)	NS - No Shield	27 - 2700K 40 - 4000K	25x25 - 25x25°	TS - Tilttable Stand
	24 - 23.6 in. / 600 mm (12 W)	GS - Glare Shield	30 - 3000K 50 - 5000K	25x35 - 25x35°*	SI - Symmetric Clip
	47 - 47.2 in. / 1200 mm (24 W)		35 - 3500K 60 - 6000K		QR - Quick Release Clip

OPTIONAL ACCESSORIES:

1.) Symmetric Louver:

ATOMLOUV300 (300 mm)
ATOMLOUV600 (600 mm)
ATOMLOUV1200 (1200 mm)

2.) Asymmetric Louver:

ATOMALOUV300 (300 mm)
ATOMALOUV600 (600 mm)
ATOMALOUV1200 (1200 mm)

3.) 2 Pin Female Cable to Bare Wire:

ATOMCBLFB300 (300 mm)
ATOMCBLFB2000 (2000 mm)
ATOMCBLFB6000 (6000 mm)

4.) 2 Pin Male To Female Jumper Cable:

ATOMJUMPMF300 (300 mm)
ATOMJUMPMF600 (600 mm)
ATOMJUMPMF1800 (1800 mm)

* 25x35° with honeycomb louver

DRIVERS:

NON-DIMMING ELECTRONIC DRIVERS



30W, 60W, 96W Non-Dimming
Electronic Class 2 Drivers

Part No.:
• DRVW2430 (30 W)
• DRVW2460 (60 W)
• DRVW2496 (96 W)



240W, 320W Non-Dimming
Electronic Drivers

Part No.:
• DRVW24240 (240 W)
• DRVW24320 (320 W)



60W, 96W Non-Dimming
Compact Drivers

Part No.:
• DRV2460C (60 W)
• DRV2496C (96 W)



60W, 96W, 288W 0-10V/ELV/MLV
3-in-1 Dimmable Drivers

Part No.:
• DRVW2460TRI010 (60 W)
• DRVW2496TRI010 (96 W)
• DRVW24288TRI010 (288 W)

ATHENA WIRELESS COMPATIBLE



94W Athena Wireless
Compatible Drivers

Part No.:
• DRVW2494ATH1CH (1 channel)
• DRVW2494ATH2CH (2 channel)

CASAMBI COMPATIBLE DRIVERS



100W & 200W Casambi Compatible
4 Channel Drivers

Part No.:
• DRVW24100CAS4CH (100 W)
• DRVW24200CAS4CH (200 W)

DIMMABLE DALI-2 DRIVERS



96W Dimmable DALI-2
DT6 D4I & DT8 D4I Drivers

Part No.:
• DRVW2496DALI1CH (1 channel)
• DRVW2496DALI2CH (2 channel)


DIMMABLE DALI-2 DRIVERS




75W, 150W, 240W DALI-2 Dimmable Drivers

Part No.:
• DRVW2475DALI1CH (75 W, 1 channel)
• DRVW24150DALI1CH (150 W, 1 channel)
• DRVW24240DALI1CH (240 W, 1 channel)
• DRV24150DALI2CH (150 W, 2 channels)
• DRV24150DALI4CH (150 W, 4 channels)

AVAILABLE COLOR TEMPERATURES





BEAM ANGLES




SPECIFICATIONS / DIMENSIONS

Operating Voltage	24 VDC					
Amperage	257 mA/ft					
Length	11.8 in. / 300 mm		23.6 in. / 600 mm		47.2 in. / 1200 mm	
Power Consumption	6 W		12 W		24 W	
LEDs per Fixture	9 LEDs		18 LEDs		36 LEDs	
Max. Run Length	Up to 12 fixtures		Up to 6 fixtures		Up to 4 fixtures	
Weight	6.9 oz (0.20 kg)		13.8 oz (0.39 kg)		27.6 oz (0.78 kg)	
Color Temperature	2700K, 3000K, 3500K, 4000K, 5000K, 6000K					
Beam Angle	25x25°	25x35° (honeycomb louver)	25x25°	25x35° (honeycomb louver)	25x25°	25x35° (honeycomb louver)
Lumen Output / Foot	619.56 lm/ft	378.56 lm/ft	619.56 lm/ft	378.56 lm/ft	619.56 lm/ft	378.56 lm/ft
Lumen Output / Meter	2032.16 lm/m	1241.68 lm/m	2032.16 lm/m	1241.68 lm/m	2032.16 lm/m	1241.68 lm/m
Total Lumens	609.8 lm	372.6 lm	1219.6 lm	745.2 lm	2439.2 lm	1490.4 lm
CRI	80+					
LED Binning SDCM	3-step					
Dimming Options	0-10V, Triac, DALI					
Ambient Temperature	-40 — 122 °F (-40 — 50 °C)					
Housing / Lens	Housing: Extruded Aluminum / Lens: UV Protected PMMA / Cover: Acrylic					
Connector	2 pin power connector					
Cable Length for 2 Pin Female to Bare Wire	11.81 in. (300 mm), 78.74 in. (2000 mm), 236.22 in. (6000 mm)					
Protection Rating	IP40 (Indoor only)					
UGR Rating	<7.8	<7.2	<7.8	<7.2	<7.8	<7.2
Mounting Options	Tilttable stand, Symmetric Clip, Quick Release Clip					
Fixture Color Finish	Black (Standard), Custom colors available (Minimum quantities apply)					
Certifications	ETL Listed: UL 2108 Issued: 2004/02/27 Ed: 1 Rev: 2014/02/24 Low Voltage Lighting Systems CSA C22.2#9.0 Issued: 1996/06/01 Ed: 1 (R2011) General Requirements for Luminaries; with Gen. Inst. 1: 1997, Gen Inst. 2: 1998. ROHS compliant					




DIMENSIONS


Side View:
11.8 in. / 300 mm:



Side View:
23.6 in. / 600 mm:



Side View:
47.2 in. / 1200 mm:




Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

DIMENSIONS / MOUNTING HARDWARE / ACCESSORIES

MOUNTING HARDWARE


Tiltable Stand

For adjustable mounting angles



Symmetric Clip


For narrow installations where mounting clips need to be installed first



0.78 in. L x 1.14 in. W x 0.72 in. H
(19.8 L x 29.0 W x 18.3 H mm)

Quick Release Clip

For quick, one step release of fixture



1.18 in. L x 1.06 in. W x 0.72 in. H
(30 L x 27 W x 18.29 H mm)

ACCESSORIES

Symmetric Louver


For glare reduction

Note: This will affect beam angle




Part Number: ATOMLOUV300
ATOMLOUV600
ATOMLOUV1200

Top View



Note: Not recommended for exterior applications


Side View



Asymmetric Louver


For glare reduction

Note: This will affect beam angle




Part Number: ATOMALOUV300
ATOMALOUV600
ATOMALOUV1200

Top View




Note: Not recommended for exterior applications

Side View



Glare Shield

To reduce glare or direct light



Glare shield is part of the extrusion and cannot be removed. It extends the entire length of the fixture.

2 Pin Female Cable To Bare Wire

To bare wire for incoming power


Default cable lengths:

11.81 in. / 300 mm, 78.74 in. / 2000 mm, 236.22 in. / 6000 mm
(Consult factory for custom length)



Part Number: AtomCBLFB300
AtomCBLFB2000
AtomCBLFB6000

ø 0.715 in.



2 Pin Male To Female Jumper Cable

To connect 2 pin male connector to 2 pin female connector

Default cable length:

11.81 in. / 300 mm, 23.62 in. / 600 mm, 70.87 in. / 1800 mm
(Consult factory for custom length)




Part Number: ATOMJUMPMF300
ATOMJUMPMF600
ATOMJUMPMF1800


CONNECTION

NON DIMMING:


Case 1.



Case 2.




0-10V DIMMING:




CONNECTION


DALI DIMMING:



TRIAC DIMMING:



CONNECTORS:



REV.22OCT2025

GLOBAL HQ

320 Murray Hill Pkwy
East Rutherford, NJ 07073
U.S.
T: (+1) 212 629 6830
E: Sales-US@GENLEDBrands.com

EUROPEAN HQ

Hogeweyselaan 119
1382 JK Weesp
Netherlands
T: (+31) 346 235 000
E: SalesEurope@GENLEDBrands.com

MEINA HQ

PO Box 371378, #823, Building 4EA
Dubai Airport Free Zone
Dubai, UAE
T: (+971) 4 701 7901
E: SalesMEINA@genledbrands.com

ASIA-PACIFIC HQ

Room 402, Building D
Shenchi Tongchuang Science and Technology Park
No. 16 Hongyin Road
Xingqiang Community, Xinhua Street
Guangming District, Shenzhen, China 518107
T: (+86) 755 8529 0710
E: Sales-Pacific@GENLEDBrands.com