

AR5 CHANNEL FIXTURE

Our AR5 Channel Fixture is a flexible micro channel with a 110-degree beam angle for decorative illumination in small gaps. Use in counter tops and edges or create light drawings in straight lines or gentle arcs. The pinpoint lighting surface is a smooth milky lens built into the channel at just .2 in. (5.3) mm high. Design an elegant custom fixture with AR5 Channel and our Micro RibbonLyte products.




- Available for field assembly or factory assembly
- 0.51 in. (13 mm) wide by 0.2 in. (5.3 mm) deep
- 110-degree beam angle
- Wattage Range from 0.75 W/ft (2.46 W/m) to 6.0 W/ft (19.7 W/m)
- Static White delivered lumen range from 4 lm/ft (14 lm/m) up to 41 lm/ft (133 lm/m)
- Milky Lens built into channel

AVAILABLE LENS / HOUSING FINISH



Milky Lens built into channel
7% Light Transmission

AVAILABLE COLORS & COLOR TEMPERATURES




The profile can be used to create a light drawing using straight lines or arcs.
Minimum bending radius 9.84 in. (25 cm)




DIMENSIONS

AR5 Channel



Width: 0.51 in. (13 mm)
Height: 0.2 in. (5.3 mm)
Internal Width: 0.33 in. (8.3 mm)
Internal Height: 0.13 in. (3.2 mm)



Note: This channel does not require mounting clips. Please see our installation guide for instructions.


Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

SPECIFICATIONS

Beam Angle	110°
Lens Type	Milky Lens built into channel
Length	Channel is sold by the foot and cut to your exact desired length
Operating Voltage	24V
Dimming	MLV / 0-10 Volt / Lutron Hi-Lume 1% dimming LED drivers / Lutron VIVE code compliance available / ELV / DALI / DMX
Operating Temperature	-40° F to 158° F (-40° C to 70° C)
Colors	1800K, 2000K, 2200K, 2400K, 2700K, 3000K, 3500K, 4000K, 6000K, Red, Amber, Green, Blue, VW (1800K, 2000K, 2200K only available in IP20)
CRI	90+ CRI (Static white only)
Minimum Bending Radius	9.8 in. (25 cm)
Lamp Life	L70 at 50,000 Hours
MacAdam Ellipses (SDCM)	2-Step Binning (For Static White LEDs only)
Certifications	ETL Listed: UL 2108 Issued: 2004/02/27 Ed: 1 Rev: 2014/02/24 Low Voltage Lighting Systems CSA C22.2#9.0 Issued: 1996/06/01 Ed: 1 (R2011) General Requirements for Luminaires; with Gen. Inst. 1: 1997, Gen Inst. 2: 1998. ROHS compliant UL 2108 - Low Voltage Lighting Systems UL 8750 - Light Emitting Diode (LED) Equipment for Use in Lighting Products UL 1598 / CSA 250.0-08 - Luminaires

ACCESSORIES

Milky End Caps



STEP 1 Complete Channel Part Number

CHANNEL

CHAR5

CHAR5 - AR5 Channel

STEP 2 Complete RibbonLyte Part Number

CATEGORY

RB

RB - RibbonLyte

CRI

0 - Static Color, Color Changing

90 - 90+ CRI Static White

RIBBON TYPE & IP RATING

SWS220 - Static White Series 2 IP20

SWS265 - Static White Series 2 IP65

SCS220 - Static Color Series 2 IP20

SCS265 - Static Color Series 2 IP65

VWS220 - VW Series 2 IP20

VWS265 - VW Series 2 IP65

WATTAGE

0.75 - 0.75 W/ft (2.46 W/m - Static White, Static Color)

1.0 - 1.0 W/ft (3.3 W/m - Variable White)

1.5 - 1.5 W/ft (4.9 W/m - Static White, Static Color)

2.2 - 2.2 W/ft (7.2 W/m - Static White, Static Color)

3.0 - 3.0 W/ft (9.8 W/m - Static White, Static Color, Variable White)

4.4 - 4.4 W/ft (14.4 W/m - Static White, Static Color)

6.0 - 6.0 W/ft (19.7 W/m - Variable White)

COLOR

18 - 1800K

20 - 2000K

22 - 2200K

24 - 2400K

27 - 2700K

30 - 3000K

35 - 3500K

40 - 4000K

60 - 6000K

R - Red

A - Amber

G - Green

B - Blue

VW - Variable White

Z - Undecided**

** For quotes only. Must be chosen before final order.

CONNECTION OPTIONS (See diagrams on the right)

1 - End Feed Bare Wire Connection

4 - End Feed with IP67 Male Coupler


2 - Back Feed Bare Wire Connection

5 - Soldered Daisy Chain

3 - Side Feed Bare Wire Connection

6 - Daisy Chain With IP67 Couplers

Custom Length (ft.)



STEP 3 Complete Assembly Option & Length

ASSEMBLY OPTION

FI - Field Assembly

FA - Factory Assembly

LENGTH (Standard factory assembled length up to 78 in. / 2 m)

Consult factory for custom factory assembled length (up to 13 ft / 4 m)

SPECIFICATIONS

Available Wattages	Cutttable Length	LED Pitch	Color Temp.	lm/W without Lens	Delivered Lumens with Milky Lens (lm/ft / lm/m)	Standard Cable Length	Compatible with Channel		
							IP20	IP65	IP68
0.75 Static White Series 2	1.97 in. (50 mm)	48 LEDs/ft (160 LEDs/m)	1800K	84	4 / 14	12 in. (30.5 cm)	✓	✓	
			2000K	99	5 / 17				
			2200K	109	6 / 19				
			2400K	113	6 / 19				
			2700K	123	6 / 21				
			3000K	123	6 / 21				
			3500K	130	7 / 22				
			4000K	134	7 / 23				
			6000K	131	7 / 23				
1.5 Static White Series 2	1.97 in. (50 mm)	48 LEDs/ft (160 LEDs/m)	1800K	84	9 / 29	12 in. (30.5 cm)	✓	✓	
			2000K	98	10 / 34				
			2200K	109	11 / 38				
			2400K	113	12 / 39				
			2700K	123	13 / 42				
			3000K	123	13 / 42				
			3500K	129	14 / 44				
			4000K	134	14 / 46				
2.2 Static White Series 2	1.97 in. (50 mm)	48 LEDs/ft (160 LEDs/m)	1800K	83	13 / 42	12 in. (30.5 cm)	✓	✓	
			2000K	96	15 / 49				
			2200K	106	16 / 54				
			2400K	111	17 / 56				
			2700K	120	18 / 61				
			3000K	122	19 / 62				
			3500K	127	20 / 64				
			4000K	133	20 / 67				
3.0 Static White Series 2	1.97 in. (50 mm)	48 LEDs/ft (160 LEDs/m)	1800K	84	18 / 58	12 in. (30.5 cm)	✓	✓	
			2000K	98	21 / 68				
			2200K	108	23 / 74				
			2400K	109.8	23 / 76				
			2700K	122.9	26 / 85				
			3000K	130	27 / 90				
			3500K	133	28 / 92				
			4000K	133	28 / 92				
4.4 Static White Series 2	1.97 in. (50 mm)	48 LEDs/ft (160 LEDs/m)	1800K	81	25 / 82	12 in. (30.5 cm)	✓	✓	
			2000K	95	29 / 96				
			2200K	105	32 / 106				
			2400K	109	34 / 110				
			2700K	122	38 / 123				
			3000K	129	40 / 130				
			3500K	132	41 / 133				
			4000K	132	41 / 133				
0.75 Static Color Series 2	1.97 in. (50 mm)	48 LEDs/ft (160 LEDs/m)	Red	41	2 / 7	12 in. (30.5 cm)	✓	✓	
			Green	175	9 / 30				
			Blue	19	1 / 3				
			Amber	34	2 / 6				

SPECIFICATIONS

Available Wattages	Cuttable Length	LED Pitch	Color Temp.	lm/W without Lens	Delivered Lumens with Milky Lens (lm/ft / lm/m)	Standard Cable Length	Compatible with Channel		
							IP20	IP65	IP68
1.5 Static Color Series 2	1.97 in. (50 mm)	48 LEDs/ft (160 LEDs/m)	Red	42	4 / 14	12 in. (30.5 cm)	✓	✓	
			Green	160	17 / 55				
			Blue	18	2 / 6				
			Amber	34	4 / 12				
2.2 Static Color Series 2	1.97 in. (50 mm)	48 LEDs/ft (160 LEDs/m)	Red	42	6 / 21	12 in. (30.5 cm)	✓	✓	
			Green	145	22 / 73				
			Blue	18	3 / 9				
			Amber	34	5 / 17				
3.0 Static Color Series 2	1.97 in. (50 mm)	48 LEDs/ft (160 LEDs/m)	Red	40	8 / 28	12 in. (30.5 cm)	✓	✓	
			Green	127	27 / 87				
			Blue	25	5 / 17				
			Amber	29	6 / 20				
4.4 Static Color Series 2	1.97 in. (50 mm)	48 LEDs/ft (160 LEDs/m)	Red	38	12 / 38	12 in. (30.5 cm)	✓	✓	
			Green	117	36 / 118				
			Blue	24	7 / 24				
			Amber	25	8 / 25				
1.0 Variable White Series 2	1.97 in. (50 mm)	42 LEDs/ft (140 LEDs/m)	2000K + 6500K	85	6 / 20	12 in. (30.5 cm)	✓	✓	
3.0 Variable White Series 2	1.97 in. (50 mm)	42 LEDs/ft (140 LEDs/m)	2000K + 6500K	80	16.8 / 55	12 in. (30.5 cm)	✓	✓	
6.0 Variable White Series 2	1.97 in. (50 mm)	42 LEDs/ft (140 LEDs/m)	2000K + 6500K	75	31.5 / 103	12 in. (30.5 cm)	✓	✓	

DIODE VISIBILITY CHART (Data below applies to installations with Milky lens only)

	No Visible Diode = N		With Visible Diode = Y
Static White & Static Color RibbonLyte		Color Changing RibbonLyte	
0.75/1.5/2.2	3.0/4.4	Variable White	
IP20 IP65	IP20 IP65	IP20 IP65	
N	N	N	

AVAILABLE DRIVERS

NON-DIMMING ELECTRONIC DRIVERS



30W, 60W, 96W Non-Dimming Electronic Class 2 Drivers

Part No.:

- DRVW2430 (30 Watt)
- DRVW2460 (60 Watt)
- DRVW2496 (96 Watt)

Output Voltage: 24 V

Voltage Range: 120-277 VAC

IP Rating: Dry or Damp

UL Listed



240W, 320W Non-Dimming Electronic Drivers

Part No.:

- DRVW24240 (240 Watt)
- DRVW24320 (320 Watt)

Output Voltage: 24 V

Voltage Range: 90-305 VAC

IP Rating: Dry or Damp

UL Recognized

LUTRON HI-LUME DRIVERS



40W, 96W Class 2 Lutron Hi-Lume Drivers

Part No.:

- DRVLUT24403W (40 Watt)
- DRVLUT24402W (40 Watt)
- DRVLUT24963W (96 Watt)

Output Voltage: 24 V

Voltage Range: 120-277 VAC or 120V (2-wire model)

IP Rating: Dry or Damp

Dimmable using 2-wire forward phase or 3-wire ecosystem

UL Listed

MAGNETIC, ELV & MLV DRIVERS WITH COMPATIBLE DIMMERS



60W, 96W, 200W, 300W Class 1 & 2 Magnetic Drivers

Part No.:

- DRVWDIM2460 (60 Watt)
- DRVWDIM24100 (96 Watt)
- DRVWDIM24200 (200 Watt)
- DRVWDIM24300 (300 Watt)

Magnetic Driver

Output Voltage: 24 V

Voltage Range: 120/277 VAC

IP Rating: Dry or Damp

Forward Phase Dimming

ETL Listed



60W, 96W, 150W, 200W ELV & MLV Drivers

Part No.:

- DRVW2460ELV (60 Watt)
- DRVW2496ELV (96 Watt)
- DRVW24150ELV (150 Watt)
- DRVW24200ELV (200 Watt)

Line Voltage Dimmable Drivers

Output Voltage: 24 V

Voltage Range: 100-130 VAC

IP Rating: Dry or Damp

Dimmable

ETL, UL and CSA Listed



LUTRON Skylark Contour Dimmer

Part No.: TRIDIMSKY

Width: 2.94 in. (75 mm)

Length: 4.69 in. (120 mm)

Depth: 0.30 in. (7.6 mm)

- Single pole and 3-way versions
- Compatible with Acolyte Triac Dimmer
- Slide adjusts brightness and On/Off control
- 30 mA max control current
- Available in white finish



LUTRON NOVA-T Dimmer

Part No.: TRIDIMNOVA

Width: 2.75 in. (70 mm)

Length: 4.56 in. (116 mm)

Depth: 0.30 in. (7.6 mm)

- Slide adjusts brightness and On/Off control
- 30 mA max control current
- Available in white finish



LUTRON DIVA Dimmer

Part No.: TRIDIMDIVA

(With Locator Light) TRIDIMDIVAL

Width: 2.94 in. (75 mm)

Length: 4.69 in. (120 mm)

Depth: 0.30 in. (7.6 mm)

- Large paddle switch with a captive linear-slide dimmer
- 30 mA max control current
- Available in white finish
- Available with locator light which glows green when the switch is off

Note: For more options, please reference the Optional Dimmer List on Acolyte product website page.

AVAILABLE DRIVERS / CONTROLLERS AND DIMMING OPTIONS / WIRE GAUGE CHART

0-10V DRIVERS AND DIMMERS

DIMMING MODULE



0-10V Dimmable Waterproof Drivers

96W Part No.: DRVW249610P
288W Part No.: DRVW2428810P
 Output Voltage: 24 V (+/- 0.5V)
 Voltage Range: 100-277 VAC
 Environmental Rating: UL Wet Location
 UL Listed



LUTRON DIVA Dimmer

Part No.: LVDIMDIVA
 Width: 2.94 in. (75 mm)
 Length: 4.69 in. (120 mm)
 Depth: 0.30 in. (7.6 mm)

- Compatible with 0-10 V Dimming Module
- Large paddle switch with a captive linear-slide dimmer
- 30 mA max control current
- Available in white finish



LUTRON NOVA-T Dimmer

Part No.: LVDIMNOVA
 Width: 2.75 in. (70 mm)
 Length: 4.56 in. (116 mm)
 Depth: 0.30 in. (7.6 mm)

- Compatible with 0-10 V Dimming Module
- Slide adjusts brightness and On/Off control
- 30 mA max control current
- Available in white finish



Variable White Dimming Module

- Part No.: VWDIMMOD
- 1 dimming module required per 30 ft (9.1 m)
 - This product is only compatible with Variable White RibbonLyte, not Variable White Amber or Variable White Red. Works with any 0-10V dimmers to provide CCT change with one dimmer and brightness change with the other.


Note: Max length before additional power is introduced

DRIVER AND RIBBONLYTE AT FULL LOAD


Wattages	30		60		96		150		200		240		300		320	
Wire Gauge	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters
24 AWG	14	4.27	9	2.74	5.5	1.68	3.75	1.14	2.75	0.84	2.25	0.69	1.75	0.53	1.75	0.53
22 AWG	22	6.71	14	4.27	9	2.74	5.75	1.75	4.5	1.37	3.5	1.07	2.75	0.84	2.75	0.84
20 AWG	35	10.67	23	7.01	14	4.27	9	2.74	7	2.13	5.75	1.75	4.5	1.37	4.25	1.30
18 AWG	56	17.07	37	11.28	23	7.01	15	4.57	11	3.35	9	2.74	7.5	2.29	7	2.13
16 AWG	90	27.44	60	18.29	37	11.28	24	7.32	18	5.49	15	4.57	12	3.66	11	3.35
14 AWG	142	43.29	95	28.96	59	17.99	38	11.59	28	8.54	23	7.01	19	5.79	17	5.18
12 AWG	226	68.90	151	46.04	94	28.66	60	18.29	45	13.72	37	11.28	30	9.15	28	8.54
10 AWG	360	109.76	240	73.17	150	45.73	96	29.27	72	21.95	60	18.29	48	14.63	45	13.72
8 AWG	574	175.00	381	116.16	239	72.87	153	46.65	115	35.06	95	28.96	76	23.17	71	21.65

WIRING DIAGRAMS


0-10V




MLV / ELV




DMX




WARM DIM



2-CHANNEL VARIABLE WHITE DIMMING



DMX WIRING DIAGRAM - COMPATIBLE WITH ALL MODELS OF VARIABLE WHITE RIBBONLYTE



WIRE COLORS PER RIBBONLYTE COLOR

STATIC WHITE + STATIC COLOR

Red Wire (+) Positive
Black Wire (-) Negative

RGB

Black Wire (+) Positive
Red Wire (-) goes to Red Channel
Green Wire (-) goes to Green Channel
Blue Wire (-) goes to Blue Channel

RGBW/A

Black Wire (+) Positive
Red Wire (-) goes to Red Channel
Green Wire (-) goes to Green Channel
Blue Wire (-) goes to Blue Channel
White Wire (-) goes to White Channel

WARM DIM

Red Wire (-) goes to Warm White Channel
Blue Wire (-) goes to Cool White Channel
Black Wire (+) goes to Warm White Channel
Green Wire (+) goes to Cool White Channel

VARIABLE WHITE

Black Wire (+) Positive
Red Wire (-) goes to Warm White Channel
Green Wire (-) goes to Cool White Channel