


### PC1 LINEARLYTE PENDANT FIXTURE

Create a beautifully lit space with PC1 pendants. Our small round PC1 linear fixtures are 2-8 ft long, sold in 1 ft or 0.5 m increments, with five Static White CCT options, Variable White or color changing RGBW and RGBA LEDs.

- 1.6 in. (41 mm) round pendants
- Sold in 1 ft or 0.5 m increments
- UV Resistant lenses
- Static White (2700K, 3000K, 3500K, 4000K, 5000K) and Variable White (2000K-6500K) models are 0-10 V or DALI dimmable
- RGBW (2700K, 3000K, 4000K) and RGBA (amber) models use DMX controls
- Standard powder coating in silver, black and white (custom colors available)
- Assembled in USA




### ORDERING GUIDE

Category	Output	Fixture Length				Color Temp		Surface Finish	
PC1									
PC1	LO - Low	<b>FOR U.S. ONLY</b>		<b>FOR OUTSIDE OF U.S.</b>		27 - 2700K	VW - Variable White	SV - Silver	CU - Custom
	SO - Standard	2 - 2 ft	6 - 6 ft	0.5m - 0.5 m	2m - 2 m	30 - 3000K	RGB27 - RGB+2700K	WH - White	*Custom RAL # available.
	HO - High	3 - 3 ft	7 - 7 ft	1m - 1 m	2.4m - 2.4 m	35 - 3500K	RGB30 - RGB+3000K	BK - Black	
		4 - 4 ft	8 - 8 ft	1.5m - 1.5 m		40 - 4000K	RGB40 - RGB+4000K		
		5 - 5 ft				50 - 5000K	RGBA - RGB+Amber		


See available drivers on page 3

### AVAILABLE COLOR TEMPERATURES



SPECIFICATIONS / LUMEN DATA

SPECIFICATIONS



Beam Angle (FWHM)	130°
Diffuser Angle	185°
Lens Type	Milky
Length	Sold in 1 ft (305 mm) or 0.5 meter increments
Operating Voltage	27-54 VDC
Dimming	0-10 V, DALI, DMX
Colors	2700K, 3000K, 3500K, 4000K, 5000K, Variable White (2000K-6500K), RGBW (2700K, 3000K, 4000K), RGBA (Amber)
CRI	90+ CRI (for Static White and Variable White only)
Certifications	UL, RoHS
Weight	0.4 lbs/ft (0.59 kg/m)
Diameter	1.6 in. (41 mm)

STATIC WHITE LUMEN DATA / FIXTURE TESTED AT 3500K

Output	White/Color	Power Consumption		Lumen Output		Efficiency lm/W
		W/ft	W/m	lm/ft	lm/m	
LO (Low Output)	White	2.7	8.86	230	754	85
SO (Standard Output)	White	3.66	12.02	308	1010	84
HO (High Output)	White	7.63	25.04	573	1880	75

VARIABLE WHITE LUMEN DATA




Output	White/Color	Power Consumption		Lumen Output		Efficiency lm/W
		W/ft	W/m	lm/ft	lm/m	
LO (Low Output)	Warm White	1.34	4.4	95.7	314	71
	Cool White	1.34	4.4	119	392	89
	All On	2.74	9	214	702	78
SO (Standard Output)	White	3.05	10	196	644	64
	Cool White	2.99	9.8	244	802	82
	All On	6.04	19.8	439	1440	73
HO (High Output)	Warm White	6.1	20	349	1146	57
	Cool White	5.85	19.2	440	1442	75
	All On	12.31	40.4	791	2594	64

RGBW LUMEN DATA / FIXTURE TESTED AT RGB+3000K

Output	White/Color	Power Consumption		Lumen Output		Efficiency lm/W
		W/ft	W/m	lm/ft	lm/m	
LO (Low Output)	Red	0.67	2.2	32	105	48
	Green	0.61	2	107	350	175
	Blue	0.67	2.2	23	75	34
	White	0.61	2	76	248	124
	All On	2.74	9	235	770	86
SO (Standard Output)	Red	1.34	4.4	64	210	48
	Green	1.34	4.4	196	644	146
	Blue	1.28	4.2	38	126	30
	White	1.22	4	142	466	117
	All On	5.55	18.2	441	1446	79
HO (High Output)	Red	2.8	9.2	135	442	48
	Green	2.93	9.6	366	1202	125
	Blue	2.87	9.4	78	256	27
	White	2.62	8.6	282	924	107
	All On	12.07	39.6	853	2798	71

AVAILABLE DRIVERS/INTERFACE


	FOR STATIC WHITE MODELS	
	0-10V 1% DIMMABLE 25W DRIVER	0-10V 1% DIMMABLE 50W DRIVER
		
Part Number	DRVCC25SS277010	DRVCC50SS277010
Compatible Dimming	0-10 V	0-10 V
Output Voltage (VDC)	27 - 54 VDC	27 - 54 VDC
Output Wattage	25 W	50 W
Output Current	0.1 - 0.7 A	0.1 - 1.4 A
Input Voltage Range (VAC)	120 - 277 VAC	120 - 277 VAC
Input Current (A)	0.25 A (120 VAC) / 0.13 A (230 VAC) / 0.11 A (277 VAC)	0.48 A (120 VAC) / 0.25 A (230 VAC) / 0.21 A (277 VAC)
Input Frequency	50 / 60 Hz	50 / 60 Hz
Max Input Power (W)	31 W	58 W
Efficiency @ Max Load	83 (120 VAC) / 85 (277 VAC)	86 (120 VAC) / 88 (277 VAC)
Max Input Current	0.25 A	0.48 A
THD @ Max Load	< 10% (120 VAC) / < 15% (277 VAC)	< 10% (120 VAC) / < 15% (277 VAC)
Power Factor @ Max Load	> 0.95	> 0.95
Surge Protection (Combi-Wave, KV)	2.5	2.5
Expected Life Time	50,000 hours (< 65 °C)	50,000 hours (< 65 °C)
Operating Temperature	-4 – 122 °F (-20 – 50 °C)	-4 – 122 °F (-20 – 50 °C)
Safety Standards	UL8750, UL991, CSA250.13-14, C22.2 No. 0.8-12, CSA Class P, ETL Class P, UL2043 Plenum Rating	UL8750, UL991, CSA250.13-14, C22.2 No. 0.8-12, CSA Class P, ETL Class P, UL2043 Plenum Rating
Weight	0.44 lbs (0.2 kgs)	0.9 lbs (0.41 kgs)
Dimensions (L x W x H)	4.21 x 2.38 x 0.98 in. (107 x 60 x 25 mm)	4.21 x 3.01 x 1.18 in. (107 x 76 x 30 mm)

	FOR VARIABLE WHITE MODELS	FOR RGBW MODELS	
	0-10V DIMMABLE 90W VW/WD DRIVER	5 CHANNEL DMX INTERFACE	24V NON-DIMMING UL LISTED ELECTRONIC DRIVERS
			
Part Number	DRVRFWDVW2490120	DMXINFOLED5	DRVW2496
Compatible Dimming	0-10 V	DIM/CT/RGB/RGBW/RGBWY	--
Output Voltage (VDC)	24 VDC	12-24 VDC	24 VDC
Output Wattage	90 W	--	96 W
Output Current	3.75 A	6 A/channel output (x 5 channels)	4.1 A
Input Voltage Range (VAC)	100 - 277 VAC	120 - 277 VAC	120 - 277 VAC
Input Frequency	50 / 60 Hz	--	50 / 60 Hz
Efficiency @ Max Load	89%	--	> 87% Max.
Operating Temperature	-86 – 104 °F (-20 – 50 °C)	-22 – 149 °F (-30 – 65 °C)	-13 – 104 °F (-25 – 40 °C)
Safety Standards	UL8750 + UL1310	CE, FCC, RoHS, UL Recognized	UL, CLASS P
Dimensions (L x W x H)	8.4 x 4.1 x 1.5 in. (213 x 104 x 38 mm)	6.65 x 3.14 x 1.45 in. (169 x 80 x 39 mm)	12.1 x 2.36 x 1.4 in. (307 x 60 x 36 mm)

DRIVER MATRIX

Length	Current per ft (mA)	Current per meter (mA)	Max Current Driver (mA)	Driver Part Number
LO (Low Output) up to 8 ft or 2.4 m	67.5	221	700	DRVCC25SS277010
SO (Standard Output) up to 7 ft or 2.1 m	90	295	700	DRVCC25SS277010
SO (Standard Output) up to 8 ft or 2.4 m	90	295	1400	DRVCC50SS277010
HO (High Output) up to 4 ft or 1 m	175	574	700	DRVCC25SS277010
HO (High Output) up to 8 ft or 2.4 m	175	574	1400	DRVCC50SS277010

SUGGESTED SUSPENSION WIRE SEPARATED DISTANCES




IN THE U.S.

Fixture Length	A	B
2 ft	4 in.	16 in.
3 ft	6 in.	24 in.
4 ft	8 in.	32 in.
5 ft	9 in.	42 in.
6 ft	1 ft	4 ft
7 ft	1 ft	5 ft
8 ft	15 in.	66 in.

OUTSIDE THE U.S.

Fixture Length	A	B
0.5 m	85 mm	330 mm
1 m	165 mm	670 mm
1.5 m	225 mm	1.05 m
2 m	285 mm	1.43 m
2.4 m	375 mm	1.65 m

FIXTURE INSTALLATION



\* Length of provided Suspension Cable from ceiling to fixture: 150 in. (3.81 m) max.  
\* Field cuttable to any length

REV.21JAN2025

**GLOBAL HQ**

320 Murray Hill Pkwy  
East Rutherford, NJ 07073  
U.S.  
T: (+1) 212 629 6830  
E: Sales-US@GENLEDBrands.com

**EUROPEAN HQ**

Hogeweyselaan 119  
1382 JK Weesp  
Netherlands  
T: (+31) 346 235 000  
E: SalesEurope@GENLEDBrands.com

**MEINA HQ**

PO Box 371378, #823, Building 4EA  
Dubai Airport Free Zone  
Dubai, UAE  
T: (+971) 4 701 7901  
E: SalesMEINA@genlebrands.com

**ASIA-PACIFIC HQ**

Room 402, Building D  
Shenhi Tongchuang Science and Technology Park  
No. 16 Hongyin Road  
Xingqiang Community, Xihu Street  
Guangming District, Shenzhen, China 518107  
T: (+86) 755 8529 0710  
E: Sales-Pacific@GENLEDBrands.com