

### PC2 LINEARLYTE PENDANT FIXTURE

Create a beautifully lit space with PC2 pendants. Our medium round PC2 linear fixtures are 2-8 ft long, sold in 1 ft (305 mm) or 0.5 m increments, with five Static White CCT options, Variable White or color changing RGBW and RGBA LEDs.

- 2.4 in. (61 mm) round pendants
- Sold in 1 ft (305 mm) or 0.5 m increments
- UV Resistant lenses
- Static White (2700K, 3000K, 3500K, 4000K, 5000K): 0-10V, DALI
- Variable White (2000K-6500K) and RGBW (2700K, 3000K, 4000K): 0-10V VW/WD Driver, DMX, DALI, Casambi
- Standard powder coating in silver, black and white (custom colors available)
- Assembled in USA



### ORDERING GUIDE

Category	Output	Fixture Length		Color Temp		Housing finish (top strip, end caps)			
PC2									
PC2	LO - Low	<b>FOR AMERICAS ONLY</b>		<b>FOR OUTSIDE OF AMERICAS</b>		27 - 2700K	VW - Variable White	SV - Silver	CU - Custom*
	SO - Standard	2 - 2 ft	6 - 6 ft	0.5m - 0.5 m	2m - 2 m	30 - 3000K	RGB27 - RGB+2700K	WH - White	*Custom RAL # available.
	HO - High	3 - 3 ft	7 - 7 ft	1m - 1 m	2.4m - 2.4 m	35 - 3500K	RGB30 - RGB+3000K	BK - Black	
		4 - 4 ft	8 - 8 ft	1.5m - 1.5 m		40 - 4000K	RGB40 - RGB+4000K		
		5 - 5 ft				50 - 5000K	RGBA - RGB+Amber		

See available drivers on page 3

### ACCESSORIES

#### Suspended Mounting Kit (not included)

Part #: LLNONFEEDKITWHT (White)\*\*  
Part #: LLNONFEEDKITBLK (Black)



Cable length: 6 ft 6.74 in. (2 m)

#### Power Feed Canopy Kit (not included)

Part #: LLFEEDKITWHT2 (White)\*\*  
Part #: LLFEEDKITBLK2 (Black)



\*\* Recommended for fixtures in silver and white finishes


### AVAILABLE COLOR TEMPERATURES



Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

SPECIFICATIONS / LUMEN DATA

SPECIFICATIONS



Beam Angle (FWHM)	105°
Diffuser Angle	285°
Lens Type	Milky
Length	Sold in 1 ft (305 mm) or 0.5 m increments
Operating Voltage	27-54 VDC
Dimming	Static White: 0-10V, DALI RGBW and Variable White: 0-10V VW Driver, DMX, DALI, Casambi
Colors	2700K, 3000K, 3500K, 4000K, 5000K, Variable White (2000K-6500K), RGBW (2700K, 3000K, 4000K), RGBA (Amber)
CRI	90+ CRI (for Static White and Variable White only)
Certifications	UL, RoHS
Safety Standards	CE - EN61347-1:2015+A1:2021, EN61347-2-13:2024 , EN55015:2019
Weight	0.48 lbs/ft (0.72 kg/m)
Diameter	2.4 in. (61 mm)

STATIC WHITE LUMEN DATA / FIXTURE TESTED AT 3500K

Output	White/Color	Power Consumption		Lumen Output		Efficiency lm/W
		W/ft	W/m	lm/ft	lm/m	
LO (Low Output)	White	3.57	11.7	383	1256	107
SO (Standard Output)	White	8.65	28.38	919	3014	106
HO (High Output)	White	12.42	40.75	1233	4046	99

VARIABLE WHITE LUMEN DATA

Output	White/Color	Power Consumption		Lumen Output		Efficiency lm/W
		W/ft	W/m	lm/ft	lm/m	
LO (Low Output)	Warm White	1.34	4.4	98.8	324	74
	Cool White	1.34	4.4	123	404	92
	All On	2.74	9	220	722	80
SO (Standard Output)	White	3.05	10	201	660	66
	Cool White	2.99	9.8	253	830	85
	All On	6.04	19.8	450	1478	75
HO (High Output)	Warm White	6.16	20.2	356	1168	58
	Cool White	5.97	19.6	452	1484	76
	All On	12.2	40	805	2642	66

RGBW LUMEN DATA / FIXTURE TESTED AT RGB+3000K

Output	White/Color	Power Consumption		Lumen Output		Efficiency lm/W
		W/ft	W/m	lm/ft	lm/m	
LO (Low Output)	Red	0.65	2.14	29	94	44
	Green	0.62	2.02	102	334	165
	Blue	0.67	2.2	21	68	31
	White	0.62	2.02	71	234	116
	All On	2.74	9	220	722	80
SO (Standard Output)	Red	1.34	4.4	60	196	44
	Green	1.34	4.4	190	622	141
	Blue	1.28	4.2	35	116	28
	White	1.21	3.98	135	444	112
	All On	5.55	18.2	425	1394	77
HO (High Output)	Red	2.8	9.2	137	448	49
	Green	2.88	9.46	363	1190	126
	Blue	2.87	9.4	77	254	27
	White	2.62	8.6	279	914	106
	All On	11.34	37.2	858	2816	76

AVAILABLE DRIVERS/INTERFACE

<p><b>0-10V Constant Current</b> For Static White models (Americas only)</p>  <p><b>0-10V 1% Dimmable 25W &amp; 50W Drivers</b></p> <p>Part No.: DRVCC25SS277010 (25 W) DRVCC50SS277010 (50 W)</p> <p>27-54 VDC 120-277 VAC UL8750, UL991, CSA250.13-14, C22.2 No. 0.8-12, CSA Class P, ETL Class P, UL2043 Plenum Rating</p>	<p><b>Constant Current DALI</b> For Static White models (outside of Americas)</p>  <p><b>50W &amp; 96W Constant Current DALI Driver</b></p> <p>Part No.: DRVCC50DALI1CH (50 W) DRVCC96DALI1CH (96 W)</p> <p>20-54 VDC 120-277 VAC UL8750, UL1310, CSA, UL Class P</p> <p>Part No.: DRVCC50DALI1CH (50 W) DRVCC96DALI1CH (96 W)</p> <p>9-52 VDC (50 W) 9-54 VDC (96 W) 120-277 VAC CE - EN61347-1:2015+A1:2021, EN61347-2-13:2024 , EN55015:2019</p>	<p><b>CASAMBI Compatible</b> For Variable White, Warm Dim &amp; RGB models (all regions)</p>  <p><b>100W &amp; 200W Casambi Compatible 4 Channel Drivers</b></p> <p>Part No.: • DRVW24100CAS4CH (100 W) • DRVW24200CAS4CH (200 W)</p> <p>24 VDC 100-277 VAC UL Listed, CE, RoHS, Bluetooth, CASAMBI</p>		
<p><b>0-10V VW/WD</b> For Variable White &amp; Warm Dim models (Americas only)</p>  <p><b>0-10V Dimmable 90W VW/WD Driver</b></p> <p>Part No.: DRVRFWDVW2490120</p> <p>24 VDC 100-277 VAC UL 8750 + UL 1310</p>	<p><b>DALI-2 (2 channel)</b> For Variable White &amp; Warm Dim models (outside of Americas)</p>  <p><b>150W DALI-2 Dimmable 2 Channel Driver</b></p> <p>Part No.: DRV24150DALI2CH</p> <p>24 VDC 120-277 VAC CE, CB, ENEC (25), DALI2.0</p>	<p><b>0-10V/ELV/MLV 3-in-1</b> For RGBW models (Americas only)</p>  <p><b>60W, 96W, 288W 0-10V/ELV/MLV 3-in-1 Dimmable Drivers</b></p> <p>Part No.: DRVW2460TRI010 (60 W) DRVW2496TRI010 (96 W) DRVW24288TRI010 (288 W)</p> <p>24 VDC 120-277 VAC UL8750, UL1310, IEC 61000-4-2-3-4-5-6-8-11</p>	<p><b>DALI-2 (4 channel)</b> For RGBW models (outside of Americas)</p>  <p><b>150W DALI-2 Dimmable 4 Channel Drivers</b></p> <p>Part No.: DRV24150DALI4CH</p> <p>24 VDC 120-277 VAC CE, CB, ENEC (25), DALI2.0</p>	<p><b>Interface</b> For RGBW models (all regions)</p>  <p><b>5 Channel DMX Decoder</b></p> <p>Part No.: DMXINF5</p> <p>12-24 VDC CE, UL Recognized</p>


**NOTE:**  
To prevent exposure to the maximum allowable temperatures for these drivers, the suggested installation spacing between drivers is at least 4 in. (101.6 mm) side-to-side when the distance to the sidewall and top of the enclosure is 2 in. (50.8 mm). When the distance to the sidewall and top of the enclosure is 6 in. (152.4 mm), maintain at least 2 in. (50.8 mm) side-to-side spacing between drivers. Drivers should be placed at a minimum of 1 in. (25.4 mm) apart when arranging them end-to-end regardless of the enclosure size.

Please [download driver and interface specification sheets on PC2 product page for more details.](#)

DRIVER MATRIX (for Static White models only)

Length	Current per ft (mA)	Current per meter (mA)	Max Current Driver (mA)	Driver Part Number	Region
LO (Low Output) up to 7 ft or 2.1 m	90	295	700	DRVCC25SS277010	Americas only
LO (Low Output) up to 7 ft or 2.1 m	90	295	700	DRVCC50DALI1CH	Outside of Americas
LO (Low Output) up to 8 ft or 2.4 m	90	295	1400	DRVCC50SS277010	Americas only
LO (Low Output) up to 8 ft or 2.4 m	90	295	1400	DRVCC50DALI1CH	Outside of Americas
SO (Standard Output) up to 3 ft or 1 m	225	738	700	DRVCC25SS277010	Americas only
SO (Standard Output) up to 3 ft or 1 m	225	738	700	DRVCC50DALI1CH	Outside of Americas
SO (Standard Output) up to 6 ft or 1.5 m	225	738	1400	DRVCC50SS277010	Americas only
SO (Standard Output) up to 6 ft or 1.5 m	225	738	1400	DRVCC50DALI1CH	Outside of Americas
SO (Standard Output) up to 8 ft or 2.4 m	225	738	2750	DRVCC95SS277010	Americas only
SO (Standard Output) up to 8 ft or 2.4 m	225	738	2750	DRVCC96DALI1CH	Outside of Americas
HO (High Output) up to 2 ft or 0.5 m	325	1066	700	DRVCC25SS277010	Americas only
HO (High Output) up to 2 ft or 0.5 m	325	1066	700	DRVCC50DALI1CH	Outside of Americas
HO (High Output) up to 4 ft or 1 m	325	1066	1400	DRVCC50SS277010	Americas only
HO (High Output) up to 4 ft or 1 m	325	1066	1400	DRVCC50DALI1CH	Outside of Americas
HO (High Output) up to 8 ft or 2.4 m	325	1066	2750	DRVCC95SS277010	Americas only
HO (High Output) up to 8 ft or 2.4 m	325	1066	2750	DRVCC96DALI1CH	Outside of Americas

SUGGESTED SUSPENSION WIRE SEPARATED DISTANCES




IN THE U.S.

Fixture Length	A	B
2 ft	4 in.	16 in.
3 ft	6 in.	24 in.
4 ft	8 in.	32 in.
5 ft	9 in.	42 in.
6 ft	1 ft	4 ft
7 ft	1 ft	5 ft
8 ft	15 in.	66 in.

OUTSIDE THE U.S.

Fixture Length	A	B
0.5 m	85 mm	330 mm
1 m	165 mm	670 mm
1.5 m	225 mm	1.05 m
2 m	285 mm	1.43 m
2.4 m	375 mm	1.65 m

FIXTURE INSTALLATION



\* Length of provided Suspension Cable from ceiling to fixture: 150 in. (3.81 m) max.  
\* Field cuttable to any length

REV.27APR2026

**GLOBAL HQ**

320 Murray Hill Pkwy  
East Rutherford, NJ 07073  
U.S.  
T: (+1) 212 629 6830  
E: Sales-US@GENLEDBrands.com

**EUROPEAN HQ**

Hogeweyselaan 119  
1382 JK Weesp  
Netherlands  
T: (+31) 346 235 000  
E: SalesEurope@GENLEDBrands.com

**MEINA HQ**

PO Box 371378, #823, Building 4EA  
Dubai Airport Free Zone  
Dubai, UAE  
T: (+971) 4 701 7901  
E: SalesMEINA@genlebrands.com

**ASIA-PACIFIC HQ**

Room 402, Building D  
Shenhi Tongchuang Science and Technology Park  
No. 16 Hongyin Road  
Xingqiang Community, Xihu Street  
Guangming District, Shenzhen, China 518107  
T: (+86) 755 8529 0710  
E: Sales-Pacific@GENLEDBrands.com