

8.8 RGB + WHITE & RGB + AMBER RIBBONLYTE

8.8 RGBW and RGBA RibbonLyte are DMX controlled. Use with Acolyte channel profiles to create an excellent fixture with no color refraction.

RGB + WHITE: Adds 3000K and 6000K to RGB to replicate tungsten and daylight.

RGB + AMBER: Adds 590 nanometer Amber for warm accents.

- Use with Acolyte channel profiles to create a custom fixture
- Flexible
- 24 Volt input



Applications:

Commercial	Hospitality	Residential
Entertainment	Museums	Retail
Healthcare	Public Spaces	



RoHS IP20 IP65 IP68



ORDERING GUIDE

Category	CRI	Ribbon Type & IP Rating	Wattage + Color
RB	0		
RB - Ribbonlyte	0 - Color Changing	RGBWA20 - RGBW/A IP20 RGBWA65 - RGBW/A IP65 RGBWA68 - RGBW/A IP68	8.8RGB30 - 8.8 RGB+3000K 8.8RGB60 - 8.8 RGB+6000K 8.8RGBA - 8.8 RGB+Amber

CONNECTION OPTIONS

1. End Feed Bare Wire Connection (Default Option)



2. IP67 Connector Input



3. Soldered Daisy Chain



4. Daisy Chain with IP67 Connectors



5. Bare Wire on Both Ends



Standard cable length if not specified:

1. 12 in. cable with bare wire (custom length up to 20 feet)
2. Standard 12 in. cable with IP67 connectors (custom length up to 10 feet)
3. Daisy chain with 3 in. cable between runs (custom length up to 36 in.)
4. 3 in. cable between IP67 connector and RibbonLyte (custom length up to 18 in.)
5. Standard 12 in. cable with bare wire (custom length up to 10 feet)

Note: IP67 connectors are used for both IP20 and IP65/IP68 RibbonLyte







AVAILABLE COLORS





RGBA RGBW

SPECIFICATIONS / DIAGRAM / USAGE GUIDELINES

8.8 RGB WHITE/ AMBER	
Operating Voltage	24 V
Power Consumption	8.8 W/ft (28.9 W/m)
Current (mA) - 24V	367 mA/ft (1203.8 mA/m)
LED Pitch	36 LEDs/ft (120 LEDs/m)
Protection Rating	IP20, IP65, IP68
Dimming/Control	DMX / Lutron A-Series 1% dimming LED drivers
Operating Temperature	-40° F to 158° F (-40° C to 70° C)
Colors/Color Temperatures	RGBW (3000K), RGBW (6000K), RGB+Amber
Lumens - RGBW	536.8 lm/ft (1761.2 lm/m) All LEDs at 100%
Binning Tolerance	+/- 100K (White)
LED Beam Angle	120°
Lamp Life	50,000 Hours
Cutable Length - 24V	3.94 in (100 mm)
Lumens/Watt - RGBW	61 lm/W (All LEDs at 100%)
Lumens/Watt - RGBA	22 lm/W (All LEDs at 100%)
Constant Voltage	✓
Cable Length	12 in (30.5 cm)
Certifications	UL 2108 Issued: 2016/06/17 Ed: 1 Rev: 2021/10/16 Low Voltage Lighting Systems. CSA C22.2 No. 250.0, General Requirements for Luminaires. ROHS compliant UL 2108.

24V DIMENSIONS	Top View	Side View	Dimensions
IP20	 CUTTABLE EVERY: 3.94 in (100 mm)		Width 0.80 in (20.2 mm) Max Length* 19 ft 7.9 in (6 m) Height 0.09 in (2.3 mm)
IP65	 CUTTABLE EVERY: 3.94 in (100 mm)		Width 0.80 in (20.2 mm) Max Length* 19 ft 7.9 in (6 m) Height 0.125 in (3.2 mm)
IP68	 CUTTABLE EVERY: 3.94 in (100 mm)		Width 0.93 in (23.6 mm) Max Length* 19 ft 7.9 in (6 m) Height 0.21 in (5.3 mm)

OPTIONAL ACCESSORY

1 in. VHB Tape	Wide Silicone Clip
 <p>Provides superior holding power in surface mounted applications Part Number: VHBTAPE1.0BK</p>	 <p>For mounting IP20/IP65/IP68 RibbonLyte Part Number: RBMNTSILXL</p>




Note: RibbonLyte comes with an adhesive backing, but Acolyte recommends using VHB Tape for extra support in surface mounted applications.





USAGE GUIDELINES

- IP65 and IP68 RibbonLyte cannot be cut in the field. All custom cuts and connections for these models must be performed at the factory to ensure waterproofing standards are met. Any modification of the waterproofing will result in a void warranty.
- When installing this product, consider the surface temperature of the material where it will be mounted. Many building surfaces which are exposed to direct sunlight exceed the 70° C / 158° F maximum for which our product is rated. High-risk locations like this should be avoided.
- IP20 RibbonLyte products are for indoor use in dry areas. IP65 RibbonLyte products can be used in indoor dry/damp locations such as bathrooms and kitchens. IP68 RibbonLyte products can be used in wet, outdoor locations around pools and spa tubs, but our products are not intended to be submerged in pools and fountains and do not carry UL676 certification to do so.
- Please refer to the RibbonLyte Proper Usage Guide in our Application Guide for more information. Available for download at AcolyteLED.com.
- This product is compatible with a wide variety of control products including the entire line of Lutron dimming systems.
- For use with Acolyte drivers, 0-10V dimming modules and interface controllers (DMXINF models).
- Use with non-Acolyte supplied drivers is not supported or warrantied.
- Due to the nature of RibbonLyte products, cuttable lengths are generally longer or shorter than the customer requested length. Unless specified, RibbonLyte is factory cut at the shorter cuttable point.
- We reserve the right to make changes to product lineup, specifications, design and finishes at any time without notice.

Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

CHANNEL COMPATIBILITY / CHANNEL OPTIONS

CHANNEL	IP20/IP65	IP68	SURFACE MOUNTED CHANNELS					
AC1			LENS OPTIONS: C - Clear F - Frosted K - Black M - Milky NP - Narrow Prismatic WP - Wide Prismatic RM - Round Milky SM - Square Milky					
AC2								
AC3								
AC4	✓	✓						
AC5	✓	✓						
AR1								
AR3								
AR8			AC4 C, F, M	AC5 C, F, M	AS13 RM, SM	AS30 M, RM, SM	AW38 M, RM, SM	WH35 C, F, M
AR10								
AR16								
AR20								
AR25	✓	✓						
AR30	✓	✓						
AR33								
AS1								
AS2								
AS3								
AS6								
AS10								
AS12								
AS13	✓	✓						
AS16								
AS20G								
AS23								
AS30	✓	✓						
AS53								
AT4								
AT5								
AW10								
AW12								
AW14								
AW38	✓	✓						
B1								
B2								
ROUND12								
SC3								
SC4	✓	✓						
SC5	✓	✓						
SC6								
WH35	✓	✓						

RECESSED CHANNELS						
LENS OPTIONS: C - Clear F - Frosted K - Black M - Milky NP - Narrow Prismatic WP - Wide Prismatic RM - Round Milky SM - Square Milky						
						
						
						
						
AR25 M, RM, SM	AR30 M, RM, SM	SC4 M, RM, SM	SC5 M, RM, SM			


DISCLAIMER

When installing this product take into account the surface temperature of the material this product is mounted to. Many building surfaces which are exposed to direct sunlight exceed the 70°C/158°F maximum that our product is rated for. High risk locations like this should be avoided.

Our IP68 product is not intended to be submerged in pools and fountains and does not carry UL676 certification to do so.

WIRING DIAGRAMS

DMX



WIRE COLORS PER RIBBONLYTE COLOR

- RGBW & RGBA**
 Black (+) Positive
 Red Wire (-) goes to Red Channel
 Green Wire (-) goes to Green Channel
 Blue Wire (-) goes to Blue Channel
 White Wire (-) goes to White Channel