


SIMPLY CLEAN™ RECESSED FIXTURE SC3

Made from aluminum, UV-resistant and available in any length, Simply Clean™ SC3 recessed fixtures offer a variety of mounting options. Our smallest Simply Clean™ channel, SC3 has a 90° beam angle and can be installed in walls and ceilings or along a ceiling edge. Design a custom fixture with Simply Clean™ channels and RibbonLyte products.

- Wall recessed fixture
- Sold by the foot. Factory or field cuttable to any length.
- Adds an element of style and design to existing spaces
- Aluminum Channel with UV Resistant Lenses
- Wattages: 0.75 W/ft, 1.5 W/ft, 2.2 W/ft, 3 W/ft, 4.4 W/ft, 5.0 W/ft, 5.2 W/ft, 5.5 W/ft, 6.0 W/ft, 8.8 W/ft
- Assembled in USA
- For interior applications only




IP20



RoHS

Declare.



HOUSING FINISH



Silver


AVAILABLE LENS FINISHES




Milky Lens

70% Light Transmission

AVAILABLE COLORS & COLOR TEMPERATURES



DIMENSIONS



Visible Width: 0.88 in. (22.35 mm)
Height: 0.55 in. (14 mm)
Internal Width: 0.69 in. (17.5 mm)

Note: This channel does not require mounting clips. Please see our installation guide for instructions.

Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.


SPECIFICATIONS

Beam Angle	90°
Lens Type	Milky Lens
Length	Channel is sold by the foot and cut to your exact desired length
Operating Voltage	24 V
Dimming	MLV / 0-10 Volt / ELV / DALI / DMX
Operating Temperature	-40 — 158 °F (-40 — 70 °C)
Colors	1800K, 2000K, 2200K, 2400K, 2700K, 3000K, 3500K, 4000K, 6000K, Red, Amber, Green, Blue, RGBA, RGBW, RGBWW, VW, Warm Dim (1800K, 2000K, 2200K only available in IP20)
CRI	90+ CRI (Static white only)
Lamp Life	L70 at 50,000 hours
MacAdam ellipse (SDCM)	2-Step Binning (For Static White LEDs only)
Certifications	UL Listed UL 2108 Issued: 2004/02/27 Ed: 1 Rev: 2014/02/24 Low Voltage Lighting Systems CSA C22.2#9.0 Issued: 1996/06/01 Ed: 1 (R2011) General Requirements for Luminaries; with Gen. Inst. 1: 1997, Gen Inst. 2: 1998. ROHS compliant
Recessed Cutout Width	1.04 in. (26.4 mm)
Depth In Wall	0.45 in. (11.4 mm)
Length	Sold by the foot. Factory cuttable to any length. Max individual length of each piece is 78.7" (2m), but the fixture can be installed end-to-end to create long continuous recessed fixtures.
Visible Lens Width	0.88 in. / 22.35 mm


ACCESSORIES

End Cap

Material: ABS




Exploded View



End View

See basic installation steps on page 6.



Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

STEP 1 Complete Channel Part Number

CHANNEL	LENS	HOUSING COLOR
CHSC3	M	SV
CHSC3 - Simply Clean™ SC3 Recessed Fixture	M - Milky Lens	SV - Silver (default)

STEP 2 Complete RibbonLyte Part Number

CATEGORY	CRI	RIBBON TYPE & IP RATING
RB		
RB - RibbonLyte	0 - Static Color, Color Changing 90 - 90+ CRI Static White	LINEA20 - Linea RibbonLyte IP20 SWS220 - Static White S2 IP20 SCS220 - Static Colors S2 IP20 RGBWW20 - RGBWW 5-in-1 IP20 VWS220 - VW Series 2 IP20 WD20 - Warm Dim IP20 RGBWS220 - RGBW Series 2 IP20

WATTAGE

0.75 - 0.75 W/ft (2.46 W/m - Static White, Static Color)
 1.0 - 1.0 W/ft (3.3 W/m - Variable White)
 1.5 - 1.5 W/ft (4.9 W/m - Static White, Static Color)
 2.2 - 2.2 W/ft (7.2 W/m - Static White, Static Color)
 2.4 - 2.4 W/ft (8 W/m - Static White Linea)
 3.0 - 3.0 W/ft (9.8 W/m - Static White, Static Color, Variable White)
 4.3 - 4.3 W/ft (14 W/m - Static White Linea)
 4.4 - 4.4 W/ft (14.4 W/m - Static White, Static Color, RGBW, RGBWW, RGBA)
 5.2 - 5.2 W/ft (17.1 W/m - Warm Dim)
 5.0 - 5.0 W/ft (16.4 W/m - Static White, Static Color)
 5.5 - 5.5 W/ft (18.0 W/m - RGBW, RGBA)
 6.0 - 6.0 W/ft (19.7 W/m - Static White, Static Color, Variable White)
 6.1 - 6.1 W/ft (20 W/m - Variable White Linea)
 8.8 - 8.8 W/ft (28.86 W/m - RGBW, RGBWW)


COLOR

18 - 1800K
 20 - 2000K
 22 - 2200K
 24 - 2400K
 27 - 2700K
 30 - 3000K
 35 - 3500K
 40 - 4000K
 60 - 6000K
 R - Red
 A - Amber
 G - Green
 B - Blue
 RGB27 - Red, Green, Blue + 2700K
 RGB30 - Red, Green, Blue + 3000K
 RGB40 - Red, Green, Blue + 4000K
 RGB2465 - Red, Green, Blue + 2400K + 6500K
 RGBA - Red, Green, Blue + Amber
 VW - Variable White
 2920 - Warm Dim 2900K-2000K (IP20)
 2721 - Warm Dim 2900K-2000K (IP65)
 Z - Undecided**
 ** For quotes only. Must be chosen before final order.

CONNECTION OPTIONS (See diagrams on the right)

- | | |
|------------------------------------|-------------------------------------|
| 1 - End Feed Bare Wire Connection | 4 - End Feed with IP67 Male Coupler |
| 2 - Back Feed Bare Wire Connection | 5 - Soldered Daisy Chain |
| 3 - Side Feed Bare Wire Connection | 6 - Daisy Chain With IP67 Couplers |

Custom Length (ft.)





RIBBONLYTE SPECIFICATIONS & COMPATIBILITY

Available Wattages	Cuttable Length	LED Pitch	Color Temp.	lm/W without Lens	Delivered Lumens with Milky Lens	Max Length	Compatible with Channel IP20
0.75 Static White Series 2	1.97 in (50 mm)	48 LEDs/ft (160 LEDs/m)	1800K	84	44.1 lm/ft (144.6 lm/m)	49 ft (15 m)	✓
			2000K	99	52 lm/ft (170.6 lm/m)		
			2200K	109	57.2 lm/ft (187.6 lm/m)		
			2400K	113	59.3 lm/ft (194.5 lm/m)		
			2700K	123	64.6 lm/ft (211.9 lm/m)		
			3000K	123	64.6 lm/ft (211.9 lm/m)		
			3500K	130	68.3 lm/ft (224 lm/m)		
			4000K	134	70.4 lm/ft (230.9 lm/m)		
	1.97 in (50 mm)	48 LEDs/ft (160 LEDs/m)	6000K	131	68.8 lm/ft (225.7 lm/m)	49 ft (15 m)	✓
			1800K	84	88.2 lm/ft (289.3 lm/m)		
			2000K	98	102.9 lm/ft (337.5 lm/m)		
			2200K	109	114.5 lm/ft (375.6 lm/m)		
			2400K	113	118.7 lm/ft (389.3 lm/m)		
			2700K	123	129.2 lm/ft (423.8 lm/m)		
			3000K	123	129.2 lm/ft (423.8 lm/m)		
			3500K	129	135.5 lm/ft (444.4 lm/m)		
	1.97 in (50 mm)	48 LEDs/ft (160 LEDs/m)	4000K	134	140.7 lm/ft (461.5 lm/m)	42 ft (12.8 m)	✓
			6000K	131	137.6 lm/ft (451.3 lm/m)		
			1800K	83	127.8 lm/ft (419.2 lm/m)		
			2000K	96	147.8 lm/ft (484.8 lm/m)		
			2200K	106	163.2 lm/ft (535.3 lm/m)		
			2400K	111	170.9 lm/ft (560.6 lm/m)		
			2700K	120	184.8 lm/ft (606.1 lm/m)		
			3000K	122	187.9 lm/ft (616.3 lm/m)		
	1.97 in (50 mm)	48 LEDs/ft (160 LEDs/m)	3500K	127	195.6 lm/ft (641.6 lm/m)	36 ft (11 m)	✓
			4000K	133	204.8 lm/ft (671.7 lm/m)		
			6000K	128	197.1 lm/ft (646.5 lm/m)		
			2400K	109.8	230.6 lm/ft (756.5 lm/m)		
			2700K	122.9	258.1 lm/ft (846.7 lm/m)		
			3000K	130	273 lm/ft (895.3 lm/m)		
	1.97 in (50 mm)	48 LEDs/ft (160 LEDs/m)	3500K	133	279.3 lm/ft (916.1 lm/m)	28 ft 4 in. (8.64 m)	✓
			4000K	133	279.3 lm/ft (916.1 lm/m)		
			6000K	127	266.6 lm/ft (874.5 lm/m)		
			2400K	109	335.7 lm/ft (1101.2 lm/m)		
			2700K	122	375.8 lm/ft (1232.5 lm/m)		
			3000K	129	397.3 lm/ft (1303.2 lm/m)		
	1.4 in (35.7 mm)	68 LEDs/ft (224 LEDs/m)	3500K	132	406.6 lm/ft (1333.5 lm/m)	33 ft 4 in. (10.1 m)	✓
			4000K	132	406.6 lm/ft (1333.5 lm/m)		
			6000K	126	388.1 lm/ft (1272.9 lm/m)		
			2400K	109.8	384.4 lm/ft (1260.8 lm/m)		
			2700K	122.9	430.2 lm/ft (1411.2 lm/m)		
			3000K	130	454.9 lm/ft (1492.1 lm/m)		
	1.4 in (35.7 mm)	68 LEDs/ft (224 LEDs/m)	3500K	133	465.5 lm/ft (1526.8 lm/m)	28 ft (8.5 m)	✓
			4000K	133	465.5 lm/ft (1526.8 lm/m)		
			6000K	127	444.3 lm/ft (1457.4 lm/m)		
			2400K	109	457.8 lm/ft (1501.6 lm/m)		
			2700K	122	512.4 lm/ft (1680.7 lm/m)		
			3000K	129	541.8 lm/ft (1777.1 lm/m)		
	1.4 in (35.7 mm)	68 LEDs/ft (224 LEDs/m)	3500K	132	554.4 lm/ft (1818.4 lm/m)		✓
			4000K	132	554.4 lm/ft (1818.4 lm/m)		
			6000K	126	529.2 lm/ft (1735.8 lm/m)		


SPECIFICATIONS

Available Wattages	Cuttable Length	LED Pitch	Color Temp.	lm/W Delivered	Delivered Lumens with Milky Lens	Max Length	Compatible with Channel IP20
0.75 Static Color Series 2	1.97 in (50 mm)	48 LEDs/ft (160 LEDs/m)	Red	41	22 lm/ft (70.6 lm/m)	49 ft (15 m)	✓
			Green	175	92 lm/ft (301.4 lm/m)		
			Amber	19	10 lm/ft (32.7 lm/m)		
			Blue	34	18 lm/ft (58.6 lm/m)		
1.5 Static Color Series 2	1.97 in (50 mm)	48 LEDs/ft (160 LEDs/m)	Red	42	44 lm/ft (144.7 lm/m)	49 ft (15 m)	✓
			Green	160	168 lm/ft (551.1 lm/m)		
			Amber	18	19 lm/ft (62 lm/m)		
			Blue	34	36 lm/ft (117.1 lm/m)		
2.2 Static Color Series 2	1.97 in (50 mm)	48 LEDs/ft (160 LEDs/m)	Red	42	65 lm/ft (212.2 lm/m)	42 ft (12.8 m)	✓
			Green	145	223 lm/ft (732.4 lm/m)		
			Amber	18	28 lm/ft (90.9 lm/m)		
			Blue	33	51 lm/ft (166.7 lm/m)		
3.0 Static Color Series 2	1.97 in (50 mm)	48 LEDs/ft (160 LEDs/m)	Red	40	84.0 lm/ft (275.52 lm/m)	32.8 ft (10 m)	✓
			Green	127	266.7 lm/ft (874.776 lm/m)		
			Amber	25	52.5 lm/ft (172.2 lm/m)		
			Blue	29	60.9 lm/ft (199.752 lm/m)		
4.4 Static Color Series 2	1.97 in (50 mm)	48 LEDs/ft (160 LEDs/m)	Red	38	117.0 lm/ft (383.8912 lm/m)	29 ft (8.8 m)	✓
			Green	117	360.4 lm/ft (1181.981 lm/m)		
			Amber	24	73.9 lm/ft (242.4576 lm/m)		
			Blue	25	77.0 lm/ft (252.56 lm/m)		
5.0 Static Color Series 2	1.4 in (35.7 mm)	68 LEDs/ft (224 LEDs/m)	Red	37	129.5 lm/ft (424.76 lm/m)	30 ft (9.14 m)	✓
			Green	116	406.0 lm/ft (1331.68 lm/m)		
			Amber	24	84.0 lm/ft (275.52 lm/m)		
			Blue	26	91.0 lm/ft (298.48 lm/m)		
6.0 Static Color Series 2	1.4 in (35.7 mm)	68 LEDs/ft (224 LEDs/m)	Red	37	155.4 lm/ft (509.712 lm/m)	28 ft (8.5 m)	✓
			Green	113	474.6 lm/ft (1556.688 lm/m)		
			Amber	23	316.848 lm/ft (1777.1 lm/m)		
			Blue	24	330.624 lm/ft (1818.4 lm/m)		
2.4 Static White Linea	1.97 in. (50 mm)	146 LEDs/ft (480 LEDs/m)	2700K	67	112.7 lm/ft (369.6 lm/m)	21.3 ft (6.5 m)	✓
			3000K	71	119 lm/ft (391.3 lm/m)		
			3500K	83	139.3 lm/ft (457.8 lm/m)		
			4000K	83	139.3 lm/ft (457.8 lm/m)		
3.0 Static White Linea	1.97 in. (50 mm)	146 LEDs/ft (480 LEDs/m)	2700K	66	138.6 lm/ft (455 lm/m)	21.3 ft (6.5 m)	✓
			3000K	73	153.3 lm/ft (503.3 lm/m)		
			3500K	78	163.8 lm/ft (537.6 lm/m)		
			4000K	83	174.3 lm/ft (571.9 lm/m)		
4.3 Static White Linea	1.97 in. (50 mm)	146 LEDs/ft (480 LEDs/m)	2700K	75	226.1 lm/ft (740.6 lm/m)	24.6 ft (7.5 m)	✓
			3000K	78	234.5 lm/ft (770 lm/m)		
			3500K	86	259 lm/ft (849.8 lm/m)		
			4000K	86	259 lm/ft (849.8 lm/m)		
6.1 Variable White Linea	1.09 in. (27.78 mm)	175 LEDs/ft (576 LEDs/m)	2700K + 6500K	95	406 lm/ft (1332.1 lm/m)	16.4 ft (5 m)	✓
1.0 Variable White Series 2	1.97 in (50 mm)	42 LEDs/ft (140 LEDs/m)	2000K + 6500K	85	60 lm/ft (200 lm/m)	32.8 ft (10 m)	✓
3.0 Variable White Series 2	1.97 in (50 mm)	42 LEDs/ft (140 LEDs/m)	2000K + 6500K	80	168.0 lm/ft (551.2 lm/m)	32.8 ft (10 m)	✓
6.0 Variable White Series 2	1.97 in (50 mm)	42 LEDs/ft (140 LEDs/m)	2000K + 6500K	75	315.0 lm/ft (1033.5 lm/m)	19 ft 8 in. (6 m)	✓
4.4 RGBW Series 2	1.97 in. (50 mm)	36 LEDs/ft (120 LEDs/m)	RGBW	45	138.6 lm/ft (454.7 lm/m) All LEDs at 100%	19 ft 8 in. (6 m)	✓
8.8 RGBW Series 2	1.97 in. (50 mm)	36 LEDs/ft (120 LEDs/m)	RGBW	61	375.8 lm/ft (1232.9 lm/m) All LEDs at 100%	16 ft 4 in. (5 m)	✓

SPECIFICATIONS


Available Wattages	Cuttable Length	LED Pitch	Color Temp.	lm/W Delivered	Delivered Lumens with Milky Lens	Max Length	Compatible with Channel IP20
4.4 5-in-1 RGBWW	2.46 in. (62.5 mm)	29 LED/ft (96 LED/m)	RGBWW	59	194.7 lm/ft (638.8 lm/m) All LEDs at 100%	16 ft 4 in (5 m)	✓
8.8 5-in-1 RGBWW	2.46 in. (62.5 mm)	29 LED/ft (96 LED/m)	RGBWW	50	330.0 lm/ft (1082.7 lm/m) All LEDs at 100%	11 ft 6 in (3.5 m)	✓
5.2 Warm Dim	3.94 in (100 mm)	36 LEDs/ft (120 LEDs/m)	WARM DIM	39	201.6 lm/ft (661.5 lm/m)	16 ft 4 in. (5 m)	✓

DIODE VISIBILITY CHART (Data below applies to installations with Milky lens only)


 No Visible Diode = N Note: Linea RibbonLyte has no visible diode				 With Visible Diode = Y			
Static White & Static Color RibbonLyte				Color Changing RibbonLyte			
0.75/1.5/2.2	3.0/4.4	5.0/6.0	4.4 RGBW Series 2	8.8 RGBW Series 2	4.4/8.8 5-in-1 RGBWW	Warm Dim	Variable White
IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP20
N	N	N	Y	Y	Y	N	N

BASIC INSTALLATION (DOUBLE FLANGE)


1. Measure and cut a recess in the drywall and place the Fixture (A) into the recess, making sure the flanges sit flush on both walls.




2. Fasten the Fixture (A) by inserting drywall screws** through the flanges on both sides approximately every 18". Insert the Ribbonlyte into the fixture.



3. Plaster over the flanges and screws up to the lip in the fixture to create a seamless joint. Use plaster tape to preserve the lens and visible portion of the Fixture (A).



4. Insert the Lens by snapping it into place. Press fit the End Caps to complete the assembly.




* See SC3 installation guide for full installation steps.

** Recommended screw size: 4-40/48 countersunk flat head

AVAILABLE DRIVERS / CONTROLLERS AND DIMMING OPTIONS / WIRE GAUGE CHART

NON-DIMMING ELECTRONIC DRIVERS		0-10V/ELV/MLV 3-IN-1		0-10V VW/WD	
					
30W, 60W, 96W Non-Dimming Electronic Class 2 Drivers	240W, 320W Non-Dimming Electronic Drivers	60W, 96W Non-Dimming Compact Drivers	60W, 96W, 288W 0-10V/ELV/MLV 3-in-1 Dimmable Drivers	0-10V Dimmable 90W VW/WD Driver	
Part No.: • DRVW2430 (30 W) • DRVW2460 (60 W) • DRVW2496 (96 W)	Part No.: • DRVW24240 (240 W) • DRVW24320 (320 W)	Part No.: • DRV2460C (60 W) • DRV2496C (96 W)	Part No.: • DRVW2460TRI010 (60 W) • DRVW2496TRI010 (96 W) • DRVW24288TRI010 (288 W)	Part No.: • DRVRFWDVW2490120	
24 VDC 120-277 VAC IP65, dry/damp locations UL Listed	24 VDC 90-305 VAC IP65, dry/damp locations UL Recognized	24 VDC 120-277 VAC IP20, dry locations UL Class P	24 VDC 120-277 VAC IP65, dry/damp/wet locations UL Listed	24 VDC 100-277 VAC IP23, dry/damp locations UL Listed	
ATHENA WIRELESS COMPATIBLE		CASAMBI COMPATIBLE DRIVERS		DIMMABLE DALI-2 DRIVERS	
					
94W Athena Wireless Compatible Drivers	100W & 200W Casambi Compatible 4 Channel Drivers	96W DIMMABLE DALI-2 DT6 D4I & DALI-2 DT8 D4I DRIVERS		75W, 150W, 240W DALI-2 Dimmable Drivers	
Part No.: • DRVW2494ATH1CH (1 channel) • DRVW2494ATH2CH (2 channel)	Part No.: • DRVW24100CAS4CH (100 W) • DRVW24200CAS4CH (200 W)	Part No.: • DRVW2496DALI1CH (1 channel) • DRVW2496DALI2CH (2 channel)		Part No.: • DRVW2475DALI1CH (75 W, 1 channel) • DRVW24150DALI1CH (150 W, 1 channel) • DRVW24240DALI1CH (240 W, 1 channel) • DRV24150DALI2CH (150 W, 2 channels) • DRV24150DALI4CH (150 W, 4 channels)	
24 VDC 100-277 VAC Dry locations UL Listed	24 VDC 100-277 VAC IP66, dry/damp/wet locations UL Listed, CE, RoHS, Bluetooth, CASAMBI	24-26 VDC 120-277 VAC IP67, dry/damp/wet locations UL Listed		24 VDC 120-277 VAC IP67, damp/wet locations (1-channel drivers only) IP20, dry location (2-channel & 4-channel drivers only) CE, RoHS, SELV	

DMX CONTROLLERS, VARIABLE WHITE DIMMER, WARM DIM DIMMER - FOR COLOR CHANGING FIXTURES


 GLASS TOUCH WALL CONTROLLERS Part No.: • AWCRCBWWBK • AWCWBBK		 1 ZONE WALL CONTROLLER Part No.: DMXCTRLG		 5 ZONE WALL CONTROLLER Part No.: DMXCTRL		 10 ZONE WALL CONTROLLER Part No.: DMXCTRLD		 6 UNIVERSE DMX CONTROLLER Part No.: DMXCTRLDR6U	
 VARIABLE WHITE DIMMER Part No.: • RFDIMVDDWH (White) • RFDIMVDBK (Black)		 WARM DIM DIMMER Part No.: • RFDIMDDWH (White) • RFDIMDDBK (Black)		 4 CHANNEL WATERPROOF DMX INTERFACE Part No.: DMXINFWLC4D		 5 CHANNEL DMX DECODER Part No.: DMXINF5		 DMX OPTO SPLITTER Part No.: DMXOS8	

DRIVER AND RIBBONLYTE AT FULL LOAD


Wattages	30		60		96		150		200		240		300		320	
	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters
24 AWG / 0.25 mm ²	14	4.27	9	2.74	5.5	1.68	3.75	1.14	2.75	0.84	2.25	0.69	1.75	0.53	1.75	0.53
22 AWG / 0.34 mm ²	22	6.71	14	4.27	9	2.74	5.75	1.75	4.5	1.37	3.5	1.07	2.75	0.84	2.75	0.84
20 AWG / 0.5 mm ²	35	10.67	23	7.01	14	4.27	9	2.74	7	2.13	5.75	1.75	4.5	1.37	4.25	1.30
18 AWG / 0.75 mm ²	56	17.07	37	11.28	23	7.01	15	4.57	11	3.35	9	2.74	7.5	2.29	7	2.13
16 AWG / 1.5 mm ²	90	27.44	60	18.29	37	11.28	24	7.32	18	5.49	15	4.57	12	3.66	11	3.35
14 AWG / 2.5 mm ²	142	43.29	95	28.96	59	17.99	38	11.59	28	8.54	23	7.01	19	5.79	17	5.18
12 AWG / 4 mm ²	226	68.90	151	46.04	94	28.66	60	18.29	45	13.72	37	11.28	30	9.15	28	8.54
10 AWG / 6 mm ²	360	109.76	240	73.17	150	45.73	96	29.27	72	21.95	60	18.29	48	14.63	45	13.72
8 AWG / 10 mm ²	574	175.00	381	116.16	239	72.87	153	46.65	115	35.06	95	28.96	76	23.17	71	21.65

WIRING DIAGRAMS - STATIC WHITE / STATIC COLOR / RGBW / RGBA / RGBWW


0-10 V




MLV / ELV




DMX WIRING WITH STATIC WHITE & STATIC COLOR RIBBONLYTE




DALI-2 WIRING WITH STATIC WHITE & STATIC COLOR RIBBONLYTE



STATIC WHITE & STATIC COLOR RIBBONLYTE WIRING WITH ATHENA WIRELESS COMPATIBLE DRIVER



DMX WITH RGBWW 5-IN-1 RIBBONLYTE



WIRE COLORS PER RIBBONLYTE COLOR

STATIC WHITE + STATIC COLOR

Red Wire (+) Positive
Black Wire (-) Negative

RGBW + RGBA


Black Wire (+) Positive
Green Wire (-) goes to Green Channel
Red Wire (-) goes to Red Channel
Blue Wire (-) goes to Blue Channel
White Wire (-) goes to White Channel

RGBWW

Black (+) Positive
Green Wire (-) goes to Green Channel
Red Wire (-) goes to Red Channel
Blue Wire (-) goes to Blue Channel
White Wire (-) goes to White Channel 1
Brown Wire (-) goes to White Channel 2

WIRING DIAGRAMS - VARIABLE WHITE

2-CHANNEL VARIABLE WHITE DIMMING




WIRE COLORS PER RIBBONLYTE COLOR


VARIABLE WHITE

Black Wire (+) Positive
Red Wire (-) goes to Warm White Channel
Green Wire (-) goes to Cool White Channel


DMX WIRING WITH VARIABLE WHITE RIBBONLYTE



DALI-2 WIRING WITH VARIABLE WHITE RIBBONLYTE



VARIABLE WHITE RIBBONLYTE WIRING WITH ATHENA WIRELESS COMPATIBLE DRIVER



REV.21OCT2025

GLOBAL HQ

320 Murray Hill Pkwy
East Rutherford, NJ 07073
U.S.
T: (+1) 212 629 6830
E: Sales-US@GENLEDBrands.com

EUROPEAN HQ

Hogeweyselaan 119
1382 JK Weesp
Netherlands
T: (+31) 346 235 000
E: SalesEurope@GENLEDBrands.com

MEINA HQ

PO Box 371378, #823, Building 4EA
Dubai Airport Free Zone
Dubai, UAE
T: (+971) 4 701 7901
E: SalesMEINA@genledbrands.com

ASIA-PACIFIC HQ

Room 402, Building D
Shenshi Tongchuang Science and Technology Park
No. 16 Hongyin Road
Xingqiang Community, Xinhua Street
Guangming District, Shenzhen, China 518107
T: (+86) 755 8529 0710
E: Sales-Pacific@GENLEDBrands.com