



LYTERAYZ[®] LRZ3 COLOR

The LyteRayz[®] LRZ3 Color is part of our LyteRayz[®] value line series. Our triple-LED LRZ3 modules are available in three static colors: red, green and blue. Great for channel letters, box signs and cove lighting, LRZ3 Color modules have an IP66 rating and a five-year warranty.

Applications:

- Channel letters
- Box signs
- Cove lighting
- Available in red, green or blue
- Applications starting at 3" (75 mm) depth



12V DC



5 YEAR LIMITED WARRANTY



50,000 HRS
L70 LIFETIME



ORDERING GUIDE

Part Number	White Color Temperatures & Colors	LEDs per Module	Module Spacing (mm)	Number of Modules		Nominal Light Output (lm)*		
				Per Foot	Per Meter	Per Module	Per Foot	Per Meter
LS-LRZ3-RED-B200-A	Red (620-625nm)	3	200	1.5	5	40	61	200
LS-LRZ3-BLU-B200-A	Blue (460-470nm)	3	200	1.5	5	20	30	100
LS-LRZ3-GRN-B200-A	Green (520-525nm)	3	200	1.5	5	90	137	450

PRODUCT RATINGS

Luminous Efficacy	38 lm/W (Red) 19 lm/W (Blue) 79 lm/W (Green)
Wattage per Module	0.90 W/module
Input Voltage	12 V DC
Input Current	75 mA
Power Supply Loading	66 modules per 60W
Ingress Protection	IP66
Operating Temperature	-13° - + 131° F (-25° - +55° C)
L70 Lifetime @ 60° C	50,000 Hours
Warranty	5 Year Limited Warranty

LUMINOUS INTENSITY DISTRIBUTION





MODULE DIMENSIONS

Part Number	Length (in/mm)	Width (in/mm)	Height (in/mm)
LS-LRZ3-XXX-B200-A	3.32/84	0.66/17	0.33/8

POWER SUPPLY LOADING

Module Type	per 60W			
	Max. # of Modules Per String	Total # of Modules	Total # of Feet	Total # of Meters
LS-LRZ3-XXX-B200-A	25	66	44	13.2

LAYOUT GUIDE*

Channel Depth (in.)	Single Row		Multiple Rows		Channel Depth (mm)	Single Row		Multiple Rows	
	Max. Stroke	Module Spacing	Row Spacing	Module Spacing		Max. Stroke	Module Spacing	Row Spacing	Module Spacing
3	8	8	4	4	75	200	200	100	100
4	12	8	7	6	100	300	200	175	150
5	16	8	10	8	125	400	200	250	200
6	18	8	12	8	150	450	200	300	200
7	22	8	12	8	175	550	200	300	200


*Module spacing is defined by 7328 white sign face material

SHIPPING INFORMATION

Module Type	Specs	Packaging Quantity		
		Per Bag	Per Box	Per Carton
LS-LRZ3-XXX-B200-A	Modules	60	600	1200
	Feet	39.4	394	787
	Meters	12	120	240

Carton Dimensions			Carton Weight	Box Dimensions			Box Weight
L	W	H		L	W	H	
20.5	14.6	10.2	20.0 kg (44.1 lbs)	13.78	9.84	9.06	9.5 kg (20.9 lbs)
520	370	260		350	250	230	in. mm

DIMENSION DRAWING



1. UL ONLY - These products are only suitable for connection to a UL rated Class 2 power source rated 12 Volt or less.
2. UL ONLY - These products are intended for use only when connected to a power source that complies with UL rated Class 2 voltage and energy limited circuit.
3. UL ONLY - When these units are connected to a UL rated Class 2 circuit, they are not to draw a total wattage of greater than the secondary or output rating of the UL rated Class 2 power supply.
4. These products may be secured in place in the end product by any means available.
5. These products are suitable for use in dry and damp locations. Not suitable for wet or submersed applications.