



With its slim, compact shape, the ULTRA 650 module is designed for brighter and deeper signs. ULTRA 650 features an innovative optic that expands its coverage across the sign, with light output up to 100 lumens per module. With spacing at 8 in. (200 mm), ULTRA 650 modules are rated IP68 and come with a 9-year warranty.

Applications:

- Channel letters
- Box signs
- Cove lighting
- Applications starting at 3 in. (75 mm)



ORDERING GUIDE

Part Number	CCTs	Module Spacing (in./mm)	Wattage (W)	Input Current (mA)	Number of Modules		Nominal Light Output (lm)*			
					Per Foot	Per Meter	Per Watt	Per Module	Per Foot	Per Meter
LS-U650-71K-B200-A	7100K	8 / 200	0.78	65	1.5	5	128	100	150	500
LS-U650-65K-B200-A	6500K	8 / 200	0.78	65	1.5	5	128	100	150	500
LS-U650-57K-B200-A**	5700K	8 / 200	0.78	65	1.5	5	128	100	150	500
LS-U650-50K-B200-A	5000K	8 / 200	0.78	65	1.5	5	128	100	150	500
LS-U650-45K-B200-A**	4500K	8 / 200	0.78	65	1.5	5	128	100	138	460
LS-U650-40K-B200-A**	4000K	8 / 200	0.72	60	1.5	5	128	92	138	460
LS-U650-30K-B200-A**	3000K	8 / 200	0.66	55	1.5	5	129	85	128	425
LS-U650-27K-B200-A**	2700K	8 / 200	0.72	60	1.5	5	118	85	128	425

** Limited stock



* ± 10%

PRODUCT RATINGS



Input Voltage	12 VDC
Power Supply Loading	70 modules per 60 W
Ingress Protection	IP68
Operating Temperature	-40 – 140 °F (-40 – 60 °C)
Lifetime (L70 reported)	50,000 hours @ 60 °C
Warranty	9-year limited warranty

LUMINOUS INTENSITY DISTRIBUTION

600 Series Batwing Beam Pattern



DIMENSIONS



Data sheet subject to change without notice.



SHIPPING INFORMATION

Module Type	Specs	Packaging Quantity			Carton Weight	Box Dimensions			Carton Dimensions			
		Per Bag	Per Box	Per Carton		W	D	H	W	D	H	
LS-U650-xxx-B200-A	Modules	100	500	2000	46.1 lb 20.9 kg	22.1	10.6	4.5	31.0	23.1	9.9	in.
	Feet	66	328	1312		560	270	115	788	588	252	mm
	Meters	20	100	400								

LAYOUT GUIDE*

Channel Depth (in.)	Single Row		Multiple Rows		Channel Depth (mm)	Single Row		Multiple Rows	
	Max. Stroke	Module Spacing	Row Spacing	Module Spacing		Max. Stroke	Module Spacing	Row Spacing	Module Spacing
3	10	6.5	6.5	6.5	75	250	165	165	165
4	13	7.87	9	7.87	100	330	200	225	200
5	17	7.87	13	7.87	125	430	200	330	200
6	17	7.87	16	7.87	150	430	200	405	200
7	15	7.87	15	7.87	175	380	200	380	200

*Density guide designed to maintain a minimum of 600 lux for a single row or 800 lux for multiple rows at sign face (7328 white).

POWER SUPPLY LOADING

LS-U650-xxx-B200-A					
	Power Supply	Max. # of Modules Per Continuous String	Total # of Modules Per Power Supply	Total # of Feet	Total # of Meters
UL CLASS 2	12 W	14	14	9.2	2.8
	15 W	17	17	11.2	3.4
	36 W	40	41	26.9	8.2
	60 W	67	70	45.9	14
	180 W	67	210	137.7	42
UL CLASS 1	100 W	67	115	75.5	23
	150 W	67	173	113.5	34.6
	180 W	67	207	135.8	41.4
	220 W	67	253	166	50.6

Note 1. The number of modules in each of the parallel strings should not exceed the specified maximum.
2. *3 - 60 Watt Channels



1. UL ONLY - These products are only suitable for connection to a UL rated Class 2 power source rated 12 Volt or less.
2. UL ONLY - These products are intended for use only when connected to a power source that complies with UL rated Class 2 voltage and energy limited circuit.
3. UL ONLY - When these units are connected to a UL rated Class 2 circuit, they are not to draw a total wattage of greater than the secondary or output rating of the UL rated Class 2 power supply.
4. These products may be secured in place in the end product by any means available.
5. These products are suitable for use in dry, damp, and wet locations. Not suitable for submersed applications.

GLOBAL HQ

320 Murray Hill Pkwy
East Rutherford, NJ 07073
U.S.
T: (+1) 212 629 6830
E: Sales-US@GENLEDBrands.com

EUROPEAN HQ

Hogeweyselaan 119
1382 JK Weesp
Netherlands
T: (+31) 346 235 000
E: SalesEurope@GENLEDBrands.com

MEINA HQ

PO Box 371378, #823, Building 4EA
Dubai Airport Free Zone
Dubai, UAE
T: (+971) 4 701 7901
E: SalesMEINA@genlebrands.com

ASIA-PACIFIC HQ

Room 402, Building D
Shenshi Tongchuang Science and Technology Park
No. 16 Hongyin Road
Xingqiang Community, Xinhui Street
Guangming District, Shenzhen, China 518107
Sales: (+86) 139 1836 3905
Office: (+86) 755 8529 0710
E: Sales-Pacific@GENLEDBrands.com