



ULTRA MINI Color modules are a popular choice for illuminating sleek, modern miniature channel letters. ULTRA MINI Color modules are available in True Red, Blue and Green, enabling a wide variety of applications for nuanced indoor and outdoor signage and accent lighting.

Applications:

- Outdoor miniature channel letters
- Outdoor acrylic block letters
- Ultra thin small channel letters
- Accent lighting



ORDERING GUIDE


Part Number	Color Temp.	Module Spacing (mm)	Number of Modules		Nominal Light Output (lm)*		
			Per Foot	Per Meter	Per Module	Per Foot	Per Meter
LS-UMIN-TRD-L4-50A	True Red (625 nm)	50	6.10	20	4.4	27	88
LS-UMIN-BLU-L4-50A	Blue (467 nm)	50	6.10	20	2.6	16	52
LS-UMIN-GRN-L4-50A	Green (526 nm)	50	6.10	20	11.6	71	232

* ± 10%

PRODUCT RATINGS

Luminous Efficacy	36.9 (TRD) 21.7 (BLU) 96.9 (GRN)
Wattage per Module	0.12 W Nominal 0.13 W Maximum
Input Voltage	12 V DC
Input Current	0.010 A/ module
Power Supply Loading	460 modules per 60 W
Ingress Protection	IP68
Operating Temperature	-40° — +140° F (-40° — +60° C)
L70 Lifetime @ 60° C	50,000 Hours
Warranty	5 Year Limited Warranty

LUMINOUS INTENSITY DISTRIBUTION



MODULE DIMENSIONS

Part Number	Length (in/mm)	Width (in/mm)	Height (in/mm)
LS-UMIN-xxx-L4-50A	0.70/17.0	0.31/8.0	0.39/9.8

SHIPPING INFORMATION

Module Type	Specs	Packaging Quantity			Carton Weight	Box Dimensions			Carton Dimensions			
		Per Bag	Per Box	Per Carton		W	D	H	W	D	H	
LS-UMIN-xxx-L4-50A	Modules	150	1200	6000	23.3 lb (21.2 lb)	18.1	8.3	3.3	18.9	18.9	9.3	inch
	Feet	24.6 (16.5)	197 (132)	984 (659)	10.6 kg (9.6 kg)	460	210	85	480	480	235	mm
	Meters	7.5 (5.0)	60 (40)	300 (200)								

Data sheet subject to change without notice.

REV:18JUL2024



LAYOUT GUIDE

Module Color (Face)	True Red (2793) / Green (7328)		Blue (2051)		True Red (2793) / Green (7328)		Blue (2051)	
	Single Row		Single Row		Multiple Rows		Multiple Rows	
	Min. Max. Stroke	Module Spacing	Min. Max. Stroke	Module Spacing	Row Spacing	Module Spacing	Row Spacing	Module Spacing
1.0	0.31 0.79	1.18	0.31 0.79	0.98	0.79	1.18	0.79	1.18
1.6	0.31 1.60	1.97	0.31 1.60	1.97	1.60	1.97	1.60	1.77
2.0	0.31 3.25	1.97	0.31 3.25	1.97	2.50	1.97	2.50	1.97
(mm)								
25	8 20	30	8 20	25	20	30	20	30
40	8 40	50	8 40	50	40	50	40	45
50	8 82	50	8 82	50	63	50	63	50

Module spacing is defined to achieve minimum 600 lux at sign face (7328 white)


POWER SUPPLY LOADING

Module Type		LS-UMIN-xxx-L4-50A				LED Module to power supply wire size			
	Power Supply (wired in Parallel Strings)	Total # of Modules	Max. # of Modules Per String	Total # of Feet	Total # of Meters	Wire size		Max Distance	
						Gauge AWG	Metric (mm ²)	Feet	Meters
UL CLASS 2	12 W	92	92	15.1	4.6	26	0.13	3	0.9
	15 W	115	115	18.9	5.8	24	0.21	4	1.2
	35 W	268	200	44.0	13.4	22	0.33	7	2.1
	60W	460	200	75.5	23.0	20	0.52	11	3.4
	180W**	1350	200	226.5	69	18	0.82	18	5.5
UL CLASS 1	100W	750	200	123.0	37.5	16	1.31	29	8.8
	150W	1125	200	184.5	56.3	14	2.08	45	13.7
	180W	1350	200	221.5	67.5	12	3.31	71	21.6
	220W	1650	200	270.7	82.5	10	5.26	120	36.6

The number of modules in each of the parallel strings should not exceed the specified maximum.
 ** 3 - 60 watt channels

Distance from 60W power supply to 100% load

DIMENSION DRAWING



1. UL ONLY - These products are only suitable for connection to a UL rated Class 2 power source rated 12 Volt or less.
2. UL ONLY - These products are intended for use only when connected to a power source that complies with UL rated Class 2 voltage and energy limited circuit.
3. UL ONLY -When these units are connected to a UL rated Class 2 circuit, they are not to draw a total wattage of greater than the secondary or output rating of the UL rated Class 2 power supply.
4. These products may be secured in place in the end product by any means available.
5. These products are suitable for use in dry, damp, and wet locations. Not suitable for submersed applications.

GLOBAL HQ

320 Murray Hill Pkwy
East Rutherford, NJ 07073
T: (+1) 212 629 6830
E: Sales-US@GENLEDBrands.com

EUROPEAN HQ

De Corridor 16K
3621ZB Breukelen
Netherlands
T: (+31) 346 235 000
E: SalesEurope@GENLEDBrands.com

MEINA HQ

PO Box 371378, #823, Building 4EA
Dubai Airport Free Zone, Dubai, UAE
T: (+971) 4 701 7901
E: SalesMEINA@genledbrands.com

ASIA-PACIFIC HQ

Room 402, Building D
Shenshi Tongchuang Science and Technology Park
No. 16 Hongyin Road
Xingqiang Community, Xinhui Street
Guangming District, Shenzhen, China 518107
Sales: (+86) 139 1836 3905
Office: (+86) 755 8529 0710
E: Sales-Pacific@GENLEDBrands.com

 [linkedin.com/company/agilight-inc](https://www.linkedin.com/company/agilight-inc)

 [facebook.com/AgiLightLED](https://www.facebook.com/AgiLightLED)

 [instagram.com/agilightled](https://www.instagram.com/agilightled)