Rapid Channel by Acolyte



WORK WITH THE SPEED OF LIGHT

RAPID RIBBON ACCESSORIES

Every lighting system comes complete with the necessary hardware to ensure a proper installation. Accessories include solderless connectors, jumpers, mounting clips, and 20 AWG 2-conductor and 5-conductor wires.

	IP20 RibbonLyte to RibbonLyte Solderless Connector	IP20 RibbonLyte to RibbonLyte Solderless Connector for 4.4 Panid Pibbon PGRW	4" Jumper for 1.5/3.0/5.0 Rapid Ribbon 95+	4" Jumper for 4.4 Rapid Ribbon RGBW
Height	0.31 in (7.86 mm)	0.31 in (7.86 mm)	0.31 in (7.86 mm)	0.31 in (7.86 mm)
Width	0.52 in (13.2 mm)	0.57 in (14.6 mm)	0.67 in (17 mm)	0.52 in (13.2 mm)
.ength	0.96 in (24.4 mm)	0.96 in (24.4 mm)	0.96 in (24.4 mm)	0.77 in (19.6 mm)
	Part No. RBCNCT820W2S2	Part No. RBCNCT1020W2S2	Part No. RBCNCT1220W2S5	Part No. RBCNCT820S2S2
	Eddle I	E Alleria		la l
	IP20 Wire to RibbonLyte Solderless Connector for 1.5 & 3.0 Rapid Ribbon 95+	IP20 Wire to RibbonLyte Solderless Connector for 5.0 Rapid Ribbon 95+	IP20 Wire to RibbonLyte Solderless Connector for 4.4 Rapid Ribbon RGBW	IP20 RibbonLyte to RibbonLyte Solderless Connector for 1.5 & 3.0 Rapid Ribbon 95+

	IP20 RibbonLyte to RibbonLyte Solderless Connector for 5.0 Rapid Ribbon 95+	IP20 RibbonLyte to RibbonLyte Solderless Connector for 4.4 Rapid Ribbon RGBW	4" Jumper for 1.5/3.0/5.0 Rapid Ribbon 95+	4" Jumper for 4.4 Rapid Ribbon RGBW
	I. What			
	Part No. RBCNCT1020S2S2	Part No. RBCNCT1220S2S5	Part No. for 1.5/3.0 RBCNCT820JUMP4 for 5.0 RBCNCT1020JUMP4	Part No. RBCNCT1220JUMP5
Length	0.77 in (19.6 mm)	0.77 in (19.6 mm)	for 1.5/3.0: 5.83 in (148 mm) for 5.0: 6.26 in (159 mm)	7.09 in (180 mm)
Width	0.57 in (14.6 mm)	0.69 in (17.6 mm)	for 1.5/3.0: 0.52 in (13.2 mm) for 5.0: 0.57 in (14.6 mm)	0.35 in (8.9 mm)
Height	0.31 in (7.86 mm)	0.31 in (7.86 mm)	0.31 in (7.86 mm)	0.31 in (7.86 mm)

	20-foot (6.1 m) 20 GAUGE 2-Conductor Wire for 1.5/3.0/5.0 Rapid Ribbon 95+	20-foot (6.1 m) 20 GAUGE 5-Conductor Wire for Rapid Ribbon RGBW
	Part No. RBCNCT6.1M2C	Part No. RBCNCT6.1M5C
Length	20 feet (6.1 meter)	20 feet (6.1 meter)
Width	0.16 in (4 mm)	0.35 in (8.9 mm)
Height	0.08 in (2 mm)	0.08 in (2 mm)

	Flat Mounting Clip for 1.5/3.0/5.0 Rapid Ribbon 95+
	Part RBMNTSIL
Screw Head Diameter	0.27 in (6.9 mm)
Screw Head Height	0.36 in (9.2 mm)
Clip Length	1.07 in (27.2 mm)
Clip Width	0.24 in (6.1 mm)
Screw Hole Diameter	0.09 in (2.46 mm)
Screw Hole Distance	0.88 in (22.6 mm)

Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.