

Solderless Connectors

for Rapid Ribbon

8 mm Ribbon to Ribbon Solderless Connector

CE



RoHS IP20

Current: 5 A

Number of Pins: 2 pins Voltage: 3-24 V

For 1.5 & 3.0 W/ft Rapid Ribbon 95+

MA241.52ZV4

Fits in Rapid Channel C2, R2, S1 and S2







Material: Polycarbonate and copper Dimensions (L x W x H): $0.85 \times 0.37 \times 0.17$ in. 21.6 x 9.5 x 4.3 mm

Part #: RBCNCT820S2S2

8 mm Ribbon to Wire Solderless Connector

For 1.5 & 3.0 W/ft Rapid Ribbon 95+



Fits in Rapid Channel C2, R2, S1 and S2

Number of Pins: 2 pins

Voltage: 3-24 V Current: 5 A

Wire: 20AWG / 0.52 mm²

Material: Polycarbonate and copper Dimensions (L x W x H): $0.61 \times 0.37 \times 0.17$ in.

15.4 x 9.5 x 4.3 mm

Number of Pins: 2 pins

Part #: RBCNCT820W2S2

10 mm Ribbon to Ribbon Solderless Connector

For 5.0 W/ft Rapid Ribbon 95+

Fits in Rapid Channel C2, R2, S1 and S2









Voltage: 3-24 V Current: 5 A

Material: Polycarbonate and copper Dimensions (L x W x H): 0.85 x 0.45 x 0.17 in.

> 21.6 x 11.5 x 4.3 mm Part #: RBCNCT1020S2S2

10 mm Ribbon to Wire Solderless Connector

For 5.0 W/ft Rapid Ribbon 95+



Fits in Rapid Channel C2, R2, S1 and S2

Number of Pins: 2 pins

Voltage: 3-24 V Current: 5 A Wire: 20AWG / 0.52 mm²

Material: Polycarbonate and copper Dimensions (L x W x H): $0.61 \times 0.45 \times 0.17$ in.

> 15.4 x 11.5 x 4.3 mm Part #: RBCNCT1020W2S2

12 mm Ribbon to Ribbon Solderless Connector

For 4.4 W/ft Rapid Ribbon RGBW



This connector does not fit in our Rapid Channels (C2, R2, S1, S2) and needs to be placed outside of the Rapid Channels.

Number of Pins: 5 pins Voltage: 3-24 V

Material: Polycarbonate and copper Dimensions (L x W x H): 0.79 x 0.58 x 0.25 in.

20 x 14.7 x 6.4 mm Part #: RBCNCT1220S2S5

12 mm Ribbon to Wire Solderless Connector

For 4.4 W/ft Rapid Ribbon RGBW



This connector does not fit in our Rapid Channels (C2, R2, S1, S2) and needs to be placed outside of the Rapid Channels.

Number of Pins: 5 pins Voltage: 3-24 V

Current: 5.5 A Wire: 20AWG / 0.52 mm²

Material: Polycarbonate and copper Dimensions (L x W x H): 0.75 x 0.58 x 0.25 in. 19.1 x 14.7 x 6.4 mm

Part #: RBCNCT1220W2S5

GLOBAL HQ

REV.07AUG2025

320 Murray Hill Pkwy East Rutherford, NJ 07073 T: (+1) 212 629 6830

E: Sales-US@GENLEDBrands.com

EUROPEAN HQ Hogeweyselaan 119

1382 JK Weesp Netherlands T: (+31) 346 235 000 E: SalesEurope@GENLEDBrands.com MEINA HQ

PO Box 371378, #823, Building 4EA Dubai Airport Free Zone Dubai, UAE T: (+971) 4 701 7901 E: SalesMEINA@genledbrands.com

ASIA-PACIFIC HQ

Room 402, Building D Shenshi Tongchuang Science and Technology Park No. 16 Hongvin Road Xinggiang Community, Xinhu Street Guangming District, Shenzhen, China 518107 T: (+86) 755 8529 0710 E: Sales-Pacific@GENLEDBrands.com