

Report No.:

Test Time: 2021/11/16 14:34

Luminaire Property

Luminaire Manufacturer:

Luminaire Category: COB RIBBONLYTE

Lamp Catalog: FCOB-24V-D480-3000-8W-6MM-IP20 RA>90

Lamp Description: 3000K

Luminous Length (mm): 500

Luminous Height (mm): 1.5

Current: 0.156 A

Power Factor: 1.000

Luminaire Description: RB90LINEA202.430

Number of Lamps: 480/M

Luminous Width (mm): 6

Voltage: 24.0 V

Power: 3.75 W

Photometric Results

CIE Class: Direct

Measurement Flux: 265.6 lm

Downward Ratio: 97%

Horizontal Diffuse Angle(10%,50%): H159.8,H112.9

Vertical Diffuse Angle(10%,50%): V193.1,V150

Luminaire Efficacy Rating (LER): 71

Max. Intensity: 73.38 cd

Total Rated Lamp Lumens: 265.6 lm


Efficiency: 100%

Upward Ratio: 3%


Central Intensity: 73 cd

Pos of Max. Intensity: H90 V2

Picture Of Luminaire



Luminous Intensity Distribution Curve



Average Diffuse Angle(50%): 131.4° Unit: cd

— C0-C180 — C90-C270

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Kerr

Gamma Plane (°):0.0-180.0: 1.0

Test Device: GPM-1800B



Distance: 9.028 m

Humidity: 60%

Inspector:




Luminous Intensity Distribution Curve



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Kerr

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Kerr

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:


Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	118	118	118	118	115	115	115	115	109	109	109	104	104	104	99	99	99	97
1	105	99	93	89	102	96	91	87	91	87	83	87	83	80	82	80	77	75
2	94	85	77	70	91	82	75	69	78	72	67	74	69	65	71	66	63	60
3	85	74	64	57	82	72	63	56	68	61	55	65	59	53	62	56	52	49
4	78	65	55	48	75	63	54	47	60	52	46	57	50	45	55	49	44	42
5	71	58	48	41	69	56	47	40	54	46	39	51	44	39	49	43	38	36
6	66	52	42	35	64	50	41	35	48	40	34	46	39	34	44	38	33	31
7	61	47	37	31	59	46	37	31	44	36	30	42	35	30	40	34	29	27
8	57	42	34	27	55	42	33	27	40	32	27	38	32	26	37	31	26	24
9	53	39	30	25	51	38	30	24	37	29	24	35	29	24	34	28	23	21
10	50	36	28	22	48	35	27	22	34	27	22	33	26	22	32	26	21	19

Spacing Criteria (0-180): 1.26

Spacing Criteria (90-270): 1.32

Spacing Criteria (Diagonal): 1.42



C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Kerr

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:

Isocandela (rectangle)




I_{max} (100%): 73 cd

(10%):	7 cd	(20%):	15 cd
(25%):	18 cd	(30%):	22 cd
(40%):	29 cd	(50%):	37 cd
(60%):	44 cd	(70%):	51 cd
(80%):	59 cd	(90%):	66 cd

C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Kerr

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

IsoLux Plot



Mounting Height: 5.0m Max Lux(100%): 2.9 lx

(10%): 0.3 lx	(20%): 0.6 lx
(25%): 0.7 lx	(30%): 0.9 lx
(40%): 1.2 lx	(50%): 1.5 lx
(60%): 1.8 lx	(70%): 2.1 lx
(80%): 2.3 lx	(90%): 2.6 lx



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Kerr

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300

a b c d e f g h




L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	18128	17040	15811	14273	12554	10371	7755	4819	1666
C90	26672	27660	28991	31006	33957	38743	47443	65495	112708
C180	18950	18011	16954	15608	14038	12104	9654	6669	3401
C270	25873	26761	27961	29838	32743	37496	46055	63457	105497


C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Kerr

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Illuminance at a Distance



Vertical IsoLux Plot



Lowest(m): 2.0m	Highest(m): 5.0m	Max Lux: 18.3 lx
(10%): 1.8 lx	(20%): 3.6 lx	
(25%): 4.6 lx	(30%): 5.5 lx	
(40%): 7.3 lx	(50%): 9.1 lx	
(60%): 10.9 lx	(70%): 12.8 lx	
(80%): 14.6 lx	(90%): 16.4 lx	

C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Kerr

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Area Flux Table


		Vertical plane																				
		-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90	Flux(T)	Flux(E)
Horizontal plane	-90	0.0	0.0	0.1	0.2	0.4	0.5	0.7	0.8	0.8	0.8	0.8	0.7	0.5	0.4	0.2	0.1	0.0	0.0	0.0	0.2	0.0
	-80	0.0	0.1	0.2	0.3	0.5	0.7	0.9	1.0	1.1	1.1	1.0	0.9	0.7	0.5	0.3	0.2	0.1	0.0	0.0	1.7	1.6
	-70	0.0	0.1	0.2	0.4	0.6	0.8	1.0	1.2	1.2	1.2	1.2	1.0	0.8	0.6	0.4	0.2	0.1	0.0	0.0	4.8	4.7
	-60	0.0	0.1	0.2	0.4	0.7	1.0	1.2	1.3	1.4	1.4	1.3	1.2	1.0	0.8	0.5	0.3	0.2	0.1	0.0	9.0	9.0
	-50	0.0	0.1	0.2	0.4	0.7	1.0	1.2	1.5	1.7	1.7	1.7	1.5	1.2	0.9	0.7	0.4	0.2	0.0	0.0	14.0	14.0
	-40	0.0	0.1	0.3	0.6	0.9	1.2	1.5	1.7	2.0	2.0	2.0	1.9	1.6	1.3	1.0	0.7	0.4	0.1	0.0	19.2	19.2
	-30	0.0	0.1	0.3	0.6	0.9	1.2	1.5	1.7	2.0	2.1	2.1	2.0	1.7	1.4	1.1	0.8	0.5	0.2	0.0	23.9	23.9
	-20	0.0	0.1	0.4	0.7	1.0	1.4	1.7	2.0	2.1	2.2	2.2	2.1	1.8	1.5	1.2	0.9	0.6	0.3	0.1	27.2	27.2
	-10	0.0	0.1	0.4	0.7	1.1	1.5	1.8	2.1	2.2	2.2	2.2	2.1	1.8	1.5	1.2	0.9	0.6	0.3	0.1	29.2	29.2
	0	0.0	0.1	0.4	0.7	1.1	1.5	1.8	2.1	2.2	2.2	2.2	2.1	1.8	1.5	1.2	0.9	0.6	0.3	0.1	29.2	29.2
	10	0.0	0.1	0.4	0.7	1.1	1.5	1.8	2.1	2.2	2.2	2.2	2.1	1.8	1.5	1.2	0.9	0.6	0.3	0.1	27.2	27.2
	20	0.0	0.1	0.4	0.7	1.0	1.4	1.7	2.0	2.1	2.1	2.0	1.7	1.4	1.1	0.8	0.5	0.3	0.1	0.0	23.8	23.8
	30	0.0	0.1	0.3	0.6	0.9	1.2	1.5	1.8	1.9	1.9	1.8	1.5	1.2	0.9	0.6	0.4	0.2	0.1	0.0	19.1	19.1
	40	0.0	0.1	0.3	0.6	0.9	1.2	1.5	1.8	1.9	1.9	1.8	1.5	1.2	0.9	0.6	0.4	0.2	0.1	0.0	13.8	13.8
	50	0.0	0.1	0.3	0.5	0.8	1.1	1.4	1.6	1.7	1.7	1.6	1.4	1.1	0.8	0.5	0.3	0.2	0.1	0.0	8.7	8.7
	60	0.0	0.1	0.2	0.4	0.7	1.0	1.2	1.4	1.5	1.5	1.4	1.2	1.0	0.7	0.4	0.2	0.1	0.0	0.0	4.4	4.4
	70	0.0	0.1	0.2	0.4	0.6	0.8	1.1	1.2	1.3	1.3	1.2	1.1	0.8	0.6	0.4	0.2	0.1	0.0	0.0	1.5	1.5
	80	0.0	0.1	0.2	0.3	0.5	0.7	0.9	1.0	1.1	1.1	1.0	0.9	0.7	0.5	0.3	0.2	0.1	0.0	0.0	0.2	0.2
	90	0.0	0.0	0.1	0.2	0.4	0.6	0.7	0.8	0.9	0.9	0.8	0.7	0.6	0.4	0.2	0.1	0.0	0.0	0.0	7.6	7.5
	Flux(T)	0.0	1.7	4.8	9.0	14.0	19.2	23.9	27.2	29.2	29.2	27.2	23.8	19.1	13.8	8.7	4.4	1.5	0.2	0.0	257	256
	Flux(E)	0.0	1.6	4.7	9.0	14.0	19.2	23.9	27.2	29.2	29.2	27.2	23.8	19.1	13.8	8.7	4.4	1.3	0.0	0.0		256

C Plane (°): 0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Kerr

Gamma Plane (°): 0.0-180.0: 1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:



The Average Illuminance Effective Figure



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Kerr

Gamma Plane (°):0.0-180.0: 1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	26.3	28.0	26.8	28.4	28.8	27.3	29.0	27.7	29.4	29.8
3H	28.1	29.7	28.5	30.1	30.5	29.9	31.5	30.3	31.8	32.3
4H	28.8	30.2	29.2	30.6	31.1	31.2	32.6	31.6	33.0	33.5
6H	29.2	30.6	29.6	31.0	31.4	32.5	33.9	32.9	34.3	34.7
8H	29.3	30.6	29.8	31.1	31.5	33.1	34.4	33.6	34.9	35.3
12H	29.4	30.6	29.8	31.1	31.6	33.7	35.0	34.2	35.4	35.9
X=4H Y=2H	27.2	28.7	27.6	29.1	29.5	28.0	29.4	28.4	29.8	30.3
3H	29.3	30.5	29.7	31.0	31.4	30.8	32.1	31.3	32.5	33.0
4H	30.1	31.3	30.6	31.7	32.2	32.3	33.4	32.8	33.9	34.4
6H	30.7	31.8	31.2	32.3	32.8	33.8	34.8	34.3	35.3	35.8
8H	30.9	31.9	31.4	32.4	32.9	34.5	35.5	35.0	36.0	36.5
12H	31.1	32.0	31.6	32.5	33.0	35.3	36.2	35.8	36.7	37.2
X=8H Y=4H	30.9	31.8	31.4	32.3	32.9	32.7	33.7	33.2	34.2	34.7
6H	31.8	32.6	32.3	33.2	33.7	34.4	35.3	35.0	35.8	36.3
8H	32.2	32.9	32.7	33.5	34.0	35.4	36.1	35.9	36.7	37.2
12H	32.5	33.2	33.0	33.7	34.3	36.3	37.0	36.8	37.5	38.1
X=12H Y=4H	31.1	32.0	31.6	32.5	33.0	32.7	33.6	33.3	34.2	34.7
6H	32.2	32.9	32.7	33.4	34.0	34.6	35.3	35.1	35.8	36.4
8H	32.7	33.3	33.2	33.9	34.5	35.6	36.3	36.1	36.8	37.4

Calculate in accordance with CIE 190:2010

C Plane (°):0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Kerr

Gamma Plane (°):0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Utilisation Factor Table(Floor cavity)

Utilisation Factors UF(F)			SHR NOM = 1.50									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.53	0.61	0.68	0.73	0.81	0.86	0.89	0.94	0.98	
	0.30		0.45	0.53	0.60	0.66	0.74	0.79	0.83	0.89	0.93	
	0.20		0.39	0.46	0.54	0.59	0.68	0.74	0.78	0.85	0.89	
0.50	0.50	0.20	0.51	0.59	0.65	0.70	0.77	0.82	0.85	0.90	0.93	
	0.30		0.44	0.51	0.58	0.64	0.71	0.76	0.80	0.85	0.89	
	0.20		0.39	0.46	0.53	0.58	0.66	0.71	0.76	0.82	0.86	
0.30	0.50	0.20	0.50	0.56	0.63	0.67	0.74	0.78	0.81	0.86	0.89	
	0.30		0.43	0.50	0.57	0.62	0.68	0.73	0.77	0.82	0.85	
	0.20		0.38	0.45	0.52	0.57	0.64	0.69	0.73	0.79	0.83	
0.00	0.00	0.00	0.36	0.42	0.49	0.53	0.60	0.65	0.69	0.74	0.77	
Rating: 4W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Utilisation Factor Table(Wall)

Utilisation Factors UF(W)			SHR NOM = 1.50									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	1.03	0.89	0.77	0.69	0.56	0.48	0.42	0.34	0.28	
	0.30		0.86	0.76	0.67	0.61	0.51	0.44	0.39	0.32	0.27	
	0.20		0.74	0.67	0.60	0.54	0.47	0.41	0.36	0.30	0.25	
0.50	0.50	0.20	0.99	0.86	0.74	0.66	0.54	0.49	0.40	0.32	0.27	
	0.30		0.84	0.74	0.65	0.59	0.49	0.43	0.38	0.31	0.26	
	0.20		0.73	0.66	0.58	0.53	0.45	0.40	0.35	0.29	0.25	
0.30	0.50	0.20	0.96	0.82	0.71	0.63	0.52	0.44	0.38	0.31	0.26	
	0.30		0.82	0.72	0.63	0.57	0.48	0.41	0.36	0.29	0.25	
	0.20		0.71	0.64	0.57	0.52	0.44	0.39	0.34	0.28	0.24	
0.00	0.00	0.00	0.61	0.55	0.48	0.44	0.37	0.32	0.28	0.23	0.20	
Rating: 4W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Utilisation Factor Table(Ceiling cavity)

Utilisation Factors UF(C)			SHR NOM = 1.50								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.19	0.21	0.22	0.22	0.23	0.24	0.24	0.25	0.25
	0.30		0.12	0.14	0.15	0.16	0.18	0.19	0.20	0.21	0.22
	0.20		0.07	0.08	0.10	0.11	0.13	0.14	0.16	0.17	0.19
0.50	0.50	0.20	0.19	0.20	0.21	0.22	0.22	0.23	0.23	0.24	0.24
	0.30		0.12	0.14	0.15	0.16	0.17	0.18	0.19	0.20	0.21
	0.20		0.07	0.08	0.10	0.11	0.13	0.14	0.15	0.17	0.18
0.30	0.50	0.20	0.18	0.19	0.20	0.21	0.22	0.22	0.22	0.23	0.23
	0.30		0.12	0.13	0.14	0.15	0.17	0.18	0.18	0.19	0.20
	0.20		0.07	0.08	0.10	0.11	0.12	0.14	0.15	0.16	0.17
0.00	0.00	0.00	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03
Rating: 4W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980											

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	73.2	0.1	0.1	0.03	0.03
1.0-2.0	73.2	0.2	0.3	0.08	0.11
2.0-3.0	73.1	0.3	0.6	0.13	0.24
3.0-4.0	73.0	0.5	1.1	0.18	0.42
4.0-5.0	73.0	0.6	1.7	0.24	0.66
5.0-6.0	72.8	0.8	2.5	0.29	0.95
6.0-7.0	72.7	0.9	3.4	0.34	1.29
7.0-8.0	72.5	1.0	4.5	0.39	1.68
8.0-9.0	72.3	1.2	5.6	0.44	2.12
9.0-10.0	72.1	1.3	6.9	0.49	2.61
10.0-11.0	71.9	1.4	8.4	0.54	3.15
11.0-12.0	71.7	1.6	9.9	0.59	3.74
12.0-13.0	71.4	1.7	11.6	0.64	4.38
13.0-14.0	71.1	1.8	13.4	0.69	5.06
14.0-15.0	70.8	1.9	15.4	0.73	5.80
15.0-16.0	70.5	2.1	17.5	0.78	6.57
16.0-17.0	70.1	2.2	19.6	0.82	7.39
17.0-18.0	69.7	2.3	21.9	0.87	8.26
18.0-19.0	69.3	2.4	24.4	0.91	9.17
19.0-20.0	68.9	2.5	26.9	0.95	10.12
20.0-21.0	68.5	2.6	29.5	0.99	11.11
21.0-22.0	68.0	2.7	32.2	1.03	12.14
22.0-23.0	67.5	2.8	35.1	1.07	13.20
23.0-24.0	67.0	2.9	38.0	1.10	14.31
24.0-25.0	66.5	3.0	41.0	1.14	15.45
25.0-26.0	66.0	3.1	44.1	1.17	16.62
26.0-27.0	65.4	3.2	47.3	1.21	17.82
27.0-28.0	64.8	3.3	50.6	1.24	19.06
28.0-29.0	64.2	3.4	54.0	1.27	20.33
29.0-30.0	63.6	3.4	57.4	1.29	21.62
30.0-31.0	63.0	3.5	60.9	1.32	22.94
31.0-32.0	62.4	3.6	64.5	1.35	24.29
32.0-33.0	61.7	3.6	68.1	1.37	25.66
33.0-34.0	61.1	3.7	71.8	1.39	27.05
34.0-35.0	60.4	3.8	75.6	1.41	28.46
35.0-36.0	59.7	3.8	79.4	1.43	29.89

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Kerr

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	59.0	3.8	83.2	1.45	31.34
37.0-38.0	58.2	3.9	87.1	1.46	32.80
38.0-39.0	57.5	3.9	91.1	1.48	34.28
39.0-40.0	56.8	4.0	95.0	1.49	35.77
40.0-41.0	56.0	4.0	99.0	1.50	37.27
41.0-42.0	55.2	4.0	103.0	1.51	38.78
42.0-43.0	54.4	4.0	107.0	1.52	40.30
43.0-44.0	53.6	4.0	111.1	1.52	41.83
44.0-45.0	52.8	4.1	115.2	1.53	43.35
45.0-46.0	52.0	4.1	119.2	1.53	44.89
46.0-47.0	51.2	4.1	123.3	1.53	46.42
47.0-48.0	50.3	4.1	127.4	1.53	47.95
48.0-49.0	49.5	4.1	131.4	1.53	49.48
49.0-50.0	48.6	4.1	135.5	1.53	51.00
50.0-51.0	47.7	4.0	139.5	1.52	52.52
51.0-52.0	46.8	4.0	143.5	1.51	54.04
52.0-53.0	46.0	4.0	147.5	1.51	55.54
53.0-54.0	45.1	4.0	151.5	1.50	57.04
54.0-55.0	44.2	3.9	155.5	1.48	58.52
55.0-56.0	43.3	3.9	159.4	1.47	60.00
56.0-57.0	42.4	3.9	163.2	1.46	61.46
57.0-58.0	41.5	3.8	167.1	1.44	62.90
58.0-59.0	40.6	3.8	170.9	1.43	64.33
59.0-60.0	39.7	3.7	174.6	1.41	65.74
60.0-61.0	38.8	3.7	178.3	1.39	67.13
61.0-62.0	37.8	3.6	182.0	1.37	68.51
62.0-63.0	36.9	3.6	185.6	1.35	69.86
63.0-64.0	36.0	3.5	189.1	1.33	71.19
64.0-65.0	35.1	3.5	192.6	1.31	72.50
65.0-66.0	34.2	3.4	196.0	1.29	73.79
66.0-67.0	33.4	3.4	199.3	1.26	75.05
67.0-68.0	32.5	3.3	202.6	1.24	76.29
68.0-69.0	31.6	3.2	205.9	1.21	77.50
69.0-70.0	30.7	3.2	209.0	1.19	78.69
70.0-71.0	29.9	3.1	212.1	1.16	79.85
71.0-72.0	29.1	3.0	215.1	1.14	80.99

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Kerr

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 2)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
72.0-73.0	28.3	3.0	218.1	1.11	82.10
73.0-74.0	27.5	2.9	221.0	1.09	83.19
74.0-75.0	26.7	2.8	223.8	1.06	84.25
75.0-76.0	25.9	2.8	226.5	1.04	85.29
76.0-77.0	25.2	2.7	229.2	1.01	86.30
77.0-78.0	24.5	2.6	231.8	0.99	87.28
78.0-79.0	23.8	2.6	234.4	0.96	88.25
79.0-80.0	23.1	2.5	236.9	0.94	89.18
80.0-81.0	22.4	2.4	239.3	0.91	90.10
81.0-82.0	21.7	2.4	241.7	0.89	90.98
82.0-83.0	21.0	2.3	244.0	0.86	91.84
83.0-84.0	20.1	2.2	246.1	0.83	92.67
84.0-85.0	19.2	2.1	248.2	0.79	93.46
85.0-86.0	18.2	2.0	250.2	0.75	94.20
86.0-87.0	17.1	1.9	252.1	0.70	94.91
87.0-88.0	15.9	1.7	253.8	0.66	95.57
88.0-89.0	14.9	1.6	255.5	0.61	96.18
89.0-90.0	13.9	1.5	257.0	0.57	96.75
90.0-91.0	12.8	1.4	258.4	0.53	97.28
91.0-92.0	11.2	1.2	259.6	0.46	97.74
92.0-93.0	9.2	1.0	260.6	0.38	98.12
93.0-94.0	7.2	0.8	261.4	0.30	98.42
94.0-95.0	5.4	0.6	262.0	0.22	98.64
95.0-96.0	3.9	0.4	262.4	0.16	98.80
96.0-97.0	2.8	0.3	262.7	0.12	98.91
97.0-98.0	2.0	0.2	263.0	0.08	99.00
98.0-99.0	1.4	0.2	263.1	0.06	99.06
99.0-100.0	1.0	0.1	263.2	0.04	99.10
100.0-101.0	0.7	0.1	263.3	0.03	99.13
101.0-102.0	0.5	0.1	263.4	0.02	99.15
102.0-103.0	0.4	0.0	263.4	0.02	99.16
103.0-104.0	0.4	0.0	263.4	0.01	99.18
104.0-105.0	0.3	0.0	263.5	0.01	99.19
105.0-106.0	0.3	0.0	263.5	0.01	99.21
106.0-107.0	0.3	0.0	263.5	0.01	99.22
107.0-108.0	0.3	0.0	263.6	0.01	99.23

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Kerr

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 3)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
108.0-109.0	0.3	0.0	263.6	0.01	99.24
109.0-110.0	0.3	0.0	263.7	0.01	99.26
110.0-111.0	0.3	0.0	263.7	0.01	99.27
111.0-112.0	0.3	0.0	263.7	0.01	99.28
112.0-113.0	0.3	0.0	263.8	0.01	99.30
113.0-114.0	0.4	0.0	263.8	0.01	99.31
114.0-115.0	0.4	0.0	263.8	0.01	99.32
115.0-116.0	0.4	0.0	263.9	0.01	99.34
116.0-117.0	0.4	0.0	263.9	0.01	99.35
117.0-118.0	0.4	0.0	263.9	0.01	99.37
118.0-119.0	0.4	0.0	264.0	0.01	99.38
119.0-120.0	0.4	0.0	264.0	0.01	99.40
120.0-121.0	0.4	0.0	264.1	0.01	99.41
121.0-122.0	0.4	0.0	264.1	0.01	99.43
122.0-123.0	0.4	0.0	264.1	0.01	99.44
123.0-124.0	0.4	0.0	264.2	0.01	99.45
124.0-125.0	0.4	0.0	264.2	0.01	99.47
125.0-126.0	0.4	0.0	264.3	0.01	99.48
126.0-127.0	0.4	0.0	264.3	0.01	99.50
127.0-128.0	0.4	0.0	264.3	0.01	99.51
128.0-129.0	0.4	0.0	264.4	0.01	99.53
129.0-130.0	0.5	0.0	264.4	0.01	99.54
130.0-131.0	0.5	0.0	264.4	0.01	99.56
131.0-132.0	0.5	0.0	264.5	0.02	99.57
132.0-133.0	0.5	0.0	264.5	0.01	99.59
133.0-134.0	0.5	0.0	264.6	0.01	99.60
134.0-135.0	0.5	0.0	264.6	0.01	99.61
135.0-136.0	0.5	0.0	264.6	0.01	99.63
136.0-137.0	0.5	0.0	264.7	0.01	99.64
137.0-138.0	0.5	0.0	264.7	0.01	99.66
138.0-139.0	0.5	0.0	264.7	0.01	99.67
139.0-140.0	0.5	0.0	264.8	0.01	99.68
140.0-141.0	0.5	0.0	264.8	0.01	99.70
141.0-142.0	0.5	0.0	264.9	0.01	99.71
142.0-143.0	0.5	0.0	264.9	0.01	99.73
143.0-144.0	0.5	0.0	264.9	0.01	99.74

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Kerr

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 4)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
144.0-145.0	0.5	0.0	265.0	0.01	99.75
145.0-146.0	0.5	0.0	265.0	0.01	99.76
146.0-147.0	0.5	0.0	265.0	0.01	99.78
147.0-148.0	0.5	0.0	265.1	0.01	99.79
148.0-149.0	0.6	0.0	265.1	0.01	99.80
149.0-150.0	0.6	0.0	265.1	0.01	99.81
150.0-151.0	0.5	0.0	265.2	0.01	99.82
151.0-152.0	0.6	0.0	265.2	0.01	99.83
152.0-153.0	0.6	0.0	265.2	0.01	99.84
153.0-154.0	0.6	0.0	265.2	0.01	99.86
154.0-155.0	0.6	0.0	265.3	0.01	99.87
155.0-156.0	0.6	0.0	265.3	0.01	99.88
156.0-157.0	0.6	0.0	265.3	0.01	99.89
157.0-158.0	0.6	0.0	265.3	0.01	99.89
158.0-159.0	0.6	0.0	265.4	0.01	99.90
159.0-160.0	0.6	0.0	265.4	0.01	99.91
160.0-161.0	0.6	0.0	265.4	0.01	99.92
161.0-162.0	0.6	0.0	265.4	0.01	99.93
162.0-163.0	0.6	0.0	265.5	0.01	99.94
163.0-164.0	0.6	0.0	265.5	0.01	99.94
164.0-165.0	0.6	0.0	265.5	0.01	99.95
165.0-166.0	0.6	0.0	265.5	0.01	99.96
166.0-167.0	0.6	0.0	265.5	0.01	99.96
167.0-168.0	0.6	0.0	265.5	0.01	99.97
168.0-169.0	0.6	0.0	265.5	0.01	99.97
169.0-170.0	0.6	0.0	265.6	0.00	99.98
170.0-171.0	0.6	0.0	265.6	0.00	99.98
171.0-172.0	0.6	0.0	265.6	0.00	99.99
172.0-173.0	0.6	0.0	265.6	0.00	99.99
173.0-174.0	0.6	0.0	265.6	0.00	99.99
174.0-175.0	0.6	0.0	265.6	0.00	99.99
175.0-176.0	0.6	0.0	265.6	0.00	100.00
176.0-177.0	0.6	0.0	265.6	0.00	100.00
177.0-178.0	0.7	0.0	265.6	0.00	100.00
178.0-179.0	0.7	0.0	265.6	0.00	100.00
179.0-180.0	0.6	0.0	265.6	0.00	100.00

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Kerr

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector: