

Report No.:

Test Time: 2023/11/3 10:20

## Luminaire Property

Luminaire Manufacturer: Acolyte

Luminaire Category: Scroll pendants

Luminaire Description: Scroll pendants C50 RGBW SO 38W

Lamp Catalog: RED ONLY

Luminous Width (mm): 50

Voltage: 24.0 V

Power: 4.11 W

Luminous Length (mm): 300

Luminous Height (mm): 50

Current: 0.171 A

Power Factor: 1.000

## Photometric Results

CIE Class: Direct

Measurement Flux: 32.6 lm

Downward Ratio: 99%

Horizontal Diffuse Angle(10%,50%): H156.3,H97.4

Vertical Diffuse Angle(10%,50%): V156.7,V102.1

Luminaire Efficacy Rating (LER): 8

Max. Intensity: 13.18 cd

Total Rated Lamp Lumens: 32.6 lm

Efficiency: 100%

Upward Ratio: 1%


Central Intensity: 12.86 cd

Pos of Max. Intensity: H150 V1

Picture Of Luminaire



Luminous Intensity Distribution Curve



Average Diffuse Angle(50%): 99.7° Unit: cd

— C0-C180 — C90-C270

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Nick

Gamma Plane (°):0.0-180.0: 1.0

Test Device: GPM-1800B



Distance: 9.028 m

Humidity: 60%

Inspector:




## Luminous Intensity Distribution Curve



C Plane (°):0.0-360.0: 30.0  
Test Lab:  
Test Type: TYPE C  
Temperature: 25  
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0  
Test Device: GPM-1800B  
Distance: 9.028 m  
Humidity: 60%  
Inspector:

## Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-360.0: 30.0  
Test Lab:  
Test Type: TYPE C  
Temperature: 25  
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0  
Test Device: GPM-1800B  
Distance: 9.028 m  
Humidity: 60%  
Inspector:


## Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	101	101	101	99
1	109	104	100	97	106	102	98	95	98	95	92	94	91	89	90	88	86	84
2	99	92	85	79	97	90	84	78	86	81	76	83	78	75	79	76	73	71
3	91	81	73	67	88	79	72	66	76	70	65	73	68	63	70	66	62	60
4	83	72	63	57	81	70	62	56	68	61	55	65	59	55	63	58	54	52
5	77	64	56	49	75	63	55	49	61	54	48	59	53	48	57	51	47	45
6	71	58	49	43	69	57	49	43	55	48	42	53	47	42	52	46	42	39
7	66	53	44	38	64	52	44	38	50	43	38	49	42	37	47	42	37	35
8	62	48	40	34	60	48	40	34	46	39	34	45	38	34	44	38	33	31
9	58	44	36	31	56	44	36	31	43	36	31	41	35	30	40	35	30	28
10	54	41	33	28	53	41	33	28	39	33	28	38	32	28	38	32	28	26

Spacing Criteria (0-180): 1.15

Spacing Criteria (90-270): 1.19

Spacing Criteria (Diagonal): 1.29



C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Nick

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:

## Isocandela (rectangle)




Imax (100%): 13 cd

( 10%):	1 cd	( 20%):	3 cd
( 25%):	3 cd	( 30%):	4 cd
( 40%):	5 cd	( 50%):	7 cd
( 60%):	8 cd	( 70%):	9 cd
( 80%):	11 cd	( 90%):	12 cd

C Plane (°):0.0-360.0: 30.0  
Test Lab:  
Test Type: TYPE C  
Temperature: 25  
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0  
Test Device: GPM-1800B  
Distance: 9.028 m  
Humidity: 60%  
Inspector:

## IsoLux Plot



Mounting Height: 5.0m Max Lux(100%): 0.5 lx

( 10%): 0.1 lx	( 20%): 0.1 lx
( 25%): 0.1 lx	( 30%): 0.2 lx
( 40%): 0.2 lx	( 50%): 0.3 lx
( 60%): 0.3 lx	( 70%): 0.4 lx
( 80%): 0.4 lx	( 90%): 0.5 lx

C Plane (°):0.0-360.0: 30.0  
Test Lab:  
Test Type: TYPE C  
Temperature: 25  
Operator: Nick



Gamma Plane (°):0.0-180.0:1.0  
Test Device: GPM-1800B  
Distance: 9.028 m  
Humidity: 60%  
Inspector:



## Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300

a b c d e f g h




L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	345	301	260	222	181	142	103	66	32
C90	652	616	590	539	482	436	351	266	145
C180	329	287	245	202	167	127	91	50	15
C270	596	554	509	464	402	322	251	160	45

C Plane (°):0.0-360.0: 30.0  
Test Lab:  
Test Type: TYPE C  
Temperature: 25  
Operator: Nick


Gamma Plane (°):0.0-180.0:1.0  
Test Device: GPM-1800B  
Distance: 9.028 m  
Humidity: 60%  
Inspector:

## Illuminance at a Distance





## Vertical IsoLux Plot



Lowest(m): 2.0m	Highest(m): 5.0m	Max Lux: 3.2 lx
( 10%): 0.3 lx	( 20%): 0.6 lx	( 30%): 1.0 lx
( 25%): 0.8 lx	( 40%): 1.3 lx	( 50%): 1.6 lx
( 60%): 1.9 lx	( 70%): 2.3 lx	( 90%): 2.9 lx
( 80%): 2.6 lx		


C Plane (°):0.0-360.0: 30.0  
Test Lab:  
Test Type: TYPE C  
Temperature: 25  
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0  
Test Device: GPM-1800B  
Distance: 9.028 m  
Humidity: 60%  
Inspector:

Gamma Plane (°):0.0-180.0:1.0  
Test Device: GPM-1800B  
Distance: 9.028 m  
Humidity: 60%  
Inspector:



## The Average Illuminance Effective Figure



C Plane (°):0.0-360.0: 30.0  
Test Lab:  
Test Type: TYPE C  
Temperature: 25  
Operator: Nick

Gamma Plane (°):0.0-180.0: 1.0  
Test Device: GPM-1800B  
Distance: 9.028 m  
Humidity: 60%  
Inspector:

## UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	20.1	21.7	20.5	22.0	22.3	19.7	21.3	20.1	21.6	22.0
3H	21.6	23.1	22.0	23.4	23.8	21.0	22.5	21.4	22.8	23.2
4H	22.2	23.5	22.6	23.9	24.3	21.5	22.8	21.9	23.2	23.6
6H	22.5	23.8	23.0	24.2	24.6	21.7	22.9	22.1	23.3	23.7
8H	22.6	23.8	23.1	24.2	24.6	21.7	22.9	22.2	23.3	23.7
12H	22.7	23.8	23.1	24.2	24.7	21.7	22.9	22.2	23.3	23.7
X=4H Y=2H	20.4	21.8	20.8	22.1	22.5	20.2	21.6	20.7	21.9	22.3
3H	22.1	23.2	22.5	23.6	24.1	21.8	22.9	22.2	23.3	23.7
4H	22.7	23.7	23.2	24.2	24.6	22.3	23.3	22.7	23.7	24.2
6H	23.2	24.0	23.6	24.5	25.0	22.6	23.5	23.1	23.9	24.4
8H	23.3	24.1	23.8	24.6	25.0	22.7	23.5	23.1	23.9	24.4
12H	23.4	24.1	23.8	24.6	25.1	22.7	23.4	23.2	23.9	24.4
X=8H Y=4H	22.8	23.6	23.3	24.1	24.6	22.5	23.3	23.0	23.8	24.3
6H	23.3	24.0	23.8	24.5	25.0	22.9	23.6	23.4	24.1	24.6
8H	23.4	24.0	24.0	24.6	25.1	23.0	23.6	23.5	24.1	24.6
12H	23.5	24.1	24.1	24.6	25.2	23.0	23.6	23.6	24.1	24.7
X=12H Y=4H	22.8	23.5	23.3	24.0	24.5	22.5	23.2	23.0	23.7	24.2
6H	23.3	23.9	23.8	24.4	24.9	22.9	23.5	23.4	24.0	24.6
8H	23.4	24.0	24.0	24.5	25.1	23.0	23.6	23.6	24.1	24.7

Calculate in accordance with CIE 190:2010

C Plane (°): 0.0-360.0: 30.0  
 Test Lab:  
 Test Type: TYPE C  
 Temperature: 25  
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0  
 Test Device: GPM-1800B  
 Distance: 9.028 m  
 Humidity: 60%  
 Inspector:

## Utilisation Factor Table(Floor cavity)

Utilisation Factors UF(F)			SHR NOM = 1.25								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.59	0.69	0.76	0.81	0.89	0.93	0.97	1.01	1.04
	0.30		0.51	0.62	0.69	0.75	0.83	0.88	0.92	0.97	1.01
	0.20		0.46	0.56	0.64	0.69	0.78	0.84	0.88	0.94	0.98
0.50	0.50	0.20	0.57	0.67	0.74	0.79	0.85	0.90	0.93	0.97	1.00
	0.30		0.50	0.60	0.68	0.73	0.80	0.85	0.89	0.94	0.97
	0.20		0.45	0.55	0.63	0.68	0.76	0.81	0.85	0.91	0.94
0.30	0.50	0.20	0.56	0.65	0.71	0.76	0.82	0.86	0.89	0.93	0.96
	0.30		0.50	0.59	0.66	0.71	0.78	0.83	0.86	0.91	0.93
	0.20		0.45	0.55	0.62	0.67	0.74	0.80	0.83	0.88	0.91
0.00	0.00	0.00	0.43	0.52	0.59	0.64	0.71	0.76	0.79	0.84	0.86
Rating: 4W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980											

## Utilisation Factor Table(Wall)

Utilisation Factors UF(W)			SHR NOM = 1.25									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.96	0.79	0.67	0.58	0.46	0.38	0.33	0.25	0.21	
	0.30		0.80	0.68	0.58	0.52	0.42	0.35	0.30	0.24	0.20	
	0.20		0.69	0.59	0.52	0.46	0.38	0.33	0.28	0.22	0.19	
0.50	0.50	0.20	0.93	0.76	0.64	0.56	0.44	0.40	0.31	0.24	0.19	
	0.30		0.78	0.66	0.57	0.50	0.40	0.34	0.29	0.23	0.19	
	0.20		0.68	0.58	0.51	0.45	0.37	0.31	0.27	0.22	0.18	
0.30	0.50	0.20	0.90	0.73	0.61	0.53	0.42	0.35	0.30	0.23	0.19	
	0.30		0.77	0.64	0.55	0.48	0.39	0.32	0.28	0.22	0.18	
	0.20		0.67	0.57	0.50	0.44	0.36	0.30	0.26	0.21	0.17	
0.00	0.00	0.00	0.57	0.47	0.40	0.35	0.28	0.24	0.20	0.16	0.13	
Rating: 4W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

## Utilisation Factor Table(Ceiling cavity)

Utilisation Factors UF(C)			SHR NOM = 1.25									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.17	0.18	0.19	0.20	0.21	0.21	0.22	0.22	0.23	
	0.30		0.10	0.12	0.13	0.14	0.16	0.17	0.18	0.19	0.20	
	0.20		0.06	0.07	0.09	0.10	0.12	0.14	0.15	0.17	0.18	
0.50	0.50	0.20	0.16	0.18	0.18	0.19	0.20	0.20	0.21	0.21	0.22	
	0.30		0.10	0.12	0.13	0.14	0.15	0.17	0.17	0.19	0.19	
	0.20		0.06	0.07	0.09	0.10	0.12	0.13	0.15	0.16	0.17	
0.30	0.50	0.20	0.16	0.17	0.18	0.18	0.19	0.20	0.20	0.20	0.21	
	0.30		0.10	0.11	0.13	0.14	0.15	0.16	0.17	0.18	0.19	
	0.20		0.06	0.07	0.09	0.10	0.12	0.13	0.14	0.16	0.17	
0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	
Rating: 4W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

## Zonal Lumen

Gamma [°]	I <sub>mean</sub> [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	13.0	0.0	0.0	0.04	0.04
1.0-2.0	13.0	0.0	0.0	0.11	0.15
2.0-3.0	13.0	0.1	0.1	0.19	0.34
3.0-4.0	13.0	0.1	0.2	0.27	0.61
4.0-5.0	13.0	0.1	0.3	0.34	0.95
5.0-6.0	12.9	0.1	0.4	0.42	1.37
6.0-7.0	12.9	0.2	0.6	0.49	1.86
7.0-8.0	12.8	0.2	0.8	0.56	2.42
8.0-9.0	12.8	0.2	1.0	0.63	3.06
9.0-10.0	12.7	0.2	1.2	0.71	3.76
10.0-11.0	12.6	0.3	1.5	0.77	4.54
11.0-12.0	12.5	0.3	1.8	0.84	5.38
12.0-13.0	12.5	0.3	2.1	0.91	6.28
13.0-14.0	12.4	0.3	2.4	0.97	7.26
14.0-15.0	12.3	0.3	2.7	1.03	8.29
15.0-16.0	12.2	0.4	3.1	1.10	9.39
16.0-17.0	12.1	0.4	3.4	1.15	10.54
17.0-18.0	12.0	0.4	3.8	1.21	11.75
18.0-19.0	11.8	0.4	4.2	1.26	13.01
19.0-20.0	11.7	0.4	4.7	1.32	14.33
20.0-21.0	11.6	0.4	5.1	1.37	15.69
21.0-22.0	11.5	0.5	5.6	1.41	17.11
22.0-23.0	11.3	0.5	6.1	1.46	18.57
23.0-24.0	11.2	0.5	6.5	1.50	20.07
24.0-25.0	11.1	0.5	7.1	1.54	21.61
25.0-26.0	10.9	0.5	7.6	1.58	23.18
26.0-27.0	10.7	0.5	8.1	1.61	24.80
27.0-28.0	10.6	0.5	8.6	1.64	26.44
28.0-29.0	10.4	0.5	9.2	1.67	28.11
29.0-30.0	10.3	0.6	9.7	1.70	29.81
30.0-31.0	10.1	0.6	10.3	1.72	31.53
31.0-32.0	9.9	0.6	10.9	1.75	33.28
32.0-33.0	9.8	0.6	11.4	1.77	35.04
33.0-34.0	9.6	0.6	12.0	1.78	36.82
34.0-35.0	9.4	0.6	12.6	1.79	38.62
35.0-36.0	9.2	0.6	13.2	1.80	40.42

C Plane (°): 0.0-360.0: 30.0  
 Test Lab:  
 Test Type: TYPE C  
 Temperature: 25  
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0  
 Test Device: GPM-1800B  
 Distance: 9.028 m  
 Humidity: 60%  
 Inspector:



## Zonal Lumen (Continue 1)

Gamma [°]	I <sub>mean</sub> [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	9.1	0.6	13.8	1.81	42.23
37.0-38.0	8.9	0.6	14.4	1.82	44.04
38.0-39.0	8.7	0.6	15.0	1.82	45.86
39.0-40.0	8.5	0.6	15.6	1.82	47.68
40.0-41.0	8.3	0.6	16.1	1.81	49.49
41.0-42.0	8.1	0.6	16.7	1.81	51.31
42.0-43.0	7.9	0.6	17.3	1.80	53.11
43.0-44.0	7.7	0.6	17.9	1.79	54.90
44.0-45.0	7.6	0.6	18.5	1.78	56.69
45.0-46.0	7.4	0.6	19.1	1.77	58.45
46.0-47.0	7.2	0.6	19.6	1.75	60.21
47.0-48.0	7.0	0.6	20.2	1.74	61.94
48.0-49.0	6.8	0.6	20.8	1.72	63.66
49.0-50.0	6.6	0.6	21.3	1.69	65.35
50.0-51.0	6.4	0.5	21.9	1.66	67.01
51.0-52.0	6.2	0.5	22.4	1.64	68.65
52.0-53.0	6.0	0.5	22.9	1.61	70.26
53.0-54.0	5.9	0.5	23.4	1.58	71.84
54.0-55.0	5.7	0.5	23.9	1.55	73.40
55.0-56.0	5.5	0.5	24.4	1.52	74.91
56.0-57.0	5.3	0.5	24.9	1.48	76.39
57.0-58.0	5.1	0.5	25.4	1.44	77.84
58.0-59.0	4.9	0.5	25.9	1.40	79.24
59.0-60.0	4.7	0.4	26.3	1.36	80.60
60.0-61.0	4.5	0.4	26.7	1.32	81.93
61.0-62.0	4.3	0.4	27.2	1.28	83.21
62.0-63.0	4.1	0.4	27.6	1.24	84.45
63.0-64.0	3.9	0.4	27.9	1.19	85.63
64.0-65.0	3.8	0.4	28.3	1.14	86.77
65.0-66.0	3.6	0.4	28.7	1.09	87.86
66.0-67.0	3.4	0.3	29.0	1.04	88.90
67.0-68.0	3.2	0.3	29.3	1.00	89.89
68.0-69.0	3.0	0.3	29.6	0.94	90.83
69.0-70.0	2.8	0.3	29.9	0.89	91.72
70.0-71.0	2.6	0.3	30.2	0.84	92.56
71.0-72.0	2.5	0.3	30.5	0.79	93.35

C Plane (°): 0.0-360.0: 30.0  
 Test Lab:  
 Test Type: TYPE C  
 Temperature: 25  
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0  
 Test Device: GPM-1800B  
 Distance: 9.028 m  
 Humidity: 60%  
 Inspector:

## Zonal Lumen (Continue 2)

Gamma [°]	I <sub>mean</sub> [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
72.0-73.0	2.3	0.2	30.7	0.74	94.08
73.0-74.0	2.1	0.2	30.9	0.68	94.77
74.0-75.0	1.9	0.2	31.1	0.63	95.39
75.0-76.0	1.8	0.2	31.3	0.57	95.96
76.0-77.0	1.6	0.2	31.5	0.52	96.48
77.0-78.0	1.4	0.2	31.6	0.47	96.95
78.0-79.0	1.3	0.1	31.8	0.42	97.36
79.0-80.0	1.1	0.1	31.9	0.37	97.73
80.0-81.0	1.0	0.1	32.0	0.32	98.05
81.0-82.0	0.8	0.1	32.1	0.27	98.32
82.0-83.0	0.7	0.1	32.2	0.23	98.54
83.0-84.0	0.6	0.1	32.2	0.19	98.73
84.0-85.0	0.4	0.0	32.3	0.14	98.87
85.0-86.0	0.3	0.0	32.3	0.10	98.97
86.0-87.0	0.2	0.0	32.3	0.08	99.05
87.0-88.0	0.2	0.0	32.3	0.05	99.10
88.0-89.0	0.1	0.0	32.3	0.03	99.13
89.0-90.0	0.0	0.0	32.3	0.01	99.14
90.0-91.0	0.0	0.0	32.4	0.01	99.15
91.0-92.0	0.0	0.0	32.4	0.01	99.15
92.0-93.0	0.0	0.0	32.4	0.01	99.16
93.0-94.0	0.0	0.0	32.4	0.01	99.17
94.0-95.0	0.0	0.0	32.4	0.01	99.18
95.0-96.0	0.0	0.0	32.4	0.01	99.18
96.0-97.0	0.0	0.0	32.4	0.00	99.19
97.0-98.0	0.0	0.0	32.4	0.00	99.19
98.0-99.0	0.0	0.0	32.4	0.00	99.19
99.0-100.0	0.0	0.0	32.4	0.01	99.20
100.0-101.0	0.0	0.0	32.4	0.01	99.21
101.0-102.0	0.0	0.0	32.4	0.01	99.21
102.0-103.0	0.0	0.0	32.4	0.01	99.22
103.0-104.0	0.0	0.0	32.4	0.01	99.23
104.0-105.0	0.0	0.0	32.4	0.01	99.24
105.0-106.0	0.0	0.0	32.4	0.01	99.24
106.0-107.0	0.0	0.0	32.4	0.01	99.25
107.0-108.0	0.0	0.0	32.4	0.01	99.26

C Plane (°): 0.0-360.0: 30.0  
 Test Lab:  
 Test Type: TYPE C  
 Temperature: 25  
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0  
 Test Device: GPM-1800B  
 Distance: 9.028 m  
 Humidity: 60%  
 Inspector:

## Zonal Lumen (Continue 3)

Gamma [°]	I <sub>mean</sub> [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
108.0-109.0	0.0	0.0	32.4	0.01	99.27
109.0-110.0	0.0	0.0	32.4	0.01	99.28
110.0-111.0	0.0	0.0	32.4	0.01	99.29
111.0-112.0	0.0	0.0	32.4	0.01	99.30
112.0-113.0	0.0	0.0	32.4	0.01	99.31
113.0-114.0	0.0	0.0	32.4	0.01	99.33
114.0-115.0	0.0	0.0	32.4	0.01	99.34
115.0-116.0	0.0	0.0	32.4	0.02	99.36
116.0-117.0	0.0	0.0	32.4	0.01	99.37
117.0-118.0	0.0	0.0	32.4	0.01	99.38
118.0-119.0	0.0	0.0	32.4	0.01	99.39
119.0-120.0	0.0	0.0	32.4	0.01	99.40
120.0-121.0	0.0	0.0	32.4	0.01	99.41
121.0-122.0	0.0	0.0	32.4	0.01	99.42
122.0-123.0	0.0	0.0	32.4	0.01	99.43
123.0-124.0	0.0	0.0	32.4	0.01	99.44
124.0-125.0	0.0	0.0	32.5	0.01	99.46
125.0-126.0	0.0	0.0	32.5	0.01	99.47
126.0-127.0	0.1	0.0	32.5	0.01	99.48
127.0-128.0	0.1	0.0	32.5	0.01	99.50
128.0-129.0	0.0	0.0	32.5	0.01	99.51
129.0-130.0	0.0	0.0	32.5	0.01	99.52
130.0-131.0	0.1	0.0	32.5	0.02	99.54
131.0-132.0	0.1	0.0	32.5	0.01	99.55
132.0-133.0	0.1	0.0	32.5	0.01	99.57
133.0-134.0	0.1	0.0	32.5	0.01	99.58
134.0-135.0	0.1	0.0	32.5	0.01	99.60
135.0-136.0	0.1	0.0	32.5	0.01	99.61
136.0-137.0	0.1	0.0	32.5	0.01	99.62
137.0-138.0	0.1	0.0	32.5	0.01	99.63
138.0-139.0	0.1	0.0	32.5	0.02	99.65
139.0-140.0	0.1	0.0	32.5	0.02	99.67
140.0-141.0	0.1	0.0	32.5	0.01	99.68
141.0-142.0	0.1	0.0	32.5	0.01	99.69
142.0-143.0	0.1	0.0	32.5	0.01	99.70
143.0-144.0	0.1	0.0	32.5	0.01	99.72

C Plane (°): 0.0-360.0: 30.0  
 Test Lab:  
 Test Type: TYPE C  
 Temperature: 25  
 Operator: Nick

Gamma Plane (°): 0.0-180.0: 1.0  
 Test Device: GPM-1800B  
 Distance: 9.028 m  
 Humidity: 60%  
 Inspector:

## Zonal Lumen (Continue 4)

Gamma [°]	I <sub>mean</sub> [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
144.0-145.0	0.1	0.0	32.5	0.01	99.73
145.0-146.0	0.1	0.0	32.5	0.01	99.74
146.0-147.0	0.1	0.0	32.5	0.01	99.75
147.0-148.0	0.1	0.0	32.6	0.01	99.77
148.0-149.0	0.1	0.0	32.6	0.01	99.78
149.0-150.0	0.1	0.0	32.6	0.01	99.79
150.0-151.0	0.1	0.0	32.6	0.01	99.80
151.0-152.0	0.1	0.0	32.6	0.01	99.81
152.0-153.0	0.1	0.0	32.6	0.01	99.82
153.0-154.0	0.1	0.0	32.6	0.01	99.84
154.0-155.0	0.1	0.0	32.6	0.01	99.85
155.0-156.0	0.1	0.0	32.6	0.01	99.86
156.0-157.0	0.1	0.0	32.6	0.01	99.87
157.0-158.0	0.1	0.0	32.6	0.01	99.88
158.0-159.0	0.1	0.0	32.6	0.01	99.89
159.0-160.0	0.1	0.0	32.6	0.01	99.90
160.0-161.0	0.1	0.0	32.6	0.01	99.91
161.0-162.0	0.1	0.0	32.6	0.01	99.92
162.0-163.0	0.1	0.0	32.6	0.01	99.93
163.0-164.0	0.1	0.0	32.6	0.01	99.94
164.0-165.0	0.1	0.0	32.6	0.01	99.94
165.0-166.0	0.1	0.0	32.6	0.01	99.95
166.0-167.0	0.1	0.0	32.6	0.01	99.96
167.0-168.0	0.1	0.0	32.6	0.01	99.96
168.0-169.0	0.1	0.0	32.6	0.01	99.97
169.0-170.0	0.1	0.0	32.6	0.01	99.97
170.0-171.0	0.1	0.0	32.6	0.00	99.98
171.0-172.0	0.1	0.0	32.6	0.00	99.98
172.0-173.0	0.1	0.0	32.6	0.00	99.99
173.0-174.0	0.1	0.0	32.6	0.00	99.99
174.0-175.0	0.1	0.0	32.6	0.00	99.99
175.0-176.0	0.1	0.0	32.6	0.00	100.00
176.0-177.0	0.1	0.0	32.6	0.00	100.00
177.0-178.0	0.1	0.0	32.6	0.00	100.00
178.0-179.0	0.1	0.0	32.6	0.00	100.00
179.0-180.0	0.1	0.0	32.6	0.00	100.00

C Plane (°):0.0-360.0: 30.0  
Test Lab:  
Test Type: TYPE C  
Temperature: 25  
Operator: Nick

Gamma Plane (°):0.0-180.0:1.0  
Test Device: GPM-1800B  
Distance: 9.028 m  
Humidity: 60%  
Inspector: