




RoHS IP20

# Scroll Pendant Series


Design open curves and flowing custom shapes.  
If you can draw it, we can do it!

- 3 standard sizes and 2 styles
- 24V fixtures use remote drivers
- Static White (90+ CRI) fixtures are Constant Current
- Variable White and RGBW fixtures are Constant Voltage

## HOUSING FINISHES



## COLOR TEMPERATURES & COLORS




### Scroll135




Direct lighting  
Pendant or Surface Mounted fixtures  
Static White high output models at  
455 lm/ft (1492 lm/m)  
Min. bending diameter: 23.6 in. (600 mm)

### Scroll150




Direct and Indirect lighting  
Pendant or Surface Mounted fixtures  
Static White high output models at  
660 lm/ft (2160 lm/m)  
Min. bending diameter: 39.37 in. (1000 mm)

### Scroll180




Direct lighting  
Pendant or Surface Mounted fixtures  
Static White high output models at  
1075 lm/ft (3526 lm/m)  
Min. bending diameter: 23.6 in. (600 mm)

### Scroll135S




Side-illuminated  
Pendant or Surface Mounted fixtures  
Static White high output models at  
555 lm/ft (1820 lm/m)  
Min. bending diameter: 23.6 in. (600 mm)

### Scroll150S



Side-illuminated  
Pendant or Surface Mounted fixtures  
Static White high output models at  
735 lm/ft (2411 lm/m)  
Min. bending diameter: 27.6 in. (700 mm)

### Scroll180S



Side-illuminated  
Pendant or Surface Mounted fixtures  
Static White high output models at  
1120 lm/ft (3674 lm/m)  
Min. bending diameter: 27.6 in. (700 mm)