



RoHS IP20

Scroll Pendant Series

Design open curves and flowing custom shapes.
If you can draw it, we can do it!

- 3 standard sizes and 2 styles
- 24V fixtures use remote drivers
- Static White (90+ CRI) fixtures are Constant Current
- Variable White and RGBW fixtures are Constant Voltage

HOUSING FINISHES



Silver
Default



Black
RAL# 9005



White
RAL# 9003



Custom
RAL

COLOR TEMPERATURES & COLORS



2700K



3000K



3500K



4000K



RGBW

VW
(2000K-6500K)

Scroll135




Direct lighting

Pendant or Surface Mounted fixtures

Static White high output models at
455 lm/ft (1492 lm/m)

Min. bending radius: 11.81 in. (300 mm)

Scroll150




Direct and Indirect lighting

Pendant or Surface Mounted fixtures

Static White high output models at
660 lm/ft (2160 lm/m)

Min. bending radius: 19.69 in. (500 mm)

Scroll180




Direct lighting

Pendant or Surface Mounted fixtures

Static White high output models at
1075 lm/ft (3526 lm/m)

Min. bending radius: 11.81 in. (300 mm)

Scroll135S




Side-illuminated

Pendant or Surface Mounted fixtures

Static White high output models at
555 lm/ft (1820 lm/m)

Min. bending radius: 11.81 in. (300 mm)

Scroll150S




Side-illuminated

Pendant or Surface Mounted fixtures

Static White high output models at
735 lm/ft (2411 lm/m)

Min. bending radius: 13.78 in. (350 mm)

Scroll180S



Side-illuminated

Pendant or Surface Mounted fixtures

Static White high output models at
1120 lm/ft (3674 lm/m)

Min. bending radius: 13.78 in. (350 mm)