




Scroll Pendant Series


Design open curves and flowing custom shapes.
If you can draw it, we can do it!

- 3 standard sizes and 2 styles
- 24V fixtures use remote drivers
- Static White (90+ CRI) fixtures are Constant Current
- Variable White and RGBW fixtures are Constant Voltage

HOUSING FINISHES



COLOR TEMPERATURES & COLORS




Scroll135




Direct lighting
Pendant or Surface Mounted fixtures
Static White high output models at
455 lm/ft (1492 lm/m)
Min. bending radius: 11.81 in. (300 mm)

Scroll150




Direct and Indirect lighting
Pendant or Surface Mounted fixtures
Static White high output models at
660 lm/ft (2160 lm/m)
Min. bending radius: 19.69 in. (500 mm)

Scroll180




Direct lighting
Pendant or Surface Mounted fixtures
Static White high output models at
1075 lm/ft (3526 lm/m)
Min. bending radius: 11.81 in. (300 mm)

Scroll135S




Side-illuminated
Pendant or Surface Mounted fixtures
Static White high output models at
555 lm/ft (1820 lm/m)
Min. bending radius: 11.81 in. (300 mm)

Scroll150S



Side-illuminated
Pendant or Surface Mounted fixtures
Static White high output models at
735 lm/ft (2411 lm/m)
Min. bending radius: 13.78 in. (350 mm)

Scroll180S



Side-illuminated
Pendant or Surface Mounted fixtures
Static White high output models at
1120 lm/ft (3674 lm/m)
Min. bending radius: 13.78 in. (350 mm)