

SCROLL35 PENDANT FIXTURE

Fashion graceful custom fixtures with open curves or bold signature lighting pieces with the Scroll Pendant Series from Acolyte. Design fully closed shapes like simple circles and triangles or complex undulating ovals, squares and lines, all manufactured to your precise specification. If you can draw it, we can do it! The incredibly flexible Scroll Pendant Series also allows us to generate complementary custom luminaires in surface mounted fixtures.

- Pendant or surface mounted fixtures
- Available in 2700K, 3000K, 3500K, 4000K, Variable White, RGBW
- Static White high output models at 56.7 lm/W, 465 lm/ft (1525.2 lm/m)
- Minimum bending diameter: 23.6 in. (600 mm)
- Static White: 0-10V dimming (Dali coming soon)
- RGBW and Variable White: 0-10V VW Driver, DMX
- Standard silver finish
- Special order Black, White, Gold or custom RAL

HOUSING FINISHES



Silver
Default finish

Black

White

Gold


Note: Custom colors available upon request

LENS FINISH



Milky Lens
74% Light Transmission


MOUNTING OPTIONS



Surface Mount

Suspended Mount

AVAILABLE COLOR TEMPERATURES & COLORS



2700K 3000K 3500K 4000K RGBW VW



RoHS IP20

ORDERING GUIDE

Fixture Length	Output (VW and RGBW in Standard Output only)	Mounting Type	Color Temperature and Colors Direct	
SL35				
SL35 - Scroll35 Fixture	SO - Standard Direct Only HO - High Direct Only	P - Suspended Pendant S - Surface	27 - 2700K 30 - 3000K 35 - 3500K	40 - 4000K VW - Variable White RGBW - RGBW
Surface Finish	Run			
SV - Silver BK - Black WH - White	GD - Gold C - Custom	S - Straight C - Curved		
		QUOTING PROCESS	PRODUCTION PROCESS	
		Scroll Pendants allow for complex custom designs. To quote for Scroll Pendants, Acolyte requires a detailed floor plan with scale. This lets us calculate proper angles and section lengths. Quotes will take 2-3 business days.	After we receive a Purchase Order, our engineering team will provide a dimension drawing that shows the precise specifications of each pendant. Drawings take 2-3 business days. The client must review, approve and return a signed dimension drawing before production begins.	




SPECIFICATIONS

Beam Angle	110°			
Lens Type	Milky Lens (PMMA)			
Length	Channel max lengths are 8 ft 2.4 in. (2.5 m) / Lens max lengths are 19 ft 8 in. (6 m)			
Dimming	Static White: 0-10V, (DALI coming soon) RGBW and Variable White: 0-10V VW Driver, DMX			
Power	Standard Output 4.4 W/ft (14.4 W/m)	High Output 8.2 W/ft (26.9 W/m)	Standard Output 4.6 W/ft (15.1 W/m)	Standard Output 5.9 W/ft (19.4 W/m)
Voltage	Constant Current		24V Constant Voltage	
CCTs & Colors	2700K, 3000K, 3500K, 4000K		VW	RGBW
Efficacy	51.7 lm/W*	56.7 lm/W*	33.3 lm/W**	19.6 lm/W**
Lumens	227.6 lm/ft (746.5 lm/m)*	465 lm/ft (1525.2 lm/m)*	153.3 lm/ft (502.8 lm/m)**	115.8 lm/ft (379.8 lm/m)**
CRI	90+			
Certifications	UL, CE, RoHS			



* Tested at 3000K

** Tested with all LEDs on @ 100%

ACCESSORIES

Coupler	Suspended Mounting Kit (included accessory)	End Caps (included accessory)
Part #: SL35COUP 		

DIMENSIONS

SURFACE / SUSPENDED			
 <p> Width: 1.38 in. (35 mm) Height: 1.48 in. (37.5 mm) Length: Up to 8 ft 2.4 in. (2.5 m) NOTE: 1. Max length for lens is 19 ft 8 in. (6 m) 2. Each section requires its own driver. </p>	<table border="1"> <tr> <td>Minimum Bending Diameter For Surface and Suspended Models</td><td>23.6 in. (600 mm)</td></tr> </table>  <p>WARNING: DO NOT bend fixture past the listed minimum bending diameter. Defects caused by over-bending will result in a voided warranty.</p>	Minimum Bending Diameter For Surface and Suspended Models	23.6 in. (600 mm)
Minimum Bending Diameter For Surface and Suspended Models	23.6 in. (600 mm)		

Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

UNDERSTANDING THE MINIMUM BENDING DIAMETER (MAXIMUM CURVATURE)


The bending diameter of a curve is the diameter of the circle that would exist if the curve were extended to form a circle.

For example, we have a fixture of length L:




Let's bend this fixture.

If we extend this curve to form a circle, we will see something like this:



The diameter D of that circle would be our curve's bending diameter.




If we give the same fixture of length L a gentler bend, we will see:

Note that the diameter D, or bending diameter, gets larger.

A gentler bend implies a larger bending diameter.

If we give the same fixture of length L a sharper bend, we will see:




The diameter D, or bending diameter, gets smaller. A sharper bend implies a smaller bending diameter.

We define a fixture's minimum bending diameter because of this relationship; some of our fixtures are limited by the sharpness of the specified bend. A fixture's minimum bending diameter defines the sharpest curve it can make without jeopardizing the integrity of the LED performance.

Scroll35 Pendants have a minimum bending diameter of 23.6 in. (600 mm)

Minimum Bending Diameter = Maximum Curvature









Min. Bend Diameter:
< 23.6 in. (600 mm)

Min. Bend Diameter:
23.6 in. (600 mm)

SUGGESTED SUSPENSION WIRE SEPARATED DISTANCES

SUGGESTED SUSPENSION WIRE SEPARATED DISTANCES



NOTE: Each section requires its own driver.

REV.01SEP2023