

### SCROLL50S PENDANT FIXTURE

Fashion graceful custom side-illuminated fixtures with open curves or bold signature lighting pieces with the Scroll Pendant Series from Acolyte. Design fully closed shapes like simple circles and triangles or complex undulating ovals, squares and lines, all manufactured to your precise specification. If you can draw it, we can do it! The incredibly flexible Scroll Pendant Series also allows us to generate complementary custom luminaires in surface mounted fixtures.

- Create side-illuminated pendant or surface mounted fixtures
- Available in 2700K, 3000K, 3500K, 4000K, Variable White, RGBW
- Static White high output models at 66.2 lm/W, 695.6 lm/ft (2281.6 lm/m)
- Minimum bending diameter: 27.6 in. (700 mm)
- Static White: 0-10V, ELV/MLV, and DALI dimming
- RGBW and Variable White: 0-10V VW dimming
- Compatible with DMX controls
- Standard silver finish
- Special order Black, White, Gold or custom RAL



#### HOUSING FINISHES



**Silver**  
Default finish


**Black**

**White**


**Gold**

Note: Custom colors available upon request

#### LENS FINISH




#### MOUNTING OPTIONS




Surface Mount      Suspended Mount

#### ILLUMINATION OPTIONS



Inward or Outward

#### AVAILABLE COLOR TEMPERATURES & COLORS



#### ORDERING GUIDE

Fixture Length	Color Temperature and Colors	Surface Finish	Run	Mounting Type
SL50	27 - 2700K    40 - 4000K	SV - Silver    GD - Gold	S - Straight	P - Suspended Pendant
SL50 - Scroll50S Side Illuminated Fixture	30 - 3000K    VW - Variable White	BK - Black    C - Custom	C - Curved	S - Surface
	35 - 3500K    RGBW - RGBW	WH - White		








**SPECIFICATIONS**


Beam Angle	110°			
Lens Type	Milky Lens (PMMA)			
Length	Continuous lengths available. Lens max lengths are 19 ft 8 in. (6 m)			
Dimming	Static White: 0-10V, (DALI coming soon) RGBW and Variable White: 0-10V VW Driver, DMX			
Power	Standard Output 4.1 W/ft (13.4 W/m)	High Output 10.5 W/ft (34.4 W/m)	Standard Output 9.2 W/ft (30.2 W/m)	Standard Output 13.9 W/ft (45.7 W/m)
Voltage	Constant Current		24V Constant Voltage	
CCTs & Colors	2700K, 3000K, 3500K, 4000K		VW	RGBW
Efficacy	72.4 lm/W	66.2 lm/W	33.8 lm/W	21.7 lm/W
Lumens	296.8 lm/ft (973.5 lm/m)	695.6 lm/ft (2281.6 lm/m)	311.3 lm/ft (1021.1 lm/m)	301.5 lm/ft (988.9 lm/m)
CRI	90+			
Certifications	UL, CE, RoHS			

**ACCESSORIES**

<b>Coupler</b> Part #: SLS50COUP	<b>Suspended Mounting Kit</b> (included accessory)	<b>End Caps</b> (included accessory)
		


**DIMENSIONS**

**SCROLL50S**



**Width:** 1.18 in. (230 mm)  
**Height:** 1.97 in. (50 mm)  
**Length:** Up to 19 ft 8 in. (6 m)

**NOTE:** 1. Max length for lens is 19 ft 8 in. (6 m)  
2. Each section requires its own driver.



**WARNING:** DO NOT bend fixture past the listed minimum bending diameter. Defects caused by over-bending will result in a voided warranty.

**UNDERSTANDING THE MINIMUM BENDING DIAMETER (MAXIMUM CURVATURE)**


The bending diameter of a curve is the diameter of the circle that would exist if the curve were extended to form a circle.

For example, we have a fixture of length L:




Let's bend this fixture.

If we extend this curve to form a circle, we will see something like this:



The diameter D of that circle would be our curve's bending diameter.




If we give the same fixture of length L a gentler bend, we will see:

Note that the diameter D, or bending diameter, gets larger.

A gentler bend implies a larger bending diameter.

If we give the same fixture of length L a sharper bend, we will see:




The diameter D, or bending diameter, gets smaller. A sharper bend implies a smaller bending diameter.

We define a fixture's minimum bending diameter because of this relationship; some of our fixtures are limited by the sharpness of the specified bend. A fixture's minimum bending diameter defines the sharpest curve it can make without jeopardizing the integrity of the LED performance.

**Scroll50S Pendants have a minimum bending diameter of 27.6 in. (700 mm)**








**Minimum Bending Diameter = Maximum Curvature**



Min. Bend Diameter: < 27.6 in. (700 mm)

SUGGESTED SUSPENSION WIRE SEPARATED DISTANCES

SUGGESTED SUSPENSION WIRE SEPARATED DISTANCES



**NOTE:** Each section requires its own driver.

REV.26MAY2023