

4.4 RGBW SERIES 2 RIBBONLYTE

4.4 RGBW Series 2 RibbonLyte is a color changing ribbon controlled with DMX. Each diode uses four separate chips (red, green, blue and white) to provide flawless color blending. Three CCT choices (2700K, 3000K, 4000K) deliver varied levels of brightness. Our RGBW Series 2 RibbonLyte offers better pixel density and shorter cut lengths for more custom fixture options than ever before.

- Color changing with DMX controls
- Improved pitch of 36 LEDs per foot
- Increased efficacy and lumen output
- Tighter cut lengths of 2 in. (50 mm)
- 4.4 W/ft (14.4 W/m)
- All on: Up to 72 lm/W
- All on: Up to 318.78 lm/ft (1045.6 lm/m)



RoHS

IP20

Declare.



ORDERING GUIDE

Category	CRI	Ribbon Type & IP Rating	Wattage + Color
RB	0	RGBWS220	
RB - Ribbonlyte	0 - Color Changing	RGBWS220 - RGBW Series 2 IP20	4.4RGB27 - 4.4 W/ft (14.4 W/m) RGB+2700K 4.4RGB40 - 4.4 W/ft (14.4 W/m) RGB+4000K 4.4RGB30 - 4.4 W/ft (14.4 W/m) RGB+3000K

CONNECTION OPTIONS

1. End Feed Bare Wire Connection (Default Option)



2. IP67 Connector Input



3. Soldered Daisy Chain



4. Daisy Chain with IP67 Connectors



5. Bare Wire on Both Ends



Standard cable length if not specified:

- 12 in. cable with bare wire (custom length up to 20 feet)
- Standard 12 in. cable with IP67 connectors (custom length up to 10 feet)
- Daisy chain with 3 in. cable between runs (custom length up to 36 in.)
- 3 in. cable between IP67 connector and RibbonLyte (custom length up to 18 in.)
- Standard 12 in. cable with bare wire (custom length up to 10 feet)

Note: IP67 connectors are used for both IP20 and IP65/IP68 RibbonLyte

AVAILABLE COLORS



RGBW

USAGE GUIDELINES

- When installing this product, consider the surface temperature of the material where it will be mounted. Many building surfaces which are exposed to direct sunlight exceed the 60 °C / 140 °F maximum for which our product is rated. High-risk locations like this should be avoided.
- IP20 RibbonLyte products are for indoor use in dry areas only. IP20 products are not intended to be submerged in pools and fountains and do not carry UL676 certification to do so.
- Please refer to the RibbonLyte Proper Usage Guide in our Application Guide for more information. Available for download at AcolyteLED.com.
- This product is compatible with a wide variety of control products including the entire line of Lutron dimming systems.
- For use with Acolyte drivers, 0-10V dimming modules and interface controllers (DMXINF models).
- Use with non-Acolyte supplied drivers is not supported or warranted.
- Due to the nature of RibbonLyte products, cuttable lengths are generally longer or shorter than the customer requested length. Unless specified, RibbonLyte is factory cut at the shorter cuttable point.
- We reserve the right to make changes to product lineup, specifications, design and finishes at any time without notice.

Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

SPECIFICATIONS / DIAGRAM / USAGE GUIDELINES

4.4 RGBW Series 2 RibbonLyte	
Operating Voltage	24 V
Colors	RGBW (2700K, 3000K, 4000K)
Current (mA) - 24V	183 mA/ft (602 mA/m)
LED Pitch	36 LEDs/ft (120 LED/m)
Protection Rating	IP20
Dimming/Control	DMX, DALI
Operating Temperature	-40 — 140 °F (-40 — 60 °C)
LED Beam Angle	120°
Lifetime (L70 reported)	50,000 hours
Cutable Length	1.97 in (50 mm)
Lumens/Watt	Lumens/Watt - RGBW 45 lm/W (All LEDs at 100%)
Constant Voltage	✓
Cable Length	12 in (30.5 cm)
Certifications	UL 2108 Issued: 2016/06/17 Ed: 1 Rev: 2021/10/16 Low Voltage Lighting Systems. CSA C22.2 No. 250.0, General Requirements for Luminaires. ROHS compliant

RGBW (2700K)					
	Red	Green	Blue	White (2700K)	All On
Power Consumption	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	4.4 W/ft (14.4 W/m)
Lumen	40.24 lm/ft (131.99 lm/m)	127.62 lm/ft (418.59 lm/m)	28.64 lm/ft (93.94 lm/m)	90.85 lm/ft (297.99 lm/m)	292.13 lm/ft (958.19 lm/m)
Efficacy	37 lm/W	116 lm/W	26 lm/W	83 lm/W	66 lm/W
RGBW (3000K)					
	Red	Green	Blue	White (3000K)	All On
Power Consumption	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	4.4 W/ft (14.4 W/m)
Lumen	28.66 lm/ft (94 lm/m)	76.4 lm/ft (250.59 lm/m)	21.77 lm/ft (93.94 lm/m)	73.66 lm/ft (241.6 lm/m)	194.5 lm/ft (637.96 lm/m)
Efficacy	26 lm/W	69 lm/W	20 lm/W	67 lm/W	44 lm/W
RGBW (4000K)					
	Red	Green	Blue	White (4000K)	All On
Power Consumption	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	4.4 W/ft (14.4 W/m)
Lumen	42.01 lm/ft (137.8 lm/m)	139.45 lm/ft (457.4 lm/m)	32.98 lm/ft (108.17 lm/m)	94.82 lm/ft (311 lm/m)	318.78 lm/ft (1045.6 lm/m)
Efficacy	38 lm/W	127 lm/W	30 lm/W	86 lm/W	72 lm/W

DIMENSIONS	Top View	Side View	Dimensions
IP20	 CUTTABLE EVERY: 1.97 in (50 mm)		Width 0.47 in (12 mm) Max Length 19 ft 8 in (6 m) Height 0.09 in (2.3 mm)

OPTIONAL ACCESSORY

0.5 in. VHB Tape	Flat Mounting Clip
 Provides superior holding power in surface mounted applications Part Number: VHBTAPE0.5BK	 For mounting IP20 RibbonLyte Part Number: RBMNTSIL


Note: RibbonLyte comes with an adhesive backing, but Acolyte recommends using VHB Tape for extra support in surface mounted applications.

CHANNEL COMPATIBILITY / CHANNEL OPTIONS

CHANNEL	IP20	SURFACE CHANNELS					
AC1	✓						
AC2	✓						
AC3	✓						
AC4	✓						
AC5	✓						
AR1	✓						
AR3	✓						
AS1	✓						
AS2	✓						
AS3	✓						
AS5							
AS6	✓						
AS10							
AS11							
AS13	✓						
AS16	✓						
AS18	✓						
AS20G							
AS23	✓						
AS30	✓						
AS53							
AT4	✓						
AT5	✓						
B1	✓						
SC3	✓						
WH35	✓						
CORNER CHANNELS							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							
AC4							
AC5							
AC1							
AC2							
AC3							

WIRING DIAGRAMS

DMX



WIRE COLORS PER RIBBONLYTE COLOR

RGBW

Black (+) Positive
Green Wire (-) goes to Green Channel
Red Wire (-) goes to Red Channel
Blue Wire (-) goes to Blue Channel
White Wire (-) goes to White Channel

ACTUAL POWER CONSUMPTION

Length (ft)	Length (m)	Actual Power Consumed (W)	Average Wattage (W/ft)	Average Wattage (W/m)	Actual Current Drawn (A)
5	1.52	21.56	4.31	14.14	0.898
10	3.05	42.43	4.24	13.92	1.768
15	4.57	61.84	4.12	13.52	2.577
19.7	6.01	79.15	4.02	13.18	3.298

NOTE: Quotes use nominal values. We highly recommend using nominal wattages for all customer calculations. Allow for a 15% buffer (10% driver, 5% fixture) in these calculations as performance may vary. Acolyte is not liable for product performance if these tables are used instead of nominal values when orders are placed.

REV.24NOV2025

GLOBAL HQ

320 Murray Hill Pkwy
East Rutherford, NJ 07073
U.S.
T: (+1) 212 629 6830
E: Sales-US@GENLEDBrands.com

EUROPEAN HQ

Hogeweyselaan 119
1382 JK Weesp
Netherlands
T: (+31) 346 235 000
E: SalesEurope@GENLEDBrands.com

MEINA HQ

PO Box 371378, #823, Building 4EA
Dubai Airport Free Zone
Dubai, UAE
T: (+971) 4 701 7901
E: SalesMEINA@genledbrands.com

ASIA-PACIFIC HQ

Room 402, Building D
Shenshi Tongchuang Science and Technology Park
No. 16 Hongyin Road
Xingqiang Community, Xinhua Street
Guangming District, Shenzhen, China 518107
T: (+86) 755 8529 0710
E: Sales-Pacific@GENLEDBrands.com