

#### 4.4 RGBW SERIES 2 RIBBONLYTE

4.4 RGBW Series 2 RibbonLyte is a color changing ribbon controlled with DMX. Each diode uses four separate chips (red, green, blue and white) to provide flawless color blending. Three CCT choices (2700K, 3000K, 4000K) deliver varied levels of brightness. Our RGBW Series 2 RibbonLyte offers better pixel density and shorter cut lengths for more custom fixture options than ever before.

- Color changing with DMX controls
- Improved pitch of 36 LEDs per foot
- Increased efficacy and lumen output
- Tighter cut lengths of 2 in. (50 mm)
- 4.4 W/ft (14.4 W/m)
- All on: Up to 72 lm/W
- All on: Up to 318.78 lm/ft (1045.6 lm/m)



#### ORDERING GUIDE

Category	CRI	Ribbon Type & IP Rating	Wattage + Color
RB	0	RGBWS220	
RB - Ribbonlyte	0 - Color Changing	RGBWS220 - RGBW Series 2 IP20	4.4RGB27 - 4.4 W/ft (14.4 W/m) RGB+2700K    4.4RGB40 - 4.4 W/ft (14.4 W/m) RGB+4000K 4.4RGB30 - 4.4 W/ft (14.4 W/m) RGB+3000K

#### CONNECTION OPTIONS

##### 1. End Feed Bare Wire Connection (Default Option)



##### 2. IP67 Connector Input



##### 3. Soldered Daisy Chain



##### 4. Daisy Chain with IP67 Connectors



##### 5. Bare Wire on Both Ends



#### Standard cable length if not specified:

- 12 in. cable with bare wire (custom length up to 20 feet)
- Standard 12 in. cable with IP67 connectors (custom length up to 10 feet)
- Daisy chain with 3 in. cable between runs (custom length up to 36 in.)
- 3 in. cable between IP67 connector and RibbonLyte (custom length up to 18 in.)
- Standard 12 in. cable with bare wire (custom length up to 10 feet)

Note: IP67 connectors are used for both IP20 and IP65/IP68 RibbonLyte

#### AVAILABLE COLORS



RGBW

#### USAGE GUIDELINES



- IP65 and IP68 RibbonLyte cannot be cut in the field. All custom cuts and connections for these models must be performed at the factory to ensure waterproofing standards are met. Any modification of the waterproofing will result in a void warranty.
- When installing this product, consider the surface temperature of the material where it will be mounted. Many building surfaces which are exposed to direct sunlight exceed the 70° C / 158° F maximum for which our product is rated. High-risk locations like this should be avoided.
- IP20 RibbonLyte products are for indoor use in dry areas. IP65 RibbonLyte products can be used in indoor dry/damp locations such as bathrooms and kitchens. IP68 RibbonLyte products can be used in wet, outdoor locations around pools and spa tubs, but our products are not intended to be submerged in pools and fountains and do not carry UL676 certification to do so.
- Please refer to the RibbonLyte Proper Usage Guide in our Application Guide for more information. Available for download at AcolyteLED.com.
- This product is compatible with a wide variety of control products including the entire line of Lutron dimming systems.
- For use with Acolyte drivers, 0-10V dimming modules and interface controllers (DMXINF models).
- Use with non-Acolyte supplied drivers is not supported or warrantied.
- Due to the nature of RibbonLyte products, cuttable lengths are generally longer or shorter than the customer requested length. Unless specified, RibbonLyte is factory cut at the shorter cuttable point.
- We reserve the right to make changes to product lineup, specifications, design and finishes at any time without notice.

Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

SPECIFICATIONS / DIAGRAM / USAGE GUIDELINES

4.4 RGBW Series 2 RibbonLyte	
Operating Voltage	24 V
Colors	RGBW (2700K, 3000K, 4000K)
Current (mA) - 24V	183 mA/ft (602 mA/m)
LED Pitch	36 LEDs/ft (120 LED/m)
Protection Rating	IP20
Dimming/Control	DMX
Operating Temperature	-40° F to 140° F (-40° C to 60° C)
LED Beam Angle	120°
Lamp Life	50,000 Hours
Cutable Length	1.97 in (50 mm)
Lumens/Watt	Lumens/Watt - RGBW 45 lm/W (All LEDs at 100%)
Constant Voltage	✓
Cable Length	12 in (30.5 cm)
Certifications	UL 2108 Issued: 2016/06/17 Ed: 1 Rev: 2021/10/16 Low Voltage Lighting Systems. CSA C22.2 No. 250.0, General Requirements for Luminaires. ROHS compliant

RGBW (2700K)					
	Red	Green	Blue	White (2700K)	All On
Power Consumption	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	4.4 W/ft (14.4 W/m)
Lumen	40.24 lm/ft (131.99 lm/m)	127.62 lm/ft (418.59 lm/m)	28.64 lm/ft (93.94 lm/m)	90.85 lm/ft (297.99 lm/m)	292.13 lm/ft (958.19 lm/m)
Efficacy	37 lm/W	116 lm/W	26 lm/W	83 lm/W	66 lm/W
RGBW (3000K)					
	Red	Green	Blue	White (3000K)	All On
Power Consumption	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	4.4 W/ft (14.4 W/m)
Lumen	28.66 lm/ft (94 lm/m)	76.4 lm/ft (250.59 lm/m)	21.77 lm/ft (93.94 lm/m)	73.66 lm/ft (241.6 lm/m)	194.5 lm/ft (637.96 lm/m)
Efficacy	26 lm/W	69 lm/W	20 lm/W	67 lm/W	44 lm/W
RGBW (4000K)					
	Red	Green	Blue	White (4000K)	All On
Power Consumption	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	1.1 W/ft (3.6 W/m)	4.4 W/ft (14.4 W/m)
Lumen	42.01 lm/ft (137.8 lm/m)	139.45 lm/ft (457.4 lm/m)	32.98 lm/ft (108.17 lm/m)	94.82 lm/ft (311 lm/m)	318.78 lm/ft (1045.6 lm/m)
Efficacy	38 lm/W	127 lm/W	30 lm/W	86 lm/W	72 lm/W

DIMENSIONS	Top View	Side View	Dimensions
IP20	 <p>CUTTABLE EVERY: 1.97 in (50 mm)</p>		<p><b>Width</b> 0.47 in (12 mm)  <b>Max Length</b> 19 ft 8 in (6 m)  <b>Height</b> 0.09 in (2.3 mm)</p>

OPTIONAL ACCESSORY

0.5 in. VHB Tape	Flat Mounting Clip
 <p>Provides superior holding power in surface mounted applications Part Number: VHBTAPE0.5BK</p>	 <p>For mounting IP20 RibbonLyte Part Number: RBMNTSIL</p>

Note: RibbonLyte comes with an adhesive backing, but Acolyte recommends using VHB Tape for extra support in surface mounted applications.

CHANNEL COMPATIBILITY / CHANNEL OPTIONS

CHANNEL	IP20	SURFACE CHANNELS					
AC1	✓						
AC2	✓						
AC3	✓						
AC4	✓						
AC5	✓						
AR1	✓						
AR3	✓						
AR10							
AR16	✓						
AR20	✓						
AR25	✓						
AR30	✓						
AR33							
AS1	✓						
AS2	✓						
AS3	✓						
AS6	✓						
AS10							
AS13	✓						
AS16	✓						
AS20G							
AS23	✓						
AS30	✓						
AS53							
AT4	✓						
AT5	✓						
AW12	✓						
AW14	✓						
AW38	✓						
B1	✓						
SC3	✓						
SC4	✓						
SC5	✓						
WH35	✓						
		CORNER CHANNELS					
AC1							
AC2							
AC3							
AC4							
AC5							
		RECESSED CHANNELS					
AR1							
AR3							
AR16							
AR20							
AR25							
AR30							
AW14							
		MUD-IN CHANNELS					
SC3							
SC4							
SC5							


**DISCLAIMER**

When installing this product take into account the surface temperature of the material this product is mounted to. Many building surfaces which are exposed to direct sunlight exceed the 70°C/158°F maximum that our product is rated for. High risk locations like this should be avoided.

Our IP68 product is not intended to be submerged in pools and fountains and does not carry UL676 certification to do so.

WIRING DIAGRAMS

DMX



WIRE COLORS PER  
RIBBONLYTE COLOR

**RGBW**

- Black (+) Positive
- Green Wire (-) goes to Green Channel
- Red Wire (-) goes to Red Channel
- Blue Wire (-) goes to Blue Channel
- White Wire (-) goes to White Channel