

RGBW ADDRESSABLE RIBBONLYTE

RGBW Addressable RibbonLyte allows you to create completely customized patterns of light that are only limited by the imagination. Each 4-in. pixel can be individually controlled. Pair RGBW Addressable RibbonLyte with simple DMX systems to program moving effects, patterns, chases and more to create an unforgettable light display.

- 6.0 W/ft (19.7 W/m)
- All on: Up to 42 lm/W
- All on: 251.22 lm/ft (824 lm/m)
- 6 LEDs per pixel (18 LEDs/ft, 60 LEDs/m)
- 3.94 in. (100 mm) cuttable length
- 16 ft, 5.83 in. (5.025 m) max. run length (longer sections can be illuminated with multiple pieces of RibbonLyte with lead wire back to the controller or opto splitter)
- 120 degree beam angle
- Controlled with DMX512
- IP67 rating
- 24V input

Applications:

Commercial
Entertainment
Healthcare

Hospitality
Museums
Public Spaces

Residential
Retail



RoHS

IP67

ORDERING GUIDE

Category	CRI	Ribbon Type & IP Rating	Wattage + Color
RB	0	RGBWADD	
RB - RIBBONLYTE	0 - COLOR CHANGING	RGBWADD - RGBW ADDRESSABLE IP67	6.0RGBW30 - 6.0 W/ft (19.7 W/m) RGBW (3000K) 6.0RGBW40 - 6.0 W/ft (19.7 W/m) RGBW (4000K) 6.0RGBW65 - 6.0 W/ft (19.7 W/m) RGBW (6500K)

See wiring diagram on page 4.

Controllers



6 Universe DMX Controller
Part Number: DMXCTRLDR6U

- 3,072 channels
- 20 zones
- 2,000 scenes
- 16 mb internal memory



DMX Opto Splitter
Part Number: DMXOS8

- 8 DMX output terminals for 1 DMX input

AVAILABLE COLORS




RGBW

SPECIFICATIONS / DIAGRAM / USAGE GUIDELINES

RGBW ADDRESSABLE RIBBONLYTE	
Operating Voltage	24 V
Power Consumption	6 W/ft (19.7 W/m)
Current (mA) - 24 V	250 mA/ft (820 mA/m)
LED Pitch	18 LEDs/ft (60 LEDs/m)
Protection Rating	IP67
Dimming/Control	DMX
Ambient/Storage Temperature	-4 — 113 °F (-20 — 45 °C) / -40 — 158 °F (-40 — 70 °C)
LED Beam Angle	120°
Lamp Life	50,000 hours
Cutable Length	3.94 in. (100 mm)
Constant Voltage	✓
Max Run Length	16 ft 5.83 in. (5.025 m)
Cable Length Attached to RibbonLyte	11.81 in. (300 mm)
Total Multiple Runs on Single DMX Universe	42 ft 8 in. (13 m)
Certifications	UL 2108 Issued: 2016/06/17 Ed: 1 Rev: 2021/10/16 Low Voltage Lighting Systems. CSA C22.2 No. 250.0, General Requirements for Luminaires. ROHS compliant

RGBW (3000K)					
	Red	Green	Blue	White (3000K)	All On
Power Consumption	1.5 W/ft (4.92 W/m)	1.5 W/ft (4.92 W/m)	1.5 W/ft (4.92 W/m)	1.5 W/ft (4.92 W/m)	6 W/ft (19.7 W/m)
Lumen	33.54 lm/ft (110.01 lm/m)	90.24 lm/ft (295.99 lm/m)	21.34 lm/ft (70 lm/m)	97.56 lm/ft (320 lm/m)	234.15 lm/ft (768.01 lm/m)
Efficacy	22 lm/W	60 lm/W	14 lm/W	65 lm/W	39 lm/W
RGBW (4000K)					
	Red	Green	Blue	White (4000K)	All On
Power Consumption	1.5 W/ft (4.92 W/m)	1.5 W/ft (4.92 W/m)	1.5 W/ft (4.92 W/m)	1.5 W/ft (4.92 W/m)	6 W/ft (19.7 W/m)
Lumen	33.54 lm/ft (110.01 lm/m)	90.24 lm/ft (295.99 lm/m)	21.34 lm/ft (70 lm/m)	103.66 lm/ft (340 lm/m)	246.34 lm/ft (808 lm/m)
Efficacy	22 lm/W	60 lm/W	14 lm/W	69 lm/W	41 lm/W
RGBW (6500K)					
	Red	Green	Blue	White (6500K)	All On
Power Consumption	1.5 W/ft (4.92 W/m)	1.5 W/ft (4.92 W/m)	1.5 W/ft (4.92 W/m)	1.5 W/ft (4.92 W/m)	6 W/ft (19.7 W/m)
Lumen	33.54 lm/ft (110.01 lm/m)	90.24 lm/ft (295.99 lm/m)	21.34 lm/ft (70 lm/m)	106.71 lm/ft (350 lm/m)	251.22 lm/ft (824 lm/m)
Efficacy	22 lm/W	60 lm/W	14 lm/W	71 lm/W	42 lm/W



CHANNEL COMPATIBILITY / CHANNEL OPTIONS

[illegible]


RECESSED CHANNELS



AR3

W: 1.2 in. / 30.5 mm
H: 0.39 in. / 9.9 mm
Inside W: 0.81 in. / 20.6 mm

Luminous Intensity Distribution Diagram



Photometrics

Flux Out: 143.7 lm		CCT=2700K
0.02 m 167902,554247 lx		5.84 cm
0.04 m 41975,338562 lx		11.68 cm
0.06 m 18656,61583 lx		17.52 cm
0.08 m 10494,34640 lx		23.36 cm
0.1 m 6716,22170 lx		29.19 cm
0.12 m 4664,15396 lx		35.03 cm
0.14 m 3427,1131 lx		40.87 cm
0.16 m 2623,8660 lx		46.71 cm
0.18 m 2073,6843 lx		52.55 cm
0.2 m 1679,5542 lx		58.39 cm
Height Eavg, Emax	Beam Angle: 118.62°	Diameter

USAGE GUIDELINES


- IP67 RibbonLyte cannot be cut in the field. All custom cuts and connections for these models must be performed at the factory to ensure waterproofing standards are met. Any modification of the waterproofing will result in a void warranty.
- When installing this product, consider the surface temperature of the material where it will be mounted. Many building surfaces which are exposed to direct sunlight exceed the 45 °C / 113 °F maximum for which our product is rated. High-risk locations like this should be avoided.
- IP67 RibbonLyte products can be used in wet, outdoor locations around pools and spa tubs, but our products are not intended to be submerged in pools and fountains and do not carry UL676 certification to do so.
- Please refer to the RibbonLyte Proper Usage Guide in our Application Guide for more information. Available for download at [AcolyteLED.com](#).
- This product is compatible with a wide variety of control products including the entire line of Lutron dimming systems.
- For use with Acolyte drivers, 0-10 V dimming modules and interface controllers (DMXINF models).
- Use with non-Acolyte supplied drivers is not supported or warrantied.
- Due to the nature of RibbonLyte products, cuttable lengths are generally longer or shorter than the customer requested length unless specified, RibbonLyte is factory cut at the shorter cuttable point.

WIRING DIAGRAMS

One DMX Universe consists of 128 addresses and 512 channels (42 ft, 8 in. of RibbonLyte).

Any single run of RibbonLyte that is less than 16 ft, 4 in. can be wired directly to the controller.

For additional runs, Opto Splitter must be used. Each individual run will need its own Opto Splitter output.



MAX LENGTH BETWEEN DRIVER & RIBBONLYTE AT FULL LOAD

Wattages	40		60		96 + 100		150		200		240		300		320	
Wire Gauge	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters
24 AWG / 0.25 mm ²	14	4.27	9	2.74	5.5	1.68	3.75	1.14	2.75	0.84	2.25	0.69	1.75	0.53	1.75	0.53
22 AWG / 0.34 mm ²	22	6.71	14	4.27	9	2.74	5.75	1.75	4.5	1.37	3.5	1.07	2.75	0.84	2.75	0.84
20 AWG / 0.5 mm ²	35	10.67	23	7.01	14	4.27	9	2.74	7	2.13	5.75	1.75	4.5	1.37	4.25	1.30
18 AWG / 0.75 mm ²	56	17.07	37	11.28	23	7.01	15	4.57	11	3.35	9	2.74	7.5	2.29	7	2.13
16 AWG / 1.5 mm ²	90	27.44	60	18.29	37	11.28	24	7.32	18	5.49	15	4.57	12	3.66	11	3.35
14 AWG / 2.5 mm ²	142	43.29	95	28.96	59	17.99	38	11.59	28	8.54	23	7.01	19	5.79	17	5.18
12 AWG / 4 mm ²	226	68.90	151	46.04	94	28.66	60	18.29	45	13.72	37	11.28	30	9.15	28	8.54
10 AWG / 6 mm ²	360	109.76	240	73.17	150	45.73	96	29.27	72	21.95	60	18.29	48	14.63	45	13.72
8 AWG / 10 mm ²	574	175.00	381	116.16	239	72.87	153	46.65	115	35.06	95	28.96	76	23.17	71	21.65

REV.11JUL2025

GLOBAL HQ

320 Murray Hill Pkwy
East Rutherford, NJ 07073
U.S.
T: (+1) 212 629 6830
E: Sales-US@GENLEDBrands.com

EUROPEAN HQ

Hogeweyselaan 119
1382 JK Weesp
Netherlands
T: (+31) 346 235 000
E: SalesEurope@GENLEDBrands.com

MEINA HQ

PO Box 371378, #823, Building 4EA
Dubai Airport Free Zone
Dubai, UAE
T: (+971) 4 701 7901
E: SalesMEINA@genledbrands.com

ASIA-PACIFIC HQ

Room 402, Building D
Shenxi Tongchuang Science and Technology Park
No. 16 Hongyin Road
Xingqiang Community, Xinhua Street
Guangming District, Shenzhen, China 518107
T: (+86) 755 8529 0710
E: Sales-Pacific@GENLEDBrands.com