

VARIABLE WHITE DIMMER

The Variable White Dimmer from AmbienTech uses the same wire set as a standard dimmer with wireless support that reduces installation time and costs. No battery required! The Variable White Dimmer complies with CEC Title 24 flicker-free requirements. Device pairing with Dimming Control Module allows you to plug and play to quickly customize your lighting.

- Dimming for Variable White applications
- Wall switch with wireless signal
- Flicker-free dimming down to 0.1%
- Offers app and voice control
- Complies with Title 24 dimming requirements



SPECIFICATIONS

Max Input Power	700 W
Rated Input Voltage	120VAC - 60Hz
Color	White, Black
Load Type	12/24VDC Tunable White LED's
Ambient Temperature	-30 °C - + 40 °C / -86°F - + 104°F
IP Rating	IP23
Control Protocol	RF / SmartAir App
Dimming Range	0.1 - 100%
Dim to Off	Yes
Dimming Method	PWM (2400Hz)
Dimming Curve	Logarithmic (Default)
Dimensions (L x W x D)	2.9 in. x 4.7 in. x 1.6 in. (74.5 mm x 119 mm x 40.6 mm)
Case Material	PC/ABS - 5VA Rating

ORDERING GUIDE


Category

RFDIMVWWH - Variable White Dimmer white


RFDIMVWBK - Variable White Dimmer black

COMPATIBLE DIMMERS & DRIVER

DIMMING CONTROL MODULE (PART #: RFDIMMODVDVW)


DIMENSIONS	FEATURES
 <p>Width: 1.57 in. (40 mm) Length: 3.14 in. (80 mm) Depth: 0.64 in. (16.5 mm)</p>	<ul style="list-style-type: none"> - 3-in-1 module for dimming, Variable White and Warm-Dim applications - Control multiple modules - Offers app and voice control - Compatible with Constant Voltage LED drivers - Current limit overload protection - Complies with Title 24 dimming requirements

DIMMABLE INTEGRATED DRIVER (PART #: DRVRF2460120 / DRVRF2490120)

DIMENSIONS	FEATURES
 <p>Width: 4.1 in. (104 mm) Length: 8.4 in. (213 mm) Depth: 1.5 in. (38 mm)</p>	<ul style="list-style-type: none"> - Dimming for Variable White and Warm-Dim applications - Available in 60 W and 90 W options. - Controlled by wall switch with wireless signal - Single switch can control multiple LED drivers - Flicker-free dimming down to 0.1% - Complies with Title 24 dimming requirements - Current limit overload protection - No minimum load requirement - 24VDC output


DIMENSIONS

MECHANICAL DIMENSIONS




WIRING DIAGRAMS


VARIABLE WHITE




VARIABLE WHITE - WIRELESS




SMART AIR - APP / VOICE CONTROL



App Features



LOGIN




VARIABLE WHITE



WARM DIM




DIMMING



ZONE GROUPING



BIORHYTHM



SAVE SCENES

+ More

