





Date \_\_\_\_\_ Project \_\_\_\_\_

Notes \_\_\_\_\_


**PERCEPTION PENDANT FIXTURE**

The Perception Pendant Series from Acolyte offers customizable pendants in five nominal lengths\* ranging from 2 ft (609 mm) to 8 ft (2409 mm). These direct lighting pendants offer a choice of optic lenses to create the perfect beam of light for your application! Pick from 60° louvers, Asymmetric lenses or milky diffuser lenses. The flexible Perception Pendant Series also allows us to build complementary recessed, mud-in and ceiling mounted fixtures. All available in six CCTs ranging from 2700K to 6500K.


- Direct lighting pendants (105 lm/W)
- Complementary recessed and ceiling mounted fixtures (105-125 lm/W)
- Milky Lens, 60° Louver, or Asymmetric Lens
- 6 CCTs: 2700K, 3000K, 3500K, 4000K, 5000K, 6500K
- 25 mm (1 in.) wide
- 180° coupler available for continuous straight runs
- 24V fixtures with remote drivers (sold separately) and sleek aircraft cable power supply for pendants



**HOUSING FINISHES**




**COLOR TEMPERATURES**



Note: Custom colors available upon request

**MOUNTING OPTIONS**



**OPTIC OPTIONS**



**ORDERING GUIDE**

Model	Mounting Type	Length*	Color Temperature	Optics	Surface Finish
PN					
PN - Perception	P - Suspended Pendant	2 - 2 ft (613 mm)	27 - 2700K	M - Milky Lens	SV - Silver
	S - Ceiling	4 - 4 ft (1213 mm)	30 - 3000K	60 - 60° Louver	BK - Black
	R - Recessed	5 - 5 ft (1513 mm)	35 - 3500K***	AS - Asymmetric Lens	WH - White
	M - Mud-in	6 - 6 ft (1813 mm)**	40 - 4000K		C - Custom RAL
		8 - 8 ft (2413 mm)	50 - 5000K		
			65 - 6500K		






\* See exact fixture lengths on page 3  
 \*\* Not available with 60° Louver  
 \*\*\* May have longer lead time and MOQ

**SPECIFICATIONS**





<b>Beam Angle</b>	103° with Milky Lens, 140° with Square Milky Lens, 60° with 60° Louver, Asymmetric with Asymmetric Lens
<b>Lens Types</b>	Milky Lens (PMMA), 60° Louver, Asymmetric Lens
<b>Nominal Length</b> (see exact lengths on page 3)	2 ft. (613 mm), 4 ft. (1213 mm), 5 ft. (1513 mm), 6 ft. (1813 mm)*, 8 ft. (2413 mm)
<b>Operating Voltage</b>	24V DC (remote driver with 100-277 VAC input)
<b>Dimming</b>	0-10V, DALI
<b>Available Colors</b>	2700K, 3000K, 3500K, 4000K, 5000K, 6500K
<b>Efficacy</b>	104 lm/W with Milky Lens (see lumen table on page 3 for more details)
<b>Light Output</b>	625 lm/ft (2050 lm/m) with Milky Lens (see lumen table on page 3 for more details)
<b>CRI</b>	80+ Standard, 90+ Optional
<b>Certifications</b>	UL, CE, RoHS

\* Not available with 60° Louver

**ACCESSORIES**

<b>180° Coupler</b> (Part #: PN180CONNPS) 	<b>Ceiling Mounting Clip</b> (included accessory) 	<b>Spring Clip for Recessed Mount</b> (included accessory) 	<b>Suspended Mounting Kit</b> (included accessory) 	<b>Canopy Kit</b> (included accessory) 
---	---	--	---	--

**DIMENSIONS**

<b>Suspended Mount</b> 	<b>Ceiling Mount</b> 
<b>Recessed Mount</b> 	<b>Mud-in</b> 

Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

**EXACT FIXTURE LENGTHS**

Nominal Length	Exact Fixture Length with Milky Lens or Asymmetric Lens				Exact Fixture Length with 60° Louver			
	mm	in.	ft	Wattage	mm	in.	ft.	Wattage
2	609	23.9	1.99	12 W	543	21.3	1.78	10.8 W
4	1209	47.5	3.96	24 W	1083	42.6	3.55	21.6 W
5	1509	59.3	4.94	30 W	1515	59.5	4.96	30.3 W
6	1809	71.1	5.92	36 W	N/A	N/A	N/A	N/A
8	2409	94.7	7.89	48 W	2161	84.9	7.08	43.2 W

**LUMEN**

Optic	Light Output (lm/ft)	Light Output (lm/m)	Efficacy (lm/W)	Beam Angle
Milky Lens	625	2051	104	103
60° Louver	356	1168	58	60
Asymmetric Lens	650	2133	109	Asymmetric

**SUGGESTED SUSPENSION WIRE SEPARATED DISTANCES**

