


5.5 RGBA SERIES 2 RIBBONLYTE

5.5 RGBA Series 2 RibbonLyte is a DMX-controlled 4-channel color changing RibbonLyte with four separate chips (red, green, blue and amber), each combined in a single diode to provide flawless color blending. Mixing with amber LEDs helps create warmer pastels. Our Series 2 version offers more LEDs per foot, higher efficiency and output, and improved cut lengths.

- Color changing with DMX controls
- 36 LEDs/ft (120 LEDs/m)
- 2 in. (50 mm) incremental lengths
- 5.5 W/ft (18 W/m)
- All on: 51 lm/W
- All on: 280.67 lm/ft (920.6 lm/m)



ORDERING GUIDE

Category	CRI	Ribbon Type & IP Rating	Wattage + Color
RB	0		5.5RGBA
RB - Ribbonlyte	0 - Color Changing	RGBAS265 - RGBA Series 2 IP65	5.5RGBA - 5.5 W/ft (18 W/m) RGB+Amber
		RGBAS268 - RGBA Series 2 IP68	
		RGBAS269 - RGBA Series 2 IP69	

CONNECTION OPTIONS

1. End Feed Bare Wire Connection (Default Option)



2. IP67 Connector Input



3. Soldered Daisy Chain



4. Daisy Chain with IP67 Connectors



5. Bare Wire on Both Ends



Standard cable length if not specified:

1. 12 in. cable with bare wire (custom length up to 20 feet)
2. Standard 12 in. cable with IP67 connectors (custom length up to 10 feet)
3. Daisy chain with 3 in. cable between runs (custom length up to 36 in.)
4. 3 in. cable between IP67 connector and RibbonLyte (custom length up to 18 in.)
5. Standard 12 in. cable with bare wire (custom length up to 10 feet)

Note: IP67 connectors are used for IP65, IP68 and IP69 RibbonLyte

AVAILABLE COLORS



RGBA

SPECIFICATIONS / DIAGRAM / USAGE GUIDELINES

5.5 RGBA Series 2 RibbonLyte					
Operating Voltage	24 V				
Colors	RGBA (RGB+Amber)				
	Red	Green	Blue	Amber	All On
Power Consumption	1.375 W/ft (4.5 W/m)	1.375 W/ft (4.5 W/m)	1.375 W/ft (4.5 W/m)	1.375 W/ft (4.5 W/m)	5.5 W/ft (18 W/m)
Lumens	40.64 lm/ft (133.3 lm/m)	170.64 lm/ft (559.7 lm/m)	33.5 lm/ft (109.88 lm/m)	44.45 lm/ft (145.8 lm/m)	280.67 lm/ft (920.6 lm/m)
Efficacy	30 lm/W	124 lm/W	24 lm/W	32 lm/W	51 lm/W
Current (mA) - 24V	229 mA/ft (752 mA/m)				
LED Pitch	36 LEDs/ft (120 LEDs/m)				
Protection Rating	IP65, IP68, IP69				
Dimming/Control	Controlled with an external multi-channel DALI driver / CASAMBI or by DMX with an external interface and driver				
Operating Temperature	-40 – 140 °F (-40 – 60 °C)				
Binning Tolerance	+/- 100K (White)				
LED Beam Angle	120°				
Lifetime (L70 reported)	50,000 hours				
Incremental Length	1.97 in (50 mm)				
Constant Voltage	✓				
Cable Length	12 in (30.5 cm)				
Certifications	UL 2108 Issued: 2016/06/17 Ed: 1 Rev: 2021/10/16 Low Voltage Lighting Systems. CSA C22.2 No. 250.0, General Requirements for Luminaires. ROHS compliant				

DIMENSIONS	Top View	Side View	Dimensions
IP65	 Incremental length: 1.97 in. (50 mm)		Width 0.47 in (12 mm) Max Length 19 ft 7.9 in (6 m) Height 0.125 in (3.2 mm)
IP68	 Incremental length: 1.97 in. (50 mm)		Width 0.58 in (14.8 mm) Max Length 19 ft 7.9 in (6 m) Height 0.21 in (5.3 mm)
IP69	 Incremental length: 1.97 in. (50 mm)		Width 0.57 in. (14.5 mm) Max Length 19 ft 7.9 in. (6 m) Height 0.21 in. (5.3 mm)

OPTIONAL ACCESSORY

0.5 in. VHB Tape	Flat Mounting Clip	Silicone Clip
 Provides superior holding power in surface mounted applications Part Number: VHBTAPE0.5BK	 For mounting IP65 RibbonLyte Part Number: RBMNTSIL	 For mounting IP68/IP69 RibbonLyte Part Number: RBMNTSILW

Note: RibbonLyte comes with an adhesive backing, but Acolyte recommends using VHB Tape for extra support in surface mounted applications.






USAGE GUIDELINES

- IP65, IP68 and IP69 RibbonLyte cannot be cut in the field. All custom cuts and connections for these models must be performed at the factory to ensure waterproofing standards are met. Any modification of the waterproofing will result in a void warranty.
- When installing this product, consider the surface temperature of the material where it will be mounted. Many building surfaces which are exposed to direct sunlight exceed the 60 °C / 140 °F maximum for which our product is rated. High-risk locations like this should be avoided.
- IP65 RibbonLyte products can be used in indoor dry/damp locations such as bathrooms and kitchens. IP68 RibbonLyte products can be used in wet, outdoor locations around pools and spa tubs. IP69 RibbonLyte protects against water ingress from high-pressure, high-temperature water jets. But please note that our products are not intended to be submerged in pools and fountains and do not carry UL676 certification to do so.
- Please refer to the RibbonLyte Proper Usage Guide in our Application Guide for more information. Available for download at AcolyteLED.com.
- This product is compatible with a wide variety of control products including the entire line of Lutron dimming systems.
- For use with Acolyte drivers, 0-10V dimming modules and interface controllers (DMXINF models).
- Use with non-Acolyte supplied drivers is not supported or warrantied.
- Due to the nature of RibbonLyte products, cuttable lengths are generally longer or shorter than the customer requested length. Unless specified, RibbonLyte is factory cut at the shorter cuttable point.
- We reserve the right to make changes to product lineup, specifications, design and finishes at any time without notice.

Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.


CHANNEL COMPATIBILITY / CHANNEL OPTIONS

CHANNEL	IP65	IP68	IP69	SURFACE MOUNTED							
AC1	✓										
AC2	✓										
AC3	✓										
AC5	✓	✓	✓								
AC15L											
AR1	✓										
AR3	✓	✓	✓								
AR15L											
AR15AL											
AR24R	✓										
AR29L	✓										
AS1	✓										
AS1GS	✓										
AS2	✓										
AS3	✓	✓	✓								
AS5	✓										
AS10											
AS13	✓	✓	✓								
AS15L											
AS16	✓	✓	✓								
AS20G											
AS20GS											
AS21	✓	✓	✓								
AS23	✓	✓	✓								
AS24R	✓										
AS29L	✓										
AS30	✓	✓	✓								
AS31	✓	✓	✓								
AS53											
AT4	✓	✓	✓								
AT5	✓	✓	✓								
B1	✓										
SC3	✓	✓	✓								
SC10											
SC15L											
SC20C											
SC23	✓										
SC24R	✓										
SC38C	✓	✓	✓								

SURFACE MOUNTED											
											
AS1 W: 0.68 in. / 17.2 mm H: 0.34 in. / 8.6 mm	AS1GS W: 0.67 in. / 17.1 mm H: 0.55 in. / 13.9 mm	AS2 W: 0.7 in. / 17.8 mm H: 0.6 in. / 15.2 mm	AS3 W: 0.93 in. / 23.6 mm H: 0.42 in. / 10.7 mm	AS13 / round lens W: 1.31 in. / 33.4 mm H: 1.29 in. / 32.7 mm	AS13 / square lens W: 1.31 in. / 33.4 mm H: 1.37 in. / 34.8 mm	AS15L W: 0.59 in. / 15 mm H: 0.59 in. / 15 mm	AS16 W: 0.74 in. / 18.8 mm H: 0.73 in. / 18.6 mm				
											
AS21 W: 0.79 in. / 20 mm H: 0.82 in. / 20.84 mm	AS23 W: 0.91 in. / 23 mm H: 1.59 in. / 40.5 mm	AS24R W: 0.91 in. / 23 mm H: 1.03 in. / 26.2 mm	AS29L W: 1.18 in. / 30 mm H: 1.15 in. / 29.2 mm	AS30 / round lens W: 1.31 in. / 33.4 mm H: 1.95 in. / 49.5 mm	AS30 / square lens W: 1.31 in. / 33.4 mm H: 2.03 in. / 51.6 mm	AS31 W: 1.18 in. / 30 mm H: 1.22 in. / 30.92 mm					
											
AT4 W: 0.77 in. / 19.6 mm H: 0.74 in. / 18.8 mm	AT5 W: 0.77 in. / 19.6 mm H: 0.74 in. / 18.8 mm	B1 W: 0.77 in. / 19.6 mm H: 0.26 in. / 6.5 mm									
CORNER											
											
AC1 W: 0.63 in. / 16 mm H: 0.63 in. / 16 mm	AC2 W: 0.63 in. / 16 mm H: 0.63 in. / 16 mm	AC3 W: 0.74 in. / 18.8 mm H: 0.74 in. / 18.8 mm	AC5 W: 1.18 in. / 30 mm H: 1.18 in. / 30 mm								
RECESSED											
											
AR1 W: 0.9 in. / 22.9 mm H: 0.31 in. / 7.87 mm	AR3 W: 1.2 in. / 30.5 mm H: 0.42 in. / 10.8 mm	AR24R W: 1.3 in. / 33 mm H: 1.03 in. / 26.2 mm	AR29L W: 1.57 in. / 40 mm H: 1.15 in. / 29.2 mm								
MUD-IN											
											
SC3 W: 2.62 in. / 66.6 mm H: 0.55 in. / 14 mm	SC24R W: 2.48 in. / 63 mm H: 1.03 in. / 26.2 mm	SC23 W: 0.93 in. / 23.7 mm H: 3.46 in. / 88 mm	SC38C W: 2.32 in. / 58.9 mm H: 2.85 in. / 72.3 mm								

WIRING DIAGRAMS

DMX



WIRE COLORS PER RIBBONLYTE COLOR

RGBA

Black (+) Positive
Green Wire (-) goes to Green Channel
Red Wire (-) goes to Red Channel
Blue Wire (-) goes to Blue Channel
White Wire (-) goes to Amber Channel

ACTUAL POWER CONSUMPTION

Length (ft)	Length (m)	Actual Power Consumed (W)	Average Wattage (W/ft)	Average Wattage (W/m)	Actual Current Drawn (A)
5	1.52	26.91	5.38	17.65	1.121
10	3.05	52.83	5.28	17.33	2.201
15	4.57	76.68	5.11	16.77	3.195
19.7	6.01	97.55	4.95	16.24	4.065

NOTE: Quotes use nominal values. We highly recommend using nominal wattages for all customer calculations. Allow for a 15% buffer (10% driver, 5% fixture) in these calculations as performance may vary. Acolyte is not liable for product performance if these tables are used instead of nominal values when orders are placed.

REV.04AUG2026

GLOBAL HQ

320 Murray Hill Pkwy
East Rutherford, NJ 07073
U.S.
T: (+1) 212 629 6830
E: Sales-US@GENLEDBrands.com

EUROPEAN HQ

Hogeweyselaan 119
1382 JK Weesp
Netherlands
T: (+31) 346 235 000
E: SalesEurope@GENLEDBrands.com

MEINA HQ

PO Box 371378, #823, Building 4EA
Dubai Airport Free Zone
Dubai, UAE
T: (+971) 4 701 7901
E: SalesMEINA@genledbrands.com

ASIA-PACIFIC HQ

Room 402, Building D
Shenshi Tongchuang Science and Technology Park
No. 16 Hongyin Road
Xingqiang Community, Xinhua Street
Guangming District, Shenzhen, China 518107
T: (+86) 755 8529 0710
E: Sales-Pacific@GENLEDBrands.com