



ULTRA 650 RGBW

LS-U650-RGBW-B200-A

COLOR CHANGING LED MODULES

ULTRA 650 RGBW

ULTRA 650 RGBW modules are premium color changing signage modules engineered for constant current so there is no lumen drop across the full length of any string. The ULTRA 650 RGBW module features four chips in each LED – red, green, blue and white for added brightness. Use DMX controls to tune ULTRA 650 RGBW modules to any color.

Applications:

- Channel letters
- Box signs
- Cove lighting
- Applications starting at depths of 3 in. (75 mm)



RoHS

IP66



12 VDC



5-YEAR
WARRANTY



VERSALENZ[®]
ADVANCED OPTICS



CAPZUL[®]
WATERPROOF

ORDERING GUIDE


Part Number	Colors & CCT	Module Spacing (mm)	Wattage (W)	Input Current (mA)	Number of Modules Per Foot	Number of Modules Per Meter	Nominal Light Output (lm) Per Watt	Per Module	Per Foot	Per Meter
LS-U650-RGBW-B200-A	All	200	1.2	100	1.5	5	52	62.6	95.4	313
	Red (612-628 nm)	200	0.3	25	1.5	5	25.3	7.6	11.6	38
	Green (512-528 nm)	200	0.3	25	1.5	5	61.7	18.5	28.2	92.5
	Blue (457-473 nm)	200	0.3	25	1.5	5	20	6	9.1	30
	White (6500K)	200	0.3	25	1.5	5	101.7	30.5	46.5	152.5

RECOMMENDED CONTROL OPTIONS

Options	Image	Description	Part Number
1 For basic setting		4 Zone Color Changing Glass Touch Wall Controller	AWCRGBWWBK
		5 Channel DMX Decoder	DMXINF5
2 For wireless connection		4 Channel RF Interface	RFINTERFACE4CH
		4 Zone RGBW RF Remote	RFREMOTERGBW4Z
		RF to WiFi Converter	RFWIFICONVERT
3 For advanced setting		4 Channel Waterproof DMX LCD Interface	DMXINFWLCD4
		5 Zone DMX Wall Controller	DMXCTRL
		10 Zone DMX Wall Controller	DMXCTRLD

LUMINOUS DISTRIBUTION

Batwing Beam Pattern



COLOR TEMPERATURE SCALE



CONSTANT
CURRENT



UV
RESISTANT

PRODUCT RATINGS

Input Voltage	12 VDC
Power Supply Loading	46 modules per 60 W
Ingress Protection	IP66
Operating Temperature	-13 — 131 °F (-25 — 55 °C)
L70 Lifetime @ 60° C	50,000 hours
Warranty	5-year limited warranty



MODULE DIMENSIONS

Part Number	Length (in. / mm)	Width (in. / mm)	Height (in. / mm)
LS-U650-RGBW-B200-A	2.62 / 66	0.61 / 15	0.38 / 10

POWER SUPPLY LOADING

Module Type	Per 60W Power Supply			
	Max. # of Modules Per String	Total # of Modules	Total # of Feet	Total # of Meters
LS-U650-RGBW-B200-A	44	46	30.7	9.3

LAYOUT GUIDE

Channel Depth (in.)	Single Row		Multiple Rows	
	Max. Stroke	Module Spacing	Row Spacing	Module Spacing
3	6	5	4	4
4	9	6	6	7
5	12	8	10	8
6	14	8	12	8


Channel Depth (mm)	Single Row		Multiple Rows	
	Max. Stroke	Module Spacing	Row Spacing	Module Spacing
75	150	125	100	100
100	225	150	150	175
125	300	200	250	200
150	350	200	300	200

*Module spacing is defined by 7328 white sign face material

SHIPPING INFORMATION

Module Type	Specs	Packaging Quantity			Carton Weight	Carton Dimensions			Box Weight	Box Dimensions		
		Per Bag	Per Box	Per Carton		L	W	H		L	W	H
LS-U650-RGBW-B200-A	Modules	100	400	800	12.3 kg (27.1 lbs)	20.5	14.6	10.2	6 kg (13.2 lbs)	13.78	9.84	9.06 in.
	Feet	65.6	262.4	524.8		520	370	260		350	250	230 mm
	Meters	20	80	160								

DIMENSION DRAWING



1. UL ONLY - These products are only suitable for connection to a UL rated Class 2 power source rated 12 Volt or less.
2. UL ONLY - These products are intended for use only when connected to a power source that complies with UL rated Class 2 voltage and energy limited circuit.
3. UL ONLY - When these units are connected to a UL rated Class 2 circuit, they are not to draw a total wattage of greater than the secondary or output rating of the UL rated Class 2 power supply.
4. These products may be secured in place in the end product by any means available.
5. These products are suitable for use in dry, damp, and wet locations. Not suitable for submersed applications.

GLOBAL HQ

320 Murray Hill Pkwy
East Rutherford, NJ 07073
U.S.
T: (+1) 212 629 6830
E: Sales-US@GENLEDBrands.com

EUROPEAN HQ

Hogeweyselaan 119
1382 JK Weesp
Netherlands
T: (+31) 346 235 000
E: SalesEurope@GENLEDBrands.com

MEINA HQ

PO Box 371378, #823, Building 4EA
Dubai Airport Free Zone
Dubai, UAE
T: (+971) 4 701 7901
E: SalesMEINA@genlebrands.com

ASIA-PACIFIC HQ

Room 402, Building D
Shenxi Tongchuang Science and Technology Park
No. 16 Hongyin Road
Xingqiang Community, Xinhua Street
Guangming District, Shenzhen, China 518107
T: (+86) 755 8529 0710
E: Sales-Pacific@GENLEDBrands.com