



NEON360

Neon360 is a bendable LED neon tube with a round profile that provides uniform light distribution. With a one-inch (0.91 in./23 mm) diameter, the striking 24V Neon360 is available in 5 dimmable Static White CCTs (2400K-4000K). Neon360 offers flexible design with a bending diameter of 4.72 in. (120 mm) and cut lengths of less than 2 in. (50 mm). Choose from several unique mounting options for creative light displays.

- Fully illuminated flexible round LED neon
- 0.91 in. (23 mm) diameter
- 5 Static White CCTs (2400K-4000K)
- Min. bending diameter: 4.72 in. (120 mm)
- 4.8 W/ft (16 W/m), cuttable every 1.4 in. (35.71 mm)
- 389.9 lm/ft (1278.9 lm/m) @ 4000K



AVAILABLE COLORS AND COLOR TEMPERATURES




ORDERING GUIDE

Category	Wattage & Color		Power Feed Direction
NL360			
NL360 - Neon360	4.824 - 4.8 W/ft 2400K	4.835 - 4.8 W/ft 3500K	E - End Feed
	4.827 - 4.8 W/ft 2700K	4.840 - 4.8 W/ft 4000K	S - Side Feed
	4.830 - 4.8 W/ft 3000K		
ACCESSORIES			
1. Mounting Clip Part #: NL360MC	5. Ceiling Mounting Kit Part #: NL360CMNT	9. Horizontal Suspended Mounting Kit with Clear Rigid Tube Part #: NL360HSUSPC	
2. Mounting Channel Part #: NL360CH	6. Ceiling Mounting Kit with Clear Rigid Tube Part #: NL360CMNTPC	10. Horizontal Suspended Mounting Kit with Mounting Channel Part #: NL360HSUSCH Add appropriate number of non-feed channel sections for fixtures longer than 6.74 in. (2 m) Part #: NL360HSUSCHNF	
3. End Cap Part #: NL360CAP	7. Vertical Suspended Mounting Kit Part #: NL360VMNT	11. Mounting Ring Kit with Steel Cable Part #: NL360HOOK (Canopy Kit not included)	
4. Coupler Kit Part #: NL360COUP	8. Vertical Suspended Mounting Kit with Clear Rigid Tube Part #: NL360VMNTPC	12. Canopy Kit Part #: NL360CANOPY	

NOTE: Standard suspension cables are 39.37 in. (1 m) long. Order custom suspension cables up to 16 ft 4.85 in. (5 m) or longer.

DIMENSIONS



SPECIFICATIONS

SPECIFICATIONS		NEON360				
Operating Voltage		24 V				
Power Consumption		4.8 W/ft (16 W/m)				
Beam Angle		360°				
Protection Rating		IP65				
Dimming		MLV / 0-10V / ELV / DALI / DMX				
Operating Temperature		-4° F to 140° F (-20° C to 60° C)				
Color Temperatures		2400K	2700K	3000K	3500K	4000K
Lumens		298.1 lm/ft (978 lm/m)	352.3 lm/ft (1155.9 lm/m)	378.2 lm/ft (1240.9 lm/m)	388.8 lm/ft (1275.7 lm/m)	389.8 lm/ft (1278.9 lm/m)
Efficacy		62.1 lm/W	73.4 lm/W	78.8 lm/W	81 lm/W	81.2 lm/W
Lamp Life		50,000 Hours				
Length		Up to 16 ft 4. in. (5 m)				
Cuttable Length		1.4 in. (35.71 mm) NOT FIELD CUTTABLE				
Minimum Bending Diameter		4.72 in. (120 mm)				
Suspension Cable Length		Standard suspension cables are 39.37 in. (1 m) long. Order custom suspension cables up to 16 ft 4.85 in. (5 m) or longer.				
CRI (Static White)		80+ CRI				


AVERAGE ILLUMINANCE @ 4000K

Flux out: 270.7 lm













Height	Eavg, Emax	Diameter
0.5m	344.7,698.51x	100cm
1.0m	86.17,174.61x	200cm
1.5m	38.30,77.621x	300cm
2.0m	21.54,43.661x	400cm
2.5m	13.79,27.941x	500cm
3.0m	9.575,19.401x	600cm
3.5m	7.035,14.261x	700cm
4.0m	5.386,10.911x	800cm
4.5m	4.256,8.6241x	900cm
5.0m	3.447,6.9851x	1000cm

Beam Angle: 90.00°

JUNCTION BOX MAXIMUM DIMENSIONS FOR CANOPY COVERING




ACCESSORIES

<p>Mounting Clip</p>  <p>Part #: NL360MC</p>	<p>Mounting Channel</p>  <p>Part #: NL360CH</p>	<p>End Cap</p>  <p>Part #: NL360CAP</p>	<p>Coupler Kit</p>  <p>Part #: NL360COUP</p>
<p>Ceiling Mounting Kit</p>  <p>Part #: NL360CMNT</p>	<p>Ceiling Mounting Kit with Clear Rigid Tube*</p>  <p>Part #: NL360CMNTPC</p> <p>* Clear Rigid Tube is to keep Neon360 in a straight line and is not bendable, and the max length is 78.7 in. (2 m).</p>	<p>Vertical Suspended Mounting Kit</p>  <p>Part #: NL360VMNT</p>	<p>Vertical Suspended Mounting Kit with Clear Rigid Tube*</p>  <p>Part #: NL360VMNTPC</p> <p>* Clear Rigid Tube is to keep Neon360 in a straight line and is not bendable, and the max length is 78.7 in. (2 m).</p>
<p>Horizontal Suspended Mounting Kit with Clear Rigid Tube*</p>  <p>Part #: NL360HSUSPC</p> <p>* Clear Rigid Tube is to keep Neon360 in a straight line and is not bendable, and the max length is 78.7 in. (2 m).</p>	<p>Horizontal Suspended Mounting Kit with Mounting Channel</p>  <p>Part #: NL360HSUSCH</p> <p>NOTE: Neon360 fixtures can run up to 16.4 ft (5 m) long. Each section of mounting channel is a maximum of 6 ft 6.74 in. (2 m). Channel sections are pre-cut and pre-assembled. For complete fixtures longer than 6.74 in. (2 m), add the appropriate number of extra non-feed channel sections to reach desired length.</p> <p>Non-feed Part #: NL360HSUSCHNF</p>	<p>Mounting Ring Kit with Steel Cable**</p>  <p>Part #: NL360HOOK</p> <p>** To maintain a horizontal fixture, ring suspension points should be spaced every 15 in. (Canopy Kit not included)</p>	<p>Canopy Kit</p>  <p>Part #: NL360CANOPY</p>

NOTE: Standard suspension cables are 39.37 in. (1 m) long. Order custom suspension cables up to 16 ft 4.85 in. (5 m) or longer.

WIRING DIAGRAMS

0-10V




WIRE COLORS PER RIBBONLYTE COLOR


STATIC WHITE

Red Wire (+) Positive
Black Wire (-) Negative

MLV / ELV



DMX



USAGE GUIDELINES

- Neon360 cannot be cut in the field. All custom cuts and connections for these models must be performed at the factory to ensure waterproofing standards are met. Any modification of the waterproofing will result in a voided warranty.
- When installing this product take into account the surface temperature of the material this product is mounted to. Many building surfaces which are exposed to direct sunlight exceed the 60° C/140° F maximum that our product is rated for. High-risk locations like this should be avoided.
- This product is not intended to be submerged in pools and fountains and does not carry UL 676 certification to do so.
- Compatible with a wide variety of control products including the entire line of Lutron dimming systems.
- For use with Acolyte drivers, triac dimming modules, and 0-10 modules.
- Use with non-Acolyte drivers is not supported or warrantied
- Due to the cuttable points inside, this product's cuttable lengths are generally longer or shorter than the customer requested length. Unless specified, this product is factory cut at the shorter cuttable point
- This product can be used in wet, outdoor locations around swimming pools and spa tubs, but not submerged in swimming pools and spa tubs.
- We reserve the right to make changes to product lineup, specifications, design and finishes at any time without notice.

Acolyte does not warrant or represent that this information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

REV.22FEB2024