

Report No.:

Test Time: 2023/10/9 10:49

Luminaire Property

Luminaire Manufacturer:

Luminaire Category: TRI NODE RGB-0.75W-UCS8903

Luminaire Description: MILKY GLOBE IP67

Lamp Catalog: NODE

Lamp Description: 3 nodes BLUE

Luminous Length (mm): 250

Luminous Width (mm): 60

Luminous Height (mm): 75

Voltage: 24.0 V

Current: 0.059 A

Power: 1.41 W

Power Factor: 1.000

Photometric Results

CIE Class: Semi-Direct

Total Rated Lamp Lumens: 3.7 lm

Measurement Flux: 3.7 lm

Efficiency: 100%

Downward Ratio: 68%

Upward Ratio: 32%

Horizontal Diffuse Angle(10%,50%): H182.2,H155.4

Vertical Diffuse Angle(10%,50%): V306.7,V212.6

Luminaire Efficacy Rating (LER): 3

Central Intensity: 0.37 cd


Max. Intensity: 0.53 cd

Pos of Max. Intensity: H180 V35

Picture Of Luminaire



Luminous Intensity Distribution Curve



Average Diffuse Angle(50%): 184.0° Unit: cd

— C0-C180 — C90-C270

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Jacky

Gamma Plane (°):0.0-180.0: 1.0


Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Jacky

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Jacky

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:


Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	111	111	111	111	105	105	105	105	93	93	93	83	83	83	73	73	73	68
1	97	91	85	80	91	85	80	76	75	71	67	66	63	60	57	55	52	48
2	87	77	69	62	81	72	65	58	63	57	52	55	50	46	48	44	41	37
3	78	66	57	49	73	62	54	47	54	47	42	47	42	37	41	36	33	29
4	71	58	48	40	66	54	45	38	47	40	34	41	35	31	36	31	27	23
5	65	51	41	34	60	48	39	32	42	35	29	37	31	26	32	27	23	20
6	59	45	36	29	55	43	34	27	37	30	25	33	27	22	28	23	19	17
7	55	41	31	25	51	38	30	24	34	27	21	30	24	19	26	21	17	14
8	51	37	28	22	47	35	26	21	31	24	19	27	21	17	23	19	15	13
9	47	33	25	19	44	32	24	18	28	21	17	25	19	15	22	17	13	11
10	44	31	22	17	41	29	21	16	26	19	15	23	17	13	20	15	12	10

Spacing Criteria (0-180): 1.87

Spacing Criteria (90-270): 1.61

Spacing Criteria (Diagonal): 1.90



C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 25

Operator: Jacky

Gamma Plane (°):0.0-180.0: 1.0


Test Device: GPM-1800B

Distance: 9.028 m

Humidity: 60%

Inspector:

Isocandela (rectangle)




I_{max} (100%): 1 cd

(10%):	0 cd	(20%):	0 cd
(25%):	0 cd	(30%):	0 cd
(40%):	0 cd	(50%):	0 cd
(60%):	0 cd	(70%):	0 cd
(80%):	0 cd	(90%):	0 cd

C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Jacky

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

IsoLux Plot



Mounting Height: 5.0m Max Lux(100%): 0.0 lx

(10%): 0.0 lx	(20%): 0.0 lx
(25%): 0.0 lx	(30%): 0.0 lx
(40%): 0.0 lx	(50%): 0.0 lx
(60%): 0.0 lx	(70%): 0.0 lx
(80%): 0.0 lx	(90%): 0.0 lx

C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Jacky

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300

a b c d e f g h




L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	21	17	18	17	15	14	10	9	5
C90	31	37	35	38	40	36	47	55	64
C180	19	17	18	16	15	13	9	9	7
C270	33	37	36	37	35	47	40	57	57


C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Jacky

Gamma Plane (°):0.0-180.0: 1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Illuminance at a Distance



Vertical IsoLux Plot



Lowest(m): 2.0m		Highest(m): 5.0m	Max Lux: 0.1 lx
(10%):	0.0 lx	(20%):	0.0 lx
(25%):	0.0 lx	(30%):	0.0 lx
(40%):	0.0 lx	(50%):	0.1 lx
(60%):	0.1 lx	(70%):	0.1 lx
(80%):	0.1 lx	(90%):	0.1 lx


C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Jacky

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:



The Average Illuminance Effective Figure



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Jacky

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	16.3	17.5	17.0	18.3	19.3	15.4	16.6	16.2	17.4	18.4
3H	19.1	20.2	19.9	21.1	22.1	17.8	18.9	18.6	19.7	20.7
4H	20.4	21.4	21.2	22.3	23.3	19.2	20.3	20.0	21.1	22.1
6H	21.3	22.3	22.1	23.1	24.2	20.5	21.5	21.3	22.3	23.4
8H	21.7	22.7	22.5	23.5	24.5	21.1	22.1	21.9	22.9	24.0
12H	22.0	22.9	22.8	23.7	24.8	21.7	22.6	22.5	23.4	24.5
X=4H Y=2H	16.9	17.9	17.7	18.8	19.8	16.4	17.4	17.2	18.3	19.3
3H	20.1	21.1	21.0	21.9	23.0	18.9	19.8	19.7	20.6	21.7
4H	21.4	22.3	22.2	23.1	24.2	20.5	21.3	21.3	22.2	23.3
6H	22.6	23.3	23.4	24.2	25.3	21.9	22.7	22.8	23.6	24.6
8H	23.1	23.8	23.9	24.7	25.7	22.6	23.4	23.5	24.2	25.3
12H	23.4	24.1	24.3	25.0	26.1	23.3	23.9	24.1	24.8	25.9
X=8H Y=4H	21.9	22.6	22.7	23.5	24.5	21.2	21.9	22.0	22.8	23.8
6H	23.3	23.9	24.1	24.8	25.9	22.8	23.4	23.7	24.3	25.4
8H	24.0	24.6	24.9	25.5	26.5	23.7	24.2	24.5	25.1	26.2
12H	24.5	25.0	25.4	25.9	27.0	24.5	25.0	25.3	25.9	27.0
X=12H Y=4H	22.0	22.6	22.8	23.5	24.6	21.3	22.0	22.2	22.8	23.9
6H	23.5	24.0	24.3	24.9	26.0	23.1	23.6	23.9	24.5	25.6
8H	24.3	24.8	25.1	25.7	26.8	24.0	24.5	24.9	25.4	26.5

Calculate in accordance with CIE 190:2010

 C Plane (°):0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Jacky

 Gamma Plane (°):0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Utilisation Factor Table(Floor cavity)

Utilisation Factors UF(F)			SHR NOM = 1.75									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	NA	0.51	0.57	0.62	0.69	0.74	0.78	0.83	0.86	
	0.30		NA	0.42	0.49	0.54	0.62	0.67	0.72	0.77	0.81	
	0.20		NA	0.36	0.43	0.48	0.56	0.62	0.66	0.73	0.77	
0.50	0.50	0.20	NA	0.45	0.51	0.55	0.61	0.65	0.69	0.73	0.76	
	0.30		NA	0.38	0.44	0.49	0.55	0.60	0.64	0.69	0.72	
	0.20		NA	0.34	0.39	0.43	0.50	0.55	0.59	0.65	0.69	
0.30	0.50	0.20	NA	0.40	0.45	0.48	0.54	0.57	0.60	0.64	0.67	
	0.30		NA	0.34	0.39	0.43	0.49	0.53	0.56	0.61	0.64	
	0.20		NA	0.30	0.35	0.39	0.45	0.49	0.53	0.58	0.61	
0.00	0.00	0.00	NA	0.24	0.28	0.31	0.36	0.40	0.42	0.46	0.49	
Rating: 1W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Utilisation Factor Table(Wall)

Utilisation Factors UF(W)			SHR NOM = 1.75									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	NA	0.89	0.78	0.69	0.58	0.49	0.43	0.35	0.30	
	0.30		NA	0.76	0.68	0.61	0.52	0.45	0.40	0.33	0.28	
	0.20		NA	0.66	0.60	0.55	0.47	0.42	0.38	0.31	0.27	
0.50	0.50	0.20	NA	0.80	0.70	0.63	0.52	0.47	0.39	0.32	0.27	
	0.30		NA	0.69	0.62	0.56	0.48	0.41	0.37	0.30	0.26	
	0.20		NA	0.61	0.55	0.51	0.44	0.39	0.35	0.29	0.25	
0.30	0.50	0.20	NA	0.72	0.63	0.56	0.47	0.41	0.36	0.29	0.25	
	0.30		NA	0.63	0.56	0.51	0.43	0.38	0.34	0.28	0.24	
	0.20		NA	0.56	0.51	0.47	0.40	0.36	0.32	0.27	0.23	
0.00	0.00	0.00	0.68	0.44	0.40	0.37	0.32	0.28	0.25	0.21	0.18	
Rating: 1W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Utilisation Factor Table(Ceiling cavity)

Utilisation Factors UF(C)			SHR NOM = 1.75									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	NA	0.49	0.50	0.51	0.51	0.52	0.52	0.53	0.53	
	0.30		NA	0.42	0.43	0.44	0.46	0.47	0.47	0.48	0.49	
	0.20		NA	0.37	0.38	0.39	0.41	0.42	0.43	0.45	0.46	
0.50	0.50	0.20	NA	0.47	0.48	0.49	0.49	0.50	0.50	0.50	0.50	
	0.30		NA	0.41	0.42	0.43	0.44	0.45	0.46	0.47	0.47	
	0.20		NA	0.37	0.38	0.39	0.40	0.41	0.42	0.43	0.44	
0.30	0.50	0.20	NA	0.46	0.46	0.47	0.47	0.48	0.48	0.48	0.48	
	0.30		NA	0.40	0.41	0.42	0.43	0.44	0.44	0.45	0.46	
	0.20		NA	0.36	0.37	0.38	0.39	0.40	0.41	0.42	0.43	
0.00	0.00	0.00	0.32	0.32	0.32	0.32	0.32	0.32	0.32	0.32	0.32	
Rating: 1W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	0.4	0.0	0.0	0.01	0.01
1.0-2.0	0.4	0.0	0.0	0.03	0.05
2.0-3.0	0.4	0.0	0.0	0.06	0.10
3.0-4.0	0.5	0.0	0.0	0.08	0.19
4.0-5.0	0.4	0.0	0.0	0.11	0.29
5.0-6.0	0.5	0.0	0.0	0.13	0.42
6.0-7.0	0.4	0.0	0.0	0.15	0.58
7.0-8.0	0.4	0.0	0.0	0.17	0.75
8.0-9.0	0.4	0.0	0.0	0.20	0.95
9.0-10.0	0.4	0.0	0.0	0.22	1.16
10.0-11.0	0.4	0.0	0.1	0.24	1.40
11.0-12.0	0.4	0.0	0.1	0.27	1.67
12.0-13.0	0.5	0.0	0.1	0.30	1.97
13.0-14.0	0.5	0.0	0.1	0.32	2.29
14.0-15.0	0.5	0.0	0.1	0.34	2.63
15.0-16.0	0.5	0.0	0.1	0.36	2.99
16.0-17.0	0.5	0.0	0.1	0.39	3.38
17.0-18.0	0.4	0.0	0.1	0.41	3.78
18.0-19.0	0.4	0.0	0.2	0.42	4.21
19.0-20.0	0.5	0.0	0.2	0.46	4.66
20.0-21.0	0.5	0.0	0.2	0.48	5.15
21.0-22.0	0.5	0.0	0.2	0.50	5.64
22.0-23.0	0.5	0.0	0.2	0.52	6.17
23.0-24.0	0.5	0.0	0.2	0.56	6.72
24.0-25.0	0.5	0.0	0.3	0.57	7.30
25.0-26.0	0.4	0.0	0.3	0.58	7.88
26.0-27.0	0.5	0.0	0.3	0.61	8.49
27.0-28.0	0.5	0.0	0.3	0.63	9.12
28.0-29.0	0.5	0.0	0.4	0.65	9.77
29.0-30.0	0.4	0.0	0.4	0.66	10.43
30.0-31.0	0.4	0.0	0.4	0.67	11.09
31.0-32.0	0.4	0.0	0.4	0.69	11.78
32.0-33.0	0.4	0.0	0.5	0.70	12.49
33.0-34.0	0.4	0.0	0.5	0.72	13.21
34.0-35.0	0.4	0.0	0.5	0.76	13.96
35.0-36.0	0.4	0.0	0.5	0.77	14.74

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Jacky

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	0.4	0.0	0.6	0.80	15.53
37.0-38.0	0.4	0.0	0.6	0.82	16.35
38.0-39.0	0.4	0.0	0.6	0.83	17.17
39.0-40.0	0.4	0.0	0.7	0.83	18.01
40.0-41.0	0.4	0.0	0.7	0.85	18.85
41.0-42.0	0.4	0.0	0.7	0.88	19.73
42.0-43.0	0.4	0.0	0.8	0.89	20.62
43.0-44.0	0.4	0.0	0.8	0.89	21.51
44.0-45.0	0.4	0.0	0.8	0.90	22.42
45.0-46.0	0.4	0.0	0.9	0.93	23.35
46.0-47.0	0.4	0.0	0.9	0.94	24.29
47.0-48.0	0.4	0.0	0.9	0.96	25.25
48.0-49.0	0.4	0.0	1.0	0.98	26.23
49.0-50.0	0.4	0.0	1.0	1.01	27.24
50.0-51.0	0.4	0.0	1.0	1.01	28.25
51.0-52.0	0.4	0.0	1.1	1.02	29.27
52.0-53.0	0.4	0.0	1.1	1.02	30.29
53.0-54.0	0.4	0.0	1.1	1.04	31.33
54.0-55.0	0.4	0.0	1.2	1.06	32.39
55.0-56.0	0.4	0.0	1.2	1.06	33.45
56.0-57.0	0.4	0.0	1.3	1.04	34.49
57.0-58.0	0.4	0.0	1.3	1.03	35.52
58.0-59.0	0.4	0.0	1.3	1.07	36.60
59.0-60.0	0.4	0.0	1.4	1.09	37.68
60.0-61.0	0.4	0.0	1.4	1.08	38.76
61.0-62.0	0.4	0.0	1.5	1.09	39.86
62.0-63.0	0.4	0.0	1.5	1.08	40.93
63.0-64.0	0.4	0.0	1.5	1.07	42.00
64.0-65.0	0.4	0.0	1.6	1.07	43.07
65.0-66.0	0.4	0.0	1.6	1.07	44.14
66.0-67.0	0.4	0.0	1.7	1.09	45.22
67.0-68.0	0.4	0.0	1.7	1.09	46.31
68.0-69.0	0.4	0.0	1.7	1.08	47.39
69.0-70.0	0.4	0.0	1.8	1.08	48.47
70.0-71.0	0.4	0.0	1.8	1.07	49.54
71.0-72.0	0.4	0.0	1.8	1.06	50.59

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Jacky

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 2)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
72.0-73.0	0.4	0.0	1.9	1.06	51.65
73.0-74.0	0.4	0.0	1.9	1.07	52.73
74.0-75.0	0.4	0.0	2.0	1.04	53.76
75.0-76.0	0.3	0.0	2.0	1.02	54.78
76.0-77.0	0.4	0.0	2.0	1.03	55.81
77.0-78.0	0.3	0.0	2.1	1.02	56.83
78.0-79.0	0.3	0.0	2.1	1.00	57.83
79.0-80.0	0.3	0.0	2.1	1.01	58.84
80.0-81.0	0.3	0.0	2.2	1.02	59.86
81.0-82.0	0.3	0.0	2.2	1.01	60.87
82.0-83.0	0.3	0.0	2.3	0.98	61.85
83.0-84.0	0.3	0.0	2.3	0.94	62.79
84.0-85.0	0.3	0.0	2.3	0.91	63.70
85.0-86.0	0.3	0.0	2.4	0.91	64.61
86.0-87.0	0.3	0.0	2.4	0.91	65.52
87.0-88.0	0.3	0.0	2.4	0.90	66.42
88.0-89.0	0.3	0.0	2.5	0.88	67.31
89.0-90.0	0.3	0.0	2.5	0.88	68.19
90.0-91.0	0.3	0.0	2.5	0.86	69.05
91.0-92.0	0.3	0.0	2.6	0.85	69.90
92.0-93.0	0.3	0.0	2.6	0.83	70.73
93.0-94.0	0.3	0.0	2.6	0.81	71.54
94.0-95.0	0.3	0.0	2.6	0.80	72.34
95.0-96.0	0.3	0.0	2.7	0.81	73.15
96.0-97.0	0.3	0.0	2.7	0.81	73.96
97.0-98.0	0.3	0.0	2.7	0.78	74.75
98.0-99.0	0.3	0.0	2.8	0.77	75.52
99.0-100.0	0.2	0.0	2.8	0.72	76.24
100.0-101.0	0.2	0.0	2.8	0.72	76.96
101.0-102.0	0.3	0.0	2.8	0.74	77.70
102.0-103.0	0.2	0.0	2.9	0.71	78.41
103.0-104.0	0.2	0.0	2.9	0.70	79.11
104.0-105.0	0.2	0.0	2.9	0.70	79.81
105.0-106.0	0.2	0.0	2.9	0.69	80.51
106.0-107.0	0.2	0.0	3.0	0.67	81.17
107.0-108.0	0.2	0.0	3.0	0.65	81.83

C Plane (°): 0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Jacky

Gamma Plane (°): 0.0-180.0: 1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector:

Zonal Lumen (Continue 3)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
108.0-109.0	0.2	0.0	3.0	0.63	82.45
109.0-110.0	0.2	0.0	3.0	0.63	83.08
110.0-111.0	0.2	0.0	3.1	0.62	83.70
111.0-112.0	0.2	0.0	3.1	0.59	84.29
112.0-113.0	0.2	0.0	3.1	0.62	84.90
113.0-114.0	0.2	0.0	3.1	0.63	85.53
114.0-115.0	0.2	0.0	3.1	0.59	86.12
115.0-116.0	0.2	0.0	3.2	0.56	86.69
116.0-117.0	0.2	0.0	3.2	0.55	87.24
117.0-118.0	0.2	0.0	3.2	0.56	87.80
118.0-119.0	0.2	0.0	3.2	0.52	88.32
119.0-120.0	0.2	0.0	3.2	0.50	88.82
120.0-121.0	0.2	0.0	3.3	0.52	89.34
121.0-122.0	0.2	0.0	3.3	0.50	89.84
122.0-123.0	0.2	0.0	3.3	0.46	90.30
123.0-124.0	0.2	0.0	3.3	0.46	90.76
124.0-125.0	0.2	0.0	3.3	0.45	91.21
125.0-126.0	0.2	0.0	3.3	0.42	91.63
126.0-127.0	0.2	0.0	3.4	0.42	92.05
127.0-128.0	0.2	0.0	3.4	0.42	92.47
128.0-129.0	0.2	0.0	3.4	0.40	92.88
129.0-130.0	0.2	0.0	3.4	0.37	93.25
130.0-131.0	0.2	0.0	3.4	0.37	93.62
131.0-132.0	0.2	0.0	3.4	0.38	94.00
132.0-133.0	0.2	0.0	3.4	0.36	94.35
133.0-134.0	0.1	0.0	3.5	0.32	94.68
134.0-135.0	0.2	0.0	3.5	0.33	95.00
135.0-136.0	0.2	0.0	3.5	0.34	95.34
136.0-137.0	0.1	0.0	3.5	0.30	95.64
137.0-138.0	0.1	0.0	3.5	0.26	95.90
138.0-139.0	0.1	0.0	3.5	0.26	96.16
139.0-140.0	0.1	0.0	3.5	0.27	96.42
140.0-141.0	0.1	0.0	3.5	0.26	96.68
141.0-142.0	0.1	0.0	3.5	0.24	96.92
142.0-143.0	0.1	0.0	3.5	0.22	97.14
143.0-144.0	0.1	0.0	3.6	0.21	97.35

C Plane (°): 0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 25
 Operator: Jacky

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-1800B
 Distance: 9.028 m
 Humidity: 60%
 Inspector:

Zonal Lumen (Continue 4)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
144.0-145.0	0.1	0.0	3.6	0.20	97.54
145.0-146.0	0.1	0.0	3.6	0.20	97.75
146.0-147.0	0.1	0.0	3.6	0.21	97.95
147.0-148.0	0.1	0.0	3.6	0.18	98.13
148.0-149.0	0.1	0.0	3.6	0.16	98.29
149.0-150.0	0.1	0.0	3.6	0.14	98.43
150.0-151.0	0.1	0.0	3.6	0.13	98.56
151.0-152.0	0.1	0.0	3.6	0.13	98.69
152.0-153.0	0.1	0.0	3.6	0.12	98.80
153.0-154.0	0.1	0.0	3.6	0.12	98.92
154.0-155.0	0.1	0.0	3.6	0.12	99.04
155.0-156.0	0.1	0.0	3.6	0.11	99.15
156.0-157.0	0.1	0.0	3.6	0.09	99.24
157.0-158.0	0.1	0.0	3.6	0.09	99.32
158.0-159.0	0.1	0.0	3.6	0.09	99.41
159.0-160.0	0.1	0.0	3.6	0.07	99.48
160.0-161.0	0.1	0.0	3.6	0.06	99.55
161.0-162.0	0.1	0.0	3.6	0.06	99.61
162.0-163.0	0.1	0.0	3.6	0.06	99.67
163.0-164.0	0.1	0.0	3.6	0.05	99.72
164.0-165.0	0.1	0.0	3.6	0.05	99.77
165.0-166.0	0.1	0.0	3.6	0.04	99.80
166.0-167.0	0.1	0.0	3.6	0.04	99.84
167.0-168.0	0.0	0.0	3.6	0.03	99.87
168.0-169.0	0.0	0.0	3.6	0.02	99.89
169.0-170.0	0.0	0.0	3.6	0.02	99.92
170.0-171.0	0.0	0.0	3.6	0.02	99.94
171.0-172.0	0.0	0.0	3.6	0.01	99.95
172.0-173.0	0.0	0.0	3.6	0.01	99.96
173.0-174.0	0.0	0.0	3.6	0.01	99.97
174.0-175.0	0.0	0.0	3.6	0.01	99.98
175.0-176.0	0.0	0.0	3.6	0.01	99.99
176.0-177.0	0.0	0.0	3.6	0.00	99.99
177.0-178.0	0.0	0.0	3.6	0.00	100.00
178.0-179.0	0.0	0.0	3.6	0.00	100.00
179.0-180.0	0.0	0.0	3.6	0.00	100.00

C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 25
Operator: Jacky

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1800B
Distance: 9.028 m
Humidity: 60%
Inspector: