


ARMOR SERIES | HEXANODE

Armor Series HexaNodes are versatile single-point source 24V RGB or RGBW fixtures that can be used to create a unique pixel display or to highlight architectural details. Program with simple SPI (Serial Peripheral Interface) controls for maximum effects. Each HexaNode module contains six LEDs (add two white LEDs for RGBW) for precise color gradients and smooth transitions. Choose from flat or globe lenses and customize your pixel spacing and quantity.

- Pinpoint lighting for custom façade displays
- RGB at 38 lm/node (all on)
- RGBW (2700K) at 50 lm/node (all on)
- Flat lens with 110°x110° beam angle
- Globe lens with 160°x160° beam angle
- Uses SPI controls
- Custom pixel spacing (starting at 3.94 in./100 mm)
- Replace single modules for easy maintenance
- Daisy chain up to 492 ft (150 m)
- Use with anodized mounting channel (up to 6 ft 6.74 in./2 m)
Powder coating available (extra charge)
- Single mounting clips
- IP67
- 5-year warranty



RoHS

IP67

AVAILABLE COLORS



RGB



RGBW (2700K)



Custom
Pixel Quantities
Per String



Custom
Spacing



Milky
Globe Lens



Clear
Flat Lens

ORDERING GUIDE

Category	Input Voltage	Wattage	Colors	Lens	Node Color	Control
NODE6	24					S
NODE6 - HexaNode	24 - 24 V DC	1.5 - 1.5 W (RGB) 2.0 - 2.0 W (RGBW)	RGB - RGB RGB27 - RGBW (2700K)	CF - Clear Flat Lens GM - Milky Globe Lens	BK - Black BG - Beige	S - SPI

Note:

1. Specify spacing and quantity for custom mounting channel.
2. Be sure to use wire end caps at end of line.

ACCESSORIES:

1. M20E 5-Pin Female to Bare Wire Input Cable
M20CBLFB5PIN1000 (3 ft, 3.3 in. | 1 m)
M20CBLFB5PIN2000 (6 ft, 6.7 in. | 2 m)
M20CBLFB5PIN3000 (9 ft, 10 in. | 3 m)
2. M20E 5-PIN Male to Female Jumper Cable
M20JUMPMF5PIN1000 (3 ft, 3.3 in. | 1 m)
M20JUMPMF5PIN2000 (6 ft, 6.7 in. | 2 m)
M20JUMPMF5PIN3000 (9 ft, 10 in. | 3 m)
3. M20E 5-PIN Power Cable, Single Feed (59 in. | 1.5 m)
M20PYCBL55PIN1500
4. M20E 5-PIN Power Cable, Double Feed (59 in. | 1.5 m)
M20PYCBLD5PIN1500
5. M20E 5-PIN Power & Data Injector Cable (59 in. | 1.5 m)
M20YCBLP5PIN1500
6. M20E Input Cable, RJ45 to Female
M20CBLRJ45F5PIN15000 (49 ft | 15 m)
M20CBLRJ45F5PIN30000 (98 ft | 30 m)
M20CBLRJ45F5PIN50000 (164 ft | 50 m)
7. End Cap
M20EC5PIN
8. Mounting Clip
NODEMC
9. Mounting Channel (up to 78.74 in. | 2 m)
CHNODESV

CONTROLLERS:

1. C4 Extended Controller
Part # for 1 universe model: CTRLPIXEL1
Part # for 2 universe model: CTRLPIXEL2
Part # for 4 universe model: CTRLPIXEL4
Part # for 8 universe model: CTRLPIXEL8
2. C4 Live Controller
Part # for 4 universe model: CTRLPIXELLIVE4
Part # for 8 universe model: CTRLPIXELLIVE8
Part # for 12 universe model: CTRLPIXELLIVE12
Part # for 16 universe model: CTRLPIXELLIVE16
Part # for 24 universe model: CTRLPIXELLIVE24
3. PxLNet Controller
Part #: CTRLPIXEL96


DRIVERS:

1. 24V 60W Non-dimmable Driver
Part #: DRVW2460
2. 24V 96W Non-dimmable Driver
Part #: DRVW2496

SPECIFICATIONS / DIMENSIONS / LUMEN DATA

Operating Voltage	24 V DC	
Color / Temperature	RGB	RGBW (2700K)
Power Consumption	1.5 W	2.0 W
Lumens per Node	38 lm	50 lm
LEDs per Node	6 LEDs	8 LEDs (6x RGB + 2x White)
LED Beam Angle	Clear Flat Lens: 110°x110° Milky Globe Lens: 160°x160°	
Max Run Length	475 ft 8.66 in. (145 m)	
LED Pitch	Customizable, starting from 3.94 in. (100mm)	
Max. Daisy Chain Connections	492 ft 1.51 in. (150 m) including extension cables	
Storage Temperature	-22° F to 176° F (-30° C to 80° C)	
Operating Temperature	-4° F to 158° F (-20° C to 70° C)	
Connector	5-pin Connector	
Lens Options	Clear Flat Lens Cap, Milky Globe Lens Cap	
Protection Rating	IP67	
Mounting Options	Screw-in Mounting Base, Mounting Channel	
Certifications	ETL, CE, RoHS	
Fixture Color Finish	Black, Beige	
Dimensions (W x H)	1.65 x 0.87 in. (42 x 22 mm)	
Weight per Node	0.64 oz. (18 gm)	
Warranty	5 Years	


DIMENSIONS




MOUNTING HARDWARE

MOUNTING CHANNEL (PART #: CHNODESV)

Mounting Channel length up to 78.74 in. (2 m)




SCREW-IN MOUNTING BASE (PART #: NODEMC)



ACCESSORIES


M20E 5-PIN MALE TO FEMALE JUMPER CABLE

Part #:
M20JUMPMF5PIN1000 (3 ft 3.3 in. | 1 m)
M20JUMPMF5PIN2000 (6 ft 6.7 in. | 2 m)
M20JUMPMF5PIN3000 (9 ft 10 in. | 3 m)



END CAP


Part #: M20EC5PIN



ACCESSORIES


M20E 5-PIN POWER CABLE, SINGLE FEED

Part #:
M20PYCBL5PIN1500 (59 in. | 1.5 m)




M20E 5-PIN POWER CABLE, DOUBLE FEED

Part #:
M20PYCBLD5PIN1500 (59 in. | 1.5 m)



M20E 5-PIN POWER & DATA INJECTOR CABLE


Part #:
M20YCBLP5PIN1500 (59 in. | 1.5 m)



M20E 5-PIN INPUT CABLE, RJ45 TO FEMALE

Part #:
M20CBLRJ45F5PIN15000 (49 ft | 15 m)
M20CBLRJ45F5PIN30000 (98 ft | 30 m)
M20CBLRJ45F5PIN50000 (164 ft | 50 m)


RJ45		
1	Orange/White	Data +
2	Orange	Data -
3	Green/White	Not used
4	Blue	Not used
5	Blue/White	Not used
6	Green	Not used
7	Brown/White	GND
8	Brown	GND




M20E 5-Pin Female	
1	GND
2	Data -
3	Data +
4	NC

CONNECTION

Basic - Power from middle




Basic - Power from beginning



CONNECTION

Advanced



Model	Voltage	A	B @25fps	B @50fps	Bit
HexaNode RGB	24V	102	1020	510	8
HexaNode RGBW	24V	102	768	384	8

Default nodes per string: 34 nodes (Customizable)

Default spacing: 7.87 in. / 200 mm (Customizable)