

PRO LYTE 4


Great for channel letters, box signs and accent lighting, PRO Lyte 4 features quad-LED modules in a 24V true IC constant current design that maintains brilliant light across each string. With an IP67 rating and a seven-year warranty, PRO Lyte 4 allows speedy installation with a convenient continuous release liner for the mounting tape. Spaced at 12.01 in. (305 mm), PRO Lyte 4 generates up to 170 lm/W in sign-bright 6500K. Available in three CCTs (5000K, 6500K, 7100K).

Applications:

- Channel letters
- Box and cabinet signs
- Accent and cove lighting



CONTINUOUS RELEASE LINER
REDUCES INSTALLATION TIME BY 30%



24V DC



7 YEAR LIMITED WARRANTY



ONWhite[®]
COLOR CONSISTENCY



VERSALENZ[®]
ADVANCED OPTICS



CONSTANT CURRENT



UV RESISTANT



50,000 HRS
L70 LIFETIME





ORDERING GUIDE

Part Number	White Color Temperatures & Colors	LEDs per Module	Module Spacing (in. / mm)	Number of Modules		Nominal Light Output (lm)		
				Per Foot	Per Meter	Per Module	Per Foot	Per Meter
LS-PL4-71K-B305-A	7100K	4	12.01 / 305	1	3.28	245	245	803
LS-PL4-65K-B305-A	6500K	4	12.01 / 305	1	3.28	245	245	803
LS-PL4-50K-B305-A	5000K	4	12.01 / 305	1	3.28	245	245	803

PRODUCT RATINGS

Luminous Efficacy	170 lm/W
Wattage per Module	1.44 W/module
Input Voltage	24 V DC
IC Design	Constant Current
Lumen Drop	< 3%
Ingress Protection	IP67
Beam Angle	176
Molding Material	ABS
Operating Temperature	-13° - +140° F (-25° - +60° C)
L70 Lifetime @ 60° C	50,000 Hours
Warranty	7 Year Limited Warranty
Dimensions (L x W x H)	3.03 x 0.77 x 0.4 in. (77 x 19.56 x 10.16 mm)

LUMINOUS INTENSITY DISTRIBUTION



MODULE DIMENSIONS

Part Number	Length (in/mm)	Width (in/mm)	Height (in/mm)
LS-PL4-XXK-B305-A	3.03/77	0.77/19.56	0.4/10.16

POWER SUPPLY LOADING

Module Type	per 100W			
	Max. # of Modules Per String	Total # of Modules	Total # of Feet	Total # of Meters
LS-PL4-XXK-B305-A	70	64	64	19.512

LAYOUT GUIDE*

Channel Depth (in.)	Single Row		Multiple Rows		Channel Depth (mm)	Single Row		Multiple Rows	
	Max. Stroke	Module Spacing	Row Spacing	Module Spacing		Max. Stroke	Module Spacing	Row Spacing	Module Spacing
3	12	12.01	10	12.01	75	300	305	250	305
4	14	12.01	12	12.01	100	350	305	300	305
5	18	12.01	14	12.01	125	450	305	350	305
6	24	12.01	18	12.01	150	600	305	450	305
8	34	12.01	22	12.01	200	850	305	550	305

*Module spacing is defined by 7328 white sign face material

SHIPPING INFORMATION

Module Type	Specs	Packaging Quantity		
		Per Bag	Per Box	Per Carton
LS-PL4-XXK-B305-A	Modules	70	420	840

Carton Dimensions			Carton Weight	Box Dimensions			Box Weight
L	W	H		L	W	H	
20.47	14.57	10.24	19.8 kg (43.65 lbs)	13.78	9.84	9.06	9.2 kg (20.28 lbs)
520	370	260		350	250	230	in. mm

DIMENSION DRAWING



1. UL ONLY - These products are only suitable for connection to a UL rated Class 2 power source rated 12 Volt or less.
2. UL ONLY - These products are intended for use only when connected to a power source that complies with UL rated Class 2 voltage and energy limited circuit.
3. UL ONLY - When these units are connected to a UL rated Class 2 circuit, they are not to draw a total wattage of greater than the secondary or output rating of the UL rated Class 2 power supply.
4. These products may be secured in place in the end product by any means available.
5. These products are suitable for use in dry and damp locations. Not suitable for wet or submersed applications.