GEN LED
ACOLYTE®
Architectural Lighting Solutions

LUTRON®
Athena Wireless Nodes

AcolyteLED.com

# 94W
# Athena Wireless
# Compatible
# Drivers

**94W Athena Wireless Compatible 1 Channel Driver**
For use with dimmable Static White CCTs and Static Colors
Part No.: DRVW2494ATH1CH
L x W x H: 8.08 x 4.45 x 1.57 in. (205.4 x 113 x 40 mm)

**94W Athena Wireless Compatible 2 Channel Driver**
For use with Variable White (tune for CCT and warmth)
Part No.: DRVW2494ATH2CH
L x W x H: 9.49 x 4.92 x 1.57 in. (241 x 125 x 40 mm)

cULus LISTED    CE    FC    SAA    RoHS    SELV

These UL Listed constant voltage Class 2 intelligent LED drivers provide high efficiency and great heat dissipation with dimmable 24 V output. Offering wireless compatibility with the Lutron Athena control system, they feature an enclosure with isolated wire connections. With 120-277 VAC input voltage, these drivers are suitable for LED lighting in commercial, industrial and residential applications.

## FEATURES

• Constant voltage dimmable driver
• Lutron Athena Wireless compatibility
• High efficiency and high power factor
• Short circuit and constant power protection
• Overtemperature and overload protection
• Lightning surge protection
• Lumen output compensation
• Dimming range from 100% to 1%
• 6-year warranty



**NOTE:** Lutron specifies that Athena Wireless Nodes should be installed within 25 ft (7.62 m) of two or more Athena Wireless Nodes. Walls, ceilings and some signals may interfere with Athena and reduce this distance.