

Light efficiency:

73 Lumen/Watt

Light quality:

CRI: 94.7

Color temperature:

3487 K

Output: 720 lm

Peak: 213 cd

Power: 9.9 W

PF: 1.0



Tracking number: [n/a](#)

Product name:

PC10.5MRBOVWDR206.0VW-ALL ON

Item number:

Date and time:


2024/10/14 14:32:18

Operator:

Nick

Description:

DIAMETER 40.6MM,LENGTH 500MM




CIE 1931

x: 0.396



y: 0.363

Spectra




Power


Voltage: 24.0 V  
Current: 0.413 A  
Frequency: 0 Hz



TM-30: 93.0



CRI: 94.7 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
93.8	95.2	97.2	93.6	94.2	91.3	95.0	97.0	95.1	92.7	89.3	84.2	93.3	97.7	94.8


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
95.9	95.6	92.1	94.6	92.8	91.5	94.0	93.9	95.4	94.5	89.0	89.3	93.9	90.7	91.6	89.8

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
97.1	99.1	87.6	92.0	99.1	93.3	92.4	96.7	97.6	94.7	95.3	95.3	95.3	94.9	96.8

CQS: 94.4



## Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3487 K	94.7	95.1	93.0	104.9	94.4	0.396	0.363	0.241	0.332	-0.0104







**Rf 93.0**

Fidelity index Rf


**Rg 104.9**

Gamut index Rg

Hue Bin	R <sub>f</sub>	Shifts (%)	
		Chroma	Hue
1	96	-1%	0%
2	96	0%	2%
3	92	2%	4%
4	95	1%	2%
5	93	1%	2%
6	92	5%	1%
7	94	3%	0%
8	94	3%	-1%
9	95	2%	1%
10	94	0%	3%
11	89	4%	7%
12	89	5%	2%
13	94	4%	-2%
14	91	6%	-3%
15	92	3%	-3%
16	90	2%	-6%



## Beam details



### Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
213lx	53lx	24lx	13lx	9lx	6lx	4lx	3lx	3lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx
19.7fcd	4.9fcd	2.2fcd	1.2fcd	0.8fcd	0.5fcd	0.4fcd	0.3fcd	0.2fcd	0.2fcd	0.2fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0fcd

### Intensities in 0° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
213	210	202	188	170	149	127	104	83	64	46	32	20	12	6	3	2	1	1	1
100%	99%	95%	88%	80%	70%	60%	49%	39%	30%	22%	15%	9%	6%	3%	2%	1%	1%	1%	1%

### Intensities in 90° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
213	209	199	183	162	138	110	79	48	20	3	1	1	1	1	1	1	1	1	1
100%	99%	94%	86%	76%	65%	52%	37%	23%	9%	1%	0%	0%	0%	0%	0%	1%	1%	1%	1%

### Intensities in 180° c-plane


0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
213	210	202	188	170	149	127	104	83	64	46	32	20	12	6	3	2	1	1	1
100%	99%	95%	88%	80%	70%	60%	49%	39%	30%	22%	15%	9%	6%	3%	2%	1%	1%	1%	1%

### Intensities in 270° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
213	209	199	183	162	138	110	79	48	20	3	1	1	1	1	1	1	1	1	1
100%	99%	94%	86%	76%	65%	52%	37%	23%	9%	1%	0%	0%	0%	0%	0%	1%	1%	1%	1%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
116.8°	189.3°	222.9°	67.5%	45.4%

**iso-candela diagram**




10%	21 cd
20%	43 cd
30%	64 cd
40%	85 cd
50%	106 cd
60%	128 cd
70%	149 cd
80%	170 cd
90%	191 cd

Conditions:

Number of c-planes: 24

Candela at center: 213 cd

**iso-lux diagram**



3%	63.8m lx
5%	0.106 lx
10%	0.213 lx
30%	0.638 lx
50%	1.06 lx

Conditions:

Number of c-planes: 24

Lux at center: 2.13 lx

*Lux distribution on a surface  
when lamp is mounted at 10  
meters from the surface.*

Glare evaluation according to UGR


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X      Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	17.4	18.7	17.8	19.1	19.4	18.1	19.3	18.4	19.7	20.1
	3H	19.0	20.3	19.5	20.7	21.0	19.4	20.7	19.9	21.1	21.4
	4H	19.8	21.0	20.3	21.4	21.8	20.0	21.2	20.5	21.6	22.0
	6H	20.6	21.6	21.0	22.0	22.5	20.4	21.5	20.9	21.9	22.4
	8H	20.9	22.0	21.4	22.4	22.9	20.6	21.6	21.0	22.0	22.5
	12H	21.2	22.3	21.7	22.7	23.2	20.6	21.7	21.1	22.1	22.7
4H	2H	18.0	19.2	18.5	19.6	20.0	18.5	19.7	19.0	20.1	20.5
	3H	19.9	20.9	20.3	21.3	21.9	20.1	21.2	20.6	21.6	22.1
	4H	20.7	21.8	21.3	22.2	22.8	20.7	21.8	21.3	22.2	22.8
	6H	21.6	22.5	22.2	23.0	23.5	21.2	22.1	21.8	22.6	23.1
	8H	22.1	22.9	22.6	23.3	23.9	21.4	22.2	22.0	22.7	23.2
	12H	22.5	23.1	23.0	23.7	24.3	21.5	22.2	22.1	22.8	23.3
8H	4H	21.0	21.8	21.6	22.3	22.8	21.0	21.8	21.6	22.3	22.8
	6H	22.1	22.8	22.7	23.3	24.0	21.7	22.3	22.3	22.9	23.5
	8H	22.7	23.3	23.3	23.9	24.6	21.9	22.5	22.6	23.1	23.9
	12H	23.3	23.7	23.9	24.3	25.1	22.2	22.6	22.8	23.3	24.0
12H	4H	21.0	21.7	21.6	22.3	22.8	21.1	21.7	21.6	22.3	22.9
	6H	22.2	22.8	22.8	23.4	24.1	21.8	22.4	22.4	23.0	23.7
	8H	22.8	23.3	23.5	23.9	24.6	22.1	22.6	22.8	23.2	23.9
Variation of the observer position for the luminaire distance S											
S = 1.0H		0.1 / -0.1					0.1 / -0.1				
S = 1.5H		0.1 / -0.1					0.3 / -0.3				
S = 2.0H		0.3 / -0.3					0.7 / -0.7				
CIE 117-1995. Corrected glare indices referring to 720 lm total luminous flux											

## Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	117	117	117	117	114	114	114	114	107	107	107	102	102	102	96	96	96	93
1	105	100	95	90	102	97	92	88	91	88	84	86	83	81	82	79	77	74
2	95	86	79	72	92	84	77	71	79	73	68	75	70	66	71	67	63	61
3	86	75	66	60	83	73	65	59	69	62	57	65	60	55	62	57	53	51
4	79	66	57	50	76	65	56	49	61	54	48	58	52	47	55	50	45	43
5	73	59	50	43	70	58	49	42	55	47	41	52	45	40	49	44	39	37
6	67	53	44	37	65	52	43	37	49	42	36	47	40	35	45	39	34	32
7	62	48	39	33	60	47	38	32	45	37	32	43	36	31	41	35	30	28
8	58	44	35	29	56	43	35	29	41	34	28	39	33	28	38	32	27	25
9	54	40	32	26	52	39	31	26	38	30	25	36	30	25	35	29	24	23
10	50	37	29	24	49	36	29	23	35	28	23	33	27	23	32	26	22	20

LAMPS (number of lamps)

## Luminaire budgetary diagram



## Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
{LUM0-10}	57.8 lm	87.6 lm	106 lm	111 lm	103 lm	85.6 lm	62.3 lm	39.3 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
22.6 lm	12.3 lm	6.08 lm	2.78 lm	1.39 lm	0.866 lm	0.577 lm	0.366 lm	0.131 lm

LCS table

BUG rating:	B0 U2 G1	
Forward light	Lumens	Lumens %
Low(0-30):	82.5	11.5%
Medium(30-60):	159.5	22.2%
High(60-80):	74	10.3%
Very high(80-90):	19.9	2.8%
Back light		
Low(0-30):	82.5	11.5%
Medium(30-60):	159.5	22.2%
High(60-80):	74	10.3%
Very high(80-90):	19.9	2.8%
Uplight		
Low(90-100):	23	3.2%
High(100-180):	25	3.5%

LCS graph

