



ACOLYTE®
Architectural Lighting Solutions



Black or White housing

NANO FLEX DUAL-BENDING WALL GRAZERS

The Nano Flex is a large 24V flexible silicone grazer tube. Available in three dimmable Static White CCTs and nine beam angle options, this IP67 grazer is compatible with 0-10V, ELV/MLV and DMX controls. Dual bending capabilities (side- and top-bending!) make Nano Flex an amazing solution for complex grazer applications in hospitality, landscape and architectural settings. Choose from end, side or bottom power feed.



RoHS


IP67

IK07


FEATURES:

- 7.6 W/ft (25 W/m)
- 800 lm/ft (2625 lm/m) at 4000K
- 3 Static White CCTs (2700K, 3000K, 4000K)
- Use 0-10V, ELV/MLV, DMX or Casambi controls
- 7 LEDs/ft (24 LEDs/m)
- 1.64 in. (41.67 mm) LED spacing
- 16 ft 4.85 in. (5 m) max. length (single feed)
- 5.9 in. (150 mm) minimum bending radius
- Beam angles: 10x10°, 15x15°, 20x20°, 25x25°, 30x30°, 40x40°, 50x50°, 25x50°, 45xAsymmetric 30°
- IP67 rating for dry, damp and wet locations
- IK07
- Available in black or white housing
- Use with mounting clip, mounting channel, curved mounting channel, tiltable stand


MOUNTING OPTIONS



Mounting Clip



Mounting Channel



Curved Mounting Channel



Tiltable Stand

COLOR TEMPERATURES




2700K 3000K 4000K

HOUSING COLORS




Black White

BEAM ANGLES



10x10° 15x15° 20x20° 25x25° 30x30° 40x40° 50x50° 25x50° 45xAsymmetric 30°



Tiltable 45° - 90°