

0-10V/ELV/MLV 3-IN-1 DIMMABLE DRIVERS

These high-efficiency universal constant voltage output drivers provide smooth, flicker-free LED dimming. They are compatible with 0-10 V, ELV (reverse phase), TRIAC or MLV (forward phase), and PWM dimming and feature short circuit, overload and overcurrent protections. With a sturdy metal enclosure, these Class 2 output drivers are rated IP65 for dry, damp and wet locations.

- 60W or 96W drivers
- 24 VDC, 120-277 VAC
- Dimming: 0-10V, TRIAC, ELV/MLV, PWM
- Flicker free
- Short circuit, overload, overcurrent protection with auto recovery
- Class 2 output
- IP65 rated for dry, damp and wet locations
- Metal case
- UL Listed
- 5-year warranty



RoHS

Class 2

IP65

ORDERING GUIDE

Category	Voltage	Wattage	Dimming Option
DRVW	24		TRIO10
DRVW - Waterproof Driver	24 - 24 VDC Output	60 - 60 W 96 - 96 W	TRIO10 - 0-10V, ELV, MLV


SPECIFICATIONS

Wattage	60 W	96 W
Input Voltage	120-277 VAC	120-277 VAC
Input Current	0.34-0.7 A max.	0.5-1.1 A max.
Inrush Current Ipeak	14 A @ 277 VAC, 15 A @ 277 VAC	18 A @ 120 VAC, 40 A @ 277 VAC
Frequency Range	50/60 Hz	50/60 Hz
THD	< 15% @ 120 VAC, < 25% @ 277 VAC	< 5% @ 120 VAC, < 10% @ 277 VAC
Efficacy	87% @ 120 VAC, 89% @ 277 VAC (full load)	≥ 86% @ 120 VAC, ≥ 88% @ 277 VAC (full load)
PF	≥ 0.98 @ 120 VAC, 0.9 @ 277 VAC (full load)	≥ 0.98 @ 120 VAC, 0.95 @ 277 VAC (full load)
Output Voltage	24 VDC	24 VDC
Ripple	< 1%	< 1%
Output Current	2.5 A	4 A
Protection	Short circuit, overload, overcurrent protection with auto recovery	
PWM Frequency	4 kHz	4 kHz
Dimming Type	0/1-10 V, Potentiometer, PWM, Triac/ELV/MLV (@ 120 VAC, 60 Hz)	
Dimming Range	0-10 V: 0.5-100%, Triac/ELV/MLV: 1-100%	0-10 V: 0.5-100%, Triac/ELV/MLV: 1-100%
Channel	1	1
Flicker	Flicker free	Flicker free
Operating Temperature	-4 – 140 °F (-20 – 60 °C)	-4 – 140 °F (-20 – 60 °C)
Storage Temperature	-40 – 185 °F (-40 – 85 °C)	-40 – 185 °F (-40 – 85 °C)
IP Rating	IP65 for dry, damp and wet locations	IP65 for dry, damp and wet locations
Lifetime	50,000 hours @ tc 185 °F (85 °C)	50,000 hours @ tc 176 °F (80 °C)
Surge Protection	L-N: 2.5 kV, L-N-PG: 2.5 kV	L-N: 2.5 kV, L-N-PG: 2.5 kV
Dimensions (LxWxH)	9.61 x 4.17 x 1.63 in. (244 x 106 x 41.5 mm)	9.61 x 4.17 x 1.63 in. (244 x 106 x 41.5 mm)
Casing	Metal	
Safety Standard	UL8750, UL1310, IEC 61000-4-2-3-4-5-6-8-11	
Warranty	5 years	


Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

WIRING DIAGRAM - 60 W & 96 W


0-10 V



TRIAC/ELV/MLV



DIMENSIONS - 60 W & 96 W



REV.18SEP2025

GLOBAL HQ

320 Murray Hill Pkwy
East Rutherford, NJ 07073
U.S.
T: (+1) 212 629 6830
E: Sales-US@GENLEDBrands.com

EUROPEAN HQ

Hogeweyselaan 119
1382 JK Weesp
Netherlands
T: (+31) 346 235 000
E: SalesEurope@GENLEDBrands.com

MEINA HQ

PO Box 371378, #823, Building 4EA
Dubai Airport Free Zone
Dubai, UAE
T: (+971) 4 701 7901
E: SalesMEINA@genledbrands.com

ASIA-PACIFIC HQ

Room 402, Building D
Shenshi Tongchuang Science and Technology Park
No. 16 Hongyin Road
Xingqiang Community, Xinhua Street
Guangming District, Shenzhen, China 518107
T: (+86) 755 8529 0710
E: Sales-Pacific@GENLEDBrands.com