

NANO FLEX

Nano Flex is a large 24V flexible silicone grazer tube. Available in three dimmable Static White CCTs and nine beam angle options, this IP67 grazer is compatible with 0-10V, ELV/MLV, DMX or Casambi controls. Or select our special pixel programmable Nano Flex model and use SPI controls to create unique patterns and light fading sequences. Dual bending capabilities (side- and top-bending!) make any Nano Flex an amazing solution for complex grazer applications in hospitality, landscape or architectural settings. Choose from end, side or bottom power feed.

- 7.6 W/ft (25 W/m)
- 3 Static White CCTs (2700K, 3000K, 4000K)
- 800 lm/ft (2625 lm/m) at 4000K
- Choose from 0-10V, ELV/MLV, DMX or Casambi controls
OR use SPI controls with our pixel models
- Programmable pixels: 6 LEDs/9.84 in. (250 mm)
- 1.64 in. (41.67 mm) LED spacing
- 16 ft 4.85 in. (5 m) max. length (single feed)
- 5.9 in. (150 mm) minimum bending radius
- Beam angles: 10x10°, 15x15°, 20x20°, 25x25°, 30x30°, 40x40°, 50x50°, 25x50°, 45xAsymmetric 30°
- Available in white or black housing
- Use with mounting clip, mounting channel, curved mounting channel, tiltable stand



ORDERING GUIDE

Category	CRI	IP Rating	Wattage	CCT	Beam Angles	Housing Color	Power Feed	Control*
NANOFLEX	80	67	7.6					
NANOFLEX - Nano Flex	80 - 80+ CRI	67 - IP67	7.6 - 7.6 W/ft (25 W/m)	27 - 2700K	10 - 10x10°	WH - White	B - Bottom Feed	S - SPI
				30 - 3000K	15 - 15x15°	BK - Black	S - Side Feed	
				40 - 4000K	20 - 20x20°		E - End Feed	
					25 - 25x25°			
					30 - 30x30°			
					40 - 40x40°			
					50 - 50x50°			
					2550 - 25x50°			
					45A30 - 45xAsymmetric 30°			

* For SPI models only

ACCESSORIES (see page 2 for details)

1. Mounting Clip

Recommended for curved applications
Part #: NANOFLEXCLIP

3. Curved Mounting Channel

Recommended for curved applications
Part #: NANOFLEXCHANNELS


2. Mounting Channel

Recommended for all straight run applications
Part #: NANOFLEXCHANNEL


4. Tiltable Stand

Use with mounting clips or mounting channels
Part #: NANOFLEXTILTSTAND

AVAILABLE COLOR TEMPERATURES



AVAILABLE BEAM ANGLES



USAGE GUIDELINES

Nano Flex grazers cannot be cut in the field. All custom cuts and connections for these models must be performed at the factory to ensure waterproofing standards are met. Any modification of the waterproofing will result in a voided warranty.

Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.


SPECIFICATIONS

Operating Voltage	24 VDC
Power Consumption	7.6 W/ft (25 W/m)
Protection Rating	IP67
Impact Rating	IK07
Color Temperature	2700K, 3000K, 4000K
Control	0-10V, ELV/MLV, DMX, DALI and CASAMBI controls for static white OR SPI controls for SPI version
IC Code (for SPI only)	UCS2904
LED Quantity	7 LEDs/ft (24 LEDs/m)
LED Spacing	1.64 in. (41.67 mm)
Lumens	800 lm/ft (2625 lm/m) @ 4000K
Efficacy	105 lm/W @ 4000K
Beam Angle	10x10°, 15x15°, 20x20°, 25x25°, 30x30°, 40x40°, 50x50°, 25x50°, 45xAsymmetric 30°
Storage Temperature	-4 — 140 °F (-20 — 60 °C)
Operating Temperature	-4 — 113 °F (-20 — 45 °C)
Max Run Length	16 ft 4.85 in. (5 m)
Incremental Length	9.84 in. (250 mm) NOT FIELD CUTTABLE
Minimum Bend Radius	5.9 in. (150 mm)
CRI	80+ CRI
Lifetime (L70 reported)	50,000 hours
Warranty	5 years

MOUNTING ACCESSORIES


1. Mounting Clip

Part #: NANOFLEXCLIP




2. Mounting Channel

Length up to 39.4 in. (1 m)
Part #: NANOFLEXCHANNEL




3. Curved Mounting Channel

Length up to 39.4 in. (1 m)
Part #: NANOFLEXCHANNELS




4. Tiltable Stand

Use with mounting clips or channels
Part #: NANOFLEXTILTSTAND




DIMENSIONS & POWER FEED OPTIONS


BOTTOM FEED (MOLDED END CAP)



SIDE FEED WITH MOLDED END CAP




END FEED




WIRING DIAGRAMS


0-10V




MLV / ELV



DMX



SPI



WIRE COLORS

STATIC WHITE
Red Wire (+) Positive
Black Wire (-) Negative

PIXEL (SPI)
Red Wire (+) Positive
Black Wire (-) Negative
White Wire (SPI) Data

REV27JAN2026

GLOBAL HQ

320 Murray Hill Pkwy
East Rutherford, NJ 07073
U.S.
T: (+1) 212 629 6830
E: Sales-US@GENLEDBrands.com

EUROPEAN HQ

Hogeweyselaan 119
1382 JK Weesp
Netherlands
T: (+31) 346 235 000
E: SalesEurope@GENLEDBrands.com

MEINA HQ

PO Box 371378, #823, Building 4EA
Dubai Airport Free Zone
Dubai, UAE
T: (+971) 4 701 7901
E: SalesMEINA@genledbrands.com

ASIA-PACIFIC HQ

Room 402, Building D
Shensi Tongchuang Science and Technology Park
No. 16 Hongyin Road
Xingqiang Community, Xinhua Street
Guangming District, Shenzhen, China 518107
T: (+86) 755 8529 0710
E: Sales-Pacific@GENLEDBrands.com