


## SIMPLY CLEAN™ RECESSED FIXTURE SC15L

SC15L is a small Simply Clean mud-in aluminum channel extrusion. Use a milky lens or choose the frosted lens with a grille louver or honeycomb louver for enhanced glare control. Pair SC15L with our RibbonLyte to create complete custom fixtures.

- Recessed mud-in profile
- Sold by the foot. Factory or field cuttable to any length.
- Milky lens with 110x111° beam angle
- Frosted lens with Grille or Honeycomb louver
- UGR (Grille louver): < 16.2  
UGR (Honeycomb louver): < 6.4  
(see chart for beam angle with louvers)
- For interior applications only



RoHS

IP20

Declare.



### HOUSING FINISHES




Silver    Black\*    White\*  
Standard

\*Additional fee applies


### LENS / LOUVER OPTIONS



**Milky Lens (PC)**  
80% Light Transmission



**Grille Louver with Frosted Lens (PC)**  
75% Light Transmission  
UGR < 16.2




**Honeycomb Louver with Frosted Lens (PC)**  
75% Light Transmission  
UGR < 6.4


### AVAILABLE COLORS & COLOR TEMPERATURES



### DIMENSIONS



**Width:** 2.17 in. (55 mm)  
**Height:** 0.5 in. (12.8 mm)  
**Inside Width:** 0.52 in. (13.2 mm)



**Note:** This channel does not require mounting clips. Please see our installation guide for instructions.

Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

## SPECIFICATIONS


|                                   |                                                                                                                                                                                                                                        |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Beam Angle</b>                 | Milky Lens: 110x111°, Grille Louver with Frosted Lens: 81x80°, Honeycomb Louver with Frosted Lens: 49x53°                                                                                                                              |
| <b>Lens / Louver Type</b>         | Milky Lens (PC), Grille Louver with Frosted Lens (PC), Honeycomb Louver with Frosted Lens (PC)                                                                                                                                         |
| <b>UGR (Unified Glare Rating)</b> | UGR (Grille Louver): < 16.2, UGR (Honeycomb Louver): < 6.4                                                                                                                                                                             |
| <b>Operating Voltage</b>          | 24 V                                                                                                                                                                                                                                   |
| <b>Dimming</b>                    | MLV / 0-10 Volt / ELV / DALI / DMX / CASAMBI                                                                                                                                                                                           |
| <b>Operating Temperature</b>      | -40 — 158 °F (-40 — 70 °C)                                                                                                                                                                                                             |
| <b>Colors</b>                     | 1800K, 2000K, 2200K, 2400K, 2700K, 3000K, 3500K, 4000K, 6000K, Red, Amber, Green, Blue, Pixel RGB, RGBW, RGBWW, RGBA, Variable White, Warm Dim (1800K, 2000K, 2200K, Pixel RGB only available in IP20)                                 |
| <b>CRI</b>                        | 90+ CRI (for Static White LEDs only)                                                                                                                                                                                                   |
| <b>Lamp Life</b>                  | L70 at 50,000 hours                                                                                                                                                                                                                    |
| <b>MacAdam ellipse (SDCM)</b>     | 1-Step Binning (for Static White LEDs only)                                                                                                                                                                                            |
| <b>Certifications</b>             | UL Listed UL 2108 Issued: 2004/02/27 Ed: 1 Rev: 2014/02/24 Low Voltage Lighting Systems CSA C22.2#9.0 Issued: 1996/06/01 Ed: 1 (R2011) General Requirements for Luminaires; with Gen. Inst. 1: 1997, Gen Inst. 2: 1998. ROHS compliant |
| <b>Recessed Cutout Width</b>      | 0.59 in. (15 mm)                                                                                                                                                                                                                       |
| <b>Depth In Wall</b>              | 0.39 in. (9.8 mm)                                                                                                                                                                                                                      |
| <b>Length</b>                     | Sold by the foot. Factory cuttable to any length. Max individual length of each piece is 78.7 in. (2 m), but the fixture can be installed end-to-end to create long continuous recessed fixtures.                                      |
| <b>Visible Width</b>              | 0.59 in. (15 mm)                                                                                                                                                                                                                       |

## ACCESSORIES

End Cap without Hole (Part #: CHSC15LECNH)

End Cap with Hole (Part #: CHSC15LECH)

Material: ABS



## STATIC WHITE SERIES 2 RIBBONLYTE SPECIFICATIONS, COMPATIBILITY & DELIVERED LUMEN OUTPUT

| RibbonLyte Type       | Wattage  | CCT   | Incremental Length | LED Pitch               | Max. Length (IP20) | <b>A</b> Delivered Lumen at 3000K with Milky Lens (PC) |      | Compatibility with SC15L Channel |      |      |      | Diode Visibility<br>Visible = Y<br>Not Visible = N |
|-----------------------|----------|-------|--------------------|-------------------------|--------------------|--------------------------------------------------------|------|----------------------------------|------|------|------|----------------------------------------------------|
|                       |          |       |                    |                         |                    | lm/ft                                                  | lm/m | IP20                             | IP65 | IP68 | IP69 |                                                    |
| Static White Series 2 | 3.0 W/ft | 3000K | 1.97 in. (50 mm)   | 48 LEDs/ft (160 LEDs/m) | 36 ft (11 m)       | 234                                                    | 769  | ✓                                | ✓    |      |      | Y                                                  |

Lumen Multiplier by CCT (Static White Series 2 RibbonLyte)

| CCT (3.0 W/ft)      | 1800K | 2000K | 2200K | 2400K | 2700K | 3000K | 3500K | 4000K | 6000K |
|---------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| <b>B</b> Multiplier | 0.67  | 0.79  | 0.85  | 0.91  | 0.97  | 1.00  | 1.03  | 1.00  | 1.08  |

Lumen Multiplier by Wattage (Static White Series 2 RibbonLyte)

| Wattage             | 0.75 w/ft | 1.5 w/ft | 2.2 w/ft | 3.0 w/ft | 4.4 w/ft | 5.0 w/ft | 6.0 w/ft |
|---------------------|-----------|----------|----------|----------|----------|----------|----------|
| <b>C</b> Multiplier | 0.26      | 0.51     | 0.73     | 1.00     | 1.45     | 1.60     | 1.96     |

**A** x **B** x **C** = Lumen Output

Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

## ORDERING GUIDE

**STEP 1** Complete Channel Part Number

| CHANNEL                                        | LENS / LOUVER                                                                                                          | HOUSING COLOR                                                                                                                             |
|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| CHSC15L                                        |                                                                                                                        |                                                                                                                                           |
| CHSC15L - Simply Clean™ SC15L Recessed Channel | <b>M</b> - Milky Lens<br><b>GF</b> - Grille Louver with Frosted Lens<br><b>HF</b> - Honeycomb Louver with Frosted Lens | <b>SV</b> - Silver (default)<br><b>BK</b> - Black*<br><b>WH</b> - White*<br>* Additional fee applies<br>Consult factory for custom colors |

**STEP 2** Complete RibbonLyte Part Number

| CATEGORY        | CRI                                                                         | RIBBON TYPE & IP RATING                                                                                                                                                                                                        |                                                                                                                                                                                                |                                                                                                     |
|-----------------|-----------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| RB              |                                                                             |                                                                                                                                                                                                                                |                                                                                                                                                                                                |                                                                                                     |
| RB - RibbonLyte | <b>0</b> - Static Color, Color Changing<br><b>90</b> - 90+ CRI Static White | <b>SWS220</b> - Static White Series 2 IP20<br><b>SWS265</b> - Static White Series 2 IP65<br><b>SCS220</b> - Static Color Series 2 IP20<br><b>SCS265</b> - Static Color Series 2 IP65<br><b>LINEA20</b> - Linea RibbonLyte IP20 | <b>RGBADD</b> - Pixel RGB IP20<br><b>RGBWW20</b> - RGBWW 5-in-1 IP20<br><b>RGBWS220</b> - RGBW Series 2 IP20<br><b>RGBAS220</b> - RGBA Series 2 IP20<br><b>XACTA20</b> - Xacta RibbonLyte IP20 | <b>VWS220</b> - VW Series 2 IP20<br><b>VWS265</b> - VW Series 2 IP65<br><b>WD20</b> - Warm Dim IP20 |

**NOTE:** To ensure waterproofing standards are met, IP65 RibbonLyte can NOT be cut in the field.

## WATTAGE

|                                                                                   |
|-----------------------------------------------------------------------------------|
| <b>0.75</b> - 0.75 W/ft (2.46 W/m - Static White, Static Color)                   |
| <b>1.0</b> - 1.0 W/ft (3.3 W/m - Variable White)                                  |
| <b>1.5</b> - 1.5 W/ft (4.9 W/m - Static White, Static Color)                      |
| <b>2.2</b> - 2.2 W/ft (7.2 W/m - Static White, Static Color)                      |
| <b>2.4</b> - 2.4 W/ft (8 W/m - Static White Linea)                                |
| <b>3.0</b> - 3.0 W/ft (9.8 W/m - Static White, Static Color, Variable White)      |
| <b>4.3</b> - 4.3 W/ft (14 W/m - Static White Linea)                               |
| <b>4.4</b> - 4.4 W/ft (14.4 W/m - Static White, Static Color)                     |
| <b>5.2</b> - 5.2 W/ft (17.1 W/m - Warm Dim)                                       |
| <b>5.0</b> - 5.0 W/ft (16.4 W/m - Static White**, Static Color**)                 |
| <b>6.0</b> - 6.0 W/ft (19.7 W/m - Static White**, Static Color**, Variable White) |
| <b>6.1</b> - 6.1 W/ft (20 W/m - Variable White Linea, Pixel RGB)                  |

\*\* IP65 models are compatible only with Milky Lens option


## COLOR

|                   |                                                                            |
|-------------------|----------------------------------------------------------------------------|
| <b>18</b> - 1800K | <b>RGB27</b> - Red, Green, Blue + 2700K (IP20)                             |
| <b>20</b> - 2000K | <b>RGB30</b> - Red, Green, Blue + 3000K (IP20)                             |
| <b>22</b> - 2200K | <b>RGB40</b> - Red, Green, Blue + 4000K (IP20)                             |
| <b>24</b> - 2400K | <b>RGBA</b> - Red, Green, Blue + Amber (IP20)                              |
| <b>27</b> - 2700K | <b>RGB2465</b> - Red, Green, Blue + 2400K + 6500K (IP20)                   |
| <b>30</b> - 3000K | <b>RGBS</b> - Pixel RGB (SPI)                                              |
| <b>35</b> - 3500K | <b>VW</b> - Variable White 2000K-6500K                                     |
| <b>40</b> - 4000K | <b>VW1833</b> - Variable White 1800K-3300K (IP20)                          |
| <b>60</b> - 6000K | <b>2920</b> - Warm Dim 2900K-2000K (IP20)                                  |
| <b>R</b> - Red    | <b>1830</b> - Warm Dim 3000K-1800K (IP20)                                  |
| <b>A</b> - Amber  | <b>Z</b> - Undecided (For quotes only. Must be chosen before final order.) |
| <b>G</b> - Green  |                                                                            |
| <b>B</b> - Blue   |                                                                            |

## CONNECTION OPTIONS (See diagrams on the right)

- |                                    |                                     |
|------------------------------------|-------------------------------------|
| 1 - End Feed Bare Wire Connection  | 4 - End Feed with IP67 Male Coupler |
| 2 - Back Feed Bare Wire Connection | 5 - Soldered Daisy Chain            |
| 3 - Side Feed Bare Wire Connection | 6 - Daisy Chain With IP67 Couplers  |

## Custom Length (ft.)



AVAILABLE DRIVERS / CONTROLLERS AND DIMMING OPTIONS / WIRE GAUGE CHART

| 0-10V/ELV/MLV 3-IN-1                                                                                                                                                                                                                      | ELV                                                                                                                                                                   | 0-10V VW/WD                                                                                                                                         | COMPACT                                                                                                                                                                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                                                                                                           |                                                                                      |                                                                    |                                                                                       |
| <b>60W, 96W, 288W 0-10V/ELV/MLV 3-in-1 Dimmable Drivers</b><br><br>Part No.:<br>• DRVW2460TRI010 (60 W)<br>• DRVW2496TRI010 (96 W)<br>• DRVW24288TRI010 (288 W)<br><br>24 VDC<br>120-277 VAC<br>IP65, dry/damp/wet locations<br>UL Listed | <b>60W Dimmable Driver</b><br><br>Part No.:<br>• DRVW2460ELV<br><br>24 VDC<br>100-130 VAC<br>Fits in single-gang switch boxes<br>IP20, dry locations<br>UL Recognized | <b>0-10V Dimmable 90W VW/WD Driver</b><br><br>Part No.:<br>• DRVRFWDVW2490120<br><br>24 VDC<br>100-277 VAC<br>IP23, dry/damp locations<br>UL Listed | <b>60W, 96W Non-Dimming Compact Drivers</b><br><br>Part No.:<br>• DRV2460C (60 W)<br>• DRV2496C (96 W)<br><br>24 VDC<br>120-277 VAC<br>IP20, dry locations<br>UL Class P |

| ATHENA WIRELESS COMPATIBLE                                                                                                                                                                | CASAMBI COMPATIBLE DRIVERS                                                                                                                                                                                                                     | DIMMABLE DALI-2 DRIVERS                                                                                                                                                                                                         | DIMMABLE DALI-2 DRIVERS                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                                                           |                                                                                                                                                               |                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                        |
| <b>94W Athena Wireless Compatible Drivers</b><br><br>Part No.:<br>• DRVW2494ATH1CH (1 channel)<br>• DRVW2494ATH2CH (2 channel)<br><br>24 VDC<br>100-277 VAC<br>Dry locations<br>UL Listed | <b>100W &amp; 200W Casambi Compatible 4 Channel Drivers</b><br><br>Part No.:<br>• DRVW24100CAS4CH (100 W)<br>• DRVW24200CAS4CH (200 W)<br><br>24 VDC<br>100-277 VAC<br>IP66, dry/damp/wet locations<br>UL Listed, CE, RoHS, Bluetooth, CASAMBI | <b>96W DIMMABLE DALI-2 DT6 D4I &amp; DALI-2 DT8 D4I DRIVERS</b><br><br>Part No.:<br>• DRVW2496DALI1CH (1 channel)<br>• DRVW2496DALI2CH (2 channel)<br><br>24-26 VDC<br>120-277 VAC<br>IP67, dry/damp/wet locations<br>UL Listed | <b>75W, 150W, 240W DALI-2 Dimmable Drivers</b><br><br>Part No.:<br>• DRVW2475DALI1CH (75 W, 1 channel)<br>• DRVW24150DALI1CH (150 W, 1 channel)<br>• DRVW24240DALI1CH (240 W, 1 channel)<br>• DRV24150DALI2CH (150 W, 2 channels)<br>• DRV24150DALI4CH (150 W, 4 channels)<br><br>24 VDC<br>120-277 VAC<br>IP67, damp/wet locations (1-channel drivers only)<br>IP20, dry location (2-channel & 4-channel drivers only)<br>CE, RoHS, SELV |

DMX CONTROLLERS, VARIABLE WHITE DIMMER, WARM DIM DIMMER - FOR COLOR CHANGING FIXTURES


|                                                                                         |                                                                                     |                                                                                     |                                                                                      |                                                                                       |
|-----------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|      |  |  |  |  |
| <b>GLASS TOUCH WALL CONTROLLERS</b><br>Part No.:<br>• AWCRCBWWBK<br>• AWCWVBK           | <b>1 ZONE WALL CONTROLLER</b><br>Part No.: DMXCTRLG                                 | <b>5 ZONE WALL CONTROLLER</b><br>Part No.: DMXCTRL                                  | <b>10 ZONE WALL CONTROLLER</b><br>Part No.: DMXCTRLD                                 | <b>6 UNIVERSE DMX CONTROLLER</b><br>Part No.: DMXCTRLDR6U                             |
|       |  |  |  |  |
| <b>VARIABLE WHITE DIMMER</b><br>Part No.:<br>• RFDIMVWWH (White)<br>• RFDIMVWBK (Black) | <b>WARM DIM DIMMER</b><br>Part No.:<br>• RFDIMVDWH (White)<br>• RFDIMWDBK (Black)   | <b>4 CHANNEL WATERPROOF DMX INTERFACE</b><br>Part No.: DMXINFWLC4D                  | <b>5 CHANNEL DMX DECODER</b><br>Part No.: DMXINF5                                    | <b>DMX OPTO SPLITTER</b><br>Part No.: DMXOS8                                          |

DRIVER AND RIBBONLYTE AT FULL LOAD


| Wattages                      | 30   |        | 60   |        | 96   |        | 150  |        | 200  |        | 240  |        | 300  |        | 320  |        |
|-------------------------------|------|--------|------|--------|------|--------|------|--------|------|--------|------|--------|------|--------|------|--------|
| Wire Gauge                    | Feet | Meters | Feet | Meters | Feet | Meters | Feet | Meters | Feet | Meters | Feet | Meters | Feet | Meters | Feet | Meters |
| 24 AWG / 0.25 mm <sup>2</sup> | 14   | 4.27   | 9    | 2.74   | 5.5  | 1.68   | 3.75 | 1.14   | 2.75 | 0.84   | 2.25 | 0.69   | 1.75 | 0.53   | 1.75 | 0.53   |
| 22 AWG / 0.34 mm <sup>2</sup> | 22   | 6.71   | 14   | 4.27   | 9    | 2.74   | 5.75 | 1.75   | 4.5  | 1.37   | 3.5  | 1.07   | 2.75 | 0.84   | 2.75 | 0.84   |
| 20 AWG / 0.5 mm <sup>2</sup>  | 35   | 10.67  | 23   | 7.01   | 14   | 4.27   | 9    | 2.74   | 7    | 2.13   | 5.75 | 1.75   | 4.5  | 1.37   | 4.25 | 1.30   |
| 18 AWG / 0.75 mm <sup>2</sup> | 56   | 17.07  | 37   | 11.28  | 23   | 7.01   | 15   | 4.57   | 11   | 3.35   | 9    | 2.74   | 7.5  | 2.29   | 7    | 2.13   |
| 16 AWG / 1.5 mm <sup>2</sup>  | 90   | 27.44  | 60   | 18.29  | 37   | 11.28  | 24   | 7.32   | 18   | 5.49   | 15   | 4.57   | 12   | 3.66   | 11   | 3.35   |
| 14 AWG / 2.5 mm <sup>2</sup>  | 142  | 43.29  | 95   | 28.96  | 59   | 17.99  | 38   | 11.59  | 28   | 8.54   | 23   | 7.01   | 19   | 5.79   | 17   | 5.18   |
| 12 AWG / 4 mm <sup>2</sup>    | 226  | 68.90  | 151  | 46.04  | 94   | 28.66  | 60   | 18.29  | 45   | 13.72  | 37   | 11.28  | 30   | 9.15   | 28   | 8.54   |
| 10 AWG / 6 mm <sup>2</sup>    | 360  | 109.76 | 240  | 73.17  | 150  | 45.73  | 96   | 29.27  | 72   | 21.95  | 60   | 18.29  | 48   | 14.63  | 45   | 13.72  |
| 8 AWG / 10 mm <sup>2</sup>    | 574  | 175.00 | 381  | 116.16 | 239  | 72.87  | 153  | 46.65  | 115  | 35.06  | 95   | 28.96  | 76   | 23.17  | 71   | 21.65  |

WIRING DIAGRAMS - STATIC WHITE / STATIC COLOR / RGBW / RGBA / RGBWW


0-10 V




MLV / ELV




DMX WIRING WITH STATIC WHITE & STATIC COLOR RIBBONLYTE




DALI-2 WIRING WITH STATIC WHITE & STATIC COLOR RIBBONLYTE



STATIC WHITE & STATIC COLOR RIBBONLYTE WIRING WITH ATHENA WIRELESS COMPATIBLE DRIVER



DMX WITH RGBWW 5-IN-1 RIBBONLYTE



WIRE COLORS PER RIBBONLYTE COLOR

STATIC WHITE + STATIC COLOR

Red Wire (+) Positive  
Black Wire (-) Negative

RGBW + RGBA


Black Wire (+) Positive  
Green Wire (-) goes to Green Channel  
Red Wire (-) goes to Red Channel  
Blue Wire (-) goes to Blue Channel  
White Wire (-) goes to White Channel

RGBWW

Black (+) Positive  
Green Wire (-) goes to Green Channel  
Red Wire (-) goes to Red Channel  
Blue Wire (-) goes to Blue Channel  
White Wire (-) goes to White Channel 1  
Brown Wire (-) goes to White Channel 2

## WIRING DIAGRAMS - VARIABLE WHITE

### 2-CHANNEL VARIABLE WHITE DIMMING




### WIRE COLORS PER RIBBONLYTE COLOR


#### VARIABLE WHITE

Black Wire (+) Positive  
Red Wire (-) goes to Warm White Channel  
Green Wire (-) goes to Cool White Channel


### DMX WIRING WITH VARIABLE WHITE RIBBONLYTE



### DALI-2 WIRING WITH VARIABLE WHITE RIBBONLYTE



### VARIABLE WHITE RIBBONLYTE WIRING WITH ATHENA WIRELESS COMPATIBLE DRIVER



REV.30JUN2026

#### GLOBAL HQ

320 Murray Hill Pkwy  
East Rutherford, NJ 07073  
U.S.  
T: (+1) 212 629 6830  
E: Sales-US@GENLEDBrands.com

#### EUROPEAN HQ

Hogeweyselaan 119  
1382 JK Weesp  
Netherlands  
T: (+31) 346 235 000  
E: SalesEurope@GENLEDBrands.com

#### MEINA HQ

PO Box 371378, #823, Building 4EA  
Dubai Airport Free Zone  
Dubai, UAE  
T: (+971) 4 701 7901  
E: SalesMEINA@genledbrands.com

#### ASIA-PACIFIC HQ

Room 402, Building D  
Shenxi Tongchuang Science and Technology Park  
No. 16 Hongyin Road  
Xingqiang Community, Xinhua Street  
Guangming District, Shenzhen, China 518107  
T: (+86) 755 8529 0710  
E: Sales-Pacific@GENLEDBrands.com