



SURFACE MOUNTED

AS1

W: 0.68 in. / 17.2 mm
H: 0.34 in. / 8.6 mm
Inside W: 0.48 in. / 12.2 mm

AS1GS

W: 0.67 in. / 17.1 mm
H: 0.55 in. / 13.9 mm
Inside W: 0.48 in. / 12.3 mm

AS2

W: 0.7 in. / 17.8 mm
H: 0.6 in. / 15.2 mm
Inside W: 0.49 in. / 12.5 mm

AS3

W: 0.93 in. / 23.6 mm
H: 0.42 in. / 10.7 mm
Inside W: 0.81 in. / 20.6 mm

AS10

W: 0.47 in. / 12 mm
H: 0.47 in. / 12 mm
Inside W: 0.39 in. / 10 mm

AS13 round lens

W: 1.31 in. / 33.4 mm
H: 1.29 in. / 32.7 mm
Inside W: 1.22 in. / 31 mm

AS13 square lens

W: 1.31 in. / 33.4 mm
H: 1.37 in. / 34.8 mm
Inside W: 1.22 in. / 31 mm

AS15L

W: 0.59 in. / 15 mm
H: 0.59 in. / 15 mm
Inside W: 0.52 in. / 13.2 mm

AS16

W: 0.74 in. / 18.8 mm
H: 0.73 in. / 18.6 mm
Inside W: 0.65 in. / 16.4 mm

AS20G

W: 0.61 in. / 15.5 mm
H: 0.71 in. / 18 mm
Inside W: 0.42 in. / 10.7 mm

Adjust to 40°, 60°, 75° or 90° with profile assistant.

AS20GS

W: 1.11 in. / 28.3 mm
H: 1.57 in. / 40 mm
Inside W: 0.38 in. / 9.7 mm

AS21
X, T, 180°, 90°, 90° Vertical Connectors

W: 0.79 in. / 20 mm
H: 0.82 in. / 20.84 mm
Inside W: 0.72 in. / 18.3 mm

AS23

W: 0.91 in. / 23 mm
H: 1.59 in. / 40.5 mm
Inside W: 0.83 in. / 21 mm

AS24R

W: 0.91 in. / 23 mm
H: 1.03 in. / 26.2 mm
Inside W: 0.53 in. / 13.4 mm

AS29L

W: 1.18 in. / 30 mm
H: 1.15 in. / 29.2 mm
Inside W: 0.48 in. / 12.2 mm

AS30 round lens

W: 1.31 in. / 33.4 mm
H: 1.95 in. / 49.5 mm
Inside W: 1.17 in. / 29.8 mm

AS30 square lens

W: 1.31 in. / 33.4 mm
H: 2.03 in. / 51.6 mm
Inside W: 1.17 in. / 29.8 mm

AS31
X, T, 180°, 90°, 90° Vertical Connectors

W: 1.18 in. / 30 mm
H: 1.22 in. / 30.92 mm
Inside W: 0.99 in. / 25.17 mm

AS53

W: 2.09 in. / 53 mm
H: 2.09 in. / 53 mm
Inside W: 1.29 in. / 32.8 mm

AT4

W: 0.77 in. / 19.6 mm
H: 0.74 in. / 18.8 mm
Inside W: 0.66 in. / 16.8 mm

AT5

W: 0.77 in. / 19.6 mm
H: 0.74 in. / 18.8 mm
Inside W: 0.66 in. / 16.8 mm

CORNER

AC1

W: 0.63 in. / 16 mm
H: 0.63 in. / 16 mm
Inside W: 0.48 in. / 12.2 mm

AC2

W: 0.63 in. / 16 mm
H: 0.63 in. / 16 mm
Inside W: 0.48 in. / 12.2 mm

AC3

W: 0.74 in. / 18.8 mm
H: 0.74 in. / 18.8 mm
Inside W: 0.48 in. / 12.2 mm

AC5

W: 1.18 in. / 30 mm
H: 1.18 in. / 30 mm
Inside W: 0.77 in. / 19.6 mm

AC15L

W: 0.63 in. / 16 mm
H: 0.63 in. / 16 mm
Inside W: 0.52 in. / 13.2 mm

MICRO

AS9

W: 0.31 in. / 8 mm
H: 0.35 in. / 8.9 mm
Inside W: 0.22 in. / 5.7 mm

AR9

W: 0.55 in. / 14 mm
H: 0.35 in. / 8.9 mm
Inside W: 0.22 in. / 5.7 mm

Piccolo

W: 0.2 in. / 5 mm
H: 0.22 in. / 5.66 mm
Length up to 6 ft 6.81 in. / 2001.8 mm

Piccolo 45

W: 0.26 in. / 6.6 mm
H: 0.26 in. / 6.6 mm
Length up to 6 ft 6.81 in. / 2001.8 mm

BENDABLE

B1

W: 0.77 in. / 19.6 mm
H: 0.26 in. / 6.5 mm
Inside W: 0.69 in. / 17.6 mm

RECESSED

AR1

W: 0.9 in. / 22.9 mm
H: 0.31 in. / 7.87 mm
Inside W: 0.49 in. / 12.5 mm

AR3

W: 1.2 in. / 30.5 mm
H: 0.42 in. / 10.8 mm
Inside W: 0.81 in. / 20.6 mm

AR15L

W: 0.59 in. / 15 mm
H: 0.53 in. / 13.5 mm
Inside W: 0.52 in. / 13.2 mm

AR15AL

W: 1.31 in. / 33.3 mm
H: 0.6 in. / 15.3 mm
Inside W: 0.52 in. / 13.2 mm

AR24R

W: 1.3 in. / 33 mm
H: 1.03 in. / 26.2 mm
Inside W: 0.53 in. / 13.4 mm

AR29L

W: 1.57 in. / 40 mm
H: 1.15 in. / 29.2 mm
Inside W: 0.76 in. / 19.4 mm

MUD - IN

SC3

W: 2.62 in. / 66.6 mm
H: 0.55 in. / 14 mm
Inside W: 0.69 in. / 17.5 mm

SC10

W: 1.41 in. / 35.9 mm
H: 0.56 in. / 14.1 mm
Inside W: 0.41 in. / 10.5 mm

SC20C

W: 1.66 in. / 42.2 mm
H: 1.89 in. / 48.1 mm
Inside W: 0.46 in. / 11.7 mm

SC24R

W: 2.49 in. / 63 mm
H: 1.03 in. / 26.2 mm
Inside W: 0.53 in. / 13.4 mm

SC15L

W: 2.17 in. / 55 mm
H: 0.39 in. / 9.8 mm
Inside W: 0.52 in. / 13.2 mm

SC23

W: 0.93 in. / 23.7 mm
H: 3.46 in. / 88 mm
Inside W: 0.48 in. / 12.3 mm

SC38C

W: 2.32 in. / 58.9 mm
H: 2.85 in. / 72.3 mm
Inside W: 0.59 in. / 15 mm