GEN LED acolyte® Architectural Lighting Solutions


Date | Project

Notes

SIMPLY CLEAN™ RECESSED FIXTURE SC15L

SC15L is a small Simply Clean mud-in aluminum channel extrusion. Use a milky lens or choose the frosted lens with a grille louver or honeycomb louver for enhanced glare control. Pair SC15L with our RibbonLyte to create complete custom fixtures.

- Recessed mud-in profile
- Sold by the foot. Factory or field cuttable to any length.
- Milky lens with 110x111° beam angle
- Frosted lens with Grille or Honeycomb louver
- UGR (Grille louver): < 16.2
  UGR (Honeycomb louver): < 6.4
  (see chart for beam angle with louvers)
- For interior applications only



RoHS IP20

Declare. TM66 ASSESSED


HOUSING FINISHES

Silver Standard | **Black** | **White**

LENS / LOUVER OPTIONS



Milky Lens (PC)
80% Light Transmission



Grille Louver with Frosted Lens (PC)
75% Light Transmission
UGR < 16.2





Honeycomb Louver with Frosted Lens (PC)
75% Light Transmission
UGR < 6.4

AVAILABLE COLORS & COLOR TEMPERATURES

1800K | 2000K | 2200K | 2400K | 2700K | 3000K | 3500K | 4000K | 6000K | VW | WD | Red | Amber | Green | Blue | RGBW | RGBA | RGBWW | RGB

DIMENSIONS





Width: 2.17 in. (55 mm)
Height: 0.5 in. (12.8 mm)
Inside Width: 0.52 in. (13.2 mm)

Note: This channel does not require mounting clips. Please see our installation guide for instructions.

Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

SPECIFICATIONS

Beam Angle	Milky Lens: 110x111°, Grille Louver with Frosted Lens: 81x80°, Honeycomb Louver with Frosted Lens: 49x53°
Lens / Louver Type	Milky Lens (PC), Grille Louver with Frosted Lens (PC), Honeycomb Louver with Frosted Lens (PC)
UGR (Unified Glare Rating)	UGR (Grille Louver): < 16.2, UGR (Honeycomb Louver): < 6.4
Operating Voltage	24 V
Dimming	MLV / 0-10 Volt / ELV / DALI / DMX / CASAMBI
Operating Temperature	-40 — 158 °F (-40 — 70 °C)
Colors	1800K, 2000K, 2200K, 2400K, 2700K, 3000K, 3500K, 4000K, 6000K, Red, Amber, Green, Blue, Pixel RGB, RGBW, RGBWW, RGBA, Variable White, Warm Dim (1800K, 2000K, 2200K, Pixel RGB only available in IP20)
CRI	90+ CRI (for Static White LEDs only)
Lamp Life	L70 at 50,000 hours
MacAdam ellipse (SDCM)	1-Step Binning (for Static White LEDs only)
Certifications	UL Listed UL 2108 Issued: 2004/02/27 Ed: 1 Rev: 2014/02/24 Low Voltage Lighting Systems CSA C22.2#9.0 Issued: 1996/06/01 Ed: 1 (R2011) General Requirements for Luminaries; with Gen. Inst. 1: 1997, Gen Inst. 2: 1998. ROHS compliant
Recessed Cutout Width	0.59 in. (15 mm)
Depth In Wall	0.39 in. (9.8 mm)
Length	Sold by the foot. Factory cuttable to any length. Max individual length of each piece is 78.7 in. (2 m), but the fixture can be installed end-to-end to create long continuous recessed fixtures.
Visible Width	0.59 in. (15 mm)


ACCESSORIES

End Cap without Hole (Part #: CHSC15LECNH)
End Cap with Hole (Part #: CHSC15LECH)


Material: ABS

End View **Side View**

0.59 in. (15 mm)



0.5 in. (12.8 mm)



STATIC WHITE SERIES 2 RIBBONLYTE SPECIFICATIONS, COMPATIBILITY & DELIVERED LUMEN OUTPUT

RibbonLyte Type	Wattage	CCT	Incremental Length	LED Pitch	Max. Length (IP20)	A Delivered Lumen at 3000K with Milky Lens (PC)		Compatibility with SC15L Channel				Diode Visibility
						lm/ft	lm/m	IP20	IP65	IP68	IP69	Visible = Y Not Visible = N
Static White Series 2	3.0 W/ft	3000K	1.97 in. (50 mm)	48 LEDs/ft (160 LEDs/m)	36 ft (11 m)	234	769	✓	✓			Y

Lumen Multiplier by CCT (Static White Series 2 RibbonLyte)

CCT (3.0 W/ft)	1800K	2000K	2200K	2400K	2700K	3000K	3500K	4000K	6000K
B Multiplier	0.67	0.79	0.85	0.91	0.97	1.00	1.03	1.00	1.08

Lumen Multiplier by Wattage (Static White Series 2 RibbonLyte)

Wattage	0.75 w/ft	1.5 w/ft	2.2 w/ft	3.0 w/ft	4.4 w/ft	5.0 w/ft	6.0 w/ft
C Multiplier	0.26	0.51	0.73	1.00	1.45	1.60	1.96

A x B x C = Lumen Output

Acolyte does not warrant or represent that the information is free from errors or omission. The information may change without notice and Acolyte is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

GEN LED acolyte® Architectural Lighting Solutions

SIMPLY CLEAN™ RECESSED FIXTURE SC15L

ORDERING GUIDE

STEP 1 Complete Channel Part Number

CHANNEL	LENS / LOUVER	HOUSING COLOR
CHSC15L		
CHSC15L - Simply Clean™ SC15L Recessed Channel	**M** - Milky Lens	**SV** - Silver (default)
	GF - Grille Louver with Frosted Lens	**BK** - Black
	HF - Honeycomb Louver with Frosted Lens	**WH** - White

STEP 2 Complete RibbonLyte Part Number

CATEGORY	CRI	RIBBON TYPE & IP RATING		
RB				
RB - RibbonLyte	**0** - Static Color, Color Changing	**SWS220** - Static White Series 2 IP20	**RGBADD** - Pixel RGB IP20	**VWS220** - VW Series 2 IP20
	90 - 90+ CRI Static White	**SWS265** - Static White Series 2 IP65	**RGBWW20** - RGBWW 5-in-1 IP20	**VWS265** - VW Series 2 IP65
		SCS220 - Static Color Series 2 IP20	**RGBWS220** - RGBW Series 2 IP20	**WD20** - Warm Dim IP20
		SCS265 - Static Color Series 2 IP65	**RGBAS220** - RGBA Series 2 IP20	
		LINEA20 - Linea RibbonLyte IP20	**XACTA20** - Xacta RibbonLyte IP20	

NOTE: To ensure waterproofing standards are met, IP65 RibbonLyte can NOT be cut in the field.


WATTAGE	COLOR	
0.75 - 0.75 W/ft (2.46 W/m - Static White, Static Color)	**18** - 1800K	**RGB27** - Red, Green, Blue + 2700K (IP20)
1.0 - 1.0 W/ft (3.3 W/m - Variable White)	**20** - 2000K	**RGB30** - Red, Green, Blue + 3000K (IP20)
1.5 - 1.5 W/ft (4.9 W/m - Static White, Static Color)	**22** - 2200K	**RGB40** - Red, Green, Blue + 4000K (IP20)
2.2 - 2.2 W/ft (7.2 W/m - Static White, Static Color)	**24** - 2400K	**RGBA** - Red, Green, Blue + Amber (IP20)
2.4 - 2.4 W/ft (8 W/m - Static White Linea)	**27** - 2700K	**RGB2465** - Red, Green, Blue + 2400K + 6500K (IP20)
3.0 - 3.0 W/ft (9.8 W/m - Static White, Static Color, Variable White)	**30** - 3000K	**RGBS** - Pixel RGB (SPI)
4.3 - 4.3 W/ft (14 W/m - Static White Linea)	**35** - 3500K	**VW** - Variable White 2000K-6500K
4.4 - 4.4 W/ft (14.4 W/m - Static White, Static Color)	**40** - 4000K	**VW1833** - Variable White 1800K-3300K (IP20)
5.2 - 5.2 W/ft (17.1 W/m - Warm Dim)	**60** - 6000K	**2920** - Warm Dim 2900K-2000K (IP20)
5.0 - 5.0 W/ft (16.4 W/m - Static White*, Static Color*)	**R** - Red	**1830** - Warm Dim 3000K-1800K (IP20)
6.0 - 6.0 W/ft (19.7 W/m - Static White*, Static Color*, Variable White)	**A** - Amber	**Z** - Undecided (For quotes only. Must be chosen before final order.)
6.1 - 6.1 W/ft (20 W/m - Variable White Linea, Pixel RGB)	**G** - Green	
* IP65 models are compatible only with Milky Lens option	**B** - Blue	

CONNECTION OPTIONS (See diagrams on the right)

Custom Length (ft.)

1 - End Feed Bare Wire Connection
2 - Back Feed Bare Wire Connection
3 - Side Feed Bare Wire Connection
4 - End Feed with IP67 Male Coupler
5 - Soldered Daisy Chain
6 - Daisy Chain With IP67 Couplers

1. (Default) **2.** **3.** **4.**



Wire Length for 1, 2, 3:
Standard 12 in. / Custom up to 20 feet

Wire Length for 4:
Standard 12 in. / Custom up to 20 feet

5. **6.**



Wire Length for 5:
Standard 3 in. / Custom up to 3 feet

Wire Length for 6:
Standard 3 in. / Custom up to 18 in.

AVAILABLE DRIVERS / CONTROLLERS AND DIMMING OPTIONS / WIRE GAUGE CHART

0-10V/ELV/MLV 3-IN-1



60W, 96W, 288W 0-10V/ELV/MLV 3-in-1 Dimmable Drivers

Part No.:
- DRVW2460TRI010 (60 W)
- DRVW2496TRI010 (96 W)
- DRVW24288TRI010 (288 W)

24 VDC
120-277 VAC
IP65, dry/damp/wet locations
UL Listed

ELV



60W Dimmable Driver

Part No.:
- DRVW2460ELV

24 VDC
100-130 VAC
Fits in single-gang switch boxes
IP20, dry locations
UL Recognized

0-10V VW/WD



0-10V Dimmable 96W VW/WD Driver

Part No.:
- DRVW2496VWWD

24 VDC
100-277 VAC
UL wet-rated, dry/damp/wet locations
UL Listed

COMPACT



60W, 96W Non-Dimming Compact Drivers

Part No.:
- DRV2460C (60 W)
- DRV2496C (96 W)

24 VDC
120-277 VAC
IP20, dry locations
UL Class P

ATHENA WIRELESS COMPATIBLE



94W Athena Wireless Compatible Drivers

Part No.:
- DRVW2494ATH1CH (1 channel)
- DRVW2494ATH2CH (2 channel)

24 VDC
100-277 VAC
Dry locations
UL Listed

CASAMBI COMPATIBLE DRIVERS



100W & 200W Casambi Compatible 4 Channel Drivers

Part No.:
- DRVW24100CAS4CH (100 W)
- DRVW24200CAS4CH (200 W)

24 VDC
100-277 VAC
IP66, dry/damp/wet locations
UL Listed, CE, RoHS, Bluetooth, CASAMBI

DIMMABLE DALI-2 DRIVERS



96W DIMMABLE DALI-2 DT6 D4I & DALI-2 DT8 D4I DRIVERS

Part No.:
- DRVW2496DALI1CH (1 channel)
- DRVW2496DALI2CH (2 channel)

24-26 VDC
120-277 VAC
IP67, dry/damp/wet locations
UL Listed

DIMMABLE DALI-2 DRIVERS



75W, 150W, 240W DALI-2 Dimmable Drivers

Part No.:
- DRVW2475DALI1CH (75 W, 1 channel)
- DRVW24150DALI1CH (150 W, 1 channel)
- DRVW24240DALI1CH (240 W, 1 channel)
- DRV24150DALI2CH (150 W, 2 channels)
- DRV24150DALI4CH (150 W, 4 channels)

24 VDC
120-277 VAC
IP67, damp/wet locations (1-channel drivers only)
IP20, dry location (2-channel & 4-channel drivers only)
CE, RoHS, SELV

DMX CONTROLLERS, VARIABLE WHITE DIMMER, WARM DIM DIMMER - FOR COLOR CHANGING FIXTURES



GLASS TOUCH WALL CONTROLLERS
Part No.:
- AWCRGBWWBK
- AWCVWBK



1 ZONE WALL CONTROLLER
Part No.: DMXCTRLG



5 ZONE WALL CONTROLLER
Part No.: DMXCTRL



10 ZONE WALL CONTROLLER
Part No.: DMXCTRLD



6 UNIVERSE DMX CONTROLLER
Part No.: DMXCTRLDR6U



VARIABLE WHITE DIMMER
Part No.:
- RFDIMVWWH (White)
- RFDIMVWBK (Black)



WARM DIM DIMMER
Part No.:
- RFDIMWDWH (White)
- RFDIMWDBK (Black)



4 CHANNEL WATERPROOF DMX INTERFACE
Part No.: DMXINFWLCD4



5 CHANNEL DMX DECODER
Part No.: DMXINF5




DMX OPTO SPLITTER
Part No.: DMXOS8

DRIVER AND RIBBONLYTE AT FULL LOAD


Wattages	30		60		96		150		200		240		300		320	
Wire Gauge	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters	Feet	Meters
24 AWG / 0.25 mm²	14	4.27	9	2.74	5.5	1.68	3.75	1.14	2.75	0.84	2.25	0.69	1.75	0.53	1.75	0.53
22 AWG / 0.34 mm²	22	6.71	14	4.27	9	2.74	5.75	1.75	4.5	1.37	3.5	1.07	2.75	0.84	2.75	0.84
20 AWG / 0.5 mm²	35	10.67	23	7.01	14	4.27	9	2.74	7	2.13	5.75	1.75	4.5	1.37	4.25	1.30
18 AWG / 0.75 mm²	56	17.07	37	11.28	23	7.01	15	4.57	11	3.35	9	2.74	7.5	2.29	7	2.13
16 AWG / 1.5 mm²	90	27.44	60	18.29	37	11.28	24	7.32	18	5.49	15	4.57	12	3.66	11	3.35
14 AWG / 2.5 mm²	142	43.29	95	28.96	59	17.99	38	11.59	28	8.54	23	7.01	19	5.79	17	5.18
12 AWG / 4 mm²	226	68.90	151	46.04	94	28.66	60	18.29	45	13.72	37	11.28	30	9.15	28	8.54
10 AWG / 6 mm²	360	109.76	240	73.17	150	45.73	96	29.27	72	21.95	60	18.29	48	14.63	45	13.72
8 AWG / 10 mm²	574	175.00	381	116.16	239	72.87	153	46.65	115	35.06	95	28.96	76	23.17	71	21.65

WIRING DIAGRAMS - STATIC WHITE / STATIC COLOR / RGBW / RGBA / RGBWW


0-10 V




MLV / ELV




DMX WIRING WITH STATIC WHITE & STATIC COLOR RIBBONLYTE




DALI-2 WIRING WITH STATIC WHITE & STATIC COLOR RIBBONLYTE



STATIC WHITE & STATIC COLOR RIBBONLYTE WIRING WITH ATHENA WIRELESS COMPATIBLE DRIVER



DMX WITH RGBWW 5-IN-1 RIBBONLYTE



WIRE COLORS


STATIC WHITE + STATIC COLOR
Red Wire (+) Positive
Black Wire (-) Negative

RGBW + RGBA
Black Wire (+) Positive
Green Wire (-) goes to Green Channel
Red Wire (-) goes to Red Channel
Blue Wire (-) goes to Blue Channel
White Wire (-) goes to White Channel


RGBWW
Black (+) Positive
Green Wire (-) goes to Green Channel
Red Wire (-) goes to Red Channel
Blue Wire (-) goes to Blue Channel
White Wire (-) goes to White Channel 1
Brown Wire (-) goes to White Channel 2

WIRING DIAGRAMS - VARIABLE WHITE


2-CHANNEL VARIABLE WHITE DIMMING




DMX WIRING WITH VARIABLE WHITE RIBBONLYTE



DALI-2 WIRING WITH VARIABLE WHITE RIBBONLYTE



VARIABLE WHITE RIBBONLYTE WIRING WITH ATHENA WIRELESS COMPATIBLE DRIVER



WIRE COLORS

VARIABLE WHITE
Black Wire (+) Positive
Red Wire (-) goes to Warm White Channel
Green Wire (-) goes to Cool White Channel

REV.05NOV2026

GLOBAL HQ
320 Murray Hill Pkwy
East Rutherford, NJ 07073
U.S.
T: (+1) 212 629 6830
E: Sales-US@GENLEDBrands.com

EUROPEAN HQ
Hogeweyselaan 119
1382 JK Weesp
Netherlands
T: (+31) 346 235 000
E: SalesEurope@GENLEDBrands.com

MEINA HQ
PO Box 371378, #823, Building 4EA
Dubai Airport Free Zone
Dubai, UAE
T: (+971) 4 701 7901
E: SalesMEINA@genledbrands.com

ASIA-PACIFIC HQ
Room 402, Building D
Shenshi Tongchuang Science and Technology Park
No. 16 Hongyin Road
Xingqiang Community, Xinhu Street
Guangming District, Shenzhen, China 518107
T: (+86) 755 8529 0710
E: Sales-Pacific@GENLEDBrands.com